

Water Resources Audit Report: Ketza River Mine

Water Resources Branch
June 2023



The Water Resource Branch strives for water stewardship in the Yukon and is committed to responsible and collaborative management, protection and conservation of the territory's valuable water. As technical scientific experts in water resources, we provide advice for compliance and inspection purposes, and conduct reviews of projects undergoing water licensing and environmental assessment processes.

One of the Branch's responsibilities is to conduct audits of various undertakings that use or deposit waste to water. Audits are undertaken to improve our knowledge and understanding of a project's effects on the receiving water environment, with the intention of identifying emerging issues and sharing enhanced understanding of existing water quality and quantity conditions to support technical advice and input into assessment, licensing, and post-licensing processes. The opinions and recommendations expressed in this report are based on relevant data, reports, field observations, interpretation/analyses of scientific information available to the Branch. Such opinions and recommendations are subject to evolve as further information becomes available. We are also acknowledging that indigenous ways of knowing are not included in this report, nonetheless, they are relevant and they support responsive care of the land and water.

While the Branch provides support to inspectors on enforcement and compliance matters related to water licences, it is not the Branch's role to determine or enforce compliance. As such, the findings of this report should not be considered as a determination of compliance with any existing permit or licence.

Executive Summary

Water Resources Branch conducted an audit at the Ketza River Mine site, located approximately 80 km southeast of Ross River (by road), between August 30 and September 2, 2021. Information and conclusions contained in this audit are intended to support the Branch in the review process of a future water licensing renewal application for the closure and remediation phase.

The five primary objectives of the site audit were to:

- 1) Assess the hydrology monitoring network at site as requested by Assessment and Abandoned Mines (AAM),
- 2) Measure flow along of Cache Creek, Peel Creek, and Misery Creek,
- 3) Evaluate potential causes of elevated sulphate and arsenic levels observed in groundwater and surface water,
- 4) Determine if disturbed areas are influencing the water chemistry of Peel Creek, and,
- 5) Familiarize Branch staff with the site to provide support to AAM and future Water Licence application review

Surface water and groundwater samples were collected around the Ketza River Mine site to evaluate potential source(s) of elevated concentrations of contaminants of concern in site discharge. Sampled parameters included the full suite of parameters analyzed as a part of the mine's monthly sampling program as well as stable water isotopes to improve understanding of surface and groundwater flow paths on site.

Hydrology stations were investigated to determine required infrastructure for implementing a continuous monitoring program that would complement AAM's surface water monitoring. Discharge measurements and estimates were conducted to complement the surface water quality data collection for this audit.

Focused investigations of tributaries flowing into Cache Creek were conducted as a part of this audit. Sampling stations were selected based on desktop investigations and observations during the field investigation with focus on: previous sampling locations,

mine infrastructure/disturbances and key locations in the watershed (confluences & background locations)

Chemistry results were compared to the CCME Water Quality Guidelines (WQG) for the Protection of Freshwater Aquatic Life (CCME-FAL), Yukon Contaminated Site Regulation for Aquatic Life Standards (CSR-AW), British Columbia Ministry of Environment Water Quality Long-term Guideline for Freshwater Aquatic Life (BC MOE), Metal and Diamond Mine Effluent Regulations (MDMER) and the former Water Licence QZ04-063 Effluent Quality Standards (KEQS) (CCME 2021, YCSR 2002, GoC 2002). Isotope data was used to identify water provenances to further contribute to the understanding of the aquatic environment at Ketza Mine.

The key findings of the 2021 audit are the following:

- 1) Elevated concentrations (concentrations above CCME guidelines) of arsenic and sulfate were observed in headwater regions of five tributary creeks discharging into Cache Creek downstream of the Tailings Storage Facility. One of these tributaries, Peel Creek, may be affected by residual mine structures in the headwaters, but elevated concentrations observed in the other tributaries are likely representative of local background conditions. Concentrations of some contaminants contributed by these tributaries are reduced to below guideline levels through geochemical processes and dilution before Cache Creek discharges into the Ketza River.
- 2) Peel Creek may be influenced by the presence of Gully Zone Pit in its headwaters. In addition to the elevated concentrations of some contaminants in the site background water, it is likely that seepage contributing contaminants to Peel Creek is influenced by the presence of the QB Zone Pit located further down the creek's reach.
- 3) Water quality data for the Ketza River Mine site is in the process of being curated to form a complete historical record of all water data since monitoring began. Water Resources Branch analysed data from this preliminary database and other sources focused towards increasing understanding of site contaminant trends and potential for impacts to the receiving environment.

4) Improvements can be made to the current hydrology program to better inform contaminant loading into site waterways. The absence of continuous water level and flow monitoring since 2012 is detrimental to inform remediation planning (water balance modelling and monitoring).

Water Resources Branch recommends the following with respect to the Ketza River Mine site:

- Collect additional ongoing surface water quality and hydrology measurements in the vicinity of the headwaters of Cache Creek, between KR-20 and KR-01, specially, upstream and downstream of the Unnamed Creek (KR-16 Creek) confluence with Cache Creek.
- 2) Conduct a review of trends in dissolved constituents in groundwater upon completion of the Ketza geochemical database audit.
- 3) Incorporate six continuous hydrometric stage monitoring stations at the locations specified in section 4.4. The overarching goal of a continuous hydrometric network is to better quantify flowrates between in-person monitoring events. The dataset would help calibrate eventual water balance and water quality models at a wider scale along Cache Creek down to Ketza River.
- 4) Increase groundwater sampling frequency from annual to twice annually and monitor groundwater levels more monthly, if possible.

Table of Contents

ĽΧ	ecuti	ve S	ummary	∠
Та	ble o	f Co	ntents	5
Lis	st of ⁻	Γable	2S	7
Lis	st of F	igur	es	8
Lis	st of A	∆ррє	endices	.10
Lis	st of A	4cro	nyms and Abbreviations	.11
1.	Intr	odu	ction and Background	1
	1.1	Pur	pose and Objectives	1
	1.2	Site	e Review	4
2.	Me	thod	s and Materials	5
	2.1	Des	sktop Review	5
	2.2	Sur	face Water Quality	5
	2.3	Gro	undwater Quality	.14
	2.4	Нус	drology Measurements	.17
	2.4	.1	Discharge Measurements	.17
	2.4	.2	Hydrometric Station Assessments	.20
	2.5	Qua	ality Assurance / Quality Control	.23
	2.5	5.1	Surface Water Quality	.23
	2.5	5.2	Groundwater Quality	.24
	2.5	5.3	Hydrology	.24
	2.5	5.4	Laboratory QAQC	.24
3.	Res	sults		.25
	3.1	Des	sktop Review	.25

3.1.1	Groundwater	25
3.1.2	Surface Water	25
3.1.3	Draft Ketza River Mine Adaptive Management Plan	27
3.1.4	Cache Creek Flow Path	28
3.1.5	Summary of Arsenic Trends	31
3.1.6	Summary of sulfate trends	34
3.1.7	Groundwater	34
3.2 Sit	e Visit Results	37
3.2.1	Surface Water Quality	37
3.2.2	Groundwater Quality	46
3.2.3	Hydrology	48
3.2.4	Stable Water Isotopes	56
3.2.5	Audit QAQC	56
4. Analys	is and Discussion	61
4.1 Ch	nemistry in Cache Creek	61
4.2 Ch	nemistry in the Peel Creek Sub-catchment	67
4.3 Ch	nemistry in the Misery Creek sub-catchment	71
4.4 Hy	drometric monitoring network	73
5. Conclu	sions and Recommendations	75
6. Contac	ct Information	78
References	S	79
Appendice	S	82
Appendi	x A - Photo log	83
Appendi	x B - Site maps showing disturbance features and AECs/APECs	84
Appendi	x C – Water Licence QZ04-063	85

Appendix D – Water Quality Lab Raw Data	86
Appendix E – 2021 Audit Field Notes – Hemmera and Water Resources Branch	87
Appendix F - Flow Measurements Datasheets	88
Appendix G - Hydrometric Network Assessment	89
Appendix H – Surficial Geology of the Ketza River Mine site	90
Appendix I – Groundwater Contours (Hemmera, August 2021)	91
Appendix J – Groundwater Monitoring Exceedance Summary (Hemmera, August 2021)	
List of Tables	
Table 1 - Surface water quality samples collected during the 2021 site audit	6
Table 2. Water quality parameters included in the 2021 Ketza Audit	10
Table 3. Surface water quality samples collected along Peel Creek during the 2021 audit	
Table 4. Surface water quality samples collected along Misery Creek during the 202 site audit	
Table 5. Groundwater quality samples and Isotopes collected by Hemmera during t	
Table 6. Hydrology assessment location information	21
Table 7. QAQC samples included in the August 2021 site audit	23
Table 8. Summary of historical water quality data that exceeded guidelines for regusampled stations between 2015 - 2020 (n=24)	•
Table 9. Summary of AAM COPC Screening (adapted from Zajdlik and Van Gulck 2	•
Table 10. Field parameters measured during the 2021 site audit	37

Table 11. Alkalinity concentrations measured in the field during the 2021 site audit	39
Table 12. Comparison of surface water quality taken by Water Resources Branch during the August 2021 site audit that had at least one exceedance against the BC MOE Long-term, CCME, CSR and KEQS standards/guidelines	45
Table 13. Groundwater field parameters measured by Hemmera during the 2021 site audit	
Table 14. Summary of flow measurements and estimates during August 2021 site vis	
Table 15. Current conditions and recommendations for continuous stage and rating curve development (derived continuous discharge in open-water channel conditions) for Ketza River mine site hydrometric monitoring locations	54
Table 16. QAQC results from water quality parameters collected during the August 2021 audit	57
Table 17. QAQC results from stable water isotope samples collected during the Augu 2021 site visit	
Table 18. Comparison of alkalinity samples for in-situ measurements versus lab analysis during the August 2021 site visit	60
List of Figures	
Figure 1 - Location of the Ketza River Mine	3
Figure 2 - Surface Water Sample Locations for the 2021 Ketza Audit	9
Figure 3 - Groundwater sampling locations (Hemmera, August 2021)	16
Figure 4. Hydrology assessment locations for the 2021 audit	22
Figure 5 - Aerial photos of Tarn Lake showing region of white and red precipitates (Le – 1968; Right – 2019)	
Figure 6 - Distribution of historical (2015-2020) total arsenic concentrations at the Ketza River Mine site.	33

Figure 7 - Piper plot showing major ion dominance trends40
Figure 8 - Total As concentrations in surface water samples collected by Water ResourcesBranch43
Figure 9. Dissolved sulfate concentrations in surface water samples collected by WRB
Figure 10. Map of flow measurements and estimates (italicized) on 2021-08-31 and 2021-09-0149
Figure 11. Flow ranges based on 2012 estimated minimum and peak discharge (EBA 2013) and prioritization of stations locations53
Figure 12 - δ^2 H and δ^{18} O ratios for surface water and groundwater samples (solid circles) collected during the Aug. & Sept. 2021 monitoring events and precipitation (hollow circles) from Whitehorse via the Global Network of Isotopes in Precipitation (GNIP; IAEA 2021)
Figure 13 - δ^2 H and δ^{18} O ratios for surface water and groundwater samples collected in the Cache Creek catchment (upstream of TSF) during the Aug. & Sept. 2021 monitoring events, presented alongside GNIP data (GNIP; IAEA 2021). H designations represent isotope samples collected by Hemmera, W those collected by Water Resources Branch.
Figure 14. Estimated waste rock dumps and pit shells at the Ketza River Mine (TetraTech 2016)
Figure 15. Figure 1: δ^2 H and δ^{18} O ratios for surface water and groundwater samples (solid circles) collected in the Cache Creek catchment (TSF area) during the Aug. & Sept. 2021 monitoring events and Whitehorse GNIP data (GNIP; IAEA 2021)65
Figure 16. Analytical results of surface water quality along Cache Creek from August 2021 site audit samples. Sample stations compared in order of flow direction. Orange highlighted area shows influence of Peel Creek. Blue highlighted area shows influence of Misery Creek. Zinc and Copper CCME guidelines are based on hardness values67
Figure 17 - Evolution in As(T/D) and Fe(T/D) along the Peel Creek flow path69

Figure 18. Analytical results of surface water quality along Peel Creek from August 2021 site audit samples. Sample stations compared in order of flow direction. Highlighted area shows possible influence of QB Zone Pit. Zinc and Copper CCME guidelines are based on hardness values
Figure 19. Analytical results of surface water quality along Misery Creek from August 2021 site audit samples. Sample stations compared in order of flow direction. Highlighted area shows possible influence of KR-18. Zinc CCME guidelines are based on hardness values
List of Appendices
Appendix A - Photo log
Appendix B - Site maps showing disturbance features and AECs/APECs
Appendix C – Water Licence QZ04-063
Appendix D - WQ Lab Raw data
Appendix E – 2021 Audit Field Notes – Hemmera and WRB
Appendix F - Flow Measurements Datasheets
Appendix G – Hydrometric Station Infrastructure and Technology Options
Appendix H – Surficial Geology of the Ketza River mine site

Appendix J – Groundwater Monitoring Exceedance Summary (Hemmera, August 2021)

Appendix I – Groundwater Contours (Hemmera, August 2021)

List of Acronyms and Abbreviations

Acronym/ Abbreviation	Definition		
AAM	Government of Yukon - Assessment and Abandoned Mines		
AEC	Area of Environmental Contamination		
Al	Aluminum		
AMP	Adaptive Management Plan		
APEC	Area of Potential Environmental Concern		
ARD/ML	Acid Rock Drainage/Metal Leaching		
As	Arsenic		
AW	Aquatic Wildlife		
BCG-MR	Bromocresol Green/Methyl Red		
BC-MOE	British Columbia - Ministry of the Environment		
Ca	Calcium		
CCME	Canadian Council of Ministers of the Environment		
Cd	Cadmium		
COPC	Contaminant of Potential Concern		
CSR	Yukon Contaminated Sites Regulation		
Cu	Copper		
F	Fluorine		
FAL	Freshwater Aquatic life		
Fe	Iron		
FIGQFCS	Federal Interim Groundwater Quality Guidelines for Contaminated Sites		
GW	Groundwater		
GY	Government of Yukon		
IAEA	International Atomic Energy Agency		
KEQS	Ketza Effluent Quality Standards		
MDL	Method Detection Limit		
MDMER	Metals and Diamond Mining Effluent Regulations		
Mg	Magnesium		
mL	Millilitre		
N	Normality		
NAG	Non Acid-Generating		

Acronym/ Abbreviation	Definition		
ORP	Oxidation-Reduction Potential		
PAG	Potentially Acid-Generating		
рН	Inverse log of the activity of the hydrogen ion		
QAQC	Quality Assurance and Quality Control		
RPD	Relative Percent Difference		
Se	Selenium		
SO ₄	Sulfate		
SW	Surface Water		
TSF	Tailings Storage Facility		
TSS	Total Suspended Solids		
UW-EIL	University of Waterloo - Environmental Isotope Laboratory		
WQG	Water Quality Guideline		
WRB	Government of Yukon - Water Resources Branch		
Zn	Zinc		

1. Introduction and Background

Ketza River Mine is located in the traditional territory of the Ross River Dena Council, Liard First Nation and Teslin Tlingit Council. The site is accessible via a mine access road that connects to the Robert Campbell Highway southeast of Ross River (Figure 1). The site is situated in the Cache Creek mountain valley and is surrounded on all sides by steep rocky cliffs. Orange coloured rock is prevalent in the area due to the valley's high iron content. The mine site is located just below the tree line with gusty north winds blowing down the valley most days. The areas feels remote, rugged and wild but also is full of life with the high number of grizzly/black bears, moose, caribou and sheep in the region.

During operation, this site extracted and processed gold and silver ore from open pit operations and underground adits. Ketza River Holdings Ltd. held the last water licence (QZ04-063), which expired on December 31, 2009. The site went into care and maintenance in 2012 and was abandoned on April 10, 2015. Government of Yukon, Assessment and Abandoned Mines Branch (AAM) assumed responsibility for the site and continues to manage care and maintenance activities under Waters Act Section 37(1). Surface and groundwater quality are monitored on a monthly and annual basis, respectively. AAM is planning and preparing for remediation and site closure.

1.1 Purpose and Objectives

The purpose of this audit was to investigate potential source(s) of contaminants of concern, evaluate the existing hydrology monitoring network, and to familiarize Government of Yukon's Water Resources Branch with the site in anticipation of future regulatory processes during the closure phase.

The detailed purposes and objectives of this audit were to:

- 1) Assess the hydrology monitoring network at site as per request by AAM
 - a. Take inventory of existing hydrology stations (active and inactive).

 Evaluate the potential expansion of current monitoring scope to include discharge measurements from KR-12 (Ketza River), -13 (Cache Creek), -

- 22 (Misery Creek), and at the outlet of the water treatment station (KR-09A);
- Recommend infrastructure to reactivate continuous hydrometric monitoring (water level loggers and derived flow) based on the 2012 hydrological report (6 hydrometric stations); and
- c. Recommend a hydrology program for the site, including potential other locations or making the program more efficient for characterizing the hydrology.
- 2) Assess the hydrology of Cache and Peel Creeks:
 - a. Collect discharge measurements along Cache Creek at all accessible stations to assess contributions of surface water tributaries to inform future hydrometric station locations.
 - b. Measure discharge of Peel Creek at KR-15, KR-17, and in between to evaluate the contributions of two seeps observed by AAM in Summer 2021, and downstream of the Peel Creek confluence with Cache Creek (PCC).
- 3) Explore potential causes of elevated sulphate (SO₄) and arsenic (As) concentrations in groundwater and surface water. Collect stable water isotope (δ^2 H and δ^{18} O) samples from each regularly monitored groundwater station and several historic stations during the Aug 2021 field sampling event by AAM and their consultant. Collect water quality and isotope samples at three regularly sampled stations (KR-01, -08 and -15), ten non routine stations (KR-17, -18, -21, -22, -23, -26, -27, -28, PS1430 and PS1510), during the 2021 audit to investigate and assess potential contaminant sources.
- 4) Investigate the water chemistry within the Peel Creek catchment to determine if disturbed areas influence water chemistry. Collect water quality and isotope samples on Peel Creek downstream of Gully and QB Pits and the two seeps observed by AAM (PCS2 and PCS3).
- 5) Familiarize Branch staff with the site to provide support to AAM and future water licence application reviews.




Figure 1 - Location of the Ketza River Mine

1.2 Site Review

Surface water at the Ketza River Mine consists of a primary flow system with several contributing tributaries (Figure 2). Cache Creek originates at the headwaters of Tarn Lake and flows north-east until it discharges into Ketza River. Oxo, Peel and Misery Creeks are the main tributary creeks with some smaller unnamed creeks joining along the flow path. All of the main tributaries flow into Cache Creek downstream of the Tailings Storage Facility (TSF).

Multiple potential sources of contamination to surface water quality in Cache Creek remain from exploration and operation phases at the mine. Remaining mine infrastructure includes an ore stockpile, underground adits, a tailings storage facility, a processing facility, open pit shells, and waste rock piles (Appendix B) (Tetra Tech EBA Inc. 2016). Four surface water sampling sites are used for background water quality comparison, although their validity as such is uncertain.

The Ketza River Mine has a network of surface water and groundwater monitoring stations that are monitored by consultants contracted by AAM. The frequency of monitoring is inconsistent across the historical record, but as of 2018 all surface water sites are monitored monthly, and all groundwater sites are monitored annually.

During the care and maintenance phase, AAM manages the Ketza River Mine's water quality based on the "Use-Protection Approach" to protect fish and aquatic life (YG, 2021).

2. Methods and Materials

This audit consisted of two sampling events:

- Stable water isotope, surface water quality, and groundwater quality samples
 were collected by Hemmera Environchem Inc., a consultant of AAM, at all of the
 routine surface water and groundwater monitoring stations during the August
 sampling event. Several groundwater monitoring wells not included in the
 routine were also sampled as part of this sampling event as requested by the
 Branch.
- 2. Twenty additional stable water isotope and surface water quality samples, as well as hydrology measurements, were collected by the Branch to characterize site water discharge. These locations included routine and non-routine surface water stations some of which were previously sampled by Hemmera.

2.1 Desktop Review

Water Resources Branch carried out a review of site surface water and groundwater quality data to support the conclusions of this audit and inform comparisons with data from Hemmera's most recent monitoring event and the Branch's visit to the site. This review was comprised principally of documents supplied to the Branch by AAM, as enumerated in the 1985-2019 AAM Ketza Report Catalogue.

2.2 Surface Water Quality

Hemmera collected stable isotope samples alongside routine surface water quality samples during the monthly sampling session from August 3 to 6, 2021. Air temperatures ranged from 14°C to 17°C. Weather conditions were a mix of clouds and sun with some precipitation on August 5 and 6. There was precipitation within 24hr of sampling on August 3, 2021 (Hemmera, 2021).

Water Resources Branch investigated eight routine sites (KR-01, -08 -15, -17, -21, -26, PS1430 and PS1510), five non – historic stations (KR-18, -22, -23, -27, and -28), two seeps on Peel Creek, and one former station downstream of the Peel-Cache

confluence (PCC) from August 31 to September 2, 2021 (Table 1, Figure 2). Air temperatures ranged from 3.3°C to 17.7°C. Weather conditions were a mix of cloud cover and sun. There was no precipitation at site during this period. Site conditions at each sample location and around the mine property are presented in Appendix A.

Water Resources Branch and Hemmera staff followed Canadian Council of Ministers of the Environment's (CCME) standard sampling methods for the collection of surface water samples (CCME 2011). Stable water isotope samples were collected according to the standard methods of International Atomic Energy Agency (IAEA undated).

Stable water isotopes are a valuable tool used in water provenance determination. Analysis of the proportion of δ^2H and $\delta^{18}O$ in a given sample provides an estimate of the degree of evaporation to which a sample has been subjected to. Generally, surface water samples with a longer residence time tend to be more rich in $\delta^{18}O$, given the lighter $\delta^{16}O$ evaporates more readily. By comparing isotope ratios between water samples along flow paths, a rough estimate of hydraulic connectivity and water residence time can be hypothesized.

Water Resources Branch sample locations were selected based on the desktop review of water quality reports for this site and water quality data provided by AAM. These locations were selected with the goal of meeting the audit objectives. These sampling locations included five tributaries of Cache Creek which were sampled to delineate potential sources of elevated metals.

Table 1 - Surface water quality samples collected during the 2021 site audit

Station ID	Description	Coordinates (UTM Zone 8N)		Water Quality	Isotopes samples		
		Easting	Northing	Sample	Samples		
	Cache Creek						
KR-20	upstream of mine site and Cache Creek headwater lake (Tarn Lake)	643567	6824497	W	W		
KR-01*	upstream of mill and TSF	645088	6824842	W/H	W		
KR-13	adjacent to mill/tailings	645863	6825271	-	Н		
KR-08*	downstream of Oxo Creek	646891	6826383	W	W		
PCC	downstream of Peel Creek confluence	646860	6826425	W	W		

C: :: ID	Description	Coordinates (UTM Zone 8N)		Water	Isotopes
Station ID			1	Quality	samples
		Easting	Northing	Sample	
KR-26	unnamed creek; discharges into Cache Creek downstream of KR-08	647628	6826931	W	W
KR-27	downstream of unnamed Creek confluence	647669	6827067	W	W
KR-28	downstream of Misery Creek confluence	648506	6827197	W	W
CCT1	unnamed tributary; upstream of road crossing	650294	6828123	W	W
CCT2	unnamed tributary; upstream of road crossing	649821	6827834	W	W
ССТЗ	unnamed tributary; upstream of road crossing	648947	6827422	W	W
KR-10	upstream of Ketza River confluence	650611	6828988	-	Н
	Tailings Sto	rage Facility			
KR-09	tailings impoundment	645810	6825380	-	Н
KR-09A	discharge from Tailings Impoundment	645917	6825298	-	Н
KR-05-S1	south dam seepage; Surface discharge to Cache Creek	646090	6825391	-	Н
KR-05-S2	south dam seepage; Surface discharge to Cache Creek	646212	6825355	-	Н
KR-04-N2	north Dam seepage discharge to Cache Creek	646124	6825627	-	Н
KR-04-N3	north Dam seepage discharge to Cache Creek	646292	6825707	-	Н
	Oxo	Creek			
KR-14*	upstream of Cache Creek Diversion	646330	6825255	-	Н
	Peel Creek				
KR-17	downstream of headwater seep	644885	6826319	W	W
KR17-DS	Downstream of seeps from left bank	645040	6826278	W	W
PCS2	left bank seep (Peel Seep 2)	644909	6826343	W	W
PS2DS	downstream of seep 2 confluence	645151	6826291	W	W
PCS3	left bank seep (Peel Seep 3)	644983	6826321	W	W
PS3DS	downstream of seep 3 confluence	645192	6826301	W	W
KR-15*	upstream side of main road culvert	646325	6826284	W/H	W

Station ID	Description	Coordinates (UTM Zone 8N)		Water Quality	Isotopes
	·	Easting	Northing	Sample	samples
	Misery	/ Creek	l		
KR-21	near headwaters of Misery Creek	644200	6827875	W	W
KR-18	tributary of Misery Creek	646931	6828157	W ¹	-
KR-22	500 m upstream of Cache Creek confluence	647794	6827530	W	W
	Ketza	River			
KR-11*	upstream of Cache Creek confluence	650716	6829150	-	Н
KR-12*	downstream of Cache Creek confluence	650139	6830118	-	Н
KR-50	upstream of Campbell Highway culvert	641418	6860090	-	Н
	Other S	Stations			
Weir 2	South of tailings storage facility, within Lower Subsidiary Creek Diversion	645864	6825310	-	Н
PS1430	Mine portal seepage at 1430 masl portal location	645437	6825525	W	W
PS1510	Mine portal seepage at 1510 masl portal location	645306	6825689	dry	dry
KR-16	Unnamed tributary of Cache Creek, above mine site	644274	6825216	-	Н
KR-23	Old Iona silver portal run-off, 100m from Ketza River	651168	6828153	W	W

Note: sites listed from upstream to downstream in the respective catchment; * - Water Licence station; TSF – tailings storage facility; masl – meters above sea level; 1 – in-situ field data only; W-sampled by Water Resources, H – Sampled by Hemmera; W/H sampled by Hemmera and Water Resources




Figure 2 - Surface Water Sample Locations for the 2021 Ketza Audit

Observations recorded in field notes included brief descriptions of site conditions such as air temperature, cloud cover, and weather (Appendix E).

In-situ field measurements were collected at each station using a handheld digital thermometer for air temperature and a YSI Pro DSS multiparameter sonde for field aqueous geochemistry measurements. The thermometer was hung from vegetation in the shade while collecting the water samples at each station. The sonde was inserted into the water at each sample location so that the probes were submerged and left to equilibrate for at least 2 minutes. Parameters measured included water temperature (°C), dissolved oxygen (mg/L), pH (pH units), turbidity (NTU), specific Conductance (µS/cm) and oxidation reduction potential (ORP; mV) (Table 2). The YSI was calibrated by the Branch staff as per manufacturer specifications prior to use. Calibration was verified during and after field sampling.

Table 2. Water quality parameters included in the 2021 Ketza Audit

Parameter	Unit	Method Detection Limit (MDL)
Field		
Н	pH unit	-
Specific Conductivity (SPC)	μS/cm	-
Temperature	°C	-
Dissolved Oxygen (DO)	mg/L	-
Turbidity	NTU	-
Oxidation Reduction Potential (ORP)	mV	-
Alkalinity (total)	mgCaCO3/L	-
Laboratory		
На	pH unit	-
Specific Conductivity (SPC)	μS/cm	2
Alkalinity (bicarbonate, carbonate, hydroxide,	mgCaCO₃/L	1
phenolphthalein and total)		
Total Suspended Solids (TSS)	mg/L	1
Total Dissolved Solids (TDS)	mg/L	1
Chloride	mg/L	0.5
Sulphate (Dissolved)	mg/L	0.5
Fluoride	mg/L	0.02

		Method
Parameter	Unit	Detection
		Limit (MDL)
Phosphorus (Total Phosphate and Dissolved)	mg/L	0.001
Ammonia	mg/L	0.005
Nitrate, Nitrite	mg/L	0.002
Total Nitrogen	mg/L	0.02
Dissolved Organic Carbon (DOC)	mg/L	0.2
Cyanide (SAD and WAD)	mg/L	0.005
Metals (Total and Dissolved; including Mercury)	mg/L	Various DLs
Chromium (Total, Dissolved, -III and -VI)	mg/L	Various DLs
Hardness (Total and Dissolved)	mgCaCO₃/L	1.9*10-6

Note: SAD – strong acid dissociable; WAD – weak acid dissociable; DL – detection limit

Alkalinity was measured in the field for select sample sites using a HACH digital titrator to corroborate laboratory alkalinity measurements. Twenty millilitres of water was field filtered, measured volumetrically with a graduated cylinder, and transferred into a 30 mL Erlenmeyer flask, to which 4 drops of bromocresol green/methyl red indicator was added. Samples were titrated with 0.16 N sulfuric acid until the solution changed colour to bright pink, indicating the pH endpoint of 4.6 had been reached. The number of digital titrator units were recorded, converted to volume using the manufacturer-supplied conversion factor, and used to calculate total alkalinity.

Hemmera and Water Resources Branch collected 17 and 21 stable water isotope samples, respectively. Water Resources Branch submitted all isotope samples to the University of Waterloo-Environmental Isotope Laboratory. In-situ field measurements for pH and specific conductivity were submitted with the unfiltered samples for analysis (Appendix D). Isotope ratios were measured using a Los Gatos Research Liquid Water Isotope Analyser, model T-LWIA-45-EP with a precision (2σ) of $\delta^2H = \pm~0.8~\%$ and $\delta^{18}O = \pm~0.2~\%$.

Analysis of the Branch's samples for a suite of analytical parameters were conducted by Bureau Veritas Laboratories. Analysis of Hemerra samples for a suite of analytical parameters were conducted by CARO Laboratories. These parameters were selected to support the objectives of the Site audit, allow comparison to the current site specific sampling program, and allow comparison to water quality benchmarks and the standards outlined in the expired water licence QZ04-063 (Table 2, Appendix C). Water Resources Branch and Hemmera analytical results were compared to the CCME Water Quality Guidelines (WQG) for the Protection of Freshwater Aquatic Life (CCME-FAL), Yukon Contaminated Site Regulation for Aquatic Life Standards (CSR-AW), British Columbia Ministry of Environment Water Quality Long-term Guideline for Freshwater Aquatic Life (BC MOE), Metal and Diamond Mine Effluent Regulations (MDMER) and the former Water Licence QZ04-063 Effluent Quality Standards (KEQS) (CCME 2021, YCSR 2002, GoC 2002). Calculated guideline values for certain CCME and CSR thresholds were determined using in-situ parameters and dissolved hardness values. CSR guidelines were determined using a 1:10 dilution ratio to convert to surface water quality values. For the purposes of this audit, these benchmarks were used for comparison only. It is not the purpose of this audit to make conclusions regarding water quality exceedances with respect to standards, quidelines, or regulations.

2.2.1.1 Peel Creek Seep Assessment

In order to assess the likelihood of waste rock dumps and pit shells in Peel Creek as potential sources of contaminants into Cache Creek, surface water quality samples and isotopes were collected along the entire flow path of Peel Creek (Table 3, Figure 2). Three major seeps were assessed as well as a region of minor seepage showing bright red colouration. These seeps were sampled downstream of their respective daylighting locations where sufficient flow and mixing with the main flow path was observed. Discharge measurements were collected at strategic points along the Peel Creek flow path.

The first major seep (Seep 1) was located at the headwaters of Peel Creek, but was sampled further downstream (KR-17) due to insufficient flow for sample collection at the seep source. This sample provides potential background water quality information regarding Peel Creek before water chemistry changes occur further downstream. The other two major seeps, "Seep 2" (PCS2) and "Seep 3" (PCS3), daylight on the north side of the creek valley and flow into Peel Creek. An additional sample was collected

from a small pool just downstream from the start of the minor red seep region (KR-17DS), where the stream bed was observed with a layer of bright red precipitate (photos 27-31, Appendix A).

A final sample was collected further downstream at station KR-15 to assess the water chemistry of Peel Creek prior to its confluence with Cache Creek.

Table 3. Surface water quality samples collected along Peel Creek during the 2021 site audit

Station ID	Description	Rationale	
KR-17	downstream of headwater seep	Potential background water quality of creek	
downstream of seeps observed along		Observed change in colour of stream substrate	
KN17-D3	south bank	downstream of seep entering from south slope	
Seep 2	daylighting of seep on north bank (Peel	Water quality representing the groundwater seepage	
Seep 2	Seep 2)	entering from the north slope	
PS2DS	downstream of seep 2 confluence	Mixing of the creek and seep water to observe	
	downstream of seep 2 confidence	potential change in the creek water quality	
Seep 3	daylighting of seep on north bank (Peel	Water quality representing the groundwater seepage	
Seep 3	Seep 3)	entering from the north slope	
PS3DS	downstream of seep 3 confluence	Mixing of the creek and seep water to observe	
	downstream of seep 3 confidence	potential change in the creek water quality	
KR-15	upstream side of main road culvert	Characterize tributary before discharging into Cache	
VK-12	upstream side of main road culvert	Creek	

2.2.1.2 Misery Creek Seep Assessment

Misery Creek discharges into Cache Creek between historical stations KR-27 and KR-28. Three surface water stations are established in Misery Creek Valley, two of which were sampled by the Branch during the 2021 audit (Table 4, Figure 2). Misery Creek background water quality was sampled at KR-21, located where an access road crosses Misery Creek in the headwater region. KR-18 is located on a tributary to Misery Creek along the access road, for which only field data was obtained. KR-22 characterizes the water quality of Misery Creek upstream of its discharge into Cache Creek, where red and white precipitates were observed on the substrate. Discharge measurements were collected at strategic locations along the Misery Creek flow path.

Table 4. Surface water quality samples collected along Misery Creek during the 2021 site audit

Station ID	Description	Rationale
KR-21	Near headwaters of Misery Creek	Potential background water quality of creek
KR-18	Tributary of Misery Creek	Observe water quality of tributary before mixing with creek
KR-22	500 m upstream of Cache Creek	Observe water quality of creek before joining with Cache Creek

2.3 Groundwater Quality

Stable water isotope and groundwater quality sample collection at routine groundwater monitoring stations was completed by AAM and Hemmera during the August 2021 sampling event, including seven additional non-routine stations requested by Water Resources Branch. A total of 22 samples were collected (Table 5, Figure 3). In-situ water pH and conductivity were provided for each sample submitted for stable water isotope analysis. All groundwater sampling carried out during this event followed the methodology outlined in Hemmera's Methodology Report (Hemmera, 2020). Some minor deviations occurred, including the exchange of a Grundfos pump for a Hydrolift pump for all samples.

Table 5. Groundwater quality samples and Isotopes collected by Hemmera during the 2021 site audit

Station ID	Coordinates (UTM Zone 8N)		Sample Date - (YYYY-MM-DD)	Location Notes ¹
	Easting Northing	(1111-MIM-DD)		
		Ca	ache Creek	
GT-10-06A 6	643410 6824	6824700	2021-08-05	Located in a pit shell upgradient of
G1-10-00A	043410	043410 0624700	2021-06-05	Tarn Lake
HYD-08-17	643377	6825173	2021-08-05	North of Tarn lake
HYD-08-01A	643940	6825175	2021-08-05	Located in pit shell near Cache
HYD-08-01B	643940	6825175	2021-08-05	Creek
				Located near top of slope
HYD-08-02	644099	6825829	2021-08-04	separating Cache Creek from Peel
				Creek
Core Shack Well	644393	6825242	2021-08-05	Well near Core Shack

Station ID	Coordinates (UTM Zone 8N)		Sample Date (YYYY-MM-DD)	Location Notes ¹	
	Easting	Northing	(1111-MM-DD)		
KR-05-688	645094	6825613	2021-08-04	Located on south-facing slope	
KIY-03-000	043034	0023013	2021-00-04	across from camp area	
PS1430 Portal Well	645243	6825551	2021-08-04	Well discharging mine adit	
1 31 130 1 Ortal VVCII	0 132 13	0023331	2021 00 01	drainage	
				Located on topographic high	
GT-10-01	644990	6825921	2021-08-04	between Cache Creek and Peel	
				Creek	
BH-10-05	646387	6825905	2021-08-03	Located near confluence of	
	0.0007			unnamed creek with Cache Creek	
HYD-08-04A	645420	6825500	2021-08-04	Upgradient of TSF	
HYD-08-06A	645836	6825726	2021-08-05	Cross gradient to the north of TSF	
	Tailings Storage Facility				
P90-7B	646052	6825385	2021-08-03	Piezometer in TSF	
P96-12A	646003	6825599	2021-08-03	Piezometer in TSF	
P96-12B	646054	6825397	2021-08-03	Piezometer in TSF	
P90-8	646052	6825537	2021-08-03	Piezometer in TSF	
BH-10-01A	646212	6825597	2021-08-03	Piezometer in TSF	
BH-10-02	646239	6825923	2021-08-03	Located near confluence of	
DIT 10 02	040233	0023323	2021 00 05	unnamed creek with Cache Creek	
New Camp Water	644973	6824713	2021-08-05	Camp water supply well	
Well	011070			Camp water supply wen	
Peel Creek					
HYD-08-08	645289	6826911	2021-08-03	Near top of northern slope of Peel	
	0.0200	0010011	2021-00-03	Creek catchment	
HYD-08-09A	645369	6826441	2021-08-04	Located in waste rock dump near	
				Peel Creek	
HYD-08-10	645900	6826622		Located in pit shell upgradient of	
				Peel Creek	
HYD-08-11A	646008	6826363	2021-08-05	Downgradient of HYD-08-10	

¹Site descriptions are based on visual observation of site APECs and AECs

Groundwater monitoring wells were not sampled by WRB during the site visit.




Figure 3 - Groundwater sampling locations (Hemmera, August 2021)

2.4 Hydrology Measurements

Water Resources Branch collected discharge measurements between Aug 30 and Sept 2, 2021 on at select locations to support the audit objectives (Table 6). Measurements specifically targeted Peel Creek, lower Cache Creek around the Peel Creek confluence, and Misery Creek (Figure 4).

The conditions of flow monitoring locations were also assessed in the context of reactivating a network of continuous hydrometric stations at the site. Locations included in the hydrology assessment are presented in Table 6.

2.4.1 Discharge Measurements

Two methods were employed in the collection of stream flow data:

- Velocity-area method (mid-section) in medium size creeks (e.g Cache Creek), and
- Salt dilution method in small creeks (e.g. Peel Creek) that were too narrow, shallow or turbulent to accommodate a flowmeter.
- Estimate of tributary flow by calculating the difference between the discharge results of downstream and upstream measurements.
- Visual estimates made while observing the creek dimensions and water velocity.

2.4.1.1 Velocity-Area mid-section methodology

Field crew used a Sontek FlowTracker 2 Acoustic Doppler Velocimeter (ADV) to complete discharge measurements in Cache Creek and Misery Creek. Reaches with close to evenly distributed laminar flow uninfluenced by the presence of side channels, debris or excessive turbulence were preferentially selected, as per standard guidance documents (Water Survey of Canada 1999, Resources Information Standards Committee 2018). Stream width and measurement panels were determined by setting up a tagline across the stream perpendicular to main flow. At least 20 panels over the full stream width were used to ensure that no single panel contained more than 10% of total flow. Panel width was adjusted during the measurement to respond to observed

velocities. Where possible, staff gauge readings were recorded at the start and end of measurements to get a sense of flow rate variation. Velocity was measured at 60% of depth from water's surface where total depths were <1m. Where depth was >1m, velocity measurements were collected at 20% and 80% of maximum depth. The instrument measured velocity for 40 seconds per panel to obtain a reliable average.

The ADV automatically calculated discharge using the following standard velocity-area mid-section equation (Xylem 2019) for discharge (Q):

$$Q = \sum \bar{v}_0 d_0 \left(\frac{b_1 - b_0}{2} \right) + \bar{v}_1 d_1 \left(\frac{b_2 - b_0}{2} \right) + \bar{v}_n d_n \left(\frac{(b_{n+1}) - (b_{n-1})}{2} \right)$$

Where, \bar{v} is the average velocity in the vertical or at the station,

d is the water depth measured at the station,

b is the location of the station

SI units of m³/s, m/s, and m are used for discharge, velocity, and depth/width, respectively.

Measurements are obtained for at least 20 panels across the metering cross-section. Edge calculations are handled differently from stations in open water with reference to the first component of discharge equation. The mean velocity at the edge is scaled from the adjacent station by a user defined correction factor (CF) of 1.

The Sontek FlowTracker 2 calculated overall discharge uncertainty using the inverse variance estimator method developed by the U.S. Geological Survey (Cohn et al. 2013). This method of calculating uncertainty accounts for width, depth and accuracy of FlowTracker2 calibration and the effects of channel variability on depth and velocity across the cross-section (Xylem 2019). Discharge uncertainty calculated by the FlowTracker2 on Cache Creek and Misery Creek ranged from 3.2 % to 6.0 % (Appendix F - forthcoming). The ADV also provided a variety of quality control and assurance assessments in real-time, reducing field measurement error.

2.4.1.2 Salt dilution methodology

Salt dilution gauging method was used along Peel Creek sites where channel conditions were unsuitable for the velocity-area method of discharge measurement. Field crew used selection criteria and calculation methods provided by Gabe Sentlinger (2015). Criteria analyzed when selecting sites for salt dilution discharge gauging included turbulent flows; steep gradient; minimal pools and other backwater areas; no tributary inflows in the gauging reach; ability to perform a clean injection at a point that favours mixing; brine slug fully mixed with the flow at the point where electric conductivity is measured in the channel.

A Fathom Scientific Ltd. QiQuac salt dilution specific conductivity meter was used to collect salt dilution measurements. The QiQuac uses two very high resolution conductivity probes, reducing background noise and allowing the use of smaller quantities of salt and measurement of greater discharges compared to other conductivity meters. Calibration of the conductivity probes was conducted at the measurement locations before each reading. Given the assumption of complete mixing, the location of the probe in the stream is irrelevant. However, the location of each measurement, or each probe in the case of the QiQuac, should be on opposite sides of the stream as well as different distances along the reach to confirm complete mixing. The distance moved, or between probes, will be based on the size of the creek; 5 to 10 % of the overall distance is a good rule of thumb.

Dry salt was mixed in a 20L pail with 5-10L of water from the creek, stirred in a random fashion to keep the mixing turbulent and prevent the salt sludge concentration at the bottom of the pail. The QiQuac was set up to log in 5 second intervals. Mass of salt used at each location on Peel Creek was 100 g of Sifto Pool NaCl.

The audit team reviewed the field discharge results using the post processing spreadsheet template developed by Fathom Scientific. This report presents the post-processed discharge results and both field and QAQC results are available in Appendix F.

2.4.2 Hydrometric Station Assessments

The audit team reviewed the EBA (2013) Ketza River Project Hydrological Report for familiarization with the previous hydrometric monitoring program. The 2021 assessment included the six stations of the 2012 monitoring scope (KR-13/14/15/22/10/12) as well as water licence compliance locations KR-01 and KR-08 (Table 6).

Site assessments in 2021 included the following actions for each station assessed to be activated or re-activated in a future hydrometric network (Appendix G):

- In-situ confirmation of locations
- Calculation of watershed areas using ESRI Spatial Analysis hydrology tools with the 30m Digital Elevation Model published by Government of Yukon
- Review of 2012 flow ranges and peak flow timing
- Review of rationale for station location and purpose
- Field visit photos
- Comparison with historical site sketches
- Inspection of channel conditions
- Post-field review of satellite imagery to investigate changes in channel morphology (2005-2021 period when imagery available)
- Inspection of current infrastructure (2012 installation)
- Recommend infrastructure replacements and/or upgrades
- Establish hydrometric monitoring objectives
- Recommend measurement methods for various flow levels (open water high/moderate/low flows, winter/under-ice flows)

The audit team did not review the current Hemmera hydrometric monitoring program as it was ruled out of the scope of this report.

Table 6. Hydrology assessment location information

Station ID	Coordinates (UTM Zone 8N)		Discharge method	Station		
Station ib	Easting	Northing	Discharge method	Assessment		
	Cache Creek					
KR-01	645088	6824842	Visual Estimate	Yes		
KR-13	645863	6825271	Visual Estimate	Yes		
KR-08	646891	6826383	Velocity-Area	Yes		
PCC	646860	6826425	Velocity-Area	No		
KR-10	650611	6828988	Visual Estimate	Yes		
		Oxo Creek				
KR-14	646330	6825255	Visual Estimate	Yes		
		Peel Creek				
KR-17	644885	6826319	Visual Estimate	No		
PC-DS1 (or KR17-	645040	6826278	Salt Dilution	No		
DS)	043040	0020270	Sait Dilation	140		
PC-DS2	645151	6826291	Salt Dilution	No		
PC-DS3	644983	6826321	Salt Dilution	No		
KR-15	646325	6826284	Calculated Estimate	Yes		
Misery Creek						
KR-22	647794	6827530	Velocity-Area	Yes		
Ketza River						
KR-12	650139	6830118	Visual Estimate	Yes		




Figure 4. Hydrology assessment locations for the 2021 audit

2.5 Quality Assurance / Quality Control

2.5.1 Surface Water Quality

Calibration of the project YSI Pro DSS Sonde was completed by Water Resources Branch prior to the site visit. Calibration checks were conducted during and after the site visit to monitor instrument calibration drift. No issues were observed regarding measurement drift for any field parameters. Calibration of the YSI was carried out according to the manufacturer's protocols.

The Branch collected samples for quality assurance/quality control (QAQC) as required by CCME sampling requirements for water quality sampling (Table 7).

Table 7. QAQC samples included in the August 2021 site audit

QAQC Sample Type Collected	Procedure	Purpose
	Lab provides a sample bottle set prefilled	Used to identify if any
	with lab grade deionized water. This sample	contamination of the samples was
Travel Blank	is carried for the duration of the sampling	introduced during or as a result of
	event then returned to the lab. The bottles	the transportation process.
	remain unopened until analysis.	
	A set of sample bottles is filled with lab	Used to identify if any
	grade deionized water in the field by	contamination could be introduced
Field Blank	sampling staff following the same standard	into the sample from the
	protocols and procedures of collecting a	environment while collecting
	regular sample.	samples or from sampling staff
		handling protocols and procedures.
	Two samples are collected consecutively at	Identify the precision of sampling
	the same station while adhering to the same	technique and methods and
Replicate	standard protocols and procedures. One	provide an estimate of sampling
	replicate is collected for every ten samples,	error and analytical error.
	rounded up to the nearest ten samples.	
	Analytical results are compared and Relative	
	Percent Difference (RPD) is calculated.	

Analytical results for the blanks were compared to the method detection limit by calculating the difference between the reported values and the MDL and reported as Difference Magnitude.

$$Difference\ Magnitude = Blank\ concentration - MDL$$

Duplicate water isotope samples were collected and analyzed alongside regular samples at a rate of one duplicate per ten samples.

2.5.2 Groundwater Quality

During Hemmera's August 2021 GW sampling program, two duplicate samples, a field blank, and a travel blank were submitted for analysis alongside collected samples. Information was not provided to the Branch regarding their instrument calibration protocols, but it is assumed that the standard calibration frequency of once per field day was followed.

2.5.3 Hydrology

No replicate or concurrent hydrometric measurements were collected during the 2021 Water Resources Branch audit. However, each salt dilution gauging measurements are replicates since two conductivity probes are in simultaneous use. Appendix F (forthcoming) displays QAQC indicators such as probe comparisons and uncertainty calculations for each field measurements.

2.5.4 Laboratory QAQC

Analytical results from all replicate water quality data obtained by the Branch (both lab and field) were compared by calculating Relative Percent Difference using the equation below:

Relative Percent Difference (%) =
$$\left| \left(\frac{(S_1 - S_2)}{(S_1 + S_2)/2} \right) \right| * 100$$

Results are considered within acceptable limits when compared values show less than 25% difference (CCME 2011). The difference between replicated parameters was

calculated where RPD > 25%, referred to as Difference Magnitude (Table 7). When considering analyte concentrations in the minor or trace range (<0.001), a small difference between replicates can result in a large RPD value.

An RPD value was not calculated for parameters under the minimum detection limit (MDL).

3. Results

3.1 Desktop Review

3.1.1 Groundwater

The Ketza River Mine has an intermittent surface water and groundwater sampling record spanning back to at least 1990. Varied collection methodologies, periodic renaming of sampling sites, and lack of consistent monitoring constrains analysis of temporal trends in site contaminants. A report by Arktis (2020) reviewed all historic data for surface water sites, but to date no similar review has been carried out for groundwater monitoring stations. As of February 2022, AAM is in the final stages of curating and reviewing a comprehensive water quality database file for the Ketza River Mine. This database, when complete, will facilitate analysis of long-term trends in sitewide surface water and groundwater contamination.

3.1.2 Surface Water

Water Resources Branch's review of the period of record from 2015 to 2020 identified 15 chemical and physical parameters that occasionally or frequently exceeded at least one of the applicable site water quality benchmarks (Table 8). Arsenic was the parameter showing the highest frequency of exceedances, at 80.51 % (CCME guideline).

Table 8. Summary of historical water quality data that exceeded guidelines for regularly sampled stations between 2015 - 2020 (n=24)

	\	Water Qual	ity Standaı (mg/L)	rd/Guidelin	е	% of samples	# of
Parameter	вс мое	ССМЕ	CSR	MDMER 1	KEQS	over standard / guideline	exceedance/ # of samples
Aluminum ²	N/A	*	N/A	N/A	N/A	8.97	70 / 780
Arsenic	N/A	0.005	0.005	0.20	0.5	80.51	628 / 780
Cadmium	N/A	*	*	N/A	N/A	11.41	89 / 780
Cadmium ²	*	N/A	N/A	N/A	N/A	0.64	5/780
Cobalt	0.004	N/A	0.0009	N/A	N/A	23.72	185 / 780
Copper	N/A	*	*	0.20	0.003	10.64	83 / 780
Fluoride	*	N/A	*	N/A	N/A	1.15	9/780
Iron	N/A	0.3	N/A	N/A	N/A	15.64	122 / 780
Lead	N/A	*	*	0.16	0.2	0.38	3 / 780
Mercury	N/A	0.00002 6	0.0001	N/A	N/A	0.22	1 / 457
Selenium	0.002	0.001	0.001	N/A	N/A	8.59	67 / 780
Silver	*	0.00025	*	N/A	N/A	0.26	2/780
Sulphate	*	N/A	100	N/A	N/A	76.05	581 / 764
Total							
Suspended	N/A	N/A	N/A	30.00	15.0	3.72	29 / 780
Solids							
Zinc	*	N/A	*	0.80	0.5	7.69	60 / 780

Note: n – number of stations; BC MOE – British Columbia Ministry of Environment Long-term Water Quality Guideline for Freshwater Aquatic Life; CCME - Canadian Council of Ministers of the Environment Protection of Freshwater Aquatic Life; CSR - Yukon Contaminated Sites Regulations Schedule 3 Protection of Aquatic Life; KEQS – Ketza Effluent Quality Standards; MDMER – Metal and Diamond Mine Regulations; '*'- the standard is calculated (Appendix A); N/A – not applicable; 1- Schedule 4 Table 1 maximum authorized concentrations of prescribed deleterious substances; 2 – dissolved metal.

Assessment based on data provided by YG AAM between 2015-2020. Includes all parameters with exceedances and the percentage of samples that exceeded a guideline or standard. All metal parameters reported are total metals unless otherwise indicated. CSR standard values were divided by 10 to remove the dilution factor for surface water YG 2020). Dissolved hardness, field pH and field temperature were used to calculate CCME guidelines where required, as indicated by *.

A 2020 study of historical surface water quality data from the Ketza River Mine over the entire period of record identified temporal trends of 11 parameters from the expired water licence (QZ04-063), and two additional parameters requested by Government of Yukon, as a part of the development of the site Adaptive Management Plan (AMP) (Arktis, 2020). NH₃, As, Cu, CN, Pb, Ni, Se, SO₄, TSS, pH and Zn were assessed to detect changes in concentrations throughout the entire sampling record. Concentrations were compared to either the KEQS or CCME long-term water quality guidelines for aquatic life depending on the proximity of the station to the mine site. SO₄ was compared to the BC MOE long-term water quality guideline.

A general decrease in concentrations was observed over time for these water quality parameters, except for SO₄, along Cache Creek. Arsenic concentrations decreased after the installation of the water treatment plant in 2012, but remain generally above CCME guidelines (Arktis, 2020).

3.1.3 Draft Ketza River Mine Adaptive Management Plan

Surface water quality data at the Ketza River Mine was analyzed in 2021 to identify parameters for inclusion in the surface water AMP (Arktis, 2021). The screening process included parameters included all parameters with a CCME DWG or AL standard (Arktis, 2021). Thirteen parameters were assessed for their potential as indicators of changes in environmental conditions, referred to as contaminants of potential concern (COPC). Nine of the 13 parameters considered as COPCs were recommended for developing an adaptive management plan for the mine site (Table 9). Further investigation is recommended for four of the parameters to confirm if they should continue to be identified as COPCs.

Table 9. Summary of AAM COPC Screening (adapted from Zajdlik and Van Gulck 2021)

Chemical	Recommendation						
Aluminum							
Chromium	Requires additional investigation to confirm need to develop AMP						
Cobalt	Trequires additional investigation to commit need to develop Aim						
Cyanide							
Arsenic							
Copper	AMP Trigger required						
Fluoride							
Iron							
Zinc							
Cadmium							
Manganese	AMP trigger not required						
Mercury	Aivii digger notrequired						
Sulphate							

3.1.4 Cache Creek Flow Path

This section presents a review of historic trends in key contaminants along the Cache Creek flow path, from the headwater region to its discharge into the Ketza River.

Historical concentrations of As, Fe and Se have been detected at elevated concentrations along the Cache Creek flow path. Elevated concentrations have been detected at the farthest upstream station, KR-01. Exceedances of As guidelines are consistent along the flow path to the confluence of Cache Creek and Ketza River. Selenium concentrations historically decline along the creek, resulting in fewer exceedances at confluence point KR-10. Aluminum and Cd concentrations increase as the creek progresses. Concentrations of Cu and Fe historically reach their highest values in Cache Creek downstream of the Peel and Misery Creek confluences. TSS consistently exceeds guidelines at all stations downstream of the TSF and shows strong seasonal variation (Higher in summer months and lower in winter months).

Background water quality for Cache Creek at station KR-20 (Tarn Lake) contains high levels of AI, Cd and Zn. These parameters frequently exceed CCME guidelines at this station. Water quality downstream of Tarn Lake and upstream of the TSF shows frequent CCME guideline exceedances for As, Fe and Se (Tetra Tech, 2016, App B).

The exceedances at the stations upstream the TSF (KR-16, -01 and -13) and the headwater station KR-20 suggest that these elements may occur naturally at high concentrations in the headwaters but this can be difficult to fully attribute to background conditions as there are several mining related disturbances in the vicinity (e.g. Tarn Lake Pit). A groundwater discharge area with precipitates can be seen along the northern shore of Tarn Lake, suggesting that Tarn Lake may be groundwater fed, which may be the source of some of these dissolved elements (Figure 5). Again, though, the proximity of the Tarn Lake Pit may be affecting the groundwater concentrations entering Tarn Lake. This makes it difficult to determine what background conditions are in the catchment. Aerial photos showing this precipitate area in 1968 and in 2019 in Figure 5.

There are four stations around the TSF to monitor seepage and assess related contamination that may influence Cache Creek (KR-04-N3, KR-04-N2, KR-05-S1, KR-05-S2). The TSF water prior to treatment has a history of CCME guideline exceedances



Figure 5 - Aerial photos of Tarn Lake showing region of white and red precipitates (Left – 1968; Right – 2019).

1968 – Photography provided by Energy Mines and Resources Aerial Photo Library

2019 - Imagery provided by GeoYukon.ca

for NH₄, arsenic, and total CN.

Elemental concentrations in the two tributaries (Oxo and Unnamed) joining from the south side of Cache Creek immediately downstream of the TSF suggest that there are naturally elevated concentrations of some elements in surface water, as these tributaries flow through their respective catchments with very little exposure to anthropogenic disturbances. Samples from station KR-14 on Oxo Creek frequently

exceed CCME guidelines for Cd and Se concentrations, and intermittently exceed CCME guidelines for Al, As, Cu, Fe, and Zn (Arktis, 2021).

The Peel Creek sub catchment contains several disturbed areas associated with historical mining activity including pit shells, waste rock dumps, and access roads. These features present a high potential for water quality impacts, but due to the first observed daylighting of Cache Creek in previously disturbed areas, collecting suitable un-impacted surface water samples in the Peel Creek catchment was not feasible. Historical data indicates over 80% of all Peel Creek samples exceeded the CCME guidelines for As, Al, Cd, Cu, Fe and Zn. Selenium exceeded guidelines at the headwater station (KR-17) in 49% of samples but had fewer exceedances further downstream at KR-15. Inversely, TSS showed more exceedances at the KR-15 station when compared to KR-17 (62% of all samples). Seasonal trends indicate that groundwater is a major source of As to Peel Creek, as As concentrations are low in spring months and increase in summer months.

Water quality in Misery Creek appears to support elevated background levels of some geochemical parameters. Exceedances of CCME guidelines for As and Se are frequently observed along the entire stream. Arsenic concentrations increase as the flow progresses downstream, while Se concentrations decrease. Other parameters showing CCME exceedances at the KR-22 include Al, Cd, Cu and Zn. Surface water input appears to account for exceedances observed downstream as the majority occurred between May to December, surface water flows are the highest. A small tributary of Misery Creek, where station KR-18 is located, is below a natural talus slope and has shown evidence of acid rock drainage since the initiation of sampling in 2005. The pH of this tributary fluctuates between 4.1 and 4.3, well below the CCME guideline. However, this low pH does not appear to influence Misery Creek, as the pH at the downstream station remains higher than at the headwater station. Parameters exceeding CCME guidelines in this tributary include AI, As, Cd, Cu, Ni and Zn. These elevated metal concentrations appear to contribute to the greater concentrations of metals observed downstream in Misery Creek. High variability and poor consistency in the sampling record restricts interpretation of the potential effects of Misery Creek on Cache Creek (Arktis 2020). It should also be noted that there have been fewer samples

collected from the headwaters of Misery and Cache Creeks in the winter months due to avalanche risk in these locations.

Water quality in Ketza River is measurably influenced by Cache Creek (Tetra Tech 2016). Seasonal fluctuations and guideline exceedances in Ketza River resemble what is observed in lower stations on Cache Creek. Previous studies concluded that Peel and Misery Creeks are the main contributors of elevated As, Al, Cd and Cu concentrations in Ketza River downstream of the mine site. Fluctuations in Fe concentrations observed in Ketza River were less influenced by site discharge and were linked to upstream Ketza River concentrations.

3.1.5 Summary of Arsenic Trends

Arsenic was identified as the main COPC at the site (Arktis. 2021). Arsenic concentrations in surface water are elevated at most of the monitoring stations. Historical trend analysis shows that Tarn Lake has one of the lowest As concentrations among the stations located along the Cache Creek flow path, although it has had exceedances of the CCME guideline in the past. A significant source of As enters Cache Creek somewhere between the headwater station, Tarn Lake (KR-20) and the next downstream station (KR-01). The tributary to Cache Creek between KR-20 and KR-01 (KR-16) As concentrations are consistently below those of KR-01 and Tarn Lake indicating the source of As is likely a product of groundwater infiltration and not the KR-16 drainage. KR-01 usually has the highest As concentration observed along Cache Creek. Other monitoring stations with elevated As concentrations include the TSF seepage station KR-05S2, as well as stations in Oxo (KR-14) and Peel Creeks (KR-15, KR-17). Once Cache Creek discharges into Ketza River As concentrations (at KR-12) are reduced to the lowest values observed among all monitoring sites although remaining above the CCME guideline (Arktis 2020).

The range of As concentrations in surface water across the site between 2015 and 2020 is presented in Figure 6. Each box plot consists of three sections representing specific ranges within the dataset. The bottom of the box (lower quartile) represents the bottom 25% range of the data. Data within the box represent the middle 50% range, also known as the interquartile range. The top of the box represents the upper

25% range of the data, or the upper quartile. The top and bottom whisker represent the minimum and maximum values excluding outliers. The median is represented by the line inside the box. The "n" values indicate the number of historical data points used to create the box and whisker plots. The intent of this figure is to represent the range of concentrations across the site from 2015-2020.




Figure 6 - Distribution of historical (2015-2020) total arsenic concentrations at the Ketza River Mine site

3.1.6 Summary of sulfate trends

Sulfate was added by AAM to the COPC list as it can be used as an indicator of acid rock drainage / metal leaching (ARD/ML) (Arktis 2020). Water quality evidence of ARD has been observed at KR-18 in the Misery Creek sub catchment since August 2005 (Tetra Tech 2016), and increasing SO_4 concentrations at most stations has been observed since approximately 2005 although concentrations generally remain well below the BC MOE WQG used for comparison. One of the exceptions is at the Cache Creek headwater station, KR-20, which shows a decreasing trend since 2005. Sulfate concentrations in Oxo Creek appear to be increasing. Peel Creek was determined not to contribute to increasing SO_4 concentrations in Cache Creek. Historical reports have not reported ARD as a potential issue at Ketza River Mine.

3.1.7 Groundwater

Groundwater wells are located throughout the site to monitor the impact of APECs on groundwater quality. Locations and boundaries of these site features differ slightly across reports. A comprehensive review of existing hydrogeological conditions at the Ketza River Mine site is represented in Appendix B6 of Tetra Tech's 2016 closure report.

Yukon CSR & FIGQFCS are the only guidelines that have been applied to monitor exceedances in groundwater on site by the Branch. However, the CSR specifically state that exceedances are only triggered when concentrations exceed background levels, which have not been conclusively determined for the site. Other guidelines including CCME, BC MOE and MDMER guidelines have been included in past analyses, but as they apply only to surface water their analysis in prior reports has been for reference purposes only. FIG

3.1.7.1 General site hydrogeology

Lithologies underlying the site include argillite, limestone, mudstone, and shale. The distribution of these units is presented in Appendix H (Tetra Tech. 2016).

Drilling programs carried out in 2008 and 2010 advanced a series of boreholes across the site, which make up the majority of the groundwater monitoring network currently in place. Boreholes in the HYD-XX-XX series were drilled in 2008 using a combination of diamond drilling and augur drilling methodology, and boreholes in the GT-XX-XX and BHXX-XX series were advanced using Becker hammer drilling methodology in 2010. Since the installation of these monitoring wells, they have been monitored on an annual basis by consultants engaged by AAM.

Based on water level monitoring results, Hemmera calculated groundwater equipotential contours for the August 2021 site visit. The general hydraulic gradient appears to be from the topographic highs at the western edge of the site, decreasing towards the east-southeast. The resolution of the monitoring wells and piezometers was insufficient to draw detailed contours for each watershed, and may not be representative of the actual groundwater elevations across the site. These groundwater elevations are presented in Appendix I (Hemmera, 2021).

3.1.7.2 Groundwater Geochemistry

The range in pH for site groundwater spans from acidic (2.68) to slightly basic (12.15). Calcium (Ca) and magnesium (Mg) are the dominant cations across the site, and bicarbonate (HCO_3) and SO_4 represent the dominant anions.

No statistically significant correlation has been proven between areas of high As exceedances and locations downgradient of historical mining activities. However, elevated dissolved metal concentrations in site groundwater indicate that the region may be affected by high local background dissolved metal concentrations in addition to any contributions from mine infrastructure (Tetra Tech, 2016).

No long-term analysis of groundwater geochemical trends has yet been undertaken. Geochemical database auditing and restructuring is currently being undertaken by AAM, with one of the primary goals of the audit being consolidation of all historic groundwater data which would facilitate trend analysis. Frequent CCME and CSR (surface water standards) exceedances of some dissolved metals have been observed in samples collected from groundwater sampling locations, including AI, As, Cd, Cr, Cu,

Fe, Hg, Ni, Ag, and Zn. These exceedances show a high degree of spatial variability across the site. No groundwater stations exist in the Misery Creek sub catchment.

3.1.7.3 Groundwater in the Peel Creek Catchment

Three groundwater monitoring stations currently exist in the Peel Creek drainage area (HYD-08-08. -09A, and -11A), and one on the topographic high separating Peel and Cache Creeks. (GT-10-01). HYD-08-09 and 08-11 are located directly downgradient of ore handling areas QB Pit. HYD-08-10 is also directly downgradient of an ore handling (Gully Zone Pit) (Tetra Tech, 2016). HYD-08-11 is also downgradient of WB Pit and Gully Zone Pit but this well was found to be destroyed by a landslide during the August 2022 sampling event.

Peel Creek geochemistry is expected to be dominated by groundwater influences, as the principle flow channel is a spring source. Two large seeps between KR-17 and KR-15 further contribute to flow, as well as several smaller seeps in the upper regions.

All groundwater monitoring wells in the Peel Creek drainage show acidic pH values ranging from 2.68 to 6.02. No clear spatial trend was observed in the distribution of the exceptionally low pH values. However, HYD-08-10 is consistently observed to have one of the lowest pH values of any station at the site. All of these wells show exceedances of CCME-FAL, FIGQFCS, CSR-AW, or CSW-DW guidelines for several dissolved metals throughout the sampling record. In particular, HYD-08-09A and -11A have a history of guideline exceedances for As, Cd, and Cu.

To date, it has not been conclusively determined whether the low pH values in these wells and associated high dissolved metal concentrations result from natural groundwater contacts with local reactive minerals or whether mining-related subsurface perturbation has exacerbated these issues.

3.2 Site Visit Results

3.2.1 Surface Water Quality

3.2.1.1 In-situ Field Measurements

In-situ field parameters measured by the Branch are presented in Table 10. All measurements are within guideline or licence values except for pH at KR-18 (4.17). Two measurements using different YSI's were recorded, confirming the acidic pH at this site. The pH value at KR-18 is outside the BC MOE long-term water quality guideline for freshwater aquatic life and the effluent quality standard for this mine.

Table 10. Field parameters measured during the 2021 site audit

Station ID		Air Temp (°C)	Water Temp (°C)	DO (mg/L)	SPC (µs/cm)	рН	ORP (mV)	Turbidity (NTU)			
Water	BC MOE	N/A	18	≥8	N/A	6.5-9	N/A	N/A			
Quality	CCME	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
Standard /	CSR	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
Guideline (mg/L)	KEQS	N/A	N/A	N/A	N/A	>6.5	N/A	N/A			
			Ca	ache Creek							
KR-2	.0	6.5	6.2	10.53	274.4	8.0	185.1	1.31			
KR-0	1*	9.3	5.4	10.69	450.3	8.29	123.1	0			
KR-0	8*	3.6	4.2	11.45	528	8.18	71.7	0.5			
PCC	2	3.3	3.7	11.59	587	8.08	-93.6	2.06			
KR-2	.6	16.4	9.4	10.18	586	8.5	179.5	1.16			
KR-2	.7	14.4	7	10.72	574	8.25	176.4	1.14			
KR-2	.8	13.4	7.2	10.7	597	8.23	197.6	1.83			
CCT	1	8.3	2.4	12.23	623	8.29	225.7	0.44			
CCT	2	12.2	3.5	11.78	1044	8.36	195.6	1.85			
CCT	3	12.3	4.9	11.34	1776	8.34	209.5	0.33			
	Peel Creek										
KR-1	KR-17 11.8		3.2	10.83	583	7.21	161.4	0			
KR17-	-DS 10.1		3.6	11.28	796	7.44	-2	0.32			
PCS	2	13.1	1.4	10.92	505	7.4	130.9	0.15			

Station ID		Air Temp (°C)	Water Temp (°C)	DO (mg/L)	SPC (µs/cm)	рН	ORP (mV)	Turbidity (NTU)
Water	BC MOE	N/A	18	≥8	N/A	6.5-9	N/A	N/A
Quality	CCME	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Standard /	CSR	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Guideline (mg/L)	KEQS	N/A	N/A	N/A	N/A	>6.5	N/A	N/A
PS2D	S	14.3	4.2	11.07	609	7.71	99.4	1.48
PCS:	3	17.7	1.4	11.2	500	7.35	81.6	9.62
PS3D)S	12.5	3.7	11.28	579	7.73	-87	2.44
KR-1	5	12.7	3.4	11.6	715	7.71	-122	2.98
			М	isery Creek				
KR-2	1	13.7	3.9	10.77	685	7.74	189.2	0.86
KR-18		15.1	2.2	11.00	1340	4.17 (BC MOE, KEQS)	225.3	0.40
KR-22		15.9	7.9	10.45	634	8.22	185.1	2.72
			Otl	ner Station	S			
PS143	30	16.8	1.8	11.61	1145	7.87	233.2	1.76
KR-2	3	10.2	4.1	11.31	759	7.93	235.3	0

Note: Temp – temperature; DO – dissolved oxygen; SPC – specific conductivity; ORP – oxidation reduction potential; $^{\circ}$ C – degrees Celsius; mg/L – milligrams per litre; μ S/cm – micro Siemens per centimeter; mV – milli volts; NTU – nephelometric turbidity units; BC MOE – British Columbia Ministry of Environment Long-term Water Quality Guideline for Freshwater Aquatic Life; CCME - Canadian Council of Ministers of the Environment Protection of Freshwater Aquatic Life; CSR - Yukon Contaminated Sites Regulations Schedule 3 Protection of Aquatic Life; KEQS – Ketza Effluent Quality Standards; Highlighted values are in exceedance with the indicated standard/guideline in brackets.

The range in field-measured alkalinity values across the site is from 90.8 (KR-17DS) to 167.9 (KR-8) mg CaCO₃/L (Table 11). The results of these measurements, carried out at select surface water sites as per the methods described in section 2.2, are presented in Table 11. Comparison of these values to lab-analyzed alkalinity is discussed in section 3.2.5.1.1.

Table 11. Alkalinity concentrations measured in the field during the 2021 site audit

Sample ID	Date (YY-MM- DD)	Titration units	Titrant Vol (mL) ¹	Sample Vol (mL)	Bicarbonate (eq/L)	Bicarbonate (mg/L)	Alkalinity (mg/L CaCO₃)
			(Cache Creek			
KR-8	2021-08- 31	335.5	0.4	20.0	0.003355	204.7	167.9
PCC	2021-08- 31	303.0	0.4	20.0	0.00303	184.9	151.6
				Peel Creek			
KR-17	2021-08- 31	246.5	0.3	20.0	0.002465	150.4	123.3
KR- 17DS	2021-08- 31	181.5	0.2	20.0	0.001815	110.7	90.8
PCS2	2021-08- 31	253.5	0.3	20.0	0.002535	154.7	126.8
PC2- DS	2021-08- 31	232.5	0.3	20.0	0.002325	141.9	116.3
PCS3	2021-08- 31	246.5	0.3	20.0	0.002465	150.4	123.3
PCS3- DS	2021-08- 31	235.0	0.3	20.0	0.00235	143.4	117.6
KR-15	2021-08- 31	185.5	0.2	20.0	0.001855	113.2	92.8

Note: YY-MM-DD – year month day; 1 – 0.16 N sulphuric acid; mg/L – milligrams per liter; μ S/cm – micro Siemens per centimeter; mV – milli volts; NTU – nephelometric turbidity units; mg CaCO₃/L – milligrams calcium carbonate per litre

3.2.1.2 Observed surface water chemistry

Analytical results for surface water quality and stable water isotopes are presented in Appendix D. Comparison of water quality data to guidelines, standards, and the previous effluent quality standard is for use only in surface water characterization, any exceedances are not indications of non-compliance and should not be used for any purpose beyond the present analysis.

Trends in major ion geochemistry align with expected compositions of groundwater and surface water for mine-influenced sites. Surface water across the site shows a

higher degree of Mg dominance than groundwater samples, which appear to be more Ca-dominated. Surface water samples appear to show a higher degree of SO_4 dominance, whereas groundwater samples appear to be more HCO_3 dominated. Major ion dominance trends for all samples collected over the course of the Branch's 2021 audit are presented in Figure 7.




Figure 7 - Piper plot showing major ion dominance trends

As anticipated, regulatory guidelines are exceeded numerous times in the sampling results of the present study (BC-MOE = 10 samples, CCME = 38 samples, CSR = 54 samples); however, there are no exceedances of the Ketza EQS. Arsenic and SO₄ (dissolved) show the most exceedances among the 13 parameters that had at least one exceedance of any guideline. This study observed exceedances for seven of the nine COPCs established for this site including Al, Co, As, Cu, F, Fe, and Zn. Chromium and cyanide are the two COPCs that do not exceed any guidelines. Exceedances of guidelines and standards are summarized in Table 12.

Arsenic exceeds the CCME guideline and CSR standard for As (0.005 mg/L) 16 times, whereas SO₄ exceeds the CSR standard (65 mg/L) 19 times. Among the Cache Creek samples, stations PCC and KR-28 show the highest rates of guideline and standard exceedances with seven parameters each. In Peel Creek, KR-15 exceeds guidelines for six parameters, the most in this tributary. Station KR-22 in Misery Creek shows eight parameter exceedances.

Arsenic concentration surpasses the CCME guideline (0.005 mg/L) somewhere between the Tarn Lake station (KR-20) and the first station downstream on Cache Creek (KR-01), increasing by 0.011 mg/L between these two stations. Four tributaries discharging into Cache Creek along the north bank after the TSF were sampled during the audit and were found not to contribute additional arsenic as flow progresses. The highest concentration of As in Cache Creek (0.0192 mg/L) occurred at a new station downstream of the confluence of Peel and Cache Creek (PCC). Peel Creek shows high As concentrations throughout the entire flow with the highest concentration occurring at KR-15 (0.0444mg/L As(total)). This station is the most downstream station on Peel Creek before discharging into Cache Creek. Misery Creek also shows high As throughout the entire flowpath, with the highest concentration occurring at KR-21 (0.0397mg/L As (total)), which exceeded CCME and CSR guidelines.

The distribution of total As concentrations from samples taken during the 2021 site visit are displayed in Figure 8. The highest concentrations of As amongst the sampled locations occured at PS1430, KR-15, KR-21 and KR-23. The highest concentration of As amongst all of the sampled locations occured at the seep emerging from the mine adit at PS1430 (0.269 mg/L).

An alternative guideline for As (0.025 mg/L) was established for the Giant Mine in the Northwest Territories in 2019 (CIRNAC 2019). This guideline uses the methodology defined most recently by CCME (CCME 2007) which uses the species sensitivity distribution (SSD) approach and was deemed to be a robust guideline in past licencing conversations in Keno, Yukon. This 0.025 mg/L guideline was incorporated into the analysis presented below (section 4.0). Based on this alternative guideline, the water quality in Cache Creek shows acceptable As concentrations throughout its entire flow path. However, Peel Creek exceeds this guideline four times from where the first minor

unnamed red seeps enter along the south bank (KR-17DS) until it discharges into Cache Creek. The two major seeps (PCS2, PCS3) remain slightly below this guideline value and do not provide sufficient flow to dilute concentrations below guideline levels.

Dissolved SO₄ concentrations exceed the CSR standard (100 mg/L) at all of the stations except for two. (Table 12, Figure 9). The discharge of Tarn Lake shows the lowest observed sulfate concentration of 65 mg/L. The second lowest reported concentration occurs in the water emerging from the abandoned adit located off site at KR-23 (85 mg/L). An unnamed tributary discharging into Cache Creek along the south bank (CCT3) shows the highest SO₄ concentration (830 mg/L) among all site stations. Adit PS1430 shows the second highest concentration of 410 mg/L. Within the Peel and Misery tributaries, KR-17DS and KR-21 show the highest SO₄ concentrations at 350 and 250 mg/L, respectively.




Figure 8 - Total As concentrations in surface water samples collected by Water ResourcesBranch




Figure 9. Dissolved sulfate concentrations in surface water samples collected by WRB

Table 12. Comparison of surface water quality taken by Water Resources Branch during the August 2021 site audit that had at least one exceedance against the BC MOE Long-term, CCME, CSR and KEQS standards/guidelines

		Wate	r Quality												Station										
Parameter ¹	S		d/Guideli ng/L)	ne	KR-20	KR-01	KR-08	PCC	KR-26	KR-27	KR-28	CCT1	ССТ2	ССТЗ	KR-17	KR- 17DS	PCS2	PS2-DS	PCS3	PS3- DS	KR-15	KR-21	KR-22	KR-23	PS143 0
	BC MOE	CC ME	CSR	KEQ S					Cache	Creek							F	eel Creek				Misery	Creek	Ad	lits
Aluminum ²	*	N/A	N/A	N/A	0.043	0.00436	0.00304	0.0546 (BC MOE)	0.00174	0.0762 (BC MOE)	0.14 (BC MOE)	0.00154	0.00211	0.0031	0.001	0.00662	0.00133	0.0277	0.00126	0.0162	0.069 (BC MOE)	0.00153	0.228 (BC MOE)	0.00152	0.00156
Aluminum	N/A	*	N/A	N/A	0.0636	0.0055	0.0046	0.44 (CCME)	0.0028	0.262 (CCME)	0.987 (CCME)	0.0034	0.0085	0.0043	0.0013	0.0075	0.0012	0.0493	0.0011	0.0273	0.422 (CCME)	0.0041	2.69 (CCME)	0.014	0.0032
Antimony	N/A	N/A	0.02	N/A	0.00005	0.00039	0.00022	0.00019	0.00028	0.00022	0.00020	0.00092	0.00028	0.00021	0.00010	0.00018	0.00007	0.00013	0.00007	0.00012	0.00016	0.00038	0.00022	0.0411 (CSR)	0.00024
Arsenic	N/A	0.00 5	0.005	0.5	0.00205	0.013 (CCME, CSR)	0.0145 (CCME, CSR)	0.0192 (CCME, CSR)	0.00036	0.0159 (CCME, CSR)	0.0134 (CCME, CSR)	0.00100	0.00014	0.00029	0.0225 (CCME, CSR)	0.0277 (CCME, CSR)	0.0209 (CCME, CSR)	0.0353 (CCME, CSR)	0.0243 (CCME, CSR)	0.0284 (CCME, CSR)	0.0444 (CCME, CSR)	0.0397 (CCME, CSR)	0.0134 (CCME, CSR)	0.0411 (CCME, CSR)	0.269 (CCME, CSR)
Cadmium	N/A	*	*	N/A	0.00016 (CSR)	9.1*10 ⁻⁶	0.00004	0.00026	<mdl< td=""><td>0.00015</td><td>0.00034</td><td>5.8*10⁻⁶</td><td><mdl< td=""><td><mdl< td=""><td><mdl< td=""><td>7.3*10⁻⁶</td><td><mdl< td=""><td>0.00001</td><td><mdl< td=""><td>6.2*10⁻⁶</td><td>0.00020</td><td>6.5*10⁻⁶</td><td>0.00076 7 (CSR)</td><td>0.00002</td><td>0.00015</td></mdl<></td></mdl<></td></mdl<></td></mdl<></td></mdl<></td></mdl<>	0.00015	0.00034	5.8*10 ⁻⁶	<mdl< td=""><td><mdl< td=""><td><mdl< td=""><td>7.3*10⁻⁶</td><td><mdl< td=""><td>0.00001</td><td><mdl< td=""><td>6.2*10⁻⁶</td><td>0.00020</td><td>6.5*10⁻⁶</td><td>0.00076 7 (CSR)</td><td>0.00002</td><td>0.00015</td></mdl<></td></mdl<></td></mdl<></td></mdl<></td></mdl<>	<mdl< td=""><td><mdl< td=""><td>7.3*10⁻⁶</td><td><mdl< td=""><td>0.00001</td><td><mdl< td=""><td>6.2*10⁻⁶</td><td>0.00020</td><td>6.5*10⁻⁶</td><td>0.00076 7 (CSR)</td><td>0.00002</td><td>0.00015</td></mdl<></td></mdl<></td></mdl<></td></mdl<>	<mdl< td=""><td>7.3*10⁻⁶</td><td><mdl< td=""><td>0.00001</td><td><mdl< td=""><td>6.2*10⁻⁶</td><td>0.00020</td><td>6.5*10⁻⁶</td><td>0.00076 7 (CSR)</td><td>0.00002</td><td>0.00015</td></mdl<></td></mdl<></td></mdl<>	7.3*10 ⁻⁶	<mdl< td=""><td>0.00001</td><td><mdl< td=""><td>6.2*10⁻⁶</td><td>0.00020</td><td>6.5*10⁻⁶</td><td>0.00076 7 (CSR)</td><td>0.00002</td><td>0.00015</td></mdl<></td></mdl<>	0.00001	<mdl< td=""><td>6.2*10⁻⁶</td><td>0.00020</td><td>6.5*10⁻⁶</td><td>0.00076 7 (CSR)</td><td>0.00002</td><td>0.00015</td></mdl<>	6.2*10 ⁻⁶	0.00020	6.5*10 ⁻⁶	0.00076 7 (CSR)	0.00002	0.00015
Cobalt	0.004	N/A	0.0009	N/A	0.00146 (CSR)	0.00002	0.00003	0.0151 (CSR, BC MOE)	0.00003	0.00789 (CSR, BC MOE)	0.00994 (CSR, BC MOE)	0.00002	0.00004	0.00003	0.00002	0.00068	0.00002	0.00144 (CSR)	0.00002	0.00092 (CSR)	0.0156 (CSR, BC MOE)	0.00003	0.0154 (CSR, BC MOE)	0.00008	0.00025
Copper	N/A	*	*	0.003	0.00040	0.00016	0.00015	0.00131	0.00005	0.00076	0.00651 (CCME)	0.00008	0.00006	<mdl< td=""><td>0.00008</td><td>0.00016</td><td><mdl< td=""><td>0.00012</td><td><mdl< td=""><td><mdl< td=""><td>0.00398</td><td>0.00011</td><td>0.0185 (CCME, CSR)</td><td>0.00366</td><td>0.00016</td></mdl<></td></mdl<></td></mdl<></td></mdl<>	0.00008	0.00016	<mdl< td=""><td>0.00012</td><td><mdl< td=""><td><mdl< td=""><td>0.00398</td><td>0.00011</td><td>0.0185 (CCME, CSR)</td><td>0.00366</td><td>0.00016</td></mdl<></td></mdl<></td></mdl<>	0.00012	<mdl< td=""><td><mdl< td=""><td>0.00398</td><td>0.00011</td><td>0.0185 (CCME, CSR)</td><td>0.00366</td><td>0.00016</td></mdl<></td></mdl<>	<mdl< td=""><td>0.00398</td><td>0.00011</td><td>0.0185 (CCME, CSR)</td><td>0.00366</td><td>0.00016</td></mdl<>	0.00398	0.00011	0.0185 (CCME, CSR)	0.00366	0.00016
Iron	N/A	0.3	N/A	N/A	0.0821	0.0078	0.0039	1.09 (CCME)	0.0155	0.592 (CCME)	0.375 (CCME)	0.0196	0.0291	0.0027	<mdl< td=""><td>0.246</td><td><mdl< td=""><td>2.56 (CCME)</td><td><mdl< td=""><td>1.38 (CCME)</td><td>3.23 (CCME)</td><td>0.0133</td><td>0.0465</td><td>0.188</td><td>0.256</td></mdl<></td></mdl<></td></mdl<>	0.246	<mdl< td=""><td>2.56 (CCME)</td><td><mdl< td=""><td>1.38 (CCME)</td><td>3.23 (CCME)</td><td>0.0133</td><td>0.0465</td><td>0.188</td><td>0.256</td></mdl<></td></mdl<>	2.56 (CCME)	<mdl< td=""><td>1.38 (CCME)</td><td>3.23 (CCME)</td><td>0.0133</td><td>0.0465</td><td>0.188</td><td>0.256</td></mdl<>	1.38 (CCME)	3.23 (CCME)	0.0133	0.0465	0.188	0.256
Fluoride	*	N/A	*	N/A	0.028	0.046	0.048	0.11	0.027	0.09	0.12	0.12	0.084	0.16	0.029	0.067	0.023	0.055	0.026	0.046	0.21	0.04	0.17	0.5 (CSR)	0.81 (CSR))
Lead	*	*	*	0.2	0.00003	0.00003	0.00001	0.00042	0.00004	0.00023	0.00023	0.00060	0.00014	0.00004	<mdl< td=""><td>5.8*10⁻⁶</td><td>6.5*10⁻⁶</td><td>0.00001</td><td><mdl< td=""><td><mdl< td=""><td>9.2*10⁻⁶</td><td>0.00002</td><td>0.00028</td><td>0.0133 (CCME)</td><td>5.6*10⁻⁶</td></mdl<></td></mdl<></td></mdl<>	5.8*10 ⁻⁶	6.5*10 ⁻⁶	0.00001	<mdl< td=""><td><mdl< td=""><td>9.2*10⁻⁶</td><td>0.00002</td><td>0.00028</td><td>0.0133 (CCME)</td><td>5.6*10⁻⁶</td></mdl<></td></mdl<>	<mdl< td=""><td>9.2*10⁻⁶</td><td>0.00002</td><td>0.00028</td><td>0.0133 (CCME)</td><td>5.6*10⁻⁶</td></mdl<>	9.2*10 ⁻⁶	0.00002	0.00028	0.0133 (CCME)	5.6*10 ⁻⁶
Selenium	0.002	0.00	0.001	N/A	0.00007	0.00035	0.00070	0.00064	0.00047	0.00075	0.00074	0.00086	0.00098	0.00102 (CCME, CSR)	0.00139 (CCME, CSR)	0.00063	0.00117 (CCME, CSR)	0.00096	0.00096	0.00104 (CCME, CSR)	0.00060	0.00195 (CCME, CSR)	0.00095	0.00019	0.00061
Sulphate ²	*	N/A	100	N/A	65	110 (CSR)	140 (CSR)	190 (CSR)	130 (CSR)	160 (CSR)	180 (CSR)	160 (CSR)	370 (CSR)	830 (CSR)	190 (CSR)	350 (CSR)	150 (CSR)	260 (CSR)	170 (CSR)	240 (CSR)	280 (CSR)	250 (CSR)	210 (CSR)	85	410 (CSR)
Zinc ²	N/A	*	N/A	N/A	0.00704	0.00056	0.00208	0.0366 (CCME)	0.00016	0.0173 (CCME)	0.0131	0.0007	0.00115	0.0018	<mdl< td=""><td>0.00053</td><td><mdl< td=""><td>0.00183</td><td><mdl< td=""><td>0.00122</td><td>0.0188</td><td>0.0012</td><td>0.0107</td><td>0.00653</td><td>0.0472 (CCME)</td></mdl<></td></mdl<></td></mdl<>	0.00053	<mdl< td=""><td>0.00183</td><td><mdl< td=""><td>0.00122</td><td>0.0188</td><td>0.0012</td><td>0.0107</td><td>0.00653</td><td>0.0472 (CCME)</td></mdl<></td></mdl<>	0.00183	<mdl< td=""><td>0.00122</td><td>0.0188</td><td>0.0012</td><td>0.0107</td><td>0.00653</td><td>0.0472 (CCME)</td></mdl<>	0.00122	0.0188	0.0012	0.0107	0.00653	0.0472 (CCME)

Note: 1-All metals reported are as total metals unless labelled otherwise; ;2 – dissolved parameter; mg/L – milligrams per litre; BC MOE – British Columbia Ministry of Environment Long-term Water Quality Guideline for Freshwater Aquatic Life; CCME - Canadian Council of Ministers of the Environment Protection of Freshwater Aquatic Life; CSR - Yukon Contaminated Sites Regulations Schedule 3 Protection of Aquatic Life; KEQS – Ketza Effluent Quality Standards; <MDL – concentration below method detection limit; N/A – not applicable; '*' - calculated standard (Appendix A). Only parameters with exceedance or potential exceedance with the indicated standard/guideline in brackets; CSR standard values were divided by 10 to remove the dilution factor for surface water (YG 2020). Dissolved hardness, field pH and field temperature were used to calculate CCME guidelines where required.

3.2.1.3 Peel and Misery Creek Seeps

All of the major seeps flowing into Peel Creek in the headwaters consisted of clear water and the substrate was not discoloured from any precipitates in the flow section from seep source to confluence with Peel Creek. Algal growth was observed on the substrate and mosses growing along the flow path (photos 101-111, Appendix A). At the furthest downstream station on Peel Creek before its confluence with Cache Creek (KR-15), sediments and vegetation at this station were completely covered in red precipitate sourcing from the region of red seeps located between KR-17DS and PS2-DS. This is likely due to the groundwater seeps slowly reacting to oxygen upon daylighting from ground and ferric precipitates forming further along the creek.

In the Misery Creek sub catchment, the water appeared clear and the substrate unstained at the furthest upstream sampling site in the catchment (KR-21) (photos 47-50, Appendix A). A large seep area was observed on the uphill side of the access road leading to KR-21, at which the water was a milky white colour changing to a rusty orange (photos 51-56, Appendix A). Substrate in the Misery Creek tributary sampled by KR-18 was stained red, and no noticeable growth of periphyton was observed (photos 36-41, Appendix A). White and brown precipitates were observed to be covering the streambed sediments in Misery Creek after the confluence of the tributary and the main flow path, persisting to the lowest reaches of Misery Creek (photo 132, Appendix A).

3.2.2 Groundwater Quality

3.2.2.1 In-situ Field Measurements

Hemmera collected groundwater and stable isotope samples at each of the routine groundwater monitoring stations during the monthly sampling session from August 3 to 6, 2021. Comparison of field parameter measurements with applicable site guidelines was not a part of the reporting requirements for the site groundwater monitoring. In-situ field parameters measured by Hemmera are provided in Table 13.

Table 13. Groundwater field parameters measured by Hemmera during the 2021 site audit

Station ID	Air Temp (°C)	Water Temp (°C)	DO (mg/L)	SPC (µs/cm)	рН	ORP (mV)	Turbidity (NTU)
1510 Portal Well		8	8.72	885	7.59	157.5	1.72
BH-10-01A		5.5	6.47	1090	7.3	72.3	784
BH-10-02		2.6	2.53	895	7.7	-101.5	97.63
BH-10-05		2.4	7.35	686	7.49	46.9	618
Core Shack Well		8.7	9.37	436	7.72	9.37	0
GT-10-01		7.1	1.95	1532	7.47	124.9	17.28
GT-10-06A		6.8	7.36	3089	12.19	-41	48.6
HYD-08-01A		6	3.58	1067	7.21	116	24.75
HYD-08-01B		7.6	0.37	1043	7.17	-34.6	62
HYD-08-02		6.7	6.83	523	7.03	148.1	56.65
HYD-08-04A		4.1	5.35	1143	7.36	283	133
HYD-08-06A		3.4	3.69	1961	7.36	-9.6	188.7
HYD-08-08		5.5	3.32	1183	6.02	143.7	0
HYD-08-09A		6.9	10.59	653	5.09	146.2	0
HYD-08-10		8.2	5.36	1667	2.68	581.2	39.65
HYD-08-11A		3.7	7.59	753	3.74	474.9	114.85
HYD-08-17		3.4	1.1	1061	6.82	-55.9	147.97
KR-05-688		4.6	6.21	1304	7.26	152.2	0
New Camp Water Well		29.5	5.71	764	7.46	72.6	0
P90-7B		9.8	5.9	337	7.64	133.8	62.36
P90-8		9.6	2.48	926	7.49	-142.7	386
P96-12A		3.8	3.07	916	7.48	134.3	93.13
P96-12B		4.4	3.69	981	7.59	47.8	7.7
Upper Mill Well		6.2	5.2	964	7.83	-78.9	0

Note: Temp – temperature; DO – dissolved oxygen; SPC – specific conductance (converted from Hemmera's field notes, which were recorded in conductivity); ORP – oxidation reduction potential; $^{\circ}$ C – degrees Celsius; mg/L – milligrams per litre; μ S/cm – micro Siemens per centimeter; mV – milli volts; NTU – nephelometric turbidity units

Although guidelines for GW field parameters were not applied by Hemmera, field readings differ greatly from those collected at surface water sites. Most notably, the pH measured at the GT-10-06A is basic (12.19). Inversely, the pH values measured at wells HYD-08-09A, HYD-08-10, and HYD-08-11A are acidic, with values ranging from 2.68 to 5.09. The cause of the high pH values is not known, but the low pH values

associated with the aforementioned wells, accompanied by their generally higher dissolved metal concentrations, are likely indicative of acid rock drainage.

3.2.2.2 Analytical Results

A summary of the analytical results of the August 2021 GW sampling program carried out by Hemmera area is attached as Appendix J (Hemmera, 2021). Arsenic exceeds one or more applicable guidelines at the majority of the sampled sites, as does SO₄. The wells with lower pH values show generally the highest concentrations of dissolved As, followed by the wells with the highest pH. Measured SPC values and dissolved concentrations of other elements generally followed the same trend of lower pH resulting in higher concentrations. Other prominent exceedances of one or multiple applicable guidelines occurring across several wells included the COPCs Al, Cu, Fe, and Zn.

Wells in the Peel Creek catchment (HYD-08-08, -09A, -10, -11A, and GT-10-01) show some of the highest occurrences of guideline exceedances. In particular, the three wells closest to Peel Creek (-09A, -10, -11A) exceed guidelines for Al, As, Cd, F, and Zn.

3.2.3 Hydrology

3.2.3.1 Flow Measurements

Water Resources Branch conducted flow measurements and estimates in the Cache Creek basin from above the Peel Creek confluence to above the Ketza River confluence (Figure 10, Table 14). Weather and flow conditions were likely representative of typical late-summer at the site. Heavy rain occurred in the region during the week prior to the visit and there was moderate rainfall in the evening of 2021-08-30. The following two days were dry, with air temperatures ranging from 3°C to 14°.

Detailed information for every flow measurement collected by Branch staff between August 31 and September 1, 2021 is presented in Appendix F.

3.2.3.1.1 Peel Creek

Water Resources Branch used salt dilution gauging measurements in the upper section of Peel Creek to estimate the contribution of seepages on the northern slope of the creek (Figure 10, Table 14) on 2021-08-31. The uppermost station, KR-17, had low

flow (3L/s) and the flowrate seeping out of an iron-rich-looking talus slope 50 m downstream of KR-17 was approximately 5 L/s. The other two major seeps contribute about 10 L/s each to Peel Creek flow. Salt dilution gauging results at KR-15 were rejected since measurement quality did not meet quality standards; however, discharge was estimated in the lower reach of Peel Creek (44 L/s) by calculating the difference between discharge measurements in Cache Creek above and below Peel confluence (Table 14). At the time of sampling, Peel Creek contributed approximately 9% of Cache Creek flow after its confluence, based on pre- and post-confluence discharge results.




Figure 10. Map of flow measurements and estimates (italicized) on 2021-08-31 and 2021-09-01

3.2.3.1.2 Misery Creek

Velocity-area cross-section measurements downstream of station KR-22 on 2021-09-01 (Figure 10, Table 14) indicate that Misery Creek (0.337 m³/s) contributed

approximately 42% of Cache Creek flow downstream of their confluence (estimated $0.800 \text{ m}^3\text{/s}$) at the time of sampling.

3.2.3.1.3 Cache Creek

Two standard measurements were completed in Cache Creek above and below Peel Creek confluence. In combination with other measurements and estimates (Figure 10, Table 14), we aim at representing flow patterns in late-summer conditions between stations KR-08 (approximately 1.5 km downstream of TSF - 0.388 m³/s measured) and KR-10 (approximately 0.2 km U/S of the Cache/Ketza confluence - 0.900 m³/s estimated).

Table 14. Summary of flow measurements and estimates during August 2021 site visit

Sample ID – Description (upstream to downstream order)	Observation date-time	Discharge (m³/sec)	Measurement Method	Contribution to downstream sites (% of Q post-confluence)	
KR-08 - Cache Creek upstream of Peel	2022-08-31 10:24	0.388	Velocity-Area	90% of PCC-1	
KR-17 – Peel Creek Upper	2021-08-31 18:15	0.003	Estimate (visual)	7% of KR-15	
PC-DS1 – Peel Creek upstream of Seep 2	2021-08-31 18:15	0.008	Salt Dilution	18% of KR-15	
Seep 2 (Peel Creek Valley)			Estimate (visual)	23% of KR015	
PC-DS2 – Peel Creek downstream of Seep 2	2021-08-31 14:35	0.021	Salt Dilution	48% of KR-15	
Seep 3 (Peel Creek Valley)	2021-08-31 14:00	0.010 E	Estimate (visual)	23% of KR-15	
PC-DS3 – Peel Creek downstream of Seep 3	2021-08-31 13:53	0.035	Salt Dilution	80% of KR-15	
KR-15 - Peel Creek at Road	2021-08-31 11:55	0.044 E	Estimate (difference between PCC-1 and KR-08)	10% of PCC-1	
PCC-1 - Cache Creek downstream of Peel	2021-08-31 9:23	0.432	Velocity-Area	94% of KR-27	
KR-26 - East Tributary Unnamed	2021-09-01 13:20	0.030 E	Estimate (visual)	6% of KR-27	

Sample ID – Description (upstream to downstream order)	Observation date-time	Discharge (m³/sec)	Measurement Method	Contribution to downstream sites (% of Q post-confluence)
KR-27 – Cache Creek at Bridge	2021-09-01 12:40	0.460 E	Estimate (visual with combined upstream meas.)	58% of KR-28
KR-22 - Misery Creek	2021-09-01 15:34	0.337	Velocity-Area	42% of KR-28
KR-28 – Cache Creek downstream of Misery	2021-09-01 12:10	0.800 E	Estimate (visual with combined upstream meas.)	89% of KR-10
CCT3 - Small tributary east unnamed	2021-09-01 11:30	0.010 E	Estimate (visual)	1% of KR-10
CCT2 - Small tributary east unnamed	2021-09-01 10:50	0.040 E	Estimate (visual)	4% of KR-10
CCT1 - Small tributary east unnamed	2021-09-01 10:50	0.025 E	Estimate (visual)	3% of KR-10
KR-10 – Cache Creek upstream of Ketza River confluence	2021-09-01 09:45	0.900 E	Estimate (visual with combined upstream Q	-
KR-23	2021-09-01 09:15	0.002 E	Estimate (visual)	-

3.2.3.2 Assessment of Hydrology Monitoring Locations

A complete summary of the assessment of the hydrometric monitoring network at the Ketza River Mine site is presented in Appendix G.

In our desktop and on-the-ground assessment, we have identified six essential locations (KR-12, -10, -22, -15, -08, -13) for continuous hydrometric monitoring and two locations that would be beneficial (KR-14 and KR-01) to complement the network (Figure 11 and

Table 15). The current equipment at every hydrometric station that was installed on site in 2012 was too deteriorated to be re-used in a future network. New infrastructure, stilling wells, staff gauges and pressure transducers are required.

In addition to the six essential stream locations, discharge logs (recorded by care and maintenance staff) of the water treatment plant by the tailings storage facility (TSF) should also be incorporated in the hydrometric dataset (site KR-09A located immediately downstream of KR-13). The dataset consists of daily entries for the pump flowrate and total treated volume from 2015 to present.

Figure 11 presents locations where continuous monitoring of stage and rating curve development are needed. Three priority ranks, (1) Essential, (2) Beneficial and (3) Not required, have been assigned with best judgment based on flow patterns observed and estimated in order to represent hydrological conditions on site with reasonable accuracy. Following the 2022 field visit, we have also identified substantial changes in channel morphology at Peel Creek station KR-15 and Cache Creek stations KR-10 and KR-12. Table 15 summarizes assessment findings and recommendations for each stations, where Appendix G presents further details on the stations and channel conditions, and recommendations for continuous hydrometric monitoring redeployment.

Current Ketza River location KR-12 in the middle of a wetland and/or flood plain does not appear adequate for hydrometric monitoring (site labelled "KR-12 old" in Figure 11). Substantial bank erosion immediately downstream of KR-12 would also be detrimental for establishing a stable stage-discharge relationship. Water Resources Branch investigated an alternative location downstream (site labelled "KR-12 new" in Figure 11 at coordinates 1.57907°, -132.17929°) that presents a long, straight reach with no sign of gravel bars, braiding, bank erosion or flood plain. The proposed location "KR-12 new" would include an additional small tributary entering Ketza River below "KR-12 old" on the right downstream edge, as well as the flow through the wetland possibly not captured at the current location.




Figure 11. Flow ranges based on 2012 estimated minimum and peak discharge (EBA 2013) and prioritization of stations locations.

Table 15. Current conditions and recommendations for continuous stage and rating curve development (derived continuous discharge in open-water channel conditions) for Ketza River Mine site hydrometric monitoring locations

Station name – Location	Continuous Monitoring Priority	Rationale for location, condition and recommendation (continuous hydrometric network)
KR-12 – Ketza River d/s Cache	1 – Essential	Quantify Cache Creek contribution to Ketza River. Current location inadequate (wetland floodplain). Relocate hydro station downstream channel is more stable and contained. Develop Rating Curve to derive continuous discharge.
KR-11 – Ketza River u/s Cache	3 – Not required	Could be beneficial for KR-12 & KR-10 QAQC. Discrete flow measurements in conjunction to WQ sampling should suffice.
KR-10 – Cache Creek u/s Ketza	1 – Essential	Monitor total flow leaving the mine property. Relocate hydro station upstream nearby: find better gauging pool for sensor. Develop Rating Curve to derive continuous discharge.
KR-28 – Cache Creek d/s Misery	3 – Not required	Redundant (estimate flow with sum of KR-08,-15,-26,-22).
KR-22 – Misery Creek	1 – Essential	Significant tributary (WQ & Q). Contributes to Arsenic loading of Cache Creek. Current location needs infrastructure improvements. Develop Rating Curve to derive continuous discharge.
KR-27 – Cache Creek u/s Misery	3 – Not required	Redundant (estimate flow with sum of KR-08,-15,-26)
KR-26 – Unnamed Tributary from South	3 – Not required	Not a substantial tributary (minimal impact on Cache WQ & Q).
KR-15 – Peel Creek at Road	1 – Essential	Significant tributary (WQ & Q). Contributes to Arsenic and Sulfates loading of Cache Creek. Current gauging pool subject to aggradation: remove sediment accumulation and tweak hydraulic conditions to mitigate aggradation. Develop Rating Curve to derive continuous discharge.

Station name –	Continuous	
Location	Monitoring	Rationale for location, condition and recommendation
	Priority	(continuous hydrometric network)
KR-08 – Cache	1 – Essential	Pending inspection of new compliance station upstream: KR-08 is
Creek upstream		likely a more suitable spot for continuous stage monitoring in terms
of Peel		of channel stability.
Confluence		Current location needs new infrastructure.
		Develop Rating Curve to derive continuous discharge.
KR-29 Cache	3 – Not	Proposed new WQ compliance station removing some of the
Creek New WQ	required	distance between site impacts and the current water quality
Compliance		objective station.
Location		The location would have to be downstream of where the south
		seepage and north seepage enter Cache Creek (e.g. downstream of
		Oxo Creek), but upstream of the next unnamed creek.
		Satellite imagery not conclusive for assessing channel conditions
		relating to continuous stage monitoring.
		Difference with flow monitored at KR-08 likely not substantial
		enough to justify dedicated hydrometric station.
KR-14 – Oxo	2 – Beneficial	Substantial tributary in upper basin in flow volume but less in terms
Creek		of contaminants. Priority rank pending detailed analysis of upper
		basin.
		Current location needs infrastructure improvements.
		Develop Rating Curve to derive continuous discharge.
KR-09A – TSF	Special Record	Quantify discharge from water treatment station using existing
discharge	(Daily)	pump flowmeter logs and daily total treated volume. Existing
		record from 2015 to present and to be continued as is. Flowrate
		ranging from 0.009 m3/s to 0.015 m3/s when operating in 2020
		and 2021. Outlet in Cache Creek located downstream of KR-13
		station.
KR-13 – Upper	1 – Essential	Reach upstream of TSF discharge outlet and diversion channel, but
Cache before		downstream of mine influence (waste rock piles, mill, camp).
South Diversion		Location more suitable than KR-01 (1.1 km upstream of KR-13) for
and WTF		continuous hydrometric installation (constricted channel).
discharge		Current location needs infrastructure improvements.
KR-01	2 – Beneficial	Reach upstream of waste rock piles, mill and camp.
		Location assessed against KR-13 (1.1 km downstream of KR-01).
		Steep gradient and braiding channel not ideal for continuous
		station. Locations upstream of KR-01 not evaluated.

Note: hydrometric network assessment details presented in Appendix G.

3.2.4 Stable Water Isotopes

Water Resources Branch analyzed samples for stable water isotopes δ^2H and $\delta^{18}O$ to support interpretations of site water movement. Stable water isotope ratios (δ^2H and $\delta^{18}O$) for the samples collected during the 2021 audit, alongside Whitehorse's Global Network of Isotopes in Precipitation (GNIP) data are presented in Figure 12. The local meteoric water line may not be fully applicable to the Ketza River Mine site due to Whitehorse's distance from the site, but no closer stations exist. The significance of these isotope data relative to the audit objectives is discussed in section 4.




Figure 12 - δ^2 H and δ^{18} O ratios for surface water and groundwater samples (solid circles) collected during the Aug. & Sept. 2021 monitoring events and precipitation (hollow circles) from Whitehorse via the Global Network of Isotopes in Precipitation (GNIP; IAEA 2021)

3.2.5 Audit QAQC

Quality assurance/quality control analyses did not identify any significant issues with data collection or analysis for this project.

3.2.5.1 Surface Water QAQC

The project travel blank and field blank showed 5 and 10 parameters above detection limit respectively. However, the concentration of these parameters is small enough to limit concerns regarding sample contamination during transportation or collection.

Duplicate analysis between collected replicate samples suggest good sampling and analytical practices. Average RPD values for the two replicate surface water samples are 8.43% and 8.73% (

Table 16). Individual parameters with RPD values greater than 25% showed sufficiently low magnitudes of difference; therefore, the use of the data is acceptable.

Table 16. QAQC results from water quality parameters collected during the August 2021 audit

QAQC Sample	Parameter ¹	unit	MDL	Difference Magnitude ^{2,3}	RPD	
	Sulphate ⁴	mg/L	<0.50	0.7		
Travel	Strontium ⁴	mg/L	<0.00005	0.000008		
Blank	Strontium	mg/L	<0.00005	0.000009		
Didiik	Total Suspended Solids	mg/L	<1.0	0.6		
	Zinc ⁴	mg/L	<0.0001	0.00007		
	Aluminum ⁴	mg/L	<0.0005	0.00067		
	Aluminum	mg/L	<0.0005	0.00056		
	Alkalinity-B	mgCaCO3/L	<1.0	0.5	N/A	
	Alkalinity	mgCaCO3/L	<1.0	0.2		
Field	Total Kjeldahl Nitrogen	mg/L	<0.020	0.002		
Blank	Nitrogen	mg/L	<0.020	0.002		
	Strontium	mg/L	<0.00005	0.000007		
	Total Dissolved Solids	mg/L	<1.0	1.0		
	Uranium ⁴	mg/L	<0.00002	0.000004		
	Zinc ⁴	mg/L	<0.0001	0.00003		

QAQC Sample	Parameter ¹	unit	MDL	Difference Magnitude ^{2,3}	RPD
Replicate 1	Aluminum ⁴	mg/L	<0.0005	0.00066	49.62
	Aluminum	mg/L	<0.0005	0.00068	40.96
	Total Kjeldahl Nitrogen	mg/L	<0.020	0.033	39.05
	Total Dissolved	mg/L	<0.0010	0.0005	32.26
	Phosphorus				
	Organic Carbon ⁴	mg/L	<0.20	N/A ⁵	N/A ⁵
	Iron	mg/L	<0.001		
	Lead	mg/L	<0.00005		
	Total Suspended Solids	mg/L	<1.0		
	Zinc	mg/L	<0.0001		
Replicate 2	Copper ⁴	mg/L	<0.00005	0.000077	41.51
	Iron ⁴	mg/L	<0.001	0.0012	70.59
	Total Kjeldahl Nitrogen	mg/L	<0.020	0.045	73.17
	Nitrogen	mg/L	<0.020	0.044	39.64
	Thallium ⁴	mg/L	<0.00005	0.000018	48.65
	Thallium	mg/L	<0.00005	0.0000023	50.55
	Tungsten	mg/L	<0.00001	N/A ⁵	N/A ⁵

Note: 1 – reported as total parameter unless otherwise indicated; 2 –values calculated using analytical method detection limit for blanks; 3 – calculated values reflect comparison between paired replicate samples; 4 - dissolved parameter; 5 – one of the reported concentrations is below detection; N/A – not applicable

Stable water isotope replicate samples also showed acceptable RPD values. Average RPD values for δ^{18} O and δ^{2} H were 0.19% and 0.45% respectively (Table 17).

Table 17. QAQC results from stable water isotope samples collected during the August 2021 site visit

Sub-watershed	QAQC Sample	RPD	
		δ ¹⁸ O	δ²H
Analytical Duplicate Samples			
Cache Creek	KR-20	0.10	0.16
	1510 Portal Well	0.09	0.11
	HYD-08-02	0.23	0.02
	Core Shack Well	0.09	0.10
	KR-13	0.14	0.06
	KR-09	0.65	0.43
	P90-7B	0.51	0.01
	P96-12D	0.14	0.04
	KR-04-N2	0.09	0.08
	BH10-2D	0.74	0.23
	KR-08	0.29	0.05
	CCT2	0.65	0.24
Oxo Creek	KR-14	0.28	0.33
Peel Creek	KR-17	0.32	0.31
	HYD-08-10	0.09	0.06
	KR-15	0.14	0.14
Unnamed Tributary	KR-26	0.46	0.33
Field Replicate Samples			
Cache Creek	KR-20	0.33	0.16
	KR-01	1.46	0.56
	KR-09	0.91	0.55
	P96-12B	0.93	0.07
	BH-10-02	1.28	0.08
	KR-08	0.24	0.40
Peel Creek	KR-17	0.60	0.11

Note: QAQC – quality assurance and quality control; RPD – Relative Percent Difference; δ –isotope notation called delta

3.2.5.1.1 Field vs. lab alkalinity measurements

Field titrations were carried out on select surface water quality samples using the methods outlined in section 2.2 to corroborate laboratory results. Measurements were converted to mg/L CaCO₃ to facilitate comparison with lab-reported results. Lab and field values were found to closely align with all the samples within the acceptable 25% range (Table 18).

Table 18. Comparison of alkalinity samples for in-situ measurements versus lab analysis during the August 2021 site visit

Sample ID	Difference Magnitude ¹	RPD
KR-8	17.9	11.24%
KR-15	0.8	0.88%
KR-17	3.3	2.74%
KR-17-DS	0.2	0.21%
PCC	8.4	7.96%
PCS2	6.8	5.54%
PCS3	3.3	2.74%
PS2-DS	6.3	5.59%
PS3-DS	2.3	2.04%

Note: 1 –values calculated as difference between the field and lab alkalinity concentrations; RPD – Relative Percent Difference; δ –isotope notation called delta

3.2.5.2 Groundwater QAQC

All laboratory QAQC parameters analyzed by Hemmera, calculated from field blanks, travel blanks, and replicate samples collected alongside regular samples, were within the acceptable range according to the August 2021 monitoring report. No systemic issues were identified with the field or travel blanks collected during the course of the sampling program.

4. Analysis and Discussion

4.1 Chemistry in Cache Creek

Cache Creek is the main water body draining the Ketza River Mine, joining Ketza River approximately 5 km east/southeast of the mine itself.

Upstream station KR-20, at the discharge of Tarn Lake, has a historical record of exceedances for Al, Cd, and Zn. Samples collected by the Branch also showed high Al concentrations at this station.

One waste rock dump (thought to be non acid generating) and one pit shell exist immediately upgradient of the lakeshore region of Tarn Lake with visible red and white precipitates. Figure 14 shows the locations of these residual mine structures (TetraTech, 2016).

Groundwater monitoring well GT-10-06A is screened in these disturbance features. Monitoring well GT-10-06A exceeds CCME guidelines for Al and Zn, among other parameters, whereas HYD-08-17, located approximately 250m north of GT-10-06A shows lesser concentrations. Isotope analysis shows similar stable water isotopic signatures between GT-10-06A, HYD-08-17, and surface water site KR-20, suggesting a potential hydraulic connection between these wells and the lake. The isotopic signature of KR-01 resembles a mixture of KR-20, KR-16, and groundwater influences. KR-13 resembles a mixture of KR-01 with seepage from the 1430 portal (PS1430) and the 1510 Portal Well. The isotope signal of KR-20 indicates that Tarn Lake is not subject to significant evaporation, suggestive of a short residence time (Figure 13). The dashed red circle indicates the discrepancy between the KR-01 samples collected by Water Resources Branch and Hemmera.




Figure 13 - δ^2 H and δ^{18} O ratios for surface water and groundwater samples collected in the Cache Creek catchment (upstream of TSF) during the Aug. & Sept. 2021 monitoring events, presented alongside GNIP data (GNIP; IAEA 2021). H designations represent isotope samples collected by Hemmera, W those collected by Water Resources Branch.





△ Groundwater Monitoring Stations

• Surface Water Monitoring Stations



FIGURE 14

2021 KETZA AUDIT SAMPLE LOCATIONS
WITH ESTIMATED ROCK DUMPS
AND PIT SHELLS

DECEMBER 2022

Figure 14. Estimated waste rock dumps and pit shells at the Ketza River Mine (TetraTech 2016)

Based on historical records and Branch sampling results, a source of As enters Cache Creek somewhere between headwater station KR-20 and the next station downstream (KR-01). This source of As has not been conclusively identified, though the only obvious surface water input is the unnamed creek in which KR-16 is located. Figure 14 shows the hypothesized locations of waste rock dumps and pit shells, and identifies a Potentially Acid-Generating (PAG) waste rock dump on the northern slope immediately adjacent to the creek between these stations. Additional water quality samples and hydrology measurements upstream and downstream of KR-16 Creek confluence with Cache Creek could help distinguish this creek's impacts on Cache.

Cache Creek surface water quality in the TSF area has historically been characterized by elevated NH4, arsenic, and CN concentrations. Arsenic appears to be the only contaminant to persist in concentrations exceeding CCME guidelines downstream of the TSF, as per the historical record and Branch surface water quality sampling results. Downstream monitoring station KR-08, the station prior to the Peel - Cache confluence, shows high As and SO₄ (though not exceeding WQO's or CCME guidelines) in the historical sampling record and Branch water quality sample results. Oxo Creek and an unnamed tributary entering Cache Creek in the section of stream prior to the Peel/Cache confluence have shown elevated As and SO₄ concentrations in the historical sampling record, and are believed to be indicative of high background concentrations due to their lack of contact with any known mine infrastructure. Between stations KR-13 and KR-08, comprising Cache Creek's entire TSF flow section, As increases from 0.013 to 0.0145 mg/L, and SO₄ increases from 110 to 140 mg/L. This suggests a moderate source of SO₄ and a lesser source of As from the two unnamed tributaries.

Groundwater in the periphery of the TSF, based on limited data available from piezometer and monitoring well samples, does not appear to be impacted by TSF waters. The lack of background wells directly upstream of the TSF limits determination of pre-TSF contaminant levels. Wells HYD-08-04A and HYD-08-06A, cross-gradient from the TSF, show similar arsenic concentrations and higher sulfate concentrations than the piezometers in the TSF. The isotope signatures for the wells in the TSF and those located cross-gradient are relatively similar (ie. highly evaporated, enriched in heavier isotopes), which may indicate some hydrogeological connection. This hydraulic

connection has been observed within the tailings pond as upwellings in several locations as well as water level increases in the pond during winter months

The isotopic signature of KR-08, the station downstream of the TSF but upstream of PCC, appears to be a mix of several sampling sites local to the TSF including KR-13, KR-09A, TSF seepage KR-05-S1, Oxo Creek (KR-14), and local groundwater. The isotope sample collected from P90-8 appears to closely resemble rain water, indicative of poor isolation of the screened piezometer interval from infiltrating rain water.




Figure 15. Figure 1: δ^2 H and δ^{18} O ratios for surface water and groundwater samples (solid circles) collected in the Cache Creek catchment (TSF area) during the Aug. & Sept. 2021 monitoring events and Whitehorse GNIP data (GNIP; IAEA 2021).

Although Peel Creek contributes only approximately 9% of the Cache Creek flow following their confluence, Cache Creek's geochemistry is significantly influenced by the influx of Peel Creek at station PCC (located just downstream of the confluence mixing zone of the two watercourses). Peel Creek shows frequent historical guideline

exceedances for As, Al, Cd, Cu, Fe, and Zn, and moderate seasonal fluctuations in these concentrations. Samples collected by Water Resources Branch showed guideline exceedances for Al, As, Co, Fe, SO4, and Zn at Peel Creek Station KR-15 and Cache Creek station PCC. These exceedances indicate Peel Creek exerts a strong influence over contaminant concentrations in Cache Creek, further discussed in section 4.2. After station PCC, the streambed of Cache Creek was covered in an orange precipitate, decreasing in prevalence as flow progressed downstream.

Peel Creek does not appear to strongly impact the isotopic composition of Cache Creek after station PCC based on the close isotopic proximity of stations KR-08 and PCC, stations showing Cache Creek's pre-mixing and post-mixing conditions respectively.

Misery Creek enters Cache Creek between stations KR-27 and KR-28. Misery Creek is characterized by high As and Se along the entire flow path in the historical sampling record. Samples collected by the Branch showed increases in Cu and Al between the two stations, and comparable concentrations of As, Fe, SO₄, and Zn, which is consistent with historic data. KR-22, the furthest downstream station on Misery Creek before its confluence with Cache Creek, shows elevated Al, Cd, and Co concentrations in the historical record and in Branch 2021 samples. The concentrations of these parameters are reduced (although remaining above guideline levels) through dilution after confluence with Cache Creek. Misery Creek, and the other tributaries joining Cache Creek between stations KR-28 and KR-10 do not appear to strongly impact the isotopic composition of Cache Creek. Misery Creek exerts an influence on Cache Creek geochemistry, further discussed in section 4.3.

KR-10 is the final monitoring station before Cache Creek enters the receiving environment via Ketza River. This station shows a strong history of exceedances for As and Zn in the sampling record.

The progression in concentrations of various elements along the Cache Creek flow path is presented in Figure 16.




Figure 16. Analytical results of surface water quality along Cache Creek from August 2021 site audit samples. Sample stations compared in order of flow direction. Orange highlighted area shows influence of Peel Creek. Blue highlighted area shows influence of Misery Creek. Zinc and Copper CCME guidelines are based on hardness values.

4.2 Chemistry in the Peel Creek Sub-catchment

Most historical records pertaining to the Peel Creek sub-catchment identify KR-17 and KR-15 as background water quality sites for the Ketza River Mine due to their lack of contact with the tailings containment facility and distance from most major mine workings in the surrounding area (Tetra Tech, 2016). The validity of these sites as background water quality indicators is uncertain, as certain maps show these two sites in close proximity to PAG waste rock dump, (Gully Zone Waste Rock Dump/Pit and QB

Zone Pit) (Tetra Tech, 2016). KR-17 appears to be located topographically above any expected influence from these pits and dumps suggesting its chemistry may be a product of local area conditions in the mineralized Peel Creek Valley, though conclusions regarding trends are limited by an irregular sampling record, with fewer than 50 observations recorded for these sites from 2005-2009, largely due to winter avalanche risks in the valley

At sampling site KR-17, 100% of samples have exceeded the CCME guidelines for As (T) since sampling began in 2005. Historical concentrations of As were speculated to show a potentially increasing trend, but no level of statistical certainty could be applied (Arktis, 2020). Sulfate (T) concentrations showed a potentially decreasing trend over the same sampling record, approximately asymptotic at 200 mg/L (max 500mg/L, 2008) (Arktis, 2020). During the 2021 Branch audit, As(T) exceeded BC MOE, CCME, and CSR guidelines at KR-17 but As (D) did not exceed any guidelines. Sulfate (D) exceeded the Yukon CSR guideline.

At sampling site KR-15, 100% of samples have exceeded the CCME guidelines for As (T) since sampling began in 2005, with no evident trend (Arktis, 2020). Sulfate did not show any observable trends over the same time period, but has been observed to regularly exceed guidelines. During the 2021 Branch audit, As(T), and SO_4 (D) exceeded guidelines at KR-15.

A region showing multiple red-coloured seeps was observed originating on the south side of the stream between KR-17-DS and PCS2-DS. Discharge measurements were collected before and after these seeps joined Peel Creek, and field parameters were measured as close to the daylighting location as possible. KR-17 exact location had little flow, visually estimated at 0.003 m³/s. Immediately below KR-17, a waterfall and coarse rocky streambed caused most of the water to infiltrate in the ground, with only a trickle remaining on the surface. While there was a progressive resurgence up to 0.002 m³/s directly in the channel in the 100 m distance past the waterfall, most the flow upstream of PCS2 confluence was then coming for the red-coloured seeps, which contribution was estimated at up to 0.006 m³/s (salt dilution gauging upstream in Peel Creek upstream of PCS2 confluence returned a result of 0.008 m³/s).

A thick (~1 cm) coating of an orange precipitate was observed covering all streambed sediments in Peel Creek after the influx of the red-coloured seeps. These precipitates were observed for the entire length of Peel Creek after the influx of these seeps, and

persisted in diminishing quantities into Cache Creek after the Peel-Cache confluence. The bright red colouration of these seeps is indicative of high concentrations of Fe, among other elements. The elements contained in these red seeps may be products of the dissolution of reactive primary minerals associated with, or representative of, ore minerals. A decrease in As(D) but increase in As(T) concentrations in Peel Creek after these seeps daylight may result from an immobilization of the dissolved As from the seep and headwater as it flows onto the rocks covered by iron precipitate. Removal of dissolved As by coprecipitation or adsorption onto Fe-oxyhydroxide minerals is a well known and documented natural attenuation mechanism and seems likely in Peel Creek (Drahota 2012.). Filtration of water samples through the standard filter size used for water sampling would likely remove the majority of As associated with these Fe mineral assemblages, leaving low concentrations of As(D).

Even though there is a significant decrease of As (D), by an order of magnitude between KR-17 and KR-15 (0.022 to 0.00481 mg/L As(D) respectively), As (T) increases steadily in that section of Peel Creek. It seems that there is a source of both arsenic and iron near KR-17, which is further increased by the influx of the two red seeps.

Dissolved and total Fe concentrations also increase in the vicinity of PCS2-DS and remain consistently elevated though KR-15. Concentrations of dissolved and total As and Fe along the Peel Creek flow path are shown in Figure 17.




Figure 17 - Evolution in As(T/D) and Fe(T/D) along the Peel Creek flow path

Iron was not included in the trends analysis document produced by Arktis (2020), but if a similar relationship is observed in the sampling record between Fe and As concentrations, it is possible that the relative rates of mobilization of these elements from local reactive primary minerals will remain constant under current conditions. Dissolved and total Fe concentrations observed at KR-15 indicate a functional Fe surplus, suggesting that even if As concentrations were to increase independently of Fe in the upper reaches of Peel Creek, the As attenuation capacity of Fe has not yet been reached. The geochemical favourability of As-Fe coprecipitation or adsorption reactions will likely result in a strong reduction in dissolved As concentration as the flow path progresses if the Fe-rich conditions remain.

The red precipitates formed in Peel Creek can still be seen into Cache Creek after the confluence. It is likely that the Fe-As precipitate will continue to migrate downstream into Cache Creek. Groundwater well HYD-08-09A, located in close proximity to the upper reaches of Peel Creek, showed an isotopic and geochemical signature distinct from those of the SW sites in the area. However, groundwater wells HYD-08-10 and -11A, both upgradient of KR-15, showed similar isotopic signatures to the surface water samples. These similarities and differences may be due to the units in which these wells are screened. HYD-08-09A appears to be screened in an aquifer unit isolated from the waste rock dump, whereas HYD-08-10 and -11A appear to be screened in hydraulically connected units. The isotopic composition of KR-17DS may be the result of a mix of upstream station KR-17 with groundwater seepage (Figure 15).

All Peel Creek surface water sites assessed as part of the 2021 Branch audit (except KR-17) are located down gradient of Gully Zone Pit (Figure 14). Groundwater well HYD-08-09A, located directly down gradient of Gully Zone Pit, shows an isotopic and geochemically distinct signature from any of the SW sites in the area. If the boundaries for this rock dump proposed by Tetra Tech are correct, it is likely that the influx of contaminants into Peel Creek are the result of the QB Zone Pit.

The progression of various elements along the Peel Creek flow path is presented in Figure 18.




Figure 18. Analytical results of surface water quality along Peel Creek from August 2021 site audit samples. Sample stations compared in order of flow direction. Highlighted area shows possible influence of QB Zone Pit. Zinc and Copper CCME guidelines are based on hardness values.

4.3 Chemistry in the Misery Creek sub-catchment

There is a relative lack of historical data available on Misery Creek to assess its contribution to contaminants in Cache Creek.

Surface water quality monitoring stations KR-21, KR-18, and KR-22 are the only stations located in the Misery Creek sub-catchment, all three of which were assessed

as a part of this audit. KR-21 is located near the headwaters of the creek and is the only monitoring site out of the three previously mentioned which is currently incorporated in the C&M Monitoring Program. KR-22 is located 500 m upstream of its confluence with Cache Creek, while KR-18 is located in the headwaters of a small tributary that feeds into Misery Creek between the two other stations. A sparse historical sampling record exists for these sites, with less than one third of the number of total samples collected compared to the main sampling stations on Cache Creek (Tetra Tech 2016), largely due to avalanche risk in winter months and KR-18 and KR-22 which are no longer sampled as part of the current monitoring program. KR-18 was not sampled by Water Resources Branch or Hemmera during the 2021 audit but field parameters were collected. At both stations KR-21 and KR-22, guidelines were exceeded for As (BC-MOE, CCME, CSR), SO₄ (CSR), and Zn (CCME). Elements including Al, Cd, Co, and Cu did not exceed guidelines at KR-21, but did at KR-22. The isotopic signature between KR-21 and KR-22 appears to become less evaporated, potentially indicative of groundwater influx between the two stations. These trends suggest the tributary sampled at KR-18 is a source of Al, Cd, Co, and Cu to Misery Creek and subsequently Cache Creek as these contaminants were not observed in the upstream station KR-21. The pH at KR-18 was low (4.1-4.3 in the sampling record), which is also where the concentrations of metals were elevated. This low pH does not appear to influence Misery Creek after the convergence of the tributary and the main flow path, although the elevated concentrations of dissolved metals appear to persist into Cache Creek. As alkalinity does not undergo any drastic changes from KR-21 to KR-22, this pH neutralization is likely attributable to dilution. Figure 19 shows the progression in concentrations of various elements along the Misery Creek flow path.

A white precipitate was observed from seep sources near KR-18, persisting through the diffuse tributary flow path through local alpine wetlands into the main Misery Creek channel. Al concentrations at KR-22 were fairly high (2.69 mg Al-T/L and 0.228 mg Al-D/L) and may contribute to the production of the observed white precipitate as the pH increases from acidic to neutral. If that is the case, it is expected that other metal elements would co-precipitate along with aluminum along the Misery Creek flow path.

No groundwater monitoring stations exist in the Misery Creek sub-catchment.




Figure 19. Analytical results of surface water quality along Misery Creek from August 2021 site audit samples. Sample stations compared in order of flow direction. Highlighted area shows possible influence of KR-18. Zinc CCME guidelines are based on hardness values.

4.4 Hydrometric monitoring network

The hydrometric stations proposed by Water Resources Branch provide a means of measuring continuous stage (i.e. water level) data in addition to the regular collection of discrete discharge measurements using velocity-area method or salt dilution to inform flow rates at discrete points in time, but stage data informs overall flow over continuous time intervals.

Flow measurements should be conducted monthly alongside surface WQ sample collection at every routine monitoring site as per The Yukon Guide for Developing Water Quality Objectives and Effluent Quality Standards for Quartz Mining Projects (Yukon Government 2021B). Collection of high-quality flow measurements is critical for understanding contaminant loading and interpreting variability in water quality results.

The infrastructure described in this audit is designed to capture the full range of stage throughout the open water season on a 15 minute sampling schedule. Building a stage-discharge relationship will require regular field visits to capture accurate discharge measurements and surveying water level to benchmarks in order to correct drift and shifts in the continuous stage record. A minimum of approximately 10 hydrometric field visits at each location and at diverse flow levels (including extremes) would be necessary to establish a robust stage-discharge relationship and develop the corresponding rating curve equation that allows inference of flow between field visits, derived from the 15minute interval water level logs. Calculated continuous discharge records are also used by industry and regulators to understand overall contaminant loads in site catchments. Flow and water level data collection should follow methods and standards described in the Manual of British Columbia Hydrometric Standards, Version 2.0 (R.I.S.C. 2018).

Incorporation of continuous stage monitoring stations should be considered for at least these six essential hydrometric stations:

- KR-12 Ketza River downstream of Cache Creek
- KR-10 Cache Creek Lower
- KR-22 Misery Creek
- KR-15 Peel Creek at Road
- KR-08 Cache Creek downstream of TSF and upstream of Peel Creek
- KR-13 Cache Creek Upper

We also recommend to re-activate station KR-14 – Oxo Creek since its continuous discharge record would be beneficial to explain the increase in flow between KR-13 and KR-08 alongside other Cache Creek contributors such as the water treatment discharge (KR-09A location), diversion channels around the TSF and tailings dam seepage.

Discharge records at location KR-01 upstream of the Mill and Mine Camp are also important and we recommend collecting discrete flow measurements at the same frequency as at KR-13. However the location is not ideal for continuous stage monitoring and we have reasonable confidence in the possibility to establish a strong relationship between flows measured at KR-13 and at KR-01 and therefore produced a derived continuous discharge record at KR-01 with the KR-13 series acting as the proxy.

Discrete discharge measurements will also be important at the proposed WQ compliance station to be located between where the tailings dam seepage enters Cache Creek and station KR-08. There as well, we have reasonable confidence in the possibility to establish a strong relationship between flows measured at KR-08 and at the upstream location, eliminating the need for continuous stage monitoring at the new WQ Compliance station.

Additional continuous stations could be added later however, upon identification of further knowledge gaps; the list above is a conservative recommendation to work within resource allocation constraints.

5. Conclusions and Recommendations

Water Resources Branch carried out the 2021 Audit of the Ketza River Mine over the period of August and September 2021. Hemmera Envirochem Inc, a contractor engaged by AAM, sampled all routine surface water and groundwater monitoring sites during their August 2021 sampling event. As per the request of the Branch, stable water isotope samples were also collected from all of these sites by Hemmera to support the site investigation. Water Resources Branch collected water quality and stable water isotope samples as well as hydrology measurements at all routine and several non-routine surface water monitoring sites from August 31 to September 2, 2021, focused towards accomplishing the following objectives:

- 1) Assess the hydrology monitoring network at site as per request by AAM,
- 2) Assess the hydrology of Cache and Peel Creeks,

- 3) Evaluate potential causes of elevated sulphate (SO₄) and arsenic (As) levels observed in groundwater and surface water,
- 4) Determine if disturbed areas are influencing the chemistry of Peel Creek and,
- 5) Familiarize Branch staff with the site to provide support to AAM and future water licence application review.

A review of available historical site data was undertaken to support audit objectives. Background surface water quality sites include KR-20 (discharge from Tarn lake), KR-17 and KR-15 (Peel Creek stations), and KR-21 (Misery Creek headwaters), although the validity of these sites as unimpacted background surface water quality is uncertain. Sampling station KR-20 has historically elevated concentrations of Al, Cd, and Zn, whereas the stations on Peel Creek have elevated concentrations of As and SO_4 throughout the sampling record. The unnamed tributaries joining Cache Creek between KR-28 and KR-10 showed elevated SO_4 and dissolved metal concentrations throughout the sampling record. No mine infrastructure has yet been developed in the catchments of these three unnamed tributaries, suggesting that this region is characterized by elevated background concentrations of SO_4 and dissolved metals.

The results of the 2021 audit corroborated historical sampling records. Elevated concentrations of metals were observed in most sampling stations spread across the site.

Elevated concentrations of dissolved AI, Cd, and Zn at background station KR-20 are likely attributable to high background concentrations of these elements, or may be influenced by a pit shell located just upgradient of Tarn Lake. Groundwater monitoring wells screened in or below this pit shell showed similar geochemical and isotopic compositions to Tarn Lake, KR-20.

The Peel Creek sub catchment showed elevated concentrations of As and SO₄ at both routine stations (KR-17 and KR-15) and all non-routine stations in the main Peel Creek flow path. The three assessed major headwater seeps showed guideline exceedances of As and SO₄. These concentrations further increase in the main Peel Creek flow path after a region of minor seepage showing bright red colouration, which contributes elevated concentrations of As, Co, Fe, SO₄, and Zn. The presence of the Zone Gully Pit up gradient of these seeps suggests elevated concentrations of these elements may be the result of weathering of reactive primary minerals exposed in the waste rock dump. Trends in dissolved vs. total As, as well as the presence of red-brown precipitates

along the length of the creek, suggest that concentrations of As may be reduced between KR-17 and KR-15 through coprecipitation and adsorption of As onto Fe oxyhydroxide secondary minerals. Concentrations of total As decrease to their lowest levels in the Peel Creek flow path (although remaining above guidelines) at the point at which Peel Creek joins Cache Creek (PCC). The Fe-oxyhydroxide precipitates containing adsorbed As persist well into the Cache Creek flow path. Low As(D) concentrations (below guidelines) but high As(T) concentrations (above guidelines) persist at station KR-28, the furthest downstream site over the course of this audit.

The Misery Creek sub catchment contributes elevated concentrations of Al, As, Co, Cu, Fe, SO₄, and Zn to Cache Creek at confluence point KR-28. The majority of these elements source from a tributary creek flowing into Misery sampled by KR-18. These elements are likely representative of elevated background concentrations, as no mine structures are known to exist in the Misery Creek sub catchment.

Implementation of a continuous hydrometric stage monitoring network across the site would pair continuous water level data with data collected during routine monitoring events. High-detail hydrometric data would be provided through implementation of this network and would inform conclusions regarding contaminant loading to Ketza River and the receiving environment. However, creating a continuous flow datasets for these locations will be difficult due to the steepness and unstable channel morphology of the streams on site. Prior to proceeding with this network implementation, it is necessary to clarify the actual need for a continuous hydrometric baseline with partners and regulators of the remediation project.

Water Resources Branch recommends the following based on the results of the 2021 audit:

- 1) Collect a water sample from the creek in the adjacent watershed to Tarn Lake to see if the As exceeds the guidelines, informing background concentrations in the vicinity of Tarn Lake.
- Collect additional (quarterly) surface water quality and hydrology measurements (Velocity/Area or salt dilution Methods) upstream and downstream of the KR-16 confluence with Cache Creek to determine this tributaries effects on Cache Creek.
- 3) Conduct a review of trends in dissolved constituents in groundwater upon completion of the Ketza geochemical database audit.

- 4) Incorporate six continuous hydrometric stage monitoring stations at locations KR-12, -10, -22, -15, -08 (or -29 if location is suitable) and KR-13.
- 5) Increase groundwater sampling frequency from annual to twice annually, specifically in the spring and fall.

6. Contact Information

For more information about this report contact:

- Cole Fischer, Groundwater Technologist (Cole.Fischer@yukon.ca)
- Aaron Barker, Water Quality Technologist (<u>Aaron.Barker@yukon.ca</u>)
- Alexandre Mischler, Hydrology Technologist (alexandre.mischler@yukon.ca)
- Brendan Mulligan, Senior Scientist Groundwater (Brendan.Mulligan@yukon.ca)
- Amelie Janin, Senior Scientist Water Quality (<u>Amelie Janin@yukon.ca</u>)

References

- Arktis, 2020. Temporal Trend Analyses of Selected Surface Water Quality Analytes Ketza River Mine. Arktis Solutions and Zajdlik & Associates Inc. June 2020.
- Arktis,f 2021. Screening Contaminants of Potential Concern Ketza River Mine. Arktis solutions and Zajdlik & Associates Inc. July 2021.
- British Columbia Ministry of Environment and Climate Change Strategy. 2021. British Columbia Approved Water Quality Guidelines: Aquatic Life, Wildlife & Agriculture Guideline Summary. Water Quality Guideline Series, WQG-20. Prov. B.C., Victoria B.C.
- Canadian Council of Ministers of the Environment. 2011. Protocols Manual for Water Quality Sampling in Canada. https://ccme.ca/en/res/protocolsdocument_e_final1.0.pdf. Last accessed November 2021.
- Canadian Council of Ministers of the Environment. 2014. Canadian Water Quality Guidelines for the Protection of Aquatic Life. Retrieved from Canadian Environmental Quality Guidelines: http://ceqg-rcqe.ccme.ca/en/index.html. Last accessed November 2021.
- Canadian Council of Ministers of the Environment (CCME) (2007). A Protocol for the Derivation of Water Quality Guidelines for the Protection of Aquatic Life 2007. https://ccme.ca/en/res/protocol-for-the-derivation-of-water-quality-guidelines-for-the-protection-of-aquatic-life-2007-en.pdf
- CIRNAC (2019). Giant Mine Remediation Project Effluent Quality Criteria Report. Version 1.0, January 2019.
- Cohn TA, Kiang JE, Mason Jr RR. 2013. Estimating discharge measurement uncertainty using the interpolated variance estimator. Journal of Hydraulic Engineering; 139(5):502-10.
- Drahota, Filippi, Ettler, Rohovec, Mihaljvic, Sebek. 2012. Natural Attenuation of Arsenic in Soils Near a Highly Contaminated Historical Mine Waste Dump. Science of the Total Environment. Vol 414, 546-555p.
- EBA. 2013. Ketza River Project 2012 Hydrological Report. EBA File: V15101019.204.
- Hudson, R. and J. Fraser. 2002. Alternative methods of flow rating in small coastal streams. B.C. Ministry of Forests, Vancouver Forest Region, Nanaimo, BC. Extension Note EN-014 Hydrology. 11 p.

- International Atomic Energy Agency. Undated. Sampling Procedures for Isotope Hydrology. 8p. http://www-naweb.iaea.org/napc/ih/documents/other/Sampling%20booklet%20web.pdf. Last accessed November 2021.
- International Atomic Energy Agency (IAEA). (2020). Global Network of Isotopes in Precipitation (GNIP). Data accessed via the Water Isotope System for Data Analysis, Visualization and Electronic Retrieval (WISER) portal: https://www.iaea.org/services/networks/gnip
- Kendall and Doctor. (2004). Stable isotope applications in hydrologic studies, in Drever, J.I., ed., Surface and ground water, weathering, and soils: Treatise on Geochemistry, v. 5, p. 319-364.
- Government of Canada (GoC). 2002. Metal and Diamond Mining Effluent Regulations. SOR 2002-222. Fisheries Act. https://laws-lois.justice.gc.ca/eng/regulations/sor-2002-222/FullText.html. Last accessed December, 2021.
- Moore, R.D. 2005. Introduction to salt dilution gauging for streamflow measurement Part III: Slug injection using salt in solution. Streamline Watershed Management Bulletin 8(2):1–6.
- Sentlinger G. 2015. Introduction to Salt Dilution Gauging for Streamflow Measurement. Online: www.fathomscientific.com/introduction-to-sd-gauging/
- Tetra Tech EBA Inc. 2016. Water and Geochemistry Overview for Ketza River Phase I ESA Update and Conceptual Mine Reclamation Plan.
- Yukon Government (YG). 2002. Contaminated Sites Regulation. OIC 2002/171. Environment Act. Whitehorse. https://laws.yukon.ca/cms/images/LEGISLATION/regs/oic2002_171.pdf. Last accessed 25 November 2021.
- Yukon Government. 2020. Protocol for the Contaminated Sites Regulation under the Environment Act. https://yukon.ca/sites/yukon.ca/files/env/env-protocol-6.pdf. Last accessed 25 November, 2021
- Yukon Government (YG). 2021A. Discussion Paper to the Ketza River Working Group: Assessment and Abandoned Mines; Strategy for Protecting Receiving Waters during Care and Maintenance at Ketza River Mine. Assessment and Abandoned Mines.
- Yukon Government. 2021B. Yukon Guide for Developing Water Qulaity Objectives and Effluent Quality Standards for Quartz mining Projects. https://yukon.ca/sites/yukon.ca/files/env/env-yukon-guide-developing-water-quality-objectives-effluent-quality-standards-quartz-minig-projects.pdf. Last accessed 25 November, 2021.

Yukon Water Board. 2009. Ketza River Holdings Ltd, QZ04-063 License Conditions.

Appendices

Appendix A - Photo log

Appendix A: Photo Log

Photo 1. (KR)KR-01.

Upstream view from the left bank at the water sample station on September 2, 2021.



Photo 2. (KR) KR-01.

Downstream view from the left bank at the water sample station on September 2, 2021.



Photo 3. (KR)KR-01. Substrate at the water sample station on September 2, 2021.



Photo 4. (KR)KR-01. Right bank view from the left bank across from the water sampling station on September 2, 2021.



Photo 5. (KR)KR-01.

Left bank view from the left bank and looking downstream at the water sampling station on September 2, 2021.



Photo 6. (KR)KR-08. Upstream view from the left bank at the water sample station on August 31, 2021.



Photo 7. (KR)KR-08. Downstream view from the left bank at the water sample station on August 31, 2021.



Photo 8. (KR)KR-08. Substrate at the water sample station on August 31, 2021.



Photo 9. (KR)KR-08.

Right bank view from left bank from the water sampling station on August 31, 2021.



Photo 10. (KR)KR-08.

Left bank view from the right bank looking upstream towards the water sampling station on August 31, 2021.



Photo 11. (KR)KR-09. View of the Tailings Storage Facility towards the water treatment plant from the access road near (KR)KR-09A on September 2, 2021.



Photo 12. (KR)KR-09A. View looking upstream towards the discharge pipe at (KR)KR-09A and at (KR)KR-13 from the right bank looking upstream on September 2, 2021.



Photo 13. (KR)KR-13. Upstream view from routine sample station at the discharge of the diversion ditch into Cache Creek on September 2, 2021.



Photo 14. (KR)KR-13. Downstream view along Cache Creek from the diversion ditch discharge culvert towards routine sample stations (KR)KR-09A and (KR)KR-13 on September 2, 2021.



Photo 15. (KR)KR-14. Upstream view from the left bank at the routine sample station on September 2, 2021.



Photo 16. (KR)KR-14. Downstream view from the left bank at the routine water sample station on September 2, 2021.



Photo 17. (KR)KR-15.

Upstream view from the left bank at the water sample station on September 2, 2021.



Photo 18. (KR)KR-15.

Downstream view from the left bank at the water sample station on September 2, 2021.



Photo 19. (KR)KR-15. Substrate at the water sample station on September 2, 2021.



Photo 20. (KR)KR-15. Right bank view from left bank at the water sampling station on September 2, 2021.



Photo 21. (KR)KR-15.

Left bank view from the left bank looking towards downstream at the water sampling station on September 2, 2021.



Photo 22. (KR)KR-17.

Upstream view from the left bank at the water sample station on September 2, 2021.



Photo 23. (KR)KR-17. Downstream view from the left bank at the water sample station on August 31, 2021.



Photo 24. (KR)KR-17. Substrate at the water sample station on August 31, 2021.



Photo 25. (KR)KR-17.

Right bank view from left bank at the water sampling station on August 31, 2021.



Photo 26. (KR)KR-17.

Left bank view from the left bank looking towards downstream at the water sampling station on September 2, 2021.



Photo 27. (KR)KR-17DS.

Upstream view from the left bank at the water sample station on August 31, 2021.



Photo 28. (KR) KR-17DS.

Downstream view from the left bank at the water sample station on August 31, 2021.



Photo 29. (KR)KR-17DS.

Substrate at the water sample station on August 31, 2021.



Photo 30. (KR)KR-17DS. Right bank view from left bank at the water sampling station on August 31, 2021.



Photo 31. (KR) KR-17DS.

Left bank view from the left bank looking downstream at the water sampling station on August 31, 2021.



Photo 32. (KR)KR-17DS. Seep daylighting along right bank approximately 5 meters upstream of the water sample station on August 31, 2021.



Photo 33. (KR) KR-17DS.

Seep daylighting along the right bank approximately 1 meter upstream of the water sample station on August 31, 2021.



Photo 34. (KR)KR-17DS. Exposed right bank along Peel Creek adjacent to the water sample station on August 31, 2021.



Photo 35. (KR) KR-17DS.

Panoramic view of the exposed substrate on the right bank upstream of the water sample station on August 31, 2021.



Photo 36. (KR)KR-18. Upstream view from the right bank at the water sample station on September 1, 2021.



Photo 37. (KR)KR-18. Downstream view from the right bank at the water sample station on September 1, 2021.



Photo 38. (KR)KR-18. Substrate at the water sample station on September 1, 2021.



Photo 39. (KR)KR-18.
Right bank view from left bank at the water sampling station on September 1, 2021.



Photo 40. (KR)KR-18. Left bank view from the right bank at the water sampling station on September 1, 2021.



Photo 41. (KR)KR-18.

Downstream view from the access road downstream of the water sample station looking towards Misery Creek on September 1, 2021.



Photo 42. (KR)KR-20. Upstream view from the left bank looking towards the water sample station on September 2, 2021.



Photo 43. (KR)KR-20. Downstream view from the left bank at the water sample station on September 2, 2021.



Photo 44. (KR)KR-20. Substrate at the water sample station on September 2, 2021.



Photo 45. (KR)KR-20. Right bank view from left bank at the water sampling station on September 2, 2021.



Photo 46. (KR)KR-20. Left bank view from the left bank looking towards downstream at the water sampling station on September 2, 2021.



Photo 47. (KR)KR-21. Upstream and right bank view from the right bank at the water sample station on September 1, 2021.



Photo 48. (KR)KR-21. Downstream view from the right bank at the water sample station on September 1, 2021.



Photo 49. (KR)KR-21. Substrate at the water sample station on September 1, 2021.



Photo 50. (KR)KR-21. Left bank view from the left bank looking towards downstream at the water sampling station on September 1, 2021.



Photo 51. (KR)KR-22. Upstream view from the right bank at the water sample station on September 1, 2021.



Photo 52. (KR)KR-22. Downstream view from the right bank at the water sample station on September 1, 2021.



Photo 53. (KR)KR-22. Substrate at the water sample station on September 1, 2021.



Photo 54. (KR)KR-22. Right bank view from the right bank at the water sampling station on September 1, 2021.



Photo 55. (KR)KR-22.

Left bank view from the right bank looking towards downstream at the water sampling station on September 1, 2021.



Photo 56. (KR)KR-22.

Substrate upstream along right bank about 5 meters upstream from the right bank looking upstream on September 1, 2021.



Photo 57. (KR)KR-23. Upstream view from the right bank at the water sample station on September 1, 2021.



Photo 58. (KR)KR-23. Downstream view from the right bank at the water sample station on September 1, 2021.



Photo 59. (KR)KR-23. Substrate at the water sample station on September 1, 2021.



Photo 60. (KR)KR-23.
Right bank view from the right bank looking downstream at the water sampling station on September 1, 2021.



Photo 61. (KR)KR-23.

Left bank view from the right bank looking towards downstream at the water sampling station on September 1, 2021.



Photo 62. (KR)KR-23. Collapsed adit upstream of the water sample station on September 1, 2021.



Photo 63. (KR)KR-23.

Water emerging from the adit upstream of the water sample station on September 1, 2021.



Photo 64. (KR)KR-23.

Downstream view of the water emerging from the adit looking towards the water sample station on September 1, 2021.



Photo 65. (KR)KR-23.

Downstream view of water flowing along the access road downstream of the water sampling station on September 1, 2021.



Photo 66. (KR)KR-23.

Collapsed culvert downstream of the water sampling station causing diversion of water flow down the access road on September 1, 2021.



Photo 67. (KR)KR-26. Upstream view from the right bank at the water sample station on September 1, 2021.



Photo 68. (KR)KR-26. Downstream view from the right bank at the water sample station on September 1, 2021.



Photo 69. (KR)KR-26. Substrate at the water sample station on September 1, 2021.



Photo 70. (KR)KR-26. Right bank view from right bank looking downstream at the water sampling station on September 1, 2021.



Photo 71. (KR)KR-26. Left bank view from the right bank at the water sampling station on September 1, 2021.



Photo 72. (KR)KR-27. Upstream view from the right bank at the water sample station on September 1, 2021.



Photo 73. (KR)KR-27. Downstream view from the right bank at the water sample station on September 1, 2021.



Photo 74. (KR)KR-27. Substrate at the water sample station on September 1, 2021.



Photo 75. (KR)KR-27.

Right bank view from right bank looking upstream towards the water sampling station on September 1, 2021.



Photo 76. (KR)KR-27. Left bank view from the right bank looking upstream towards the water sampling station on September 1, 2021.




Photo 77. (KR)KR-28. Upstream view from the right bank at the water sample station on September 1, 2021.



Photo 78. (KR)KR-28. Downstream view from the right bank at the water sample station on September 1, 2021.



Photo 79. (KR)KR-28. Substrate at the water sample station on September 1, 2021.



Photo 80. (KR)KR-28. Right bank view from right bank looking upstream at the water sampling station on September 1, 2021.



Photo 81. (KR)KR-28. Left bank view from the right bank at the water sampling station on September 1, 2021.



Photo 82. PS1430. Upstream view looking towards the water sample station where the water emerges from the adit on September 1, 2021.



Photo 83. PS1430.

Downstream view from the right bank at the water sample station on September 1, 2021.



Photo 84. PS1510. Entrance of adit on September 1, 2021.



Photo 85. (KR)KR-28. Drainage pipe from adit with no discharge on September 1, 2021.



Photo 86. PCC. Upstream view from the leftt bank at the water sample station on August 31, 2021.



Photo 87. PCC.

Downstream view from the left bank at the water sample station on August 31, 2021.



Photo 88. PCC. Substrate at the water sample station on August 31, 2021.



Photo 89. PCC. Right bank view from the left bank looking downstream at the water sampling station on August 31, 2021.



Photo 90. PCC. Left bank view from the right bank at the water sampling station on August 31, 2021.



Photo 91. PS2DS.

Upstream view from the left bank at the water sample station on August 31, 2021.



Photo 92. PS2DS.

Downstream view from the right bank at the water sample station on August 31, 2021.



Photo 93. PS2DS.

Substrate at the water sample station on August 31, 2021.



Photo 94. PS2DS. Right bank view from left bank at the water sampling station on August 31, 2021.



Photo 95. PS2DS. Left bank view from the right bank at the water sampling station on August 31, 2021.



Photo 96. PS3DS. Upstream view from the right bank at the water sample station on August 31, 2021.



Photo 97. PS3DS.Downstream view from the left bank at the water sample station on August 31, 2021.



Photo 98. PS3DS.

Substrate at the water sample station on August 31, 2021.



Photo 99. PS3DS.

Right bank view from the left bank at the water sampling station on August 31, 2021.



Photo 100. PS3DS. Left bank view from the right bank at the water sampling station on August 31, 2021.



Photo 101. Seep 2. View of seep on left bank and where it merges with Peel Creek from the right bank on August 31, 2021.



Photo 102. Seep 2. View of seep on the left bank and the uphill area on August 31, 2021.



Photo 103. Seep 2.

Upstream view where the seep daylights from the left bank at the water sample station on August 31, 2021.



Photo 104. Seep 2.

Downstream view from the left bank at the water sample station on August 31, 2021.



Photo 105. Seep 2. Substrate at the water sample station on August 31, 2021.



Photo 106. Seep 2. Right bank view from left bank at the water sampling station on August 31, 2021.



Photo 107. Seep 3. Upstream view where seep daylights from the left bank at the water sample station on August 31, 2021.



Photo 108. Seep 3.

Downstream view from the left bank at the water sample station on August 31, 2021.



Photo 109. Seep 3.
Substrate at the water sample station on August 31, 2021.



Photo 110. Seep 3. Right bank view from the left bank at the water sampling station on August 31, 2021.



Photo 111. Seep 3. Left bank view from the left bank looking downstream at the water sampling station on August 31, 2021.



Photo 112. Cache Creek Tributary 1 (CCT1). Upstream view from the left bank at the water sample station on September 1, 2021.



Photo 113. Cache Creek Tributary 1 (CCT1).

Downstream view from the left bank at the water sample station on September 1, 2021.



Photo 114. Cache Creek Tributary 1 (CCT1). Substrate at the water sample station on September 1, 2021.



Photo 115. Cache Creek Tributary 1 (CCT1).

Right bank view from the left bank looking downstream at the water sampling station on September 1, 2021.



Photo 116. Cache Creek Tributary 1 (CCT1). Left bank view from the Left bank at the water sampling station on September 1, 2021.



Photo 117. Cache Creek Tributary 2 (CCT2).

Upstream view from the left bank approximately 5 meters upstream from the water sample station on September 1, 2021.



Photo 118. Cache Creek Tributary 2 (CCT2). Downstream view from the left bank towards the water sample station on September 1, 2021.



Photo 119. Cache Creek Tributary 2 (CCT2). Substrate at the water sample station on September 1, 2021.



Photo 120. Cache Creek Tributary 2 (CCT2). Right bank view from right bank looking downstream towards the water sampling station on September 1, 2021.



Photo 121. Cache Creek Tributary 2 (CCT2).

Left bank view from the left bank looking downstream towards the water sampling station on September 1, 2021.



Photo 122. Cache Creek Tributary 3 (CCT3). Upstream view from the right bank at the water sample station on September 1, 2021.



Photo 123. Cache Creek Tributary 3 (CCT3).

Downstream view from the right bank at the water sample station on September 1, 2021.



Photo 124. Cache Creek Tributary 3 (CCT3). Substrate at the water sample station on September 1, 2021.



Photo 125. Cache Creek Tributary 3 (CCT3).

Right bank view from right bank looking downstream at the water sampling station on September 1, 2021.



Photo 126. Cache Creek Tributary 3 (CCT3). Left bank view from the right bank at the water sampling station on September 1, 2021.



Photo 127. Tarn Lake.
Precipitates observed along shoreline on September 2, 2021.



Photo 128. Tarn Lake. Precipitates observed along shoreline on September 2, 2021.




Photo 129. Tarn Lake. Precipitates observed along shoreline on September 2, 2021.



Photo 130. Tarn Lake. Precipitates observed along the shoreline on September 2, 2021.



Photo 131. Tarn Lake.


View from the access road adjacent to the lake looking towards the tailings storage facility on September 2, 2021.




Photo 132. Seep in the Misery Creek valley. View from the access road adjacent to the lake looking towards the tailings storage facility on September 2, 2021.



Appendix B - Site maps showing disturbance features and AECs/APECs





Appendix C – Water Licence QZ04-063

YUKON WATER BOARD

Pursuant to the Waters Act and Regulation, the Yukon Water Board, hereinafter referred to as the Board, hereby grants to

Ketza River Holdings Ltd. Suite 540 - 688 West Hastings St. Vancouver, BC V6P 1P1

hereinafter called the Licensee, the right to use water and deposit a waste subject to the restrictions and conditions contained in the *Waters Act* and *Regulation* made hereunder and subject to and in accordance with the conditions specified in this licence.

Licence Number: QZ04-06	Water Management Area: 02 Yukon
Licence Type: A	Nature of Undertaking: Quartz Mining
Water Source: Cache Creek	Tributary of: Ketza River
Minimum Latitude: 61° 25	Maximum Latitude: 61° 26'
Minimum Longitude: 132°	14' Maximum Longitude: 132° 19'
Purpose: To store water in,	and discharge water from, an existing tailings impoundment.
Effective Date of Licence:	The date that the signature of the Chairperson of the Yukon Water Board is affixed.
Expiry Date of Licence:	December 31, 2009
Approved this day	
of, 2007 Witness	Minister, Executive Council Office
Issued this day of , 2007	YUKON WATER BOARD
Witness	Chairperson

PART A - GENERAL CONDITIONS

1. Definitions

a) "Act" means the Waters Act and any amendments thereto.



"Application" collectively means Water Use Application QZ04-063 and any additional submissions and/or revisions submitted to the Board by the Licensee up to the date of the Board's decision to issue this licence.

- c) "Board" means the Yukon Water Board.
- d) "Inspector" means any person designated as an Inspector under the Act.
- e) "Regulation" means the Waters Regulation.
- f) "Spill Response Plan" means the Emergency Response Plan (ERP), Ketza River Mine Site, that was submitted as a component of the Application and included in Water Use Register QZ04-063 as exhibit 1.5.5, and any subsequent revisions.
- g) "Waste" means any substance defined in Section 2 of the Act.
- h) "Dam Safety Guidelines" means the Dam Safety Guidelines issued by the Canadian Dam Association (1999) or its most recent revision.

Representations, Warranties and Undertakings



The Board has relied on the representations, warranties and undertakings provided by the Licensee in the material filed in the Application. Such representations, warranties and undertakings are considered by the Board to be a part of the licence, but shall be subject to, and may be modified by, the conditions of the licence.

3. Where there is a discrepancy between the Application and the conditions of this licence, the conditions of this licence shall prevail. - Ricensee review many documentation

Other Uses

- 4. If, subsequent to the issuing of this licence, the Licensee uses water and/or deposits waste in one or more ways not authorized in this licence, and the combined effect of those uses and/or deposits of wastes, as determined by an inspector:
 - a) has no potential for significant adverse environmental effects;
 - b) does not interfere with existing rights of other water users or waste depositors; and

Ketza River Holdings Ltd. QZ04-063 Licence Conditions

c) satisfies the criteria set out in column 2 of Schedule 7 of the Regulation, then no amendment to this licence will be required for that use of water and/or deposit of waste.

- No condition of this licence limits the application of any other federal, territorial, first Other Laws
- All work authorized by this licence shall occur on property that the Licensee has the right to enter upon and use for that purpose.

- Where any direction, notice, order, or report under this licence is required to be in Writing, it shall be given: Correspondence shall be given:
- a) To the Licensee, if delivered, faxed or mailed by registered mail to the following address:

Ketza River Holdings Ltd. Suite 540 - 688 West Hastings St. Vancouver, BC V6P 1P1

fax: 604 688 9426

and shall be deemed to have been given to the Licensee on the day it was delivered or faxed, or seven days after the day it was mailed, as the case may be.

b) To the Board, if delivered, faxed or sent by registered mail to the following address:

Yukon Water Board Suite 106, 419 Range Road Whitehorse, Yukon Y1A 3V1

fax: 867 456 3890

and shall be deemed to have been given to the Board on the day it was delivered or faxed, or seven days after the day it was mailed, as the case may be.

Non-Compliance

8. In the event that the Licensee fails to comply with any condition of this licence, the Board may, subject to the Act, cancel the licence.

Deleterious Substances

 Except as otherwise authorized by this licence, deleterious substances shall be used, transported, stored and disposed of in such a manner that they are not deposited in, or allowed to be deposited in, any waters.

Term of Licence

10. The term of this licence is from the effective date to December 31, 2009.

Reports

- 11. All monitoring data, reports, plans, studies, study results, designs or manuals required by this licence shall be submitted to the Board in an unbound printed form that is reproducible by standard photocopier and shall be accompanied by 5 copies.
- 12. All monitoring data, reports, plans, designs or manuals shall also be submitted in digital form, using an IBM compatible format that is readable using commonly available software.

Annual Reports

- 13. Annual reports shall be submitted to the Board by the Licensee. The first report shall be for the period from the effective date of the licence to December 31, 2008, and the next report will be for the calendar year 2009. Annual reports will be submitted to the Board on or before February 28 of the following year.
- 14. Annual reports shall include the information required by this licence and by the Regulation, including, but not necessarily limited to:
 - a) summaries of all data generated as a result of the monitoring requirements of this licence, including analysis and interpretation by a qualified individual or firm and a discussion of any variances from base line conditions or from previous years' data; and
 - a detailed record of any major maintenance work carried out or planned to be carried out that could have an impact on water.

Monthly Reports

15. Unless otherwise specified in this licence, the Licensee shall forward to the Board a copy of all data collected as part of the monitoring programs of this licence no more than 30 days after the conclusion of the month in which that data was collected.

Ketza River Holdings Ltd. OZ04-063 Licence Conditions

Spills and Unauthorized Discharges

- 16. The Licensee shall keep the Spill Response Plan current Any revisions to the plan will be submitted to the Board within 10 days of the revision.
- 17. The Licensee shall immediately contact the 24-hour Yukon Spill Report telephone number (867) 667-7244 and implement the most recent spill contingency plan that has been filed with the Board, should a spill or an unauthorized discharge occur. A detailed written report on any such event, including but not limited to, dates, quantities, parameters, causes and other relevant details and explanations, shall be delivered to the Board not later than 10 days after its occurrence.

Hazardous Materials Storage

- 18. A complete inventory of chemicals, fuels, oils, lubricants and other hazardous materials relating to the water uses authorized by this licence shall be maintained by the Licensee.
- Hazardous materials shall be stored or transferred a minimum of 30 metres from any watercourse.

Care and Maintenance

20. Throughout the term of this licence, the Licensee shall maintain all works in good order.

PART B - SECURITY

21. Within 60 days of the effective date of this licence, the Licensee shall provide security in the amount of three million, eighty seven thousand, six hundred dollars (\$3,087,600). The form of security shall be in accordance with the Regulation.

PART C - OPERATING CONDITIONS

- 22. The Licensee is hereby authorized to store water within an existing tailings impoundment and to deposit a waste in the form of controlled discharge from the tailings impoundment, as described in the Application, and subject to the conditions of this licence. Where there is a discrepancy between the Application and this licence, the terms of this licence shall prevail.
- Except as authorized by this licence, no Waste shall enter any watercourse as a result of any operation carried out by the Licensee.

PART D - EFFLUENT QUALITY STANDARDS

24. At monitoring stations KR-04-N3, KR-05-S2 and KR-9a, no waste discharge shall exceed the following limits:

Parameter	Maximum Concentration in a Grab Sample		
Total Arsenic	0.5 mg/L	di daw	
Total Copper	0.3 mg/L		
Total Cyanide	1.0 mg/L	after it	
Total Lead	0.2 mg/L	enolousal	
Total Nickel	0.5 mg/L	entra A P	
Total Zinc	0.5 mg/L	mission	
Total Ammonia	1.0 mg/L	nazati 0	
Total Suspended Solids	15.0 mg/L	watero	
рН	>6.5	M hou sag	

25. Any discharge to a watercourse must meet a bioassay standard of a 96-hour LC₅₀ bioassay using Rainbow Trout.

PART E - MODIFICATION AND CONSTRUCTION

- 26. Where modifications are required to be made to existing facilities and structures authorized by this licence, and providing that those modifications would not otherwise require a water use licence, then the Licensee shall submit plans, specifications and construction schedules for any such modifications no less than 90 days prior to the start of the construction work.
- 27. All designs shall be sealed by a Professional Engineer licenced to practice in Yukon.
- 28. At least 10 days prior to the proposed date of commencement of construction of minor modifications, the Licensee shall submit to the Board a written notification, together with a detailed construction schedule and the name and contact number(s) of the construction superintendent.
- 29. Where site conditions require minor modifications to the designs submitted to the Board, the Licensee shall notify the Board, in advance, of the details of the modifications or variations from final detailed designs, specifications and quality assurance/quality control procedures previously submitted to the Board. The notice shall include an explanation of the

reasons for the change and an assessment of the potential impact on the performance of the works. The notice shall be sealed by a Professional Engineer licenced to practice in Yukon.

- 30. As-constructed (record) drawings and construction reports, including quality assurance and quality control documentation, for all structures and facilities shall be submitted to the Board within ninety days of the completion of construction. Each submission shall be sealed by a Professional Engineer licenced to practice in Yukon.
- No later than September 30, 2008, the Licensee shall complete the construction of a supporting toe berm along the North Dam, as described in the Application.

PART F - DECOMMISSIONING

Final Closure and Reclamation Plan

- 32. A Final Closure and Reclamation Plan shall be prepared and submitted to the Board by January 31, 2009. The plan shall define the conditions under which final closure and reclamation will commence. The plan shall be premised on the following objectives:
 - a) Maintain the long term physical stability of the North and South Dams;
- b) Maintain the long term physical stability of water diversions; and
 - Ensure that effluent standards required by this licence are met at all discharges to any receiving waters.
- Subject to required assessments, authorizations or approvals, the Licensee shall implement the Final Closure and Reclamation Plan.
- 34. In the event that final closure occurs prior to the submission of the Final Closure and Reclamation Plan, then the Licensee will, at a minimum, and subject to the appropriate authorizations and approvals:
 - a) drain the tailings pond;
 - b) recontour the tailings to promote surface shedding of precipitation;
 - c) construct a dry cover over the tailings;
 - d) lower the spillway invert to allow the tailings pond to be free draining; and
 - e) upgrade the diversions to accommodate extreme precipitation events.

PART G - MONITORING AND SURVEILLANCE

 The Licensee shall comply with the water quality monitoring program contained in Schedule A of this licence.

Ketza River Holdings Ltd. QZ04-063 Licence Conditions

36. Monitoring and sampling shall be carried out in accordance with the procedures and standards described in:

Murray 1

- a) Guidance Document for the Sampling and Analysis of Metal Mining Effluents, April 2001, (Report: EPS 2/MM/5), Minerals and Metals Division, Environment Canada, and
- Guidance Document for Flow Measurement of Metal Mining Effluents, April 2001, (Report: EPS 2/MM/4), Minerals and Metals Division, Environment Canada, and.
- Standard Guide for Sampling Ground-Water Monitoring Wells, ASTM D4448-01, ASTM International, PA, USA.
- 37. Within 60 days of the effective date of this licence, the Licensee shall provide coordinates for any monitoring points listed in Schedule A, Part 1 for which coordinates are not already indicated.

Sediment, Periphyton and Benthic Invertebrate Monitoring

- 38. Once during the term of the licence, the Licensee shall carry out a sediment, periphyton and benthic invertebrate monitoring program, with sampling and analysis conducted as described below at sampling stations KR-08, KR-10, KR-11, KR-12 and KR-14. The study will be carried out by persons qualified to do so by education and/or experience. The results of the program will be included in the next annual report.
 - a) Sediment sampling shall be carried out as follows:
 - i) sediment samples shall be collected in replicates of three from within the active channel, directly into high density plastic sample jars, using an aluminum or Teflon scoop.
 - Samples shall be dried and screened, using sieves at ASTM mesh numbers 10, 20, 40, 60, 100, 140 and 270 (ASTM-E11-61) and the fraction weights shall be recorded.
 - iii) A sub-sample composed of material passing through the 100 mesh number sieve shall be analyzed for metals by a 33 element ICP scan. Loss on ignition shall also be determined by heating the sample to 600 degrees C.
 - b) Benthic invertebrate sampling shall be carried out as follows:
 - Three replicate samples shall be taken by a circular Hess sampler (0.0934 m²) or Waters and Knapp sampler (0.089 m²) equipped with a 250 μm mesh net.
 - Samples shall be preserved with 10% formalin solution, and identified to the lowest possible taxon (usually genus) and counted.

Ketza River Holdings Ltd. QZ04-063 Licence Conditions

- iii) Stream information collected at the time of the benthos collection shall include velocity, depth, temperature, substrate conditions and riparian conditions.
- c) Periphyton sampling shall be carried out as follows:
 - Samples shall be collected from rock by surface scraping (3 or more rocks combined) and the total surface area of rock scraped at that station shall be recorded.
 - ii) Each sample shall be preserved with Lugols solution.
 - iii) Each sample shall be enumerated and identified to the lowest taxonomic level.
 - iv) The results shall include the date of completion, the company performing the identification, enumerations and identifications per station, method used to perform sorting and analysis of data, and resources used for identifications.

Physical Inspections and Monitoring

- 39. An annual inspection of all earthworks shall be carried out in accordance with the Dam Safety Guidelines by a Professional Engineer licenced to practice in Yukon. A report on the inspection, prepared by the Professional Engineer, shall be submitted as a part of the annual report. The report shall document the inspection locations and methodologies, the results of the inspection, all problems identified, and remedial measures recommended. The status of any remedial measures recommended in the previous year's report shall be appended to the report together with an explanation regarding any recommendation not implemented.
- 40. Details of any maintenance, inspection and/or surveillance activities undertaken in the previous year in relation to dam safety shall be included in the annual report.

QZ04-063 SCHEDULE A

SCHEDULE A, PART I MONITORING STATIONS

Surface Water Monitoring Stations

Station	Description	Latitude	Longitude
KR-01	Cache Creek, upstream of mill and tailings pond	61° 31.7912'	132° 16.1384'
KR-04-N2	North Dam seepage discharge to Cache Creek	61° 32.2104'	132° 14.6078'
KR-04-N3	South Dam seepage discharge to Cache Creek	61° 32.21'	132° 15.2'
KR-05-S1	Surface discharge to Cache Creek	61° 32.0582'	132° 14.9534'
KR-05-S2	Surface discharge to Cache Creek	61° 32.052'	132° 15.157'
KR-08	Cache Creek, downstream of Oxo Creek	61° 32.5808'	132° 14.0366′
KR-09	Tailings Impoundment	61° 32.0204'	132° 15.1976'
KR-09A	Discharge from Tailings Impoundment	oriumique na filiva	radiagos magar
KR-10	Cache Creek, upstream of Ketza River	61° 32.8995'	132° 9.7545'
KR-11	Ketza River, upstream of Cache Creek confluence	61° 33.9895'	132° 9.6051'
KR-12	Ketza River, downstream of Cache Creek confluence	61° 34.5685'	132° 10.1996′
KR-13	Cache Creek adjacent to mill/tailings	61° 32.0174'	132° 15.2018'
KR-14	Oxo Creek above Cache Creek	61° 32.0102'	132° 14.7302'
KR-15	Peel Creek above Cache Creek	61° 32.552'	132° 14.7062'
KR-16	Unnamed tributary of Cache Creek, above mine site	61° 32.0192′	132° 17.0486'
KR-50	Cache Creek at upstream end of Campbell Highway culvert		

Ketza River Holdings Ltd. QZ04-063 Licence Conditions

Groundwater Monitoring Stations

Station	Description	Latitude	Longitude
P90-7A	South Dam		Stations
P90-7B	South Dam	Months and Water	
P90-7C	South Dam	(110,000)	
P90-8	Knoll between dams		19-21
P90-9	Knoll between dams	99 (3)	311177
P96-11A	North Dam	7/1	Espito A
P96-11 B	North Dam	40	1:5-50-21
P96-11C	North Dam		111-01-11
P96-12A	South Dam		10-2
P96-12B	South Dam		
P96-12C	South Dam	011	80-8

SCHEDULE A, PART II MONITORING SCHEDULE FREQUENCY LEGEND

Symbol	Frequency	М	KR-14
W	Weekly	3/5	ICE-15
WD	Weekly when discharging	M	KR-16
BW	Bi-weekly	M	95-3EX
M	Monthly	M	A7-999-7A
BM	Bi-Monthly	-14	P90-7B

SCHEDULE A, PART III MONITORING SCHEDULE

Monitoring Stations	Parameters			
	Metals and Water Chemistry *	Water Level	Flow	
KR-01	M	-	-	
KR-04-N2	BW		BW	
KR-04-N3	BW		BW	
KR-05-S1	BW		BW	
KR-05-S2	BW	1100/01/05/01	BW	
KR-08	M	- 100000	- 211-01	
KR-09	M	W	-	
KR-09A	WD	2000 404 00	WD	
KR-10	M	- 1000/12 1000 2/01		
KR-11	M	-	-	
KR-12	M	- SCHEDI	-	
KR-13	M	MONITORING SCHED	-	
KR-14	M	Frequency	- lodmy?	
KR-15	M	Vicelty -	- VI	
KR-16	M	Weekly when dischargi	- aw	
KR-50	M	- yldow-ill	- 978	
P90-7A	M	BM	- N	
P90-7B	M	BM	- M8	
P90-7C	M	BM	-	
P90-8	M	BM	-	
P90-9	M	BM	-	

Monitoring Stations	Parameters		
	Metals and Water Chemistry *	Water Level	Flow
P96-11A	M	ВМ	- 1
P96-11B	M	ВМ	-
P96-11C	M	ВМ	-
P96-12A	M	ВМ	-
P96-12B	M	ВМ	-
P96-12C	M	ВМ	-

^{*} ICP Total Metals by Low Method Detection Limits, ICP Dissolved Metals by Low Method Detection Limits, Hardness, Total Suspended Solids, Total Dissolved Solids, Total Alkalinity, Total Sulphate, Nitrogen-Nitrate, Nitrogen-Nitrite.

Ketza River Holdings Esd. OZ04-063 Licence Conditions

Page 12 of 12

	Parimotes	
	Want Level	
	141	
	3/48	
	3/81	
	161	
	Mile	
	181	

ICP Total Metals by Low Method Detection Limits, ICP Breathod Metals by Low Method Detection Limits, Hardness, Total Suspended Solids, Total Disnolved Solids, Total Alkalinity, Total Sulphate, Nitrogen-Nitrose, Nitrogen-Nitrose

Appendix D – Water Quality Lab Raw Data



Your Project #: 2021-Ketza Your C.O.C. #: C#644610-01-01

Attention: Stephanie Lyons

Government of Yukon – Dept of ENV Box 2703 Whitehorse, YT Canada Y1A2C6

Report Date: 2021/09/10

Report #: R3070012 Version: 1 - Final

CERTIFICATE OF ANALYSIS

BV LABS JOB #: C165062 Received: 2021/09/02, 16:11

Sample Matrix: Water # Samples Received: 10

	Date	Date		
Quantity		Analyzed	Laboratory Method	Analytical Method
10	N/A	2021/09/04	BBY6SOP-00026	SM 23 2320 B m
10	N/A	2021/09/09	BBY6SOP-00011 / BBY6SOP-00017	SM23-4500-CI/SO4-E m
10	N/A	2021/09/07	CAL SOP-00270	SM 23 4500-CN m
10	N/A	2021/09/07	CAL SOP-00270	SM 23 4500-CN m
4	N/A	2021/09/07		Auto Calc
6	N/A	2021/09/10		Auto Calc
4	N/A	2021/09/07	AB SOP-00063	SM 23 3500-Cr B m
6	N/A	2021/09/09	AB SOP-00063	SM 23 3500-Cr B m
9	N/A	2021/09/09	AB SOP-00087	MMCW 119 1996 m
1	N/A	2021/09/10	AB SOP-00087	MMCW 119 1996 m
10	N/A	2021/09/04	BBY6SOP-00026	SM 23 2510 B m
10	N/A	2021/09/10	BBY6SOP-00048	SM 23 4500-F C m
10	N/A	2021/09/07	BBY WI-00033	Auto Calc
10	N/A	2021/09/07	BBY WI-00033	Auto Calc
8	2021/09/07	2021/09/07	AB SOP-00084	BCMOE BCLM Oct2013 m
2	2021/09/10	2021/09/10	AB SOP-00084	BCMOE BCLM Oct2013 m
4	2021/09/07	2021/09/07	AB SOP-00084	BCMOE BCLM Oct2013 m
2	2021/09/07	2021/09/10	AB SOP-00084	BCMOE BCLM Oct2013 m
4	2021/09/10	2021/09/10	AB SOP-00084	BCMOE BCLM Oct2013 m
10	N/A	2021/09/07	BBY WI-00033	Auto Calc
10	N/A	2021/09/04	BBY7SOP-00002	EPA 6020b R2 m
1	2021/09/03	2021/09/04	BBY7SOP-00003 / BBY7SOP-00002	EPA 6020b R2 m
10	N/A	2021/09/07	BBY WI-00033	Auto Calc
9	N/A	2021/09/03	BBY7SOP-00002	EPA 6020b R2 m
10	N/A	2021/09/09	BBY6SOP-00016	SM 23 4500-N C m
10	N/A	2021/09/09	AB SOP-00007	SM 23 4500 NH3 A G m
10	N/A	2021/09/03	BBY6SOP-00010	SM 23 4500-NO3- I m
10	N/A	2021/09/03	BBY6SOP-00010	SM 23 4500-NO3- I m
10	N/A	2021/09/04	BBY WI-00033	Auto Calc
10	N/A	2021/09/02	BBY7 WI-00004	SM 23 3030B m
	10 10 10 10 4 6 4 6 9 1 10 10 10 10 10 10 10 10 10 10 10 10 1	10 N/A 10 N/A 10 N/A 10 N/A 4 N/A 6 N/A 4 N/A 6 N/A 9 N/A 1 N/A 10 N/A 10 N/A 10 N/A 10 N/A 2021/09/07 2 2021/09/07 2 2021/09/07 2 2021/09/10 4 2021/09/07 2 2021/09/07 4 2021/09/07 10 N/A 10 N/A 1 2021/09/03 10 N/A 10 N/A 10 N/A 10 N/A 10 N/A 10 N/A	Quantity Extracted Analyzed 10 N/A 2021/09/04 10 N/A 2021/09/07 10 N/A 2021/09/07 10 N/A 2021/09/07 10 N/A 2021/09/07 4 N/A 2021/09/07 6 N/A 2021/09/09 9 N/A 2021/09/09 1 N/A 2021/09/07 2 2021/09/07 2021/09/07 2 2021/09/07 2021/09/07 2 2021/09/07 2021/09/10 4 2021/09/07 2021/09/07 10 N/A 2021/09/07 10 N/A 2021/09/07 <td>Quantity Extracted Analyzed Laboratory Method 10 N/A 2021/09/04 BBY6SOP-00026 10 N/A 2021/09/09 BBY6SOP-00011 / BBY6SOP-00017 10 N/A 2021/09/07 CAL SOP-00270 10 N/A 2021/09/07 CAL SOP-00270 4 N/A 2021/09/07 AB SOP-00063 6 N/A 2021/09/09 AB SOP-00063 9 N/A 2021/09/09 AB SOP-00087 1 N/A 2021/09/09 AB SOP-00087 10 N/A 2021/09/09 AB SOP-00087 10 N/A 2021/09/07 BBY WI-00033 8 2021/09/07 2021/09/07 AB SOP-00084 2 2021/09/07 2021/09/07 AB SOP-00084 <</td>	Quantity Extracted Analyzed Laboratory Method 10 N/A 2021/09/04 BBY6SOP-00026 10 N/A 2021/09/09 BBY6SOP-00011 / BBY6SOP-00017 10 N/A 2021/09/07 CAL SOP-00270 10 N/A 2021/09/07 CAL SOP-00270 4 N/A 2021/09/07 AB SOP-00063 6 N/A 2021/09/09 AB SOP-00063 9 N/A 2021/09/09 AB SOP-00087 1 N/A 2021/09/09 AB SOP-00087 10 N/A 2021/09/09 AB SOP-00087 10 N/A 2021/09/07 BBY WI-00033 8 2021/09/07 2021/09/07 AB SOP-00084 2 2021/09/07 2021/09/07 AB SOP-00084 <



Your Project #: 2021-Ketza Your C.O.C. #: C#644610-01-01

Attention: Stephanie Lyons

Government of Yukon – Dept of ENV Box 2703 Whitehorse, YT Canada Y1A2C6

Report Date: 2021/09/10

Report #: R3070012 Version: 1 - Final

CERTIFICATE OF ANALYSIS

BV LABS JOB #: C165062 Received: 2021/09/02, 16:11

Sample Matrix: Water # Samples Received: 10

		Date	Date		
Analyses	Quantity	Extracted	Analyzed	Laboratory Method	Analytical Method
pH @25°C (5)	10	N/A	2021/09/04	BBY6SOP-00026	SM 23 4500-H+ B m
Total Dissolved Solids - Low Level (1)	10	2021/09/05	2021/09/05	AB SOP-00065	SM 23 2540 C m
Total Kjeldahl Nitrogen (Total)	10	N/A	2021/09/09	BBY WI-00033	Auto Calc
Total Phosphorus Low Level Dissolved (1, 6)	10	2021/09/08	2021/09/08	AB SOP-00024	SM 23 4500-P A,B,F m
Total Phosphorus Low Level Total (1)	10	2021/09/08	2021/09/08	AB SOP-00024	SM 23 4500-P A,B,F m
Total Suspended Solids (NFR)	10	2021/09/07	2021/09/08	BBY6SOP-00034	SM 23 2540 D m

Remarks:

Bureau Veritas is accredited to ISO/IEC 17025 for specific parameters on scopes of accreditation. Unless otherwise noted, procedures used by Bureau Veritas are based upon recognized Provincial, Federal or US method compendia such as CCME, MELCC, EPA, APHA.

All work recorded herein has been done in accordance with procedures and practices ordinarily exercised by professionals in Bureau Veritas' profession using accepted testing methodologies, quality assurance and quality control procedures (except where otherwise agreed by the client and Bureau Veritas in writing). All data is in statistical control and has met quality control and method performance criteria unless otherwise noted. All method blanks are reported; unless indicated otherwise, associated sample data are not blank corrected. Where applicable, unless otherwise noted, Measurement Uncertainty has not been accounted for when stating conformity to the referenced standard.

Bureau Veritas liability is limited to the actual cost of the requested analyses, unless otherwise agreed in writing. There is no other warranty expressed or implied. Bureau Veritas has been retained to provide analysis of samples provided by the Client using the testing methodology referenced in this report. Interpretation and use of test results are the sole responsibility of the Client and are not within the scope of services provided by Bureau Veritas, unless otherwise agreed in writing. Bureau Veritas is not responsible for the accuracy or any data impacts, that result from the information provided by the customer or their agent.

Solid sample results, except biota, are based on dry weight unless otherwise indicated. Organic analyses are not recovery corrected except for isotope dilution methods.

Results relate to samples tested. When sampling is not conducted by Bureau Veritas, results relate to the supplied samples tested.

This Certificate shall not be reproduced except in full, without the written approval of the laboratory.

Reference Method suffix "m" indicates test methods incorporate validated modifications from specific reference methods to improve performance.

- * RPDs calculated using raw data. The rounding of final results may result in the apparent difference.
- (1) This test was performed by Bureau Veritas Calgary Environmental
- (2) Dissolved > Total Imbalance: When applicable, Dissolved and Total results were reviewed and data quality meets acceptable levels unless otherwise noted.
- (3) DOC present in the sample should be considered as non-purgeable DOC. Dissolved > Total Imbalance: When applicable, Dissolved and Total results were reviewed and data quality meets acceptable levels unless otherwise noted.
- (4) "Total Hardness" was calculated from Total Ca and Mg concentrations and may be biased high (Hardness, or Dissolved Hardness, calculated from Dissolved Ca and Mg, should be used for compliance if available).
- (5) The CCME method requires pH to be analysed within 15 minutes of sampling and therefore field analysis is required for compliance. All Laboratory pH analyses in this report are



Your Project #: 2021-Ketza Your C.O.C. #: C#644610-01-01

Attention: Stephanie Lyons

Government of Yukon – Dept of ENV Box 2703 Whitehorse, YT Canada Y1A2C6

Report Date: 2021/09/10

Report #: R3070012 Version: 1 - Final

CERTIFICATE OF ANALYSIS

BV LABS JOB #: C165062 Received: 2021/09/02, 16:11

reported past the CCME holding time. Bureau Veritas Laboratories endeavours to analyze samples as soon as possible after receipt.

(6) Dissolved Phosphorus > Total Phosphorus Imbalance: When applicable, Dissolved Phosphorus and Total Phosphorus results were reviewed and data quality meets acceptable levels unless otherwise noted.

Encryption Key

Kandise Wilson Customer Solutions Representative 13 Sep 2021 18:23:45

Please direct all questions regarding this Certificate of Analysis to your Project Manager.

Customer Solutions, Western Canada Customer Experience Team

Email: customer solutions we st@bureauver it as.com

Phone# (604) 734 7276

BV Labs has procedures in place to guard against improper use of the electronic signature and have the required "signatories", as per ISO/IEC 17025, signing the reports. For Service Group specific validation please refer to the Validation Signature Page.



Sampler Initials: SL

RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFC782			AFC782		
Sampling Date		2021/08/31 09:05			2021/08/31 09:05		
COC Number		C#644610-01-01			C#644610-01-01		
	UNITS	2021725-1	RDL	QC Batch	2021725-1 Lab-Dup	RDL	QC Batch
Misc. Inorganics							
Fluoride (F)	mg/L	0.110	0.020	A347643	0.110	0.020	A347643
Calculated Parameters	I.	1	•	I.	1		
Dissolved Chromium III	mg/L	<0.00099	0.00099	A340344			
Filter and HNO3 Preservation	N/A	FIELD		ONSITE			
Dissolved Hardness (CaCO3)	mg/L	295	0.50	A340085			
Total Hardness (CaCO3)	mg/L	300	0.50	A339992			
Nitrate (N)	mg/L	0.0572	0.0020	A340789			
Total Total Kjeldahl Nitrogen (Calc)	mg/L	0.109	0.020	A340111			
Misc. Inorganics			I	I		I	
Conductivity	uS/cm	590	2.0	A342007	590	2.0	A342007
Strong Acid Dissoc. Cyanide (CN)	mg/L	<0.00050	0.00050	A342803			
Weak Acid Dissoc. Cyanide (CN)	mg/L	<0.00050	0.00050	A342809			
Dissolved Organic Carbon (C)	mg/L	0.35	0.20	A343810			
рН	рН	7.48	N/A	A342005	7.72	N/A	A342005
Total Suspended Solids	mg/L	4.8	1.0	A343312			
Anions		ı	I	I.	I	I	
Alkalinity (PP as CaCO3)	mg/L	<1.0	1.0	A342006	<1.0	1.0	A342006
Alkalinity (Total as CaCO3)	mg/L	140	1.0	A342006	150	1.0	A342006
Bicarbonate (HCO3)	mg/L	170	1.0	A342006	180	1.0	A342006
Carbonate (CO3)	mg/L	<1.0	1.0	A342006	<1.0	1.0	A342006
Hydroxide (OH)	mg/L	<1.0	1.0	A342006	<1.0	1.0	A342006
Dissolved Chloride (Cl)	mg/L	<0.50	0.50	A346519	<0.50	0.50	A346519
Dissolved Sulphate (SO4)	mg/L	190	0.50	A346519	190	0.50	A346519
Metals		!	ļ.		!	Į	
Dissolved Hex. Chromium (Cr 6+)	mg/L	<0.00099	0.00099	A343723			
Nutrients		I	I	I		I	
Dissolved Phosphorus (P)	mg/L	<0.0010	0.0010	A344365			
Total Phosphorus (P)	mg/L	<0.0010	0.0010	A344338			
Total Ammonia (N)	mg/L	<0.0050	0.0050	A343769			
Nitrate plus Nitrite (N)	mg/L	0.0572	0.0020	A341762	0.0607	0.0020	A341762
		<0.0020	0.0020	A341763	<0.0020	0.0020	A341763

N/A = Not Applicable



Sampler Initials: SL

RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFC782			AFC782		
Sampling Date		2021/08/31 09:05			2021/08/31 09:05		
COC Number		C#644610-01-01			C#644610-01-01		
	UNITS	2021725-1	RDL	QC Batch	2021725-1 Lab-Dup	RDL	QC Batch
Total Nitrogen (N)	mg/L	0.166	0.020	A343841			
Physical Properties							
Total Dissolved Solids	mg/L	393 (1)	1.0	A342432			

RDL = Reportable Detection Limit

Lab-Dup = Laboratory Initiated Duplicate

(1) Detection limits raised due to insufficient sample volume.



RESULTS OF CHEMICAL ANALYSES OF WATER

UNITS mg/L	2021/08/31 09:50 C#644610-01-01 2021725-2	RDL	QC Batch	2021/08/31 11:30 C#644610-01-01		2021/08/31 13:45 C#644610-01-01		
mg/L	C#644610-01-01 2021725-2	RDL	OC Batch					
mg/L	2021725-2	RDL	OC Batch	C#644610-01-01		C#644610-01-01		
mg/L		RDL	OC Ratch					-
	0.040		QC Datcii	2021725-03	QC Batch	2021725-04	RDL	QC Batch
	0.040							
	0.048	0.020	A347643	0.210	A347643	0.046	0.020	A347643
mg/L	<0.00099	0.00099	A340344	<0.00099	A340344	<0.00099	0.00099	A340344
N/A	FIELD		ONSITE	FIELD	ONSITE	FIELD		ONSITE
mg/L	267	0.50	A340085	356	A340085	297	0.50	A340085
mg/L	270	0.50	A339992	360	A339992	300	0.50	A339992
mg/L	0.0447	0.0020	A340789	0.124	A340789	0.124	0.0020	A340789
mg/L	0.124	0.020	A340111	0.128	A340111	0.161	0.020	A340111
uS/cm	530	2.0	A341967	710	A341967	570	2.0	A342007
mg/L	<0.00050	0.00050	A342803	<0.00050	A342803	<0.00050	0.00050	A342803
mg/L	<0.00050	0.00050	A342809	<0.00050	A342809	<0.00050	0.00050	A342809
mg/L	0.31	0.20	A343810	<0.20	A343810	<0.20	0.20	A343810
рН	7.84	N/A	A341963	7.28	A341963	7.43	N/A	A342005
mg/L	2.4	1.0	A343244	11	A343244	3.6	1.0	A343312
mg/L	<1.0	1.0	A341966	<1.0	A341966	<1.0	1.0	A342006
mg/L	150	1.0	A341966	92	A341966	120	1.0	A342006
mg/L	190	1.0	A341966	110	A341966	140	1.0	A342006
mg/L	<1.0	1.0	A341966	<1.0	A341966	<1.0	1.0	A342006
mg/L	<1.0	1.0	A341966	<1.0	A341966	<1.0	1.0	A342006
mg/L	0.56	0.50	A346519	<0.50	A346519	<0.50	0.50	A346519
mg/L	140	0.50	A346519	280	A346519	240	5.0	A346519
					•			
mg/L	<0.00099	0.00099	A343019	<0.00099	A343723	<0.00099	0.00099	A343723
mg/L	<0.0010	0.0010	A344365	<0.0010	A344365	0.0013	0.0010	A344365
mg/L	0.0011	0.0010	A344325	0.0046	A344325	0.0017	0.0010	A344338
mg/L	<0.0050	0.0050	A343769	0.0053	A343769	0.20	0.0050	A343769
mg/L	0.0447	0.0020	A341762	0.124	A341762	0.124	0.0020	A341762
mg/L	<0.0020	0.0020	A341763	<0.0020	A341763	<0.0020	0.0020	A341763
	N/A mg/L mg/L mg/L mg/L mg/L mg/L mg/L mg/L	N/A FIELD mg/L 267 mg/L 270 mg/L 0.0447 mg/L 0.124 uS/cm 530 mg/L <0.00050	N/A FIELD mg/L 267 0.50 mg/L 270 0.50 mg/L 0.0447 0.0020 mg/L 0.124 0.020 uS/cm 530 2.0 mg/L <0.00050	N/A FIELD ONSITE mg/L 267 0.50 A340085 mg/L 270 0.50 A339992 mg/L 0.0447 0.0020 A340789 mg/L 0.124 0.020 A340111 uS/cm 530 2.0 A341967 mg/L <0.00050	N/A FIELD ONSITE FIELD mg/L 267 0.50 A340085 356 mg/L 270 0.50 A339992 360 mg/L 0.0447 0.0020 A340789 0.124 mg/L 0.124 0.020 A340111 0.128 uS/cm 530 2.0 A341967 710 mg/L <0.00050	N/A FIELD ONSITE FIELD ONSITE mg/L 267 0.50 A340085 356 A340085 mg/L 270 0.50 A339992 360 A339992 mg/L 0.0447 0.0020 A340789 0.124 A340789 mg/L 0.124 0.020 A340111 0.128 A340111 uS/cm 530 2.0 A341967 710 A341967 mg/L <0.00050	N/A FIELD ONSITE FIELD ONSITE FIELD mg/L 267 0.50 A340085 356 A340085 297 mg/L 270 0.50 A339992 360 A339992 300 mg/L 0.0447 0.0020 A340789 0.124 A340789 0.124 mg/L 0.124 0.020 A340111 0.128 A340111 0.161 us/cm 530 2.0 A341967 710 A341967 570 mg/L <0.00050	N/A FIELD ONSITE FIELD ONSITE FIELD mg/L 267 0.50 A340085 356 A340085 297 0.50 mg/L 270 0.50 A339992 360 A339992 300 0.50 mg/L 0.0447 0.0020 A340789 0.124 A340789 0.124 0.0020 mg/L 0.124 0.020 A340111 0.128 A340111 0.161 0.020 us/cm 530 2.0 A341967 710 A341967 570 2.0 mg/L <0.00050

N/A = Not Applicable



Report Date: 2021/09/10

Government of Yukon – Dept of ENV Client Project #: 2021-Ketza Sampler Initials: SL

RESULTS OF CHEMICAL ANALYSES OF WATER

		t		1	1	1			
BV Labs ID		AFC783			AFC784		AFC785		
Sampling Date		2021/08/31 09:50			2021/08/31 11:30		2021/08/31 13:45		
COC Number		C#644610-01-01			C#644610-01-01		C#644610-01-01		
	UNITS	2021725-2	RDL	QC Batch	2021725-03	QC Batch	2021725-04	RDL	QC Batch
Total Nitrogen (N)	mg/L	0.168	0.020	A343841	0.252	A343841	0.285	0.020	A343841
Physical Properties				ļ	!				•

RDL = Reportable Detection Limit

⁽¹⁾ Detection limits raised due to insufficient sample volume.



Sampler Initials: SL

RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFC785			AFC786		
Sampling Date		2021/08/31 13:45			2021/08/31 14:15		
COC Number		C#644610-01-01			C#644610-01-01		
COCINALIBEI	UNITS	2021725-04 Lab-Dup	RDL	QC Batch	2021725-05	RDL	QC Batch
Misc. Inorganics			!				-
Fluoride (F)	mg/L				0.055	0.020	A347643
Calculated Parameters				<u>I</u>		I.	L.
Dissolved Chromium III	mg/L				<0.00099	0.00099	A340344
Filter and HNO3 Preservation	N/A				FIELD		ONSITE
Dissolved Hardness (CaCO3)	mg/L				305	0.50	A340085
Total Hardness (CaCO3)	mg/L				310	0.50	A339992
Nitrate (N)	mg/L				0.0940	0.0020	A340789
Total Total Kjeldahl Nitrogen (Calc)	mg/L				0.183	0.020	A340111
Misc. Inorganics			•				
Conductivity	uS/cm				610	2.0	A342007
Strong Acid Dissoc. Cyanide (CN)	mg/L	<0.00050	0.00050	A342803	<0.00050	0.00050	A342803
Weak Acid Dissoc. Cyanide (CN)	mg/L	<0.00050	0.00050	A342809	<0.00050	0.00050	A342809
Dissolved Organic Carbon (C)	mg/L				<0.20	0.20	A343810
рН	рН				7.47	N/A	A342005
Total Suspended Solids	mg/L				11	1.0	A343244
Anions			•				
Alkalinity (PP as CaCO3)	mg/L				<1.0	1.0	A342006
Alkalinity (Total as CaCO3)	mg/L				110	1.0	A342006
Bicarbonate (HCO3)	mg/L				140	1.0	A342006
Carbonate (CO3)	mg/L				<1.0	1.0	A342006
Hydroxide (OH)	mg/L				<1.0	1.0	A342006
Dissolved Chloride (Cl)	mg/L				<0.50	0.50	A346519
Dissolved Sulphate (SO4)	mg/L				260	5.0	A346519
Metals				-		•	
Dissolved Hex. Chromium (Cr 6+)	mg/L				<0.00099	0.00099	A343019
Nutrients						•	
Dissolved Phosphorus (P)	mg/L				<0.0010	0.0010	A344365
Total Phosphorus (P)	mg/L				0.0047	0.0010	A344325
Total Ammonia (N)	mg/L				0.0051	0.0050	A343769
Nitrate plus Nitrite (N)	mg/L				0.0940	0.0020	A341762
Nitrite (N)	mg/L				<0.0020	0.0020	A341763
RDL = Reportable Detection Limit Lab-Dup = Laboratory Initiated Dupli	icate						
Lab-Dup = Laboratory Initiated Dupli	icate						

N/A = Not Applicable



Sampler Initials: SL

RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFC785			AFC786		
Sampling Date		2021/08/31 13:45			2021/08/31 14:15		
COC Number		C#644610-01-01			C#644610-01-01		
	UNITS	2021725-04 Lab-Dup	RDL	QC Batch	2021725-05	RDL	QC Batch
Total Nitrogen (N)	mg/L				0.277	0.020	A343841
Physical Properties							-
Total Dissolved Solids	mg/L				423 (1)	1.0	A342432

RDL = Reportable Detection Limit

Lab-Dup = Laboratory Initiated Duplicate

⁽¹⁾ Detection limits raised due to insufficient sample volume.



Sampler Initials: SL

RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFC787			AFC787		
Sampling Date		2021/08/31 14:30			2021/08/31 14:30		
COC Number		C#644610-01-01			C#644610-01-01		
	UNITS	2021725-06	RDL	QC Batch	2021725-06 Lab-Dup	RDL	QC Batch
Misc. Inorganics	•		<u> </u>				<u> </u>
Fluoride (F)	mg/L	0.026	0.020	A347643			
Calculated Parameters	l						
Dissolved Chromium III	mg/L	<0.00099	0.00099	A340344			
Filter and HNO3 Preservation	N/A	FIELD		ONSITE			
Dissolved Hardness (CaCO3)	mg/L	257	0.50	A340085			
Total Hardness (CaCO3)	mg/L	250	0.50	A339992			
Nitrate (N)	mg/L	0.205	0.0020	A340789			
Total Total Kjeldahl Nitrogen (Calc)	mg/L	0.074	0.020	A340111			
Misc. Inorganics			•				•
Conductivity	uS/cm	520	2.0	A342007			
Strong Acid Dissoc. Cyanide (CN)	mg/L	<0.00050	0.00050	A342803			
Weak Acid Dissoc. Cyanide (CN)	mg/L	<0.00050	0.00050	A342809			
Dissolved Organic Carbon (C)	mg/L	<0.20	0.20	A343810			
рН	рН	7.52	N/A	A342005			
Total Suspended Solids	mg/L	<1.0	1.0	A343244			
Anions			•				•
Alkalinity (PP as CaCO3)	mg/L	<1.0	1.0	A342006			
Alkalinity (Total as CaCO3)	mg/L	120	1.0	A342006			
Bicarbonate (HCO3)	mg/L	150	1.0	A342006			
Carbonate (CO3)	mg/L	<1.0	1.0	A342006			
Hydroxide (OH)	mg/L	<1.0	1.0	A342006			
Dissolved Chloride (CI)	mg/L	<0.50	0.50	A346519			
Dissolved Sulphate (SO4)	mg/L	170	0.50	A346519			
Metals	•						
Dissolved Hex. Chromium (Cr 6+)	mg/L	<0.00099	0.00099	A343723			
Nutrients	•		•				•
Dissolved Phosphorus (P)	mg/L	0.0024	0.0010	A344365			
Total Phosphorus (P)	mg/L	0.0036	0.0010	A344325			
Total Ammonia (N)	mg/L	<0.0050	0.0050	A343769			
Nitrate plus Nitrite (N)	mg/L	0.205	0.0020	A341762			
	mg/L	<0.0020	0.0020	A341763			1

N/A = Not Applicable



Sampler Initials: SL

RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFC787			AFC787		
Sampling Date		2021/08/31 14:30			2021/08/31 14:30		
COC Number		C#644610-01-01			C#644610-01-01		
	UNITS	2021725-06	RDL	QC Batch	2021725-06 Lab-Dup	RDL	QC Batch
Total Nitrogen (N)	mg/L	0.279	0.020	A343841	0.277	0.020	A343841
Physical Properties				l .			
Physical Properties Total Dissolved Solids	mg/L	316	1.0	A342432			

RDL = Reportable Detection Limit



RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFC788		AFC789		AFC790		
Sampling Date		2021/08/31 15:30		2021/08/31 16:45		2021/08/31		
COC Number		C#644610-01-01		C#644610-01-01		C#644610-01-01		
	UNITS	2021725-07	QC Batch	2021725-08	QC Batch	2021725-09	RDL	QC Batch
Misc. Inorganics								
Fluoride (F)	mg/L	0.023	A347643	0.029	A347643	0.028	0.020	A347643
Calculated Parameters			I.	1				
Dissolved Chromium III	mg/L	<0.00099	A340344	<0.00099	A340344	<0.00099	0.00099	A340344
Filter and HNO3 Preservation	N/A	FIELD	ONSITE	FIELD	ONSITE	FIELD		ONSITE
Dissolved Hardness (CaCO3)	mg/L	247	A340085	290	A340085	281	0.50	A340085
Total Hardness (CaCO3)	mg/L	250	A339992	280	A339992	280	0.50	A339992
Nitrate (N)	mg/L	0.152	A340789	0.0503	A340789	0.0497	0.0020	A340789
Total Total Kjeldahl Nitrogen (Calc)	mg/L	0.088	A340111	0.101	A340111	0.068	0.020	A340111
Misc. Inorganics					•			
Conductivity	uS/cm	510	A342007	580	A342007	580	2.0	A342007
Strong Acid Dissoc. Cyanide (CN)	mg/L	<0.00050	A342803	<0.00050	A342803	<0.00050	0.00050	A342803
Weak Acid Dissoc. Cyanide (CN)	mg/L	<0.00050	A342809	<0.00050	A342809	<0.00050	0.00050	A342809
Dissolved Organic Carbon (C)	mg/L	<0.20	A343810	<0.20	A343810	0.33	0.20	A343810
рН	рН	7.63	A342005	7.57	A342005	7.59	N/A	A342005
Total Suspended Solids	mg/L	<1.0	A343312	2.4	A343244	<1.0	1.0	A343312
Anions			•					
Alkalinity (PP as CaCO3)	mg/L	<1.0	A342006	<1.0	A342006	<1.0	1.0	A342006
Alkalinity (Total as CaCO3)	mg/L	120	A342006	120	A342006	130	1.0	A342006
Bicarbonate (HCO3)	mg/L	150	A342006	150	A342006	150	1.0	A342006
Carbonate (CO3)	mg/L	<1.0	A342006	<1.0	A342006	<1.0	1.0	A342006
Hydroxide (OH)	mg/L	<1.0	A342006	<1.0	A342006	<1.0	1.0	A342006
Dissolved Chloride (CI)	mg/L	<0.50	A346519	<0.50	A346519	<0.50	0.50	A346519
Dissolved Sulphate (SO4)	mg/L	150	A346519	190	A346519	200	0.50	A346519
Metals								
Dissolved Hex. Chromium (Cr 6+)	mg/L	<0.00099	A343019	<0.00099	A343019	<0.00099	0.00099	A343723
Nutrients								
Dissolved Phosphorus (P)	mg/L	0.0027	A344365	0.0018	A344365	0.0013	0.0010	A344365
Total Phosphorus (P)	mg/L	0.0023	A344325	0.0029	A344338	0.0030	0.0010	A344325
Total Ammonia (N)	mg/L	<0.0050	A343769	<0.0050	A343769	<0.0050	0.0050	A343769
Nitrate plus Nitrite (N)	mg/L	0.152	A341762	0.0503	A341762	0.0497	0.0020	A341762
Nitrite (N)	mg/L	<0.0020	A341763	<0.0020	A341763	<0.0020	0.0020	A341763
RDL = Reportable Detection Limit N/A = Not Applicable								



Government of Yukon – Dept of ENV Report Date: 2021/09/10 Client Project #: 2021-Ketza Sampler Initials: SL

RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFC788		AFC789		AFC790		
Sampling Date		2021/08/31 15:30		2021/08/31 16:45		2021/08/31		
COC Number		C#644610-01-01		C#644610-01-01		C#644610-01-01		
	UNITS	2021725-07	QC Batch	2021725-08	QC Batch	2021725-09	RDL	QC Batch
Total Nitrogen (N)	mg/L	0.240	A343841	0.151	A343841	0.118	0.020	A343841
Physical Properties			•					
Total Dissolved Solids	mg/L	340	A342432	387 (1)	A342432	397	1.0	A342432
RDL = Reportable Detection Limit								

⁽¹⁾ Detection limits raised due to insufficient sample volume.



Sampler Initials: SL

RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFC790			AFC791		
Sampling Date		2021/08/31			2021/08/31 18:00		
COC Number		C#644610-01-01			C#644610-01-01		
	UNITS	2021725-09 Lab-Dup	RDL	QC Batch	2021725-10	RDL	QC Batc
Misc. Inorganics							
Fluoride (F)	mg/L				0.067	0.020	A34764
Calculated Parameters				<u>I</u>		I.	
Dissolved Chromium III	mg/L				<0.00099	0.00099	A34034
Filter and HNO3 Preservation	N/A				FIELD		ONSITE
Dissolved Hardness (CaCO3)	mg/L				408	0.50	A34008
Total Hardness (CaCO3)	mg/L				400	0.50	A33999
Nitrate (N)	mg/L				0.0588	0.0020	A34078
Total Total Kjeldahl Nitrogen (Calc)	mg/L				0.091	0.020	A34011
Misc. Inorganics							
Conductivity	uS/cm				800	2.0	A34200
Strong Acid Dissoc. Cyanide (CN)	mg/L				<0.00050	0.00050	A34280
Weak Acid Dissoc. Cyanide (CN)	mg/L				<0.00050	0.00050	A34280
Dissolved Organic Carbon (C)	mg/L	0.26	0.20	A343810	<0.20	0.20	A34381
рН	рН				7.30	N/A	A34200
Total Suspended Solids	mg/L	<1.0	1.0	A343312	2.0	1.0	A34331
Anions			•			•	
Alkalinity (PP as CaCO3)	mg/L				<1.0	1.0	A34200
Alkalinity (Total as CaCO3)	mg/L				91	1.0	A34200
Bicarbonate (HCO3)	mg/L				110	1.0	A34200
Carbonate (CO3)	mg/L				<1.0	1.0	A34200
Hydroxide (OH)	mg/L				<1.0	1.0	A34200
Dissolved Chloride (Cl)	mg/L				<0.50	0.50	A34651
Dissolved Sulphate (SO4)	mg/L				350	5.0	A34651
Metals							
Dissolved Hex. Chromium (Cr 6+)	mg/L				<0.00099	0.00099	A34372
Nutrients			•			•	
Dissolved Phosphorus (P)	mg/L				0.0017	0.0010	A34436
Total Phosphorus (P)	mg/L				0.0021	0.0010	A34433
	mg/L				<0.0050	0.0050	A34376
Total Ammonia (N)					0.0588	0.0020	A34176
Total Ammonia (N) Nitrate plus Nitrite (N)	mg/L				0.0566	0.0020	A34170

N/A = Not Applicable



Sampler Initials: SL

RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFC790			AFC791		
Sampling Date		2021/08/31			2021/08/31 18:00		
COC Number		C#644610-01-01			C#644610-01-01		
	UNITS	2021725-09 Lab-Dup	RDL	QC Batch	2021725-10	RDL	QC Batch
Total Nitrogen (N)	mg/L				0.150	0.020	A343841
Physical Properties			•				
Total Dissolved Solids	mg/L				593	1.0	A342432
	U,						

	UNITS	2021725-10 Lab-Dup	RDL	QC Batch
COC Number		C#644610-01-01		
Sampling Date		2021/08/31 18:00		
BV Labs ID		AFC791		

Metals				
Dissolved Hex. Chromium (Cr 6+)	mg/L	<0.00099	0.00099	A343723
RDL = Reportable Detection Limit				
Lab-Dup = Laboratory Initiated Dupli	cate			



MERCURY BY COLD VAPOR (WATER)

BV Labs ID		AFC782			AFC782			AFC783		
Sampling Date		2021/08/31 09:05			2021/08/31 09:05			2021/08/31 09:50		
COC Number		C#644610-01-01			C#644610-01-01			C#644610-01-01		
	UNITS	2021725-1	RDL	QC Batch	2021725-1 Lab-Dup	RDL	QC Batch	2021725-2	RDL	QC Batch
Elements										
Dissolved Mercury (Hg)	ug/L	<0.0019	0.0019	A343127				<0.0019	0.0019	A343127
Total Mercury (Hg)	ug/L	<0.0019	0.0019	A343419	<0.0019	0.0019	A343419	<0.0019	0.0019	A343419
RDL = Reportable Detection I	imit									

Lab-Dup = Laboratory Initiated Duplicate

BV Labs ID		AFC784	AFC785		AFC786		
Sampling Date		2021/08/31 11:30	2021/08/31 13:45		2021/08/31 14:15		
COC Number		C#644610-01-01	C#644610-01-01		C#644610-01-01		
	UNITS	2021725-03	2021725-04	QC Batch	2021725-05	RDL	QC Batch
Elements				•			
Elements Dissolved Mercury (Hg)	ug/L	<0.0019	<0.0019	A343127	<0.0019	0.0019	A343127
	ug/L ug/L	<0.0019 <0.0019	<0.0019 <0.0019	A343127 A343419	<0.0019 <0.0019	0.0019 0.0019	A343127 A346928

BV Labs ID		AFC786			AFC787	AFC788	AFC789			
Sampling Date		2021/08/31 14:15			2021/08/31 14:30	2021/08/31 15:30	2021/08/31 16:45			
COC Number		C#644610-01-01			C#644610-01-01	C#644610-01-01	C#644610-01-01			
	UNITS	2021725-05 Lab-Dup	RDL	QC Batch	2021725-06	2021725-07	2021725-08	RDL	QC Batch	
Elements										
Dissolved Mercury (Hg)	ug/L				<0.0019	<0.0019	<0.0019	0.0019	A343127	
Total Mercury (Hg)	ug/L	<0.0019	0.0019	A346928	<0.0019	<0.0019	<0.0019	0.0019	A346928	
RDL = Reportable Detection Limit Lab-Dup = Laboratory Initiated Duplicate										

BV Labs ID		AFC790			AFC790			AFC791		
Sampling Date		2021/08/31			2021/08/31			2021/08/31 18:00		
COC Number		C#644610-01-01			C#644610-01-01			C#644610-01-01		
	UNITS	2021725-09	RDL	QC Batch	2021725-09 Lab-Dup	RDL	QC Batch	2021725-10	RDL	QC Batch
					ւսս-ոսի					
Elements					сар-рир					
Elements Dissolved Mercury (Hg)	ug/L	<0.0019	0.0019	A346922	<0.0019	0.0019	A346922	<0.0019	0.0019	A346922

RDL = Reportable Detection Limit



BV Labs Job #: C165062 Government of Yukon – Dept of ENV Report Date: 2021/09/10 Client Project #: 2021-Ketza Sampler Initials: SL

ELEMENTS BY ATOMIC SPECTROSCOPY (WATER)

BV Labs ID		AFC782			AFC782			AFC783		
Sampling Date		2021/08/31			2021/08/31			2021/08/31		
Jamping Date		09:05			09:05			09:50		
COC Number		C#644610-01-01			C#644610-01-01			C#644610-01-01		
	UNITS	2021725-1	RDL	QC Batch	2021725-1 Lab-Dup	RDL	QC Batch	2021725-2	RDL	QC Batch
Dissolved Metals by ICPMS										
Dissolved Aluminum (Al)	ug/L	54.6	0.50	A341524				3.04	0.50	A341524
Dissolved Antimony (Sb)	ug/L	0.187	0.020	A341524				0.214	0.020	A341524
Dissolved Arsenic (As)	ug/L	7.77	0.020	A341524				14.1	0.020	A341524
Dissolved Barium (Ba)	ug/L	10.7	0.020	A341524				11.0	0.020	A341524
Dissolved Beryllium (Be)	ug/L	<0.010	0.010	A341524				<0.010	0.010	A341524
Dissolved Bismuth (Bi)	ug/L	<0.0050	0.0050	A341524				<0.0050	0.0050	A341524
Dissolved Boron (B)	ug/L	<10	10	A341524				<10	10	A341524
Dissolved Cadmium (Cd)	ug/L	0.197	0.0050	A341524				0.0327	0.0050	A341524
Dissolved Chromium (Cr)	ug/L	<0.10	0.10	A341524				<0.10	0.10	A341524
Dissolved Cobalt (Co)	ug/L	14.5	0.0050	A341524				0.0306	0.0050	A341524
Dissolved Copper (Cu)	ug/L	0.303	0.050	A341524				0.118	0.050	A341524
Dissolved Iron (Fe)	ug/L	155	1.0	A341524				<1.0	1.0	A341524
Dissolved Lead (Pb)	ug/L	0.0201	0.0050	A341524				<0.0050	0.0050	A341524
Dissolved Lithium (Li)	ug/L	2.10	0.50	A341524				1.20	0.50	A341524
Dissolved Manganese (Mn)	ug/L	125	0.050	A341524				0.242	0.050	A341524
Dissolved Molybdenum (Mo)	ug/L	0.202	0.050	A341524				0.224	0.050	A341524
Dissolved Nickel (Ni)	ug/L	8.94	0.020	A341524				0.611	0.020	A341524
Dissolved Selenium (Se)	ug/L	0.666	0.040	A341524				0.709	0.040	A341524
Dissolved Silicon (Si)	ug/L	2610	50	A341524				2080	50	A341524
Dissolved Silver (Ag)	ug/L	<0.0050	0.0050	A341524				<0.0050	0.0050	A341524
Dissolved Strontium (Sr)	ug/L	203	0.050	A341524				185	0.050	A341524
Dissolved Tellurium (Te)	ug/L	<0.020	0.020	A341524				<0.020	0.020	A341524
Dissolved Thallium (TI)	ug/L	<0.0020	0.0020	A341524				<0.0020	0.0020	A341524
Dissolved Thorium (Th)	ug/L	<0.0050	0.0050	A341524				<0.0050	0.0050	A341524
Dissolved Tin (Sn)	ug/L	<0.20	0.20	A341524				<0.20	0.20	A341524
Dissolved Titanium (Ti)	ug/L	<0.50	0.50	A341524				<0.50	0.50	A341524
Dissolved Tungsten (W)	ug/L	0.039	0.010	A341524				0.055	0.010	A341524
Dissolved Uranium (U)	ug/L	1.76	0.0020	A341524				1.99	0.0020	A341524
Dissolved Vanadium (V)	ug/L	<0.20	0.20	A341524				<0.20	0.20	A341524
Dissolved Zinc (Zn)	ug/L	36.6	0.10	A341524				2.08	0.10	A341524
Dissolved Zirconium (Zr)	ug/L	<0.10	0.10	A341524				<0.10	0.10	A341524

RDL = Reportable Detection Limit



ELEMENTS BY ATOMIC SPECTROSCOPY (WATER)

BV Labs ID		AFC782			AFC782			AFC783		
Sampling Date		2021/08/31			2021/08/31			2021/08/31		
Jamping Date		09:05			09:05			09:50		
COC Number		C#644610-01-01			C#644610-01-01			C#644610-01-01		
	UNITS	2021725-1	RDL	QC Batch	2021725-1 Lab-Dup	RDL	QC Batch	2021725-2	RDL	QC Batch
Dissolved Calcium (Ca)	mg/L	79.9	0.050	A340086				71.6	0.050	A340086
Dissolved Magnesium (Mg)	mg/L	23.2	0.050	A340086				21.5	0.050	A340086
Dissolved Potassium (K)	mg/L	0.280	0.050	A340086				0.222	0.050	A340086
Dissolved Sodium (Na)	mg/L	0.830	0.050	A340086				0.673	0.050	A340086
Dissolved Sulphur (S)	mg/L	53.0	3.0	A340086				38.7	3.0	A340086
Total Metals by ICPMS	•		•	•		•	•		•	•
Total Aluminum (Al)	ug/L	440	0.50	A341316	439	0.50	A341316	4.60	0.50	A341316
Total Antimony (Sb)	ug/L	0.196	0.020	A341316	0.199	0.020	A341316	0.216	0.020	A341316
Total Arsenic (As)	ug/L	19.2	0.020	A341316	19.5	0.020	A341316	14.5	0.020	A341316
Total Barium (Ba)	ug/L	11.5	0.020	A341316	11.3	0.020	A341316	11.3	0.020	A341316
Total Beryllium (Be)	ug/L	0.027	0.010	A341316	0.032	0.010	A341316	<0.010	0.010	A341316
Total Bismuth (Bi)	ug/L	<0.0050	0.0050	A341316	<0.0050	0.0050	A341316	<0.0050	0.0050	A341316
Total Boron (B)	ug/L	<10	10	A341316	<10	10	A341316	<10	10	A341316
Total Cadmium (Cd)	ug/L	0.263	0.0050	A341316	0.271	0.0050	A341316	0.0361	0.0050	A341316
Total Chromium (Cr)	ug/L	<0.10	0.10	A341316	<0.10	0.10	A341316	<0.10	0.10	A341316
Total Cobalt (Co)	ug/L	15.1	0.0050	A341316	15.3	0.0050	A341316	0.0317	0.0050	A341316
Total Copper (Cu)	ug/L	1.31	0.050	A341316	1.33	0.050	A341316	0.152	0.050	A341316
Total Iron (Fe)	ug/L	1090	1.0	A341316	1060	1.0	A341316	3.9	1.0	A341316
Total Lead (Pb)	ug/L	0.423	0.0050	A341316	0.422	0.0050	A341316	0.0147	0.0050	A341316
Total Lithium (Li)	ug/L	2.04	0.50	A341316	2.02	0.50	A341316	1.20	0.50	A341316
Total Manganese (Mn)	ug/L	128	0.050	A341316	128	0.050	A341316	0.573	0.050	A341316
Total Molybdenum (Mo)	ug/L	0.211	0.050	A341316	0.211	0.050	A341316	0.251	0.050	A341316
Total Nickel (Ni)	ug/L	9.27	0.020	A341316	9.49	0.020	A341316	0.603	0.020	A341316
Total Selenium (Se)	ug/L	0.636	0.040	A341316	0.682	0.040	A341316	0.701	0.040	A341316
Total Silicon (Si)	ug/L	2780	50	A341316	2760	50	A341316	2090	50	A341316
Total Silver (Ag)	ug/L	<0.0050	0.0050	A341316	<0.0050	0.0050	A341316	<0.0050	0.0050	A341316
Total Strontium (Sr)	ug/L	206	0.050	A341316	211	0.050	A341316	192	0.050	A341316
Total Tellurium (Te)	ug/L	<0.020	0.020	A341316	<0.020	0.020	A341316	<0.020	0.020	A341316
Total Thallium (TI)	ug/L	0.0024	0.0020	A341316	0.0027	0.0020	A341316	<0.0020	0.0020	A341316
Total Thorium (Th)	ug/L	0.0126	0.0050	A341316	0.0146	0.0050	A341316	<0.0050	0.0050	A341316
Total Tin (Sn)	ug/L	<0.20	0.20	A341316	<0.20	0.20	A341316	<0.20	0.20	A341316
Total Titanium (Ti)	ug/L	<0.50	0.50	A341316	<0.50	0.50	A341316	<0.50	0.50	A341316

RDL = Reportable Detection Limit



ELEMENTS BY ATOMIC SPECTROSCOPY (WATER)

BV Labs ID		AFC782			AFC782			AFC783		
Sampling Date		2021/08/31 09:05			2021/08/31 09:05			2021/08/31 09:50		
COC Number		C#644610-01-01			C#644610-01-01			C#644610-01-01		
	UNITS	2021725-1	RDL	QC Batch	2021725-1 Lab-Dup	RDL	QC Batch	2021725-2	RDL	QC Batch
Total Tungsten (W)	ug/L	0.041	0.010	A341316	0.043	0.010	A341316	0.054	0.010	A341316
Total Uranium (U)	ug/L	1.84	0.0020	A341316	1.86	0.0020	A341316	2.02	0.0020	A341316
Total Vanadium (V)	ug/L	<0.20	0.20	A341316	<0.20	0.20	A341316	<0.20	0.20	A341316
Total Zinc (Zn)	ug/L	69.0	0.10	A341316	69.8	0.10	A341316	1.88	0.10	A341316
Total Zirconium (Zr)	ug/L	<0.10	0.10	A341316	<0.10	0.10	A341316	<0.10	0.10	A341316
Total Calcium (Ca)	mg/L	80.7	0.050	A340088				71.9	0.050	A340088
Total Magnesium (Mg)	mg/L	23.0	0.050	A340088				22.0	0.050	A340088
Total Potassium (K)	mg/L	0.291	0.050	A340088				0.231	0.050	A340088
Total Sodium (Na)	mg/L	0.834	0.050	A340088				0.679	0.050	A340088
Total Sulphur (S)	mg/L	52.2	3.0	A340088				40.2	3.0	A340088

RDL = Reportable Detection Limit



244 1 12		15050	1		150-0-	i	i	450500	1	
BV Labs ID		AFC784			AFC785			AFC786		
Sampling Date		2021/08/31			2021/08/31			2021/08/31		
COC Number		11:30 C#644610-01-01			13:45			14:15		
COC Number	LINUTC		DDI	OC Datab	C#644610-01-01	DDI	OC Datab	C#644610-01-01	DDI	OC Datab
	UNITS	2021725-03	RDL	QC Batch	2021725-04	RDL	QC Batch	2021725-05	RDL	QC Batch
Dissolved Metals by ICPMS		Ī	1	ı		1	1	Ī	1	ı
Dissolved Aluminum (AI)	ug/L	69.0	0.50	A341524	16.2	0.50	A341524	27.7	0.50	A341524
Dissolved Antimony (Sb)	ug/L	0.170	0.020	A341524	0.106	0.020	A341524	0.128	0.020	A341524
Dissolved Arsenic (As)	ug/L	4.81	0.020	A341524	14.5	0.020	A341524	8.17	0.020	A341524
Dissolved Barium (Ba)	ug/L	11.2	0.020	A341524	10.9	0.020	A341524	10.2	0.020	A341524
Dissolved Beryllium (Be)	ug/L	<0.010	0.010	A341524	<0.010	0.010	A341524	<0.010	0.010	A341524
Dissolved Bismuth (Bi)	ug/L	<0.0050	0.0050	A341524	<0.0050	0.0050	A341524	<0.0050	0.0050	A341524
Dissolved Boron (B)	ug/L	<10	10	A341524	<10	10	A341524	<10	10	A341524
Dissolved Cadmium (Cd)	ug/L	0.166	0.0050	A341524	0.0056	0.0050	A341524	0.0072	0.0050	A341524
Dissolved Chromium (Cr)	ug/L	<0.10	0.10	A341524	<0.10	0.10	A341524	<0.10	0.10	A341524
Dissolved Cobalt (Co)	ug/L	15.1	0.0050	A341524	0.850	0.0050	A341524	1.36	0.0050	A341524
Dissolved Copper (Cu)	ug/L	0.722	0.050	A341524	<0.050	0.050	A341524	0.065	0.050	A341524
Dissolved Iron (Fe)	ug/L	1780	1.0	A341524	719	1.0	A341524	1300	1.0	A341524
Dissolved Lead (Pb)	ug/L	<0.0050	0.0050	A341524	<0.0050	0.0050	A341524	<0.0050	0.0050	A341524
Dissolved Lithium (Li)	ug/L	2.56	0.50	A341524	1.25	0.50	A341524	1.43	0.50	A341524
Dissolved Manganese (Mn)	ug/L	81.3	0.050	A341524	34.9	0.050	A341524	54.2	0.050	A341524
Dissolved Molybdenum (Mo)	ug/L	0.101	0.050	A341524	0.138	0.050	A341524	0.147	0.050	A341524
Dissolved Nickel (Ni)	ug/L	9.80	0.020	A341524	1.52	0.020	A341524	2.14	0.020	A341524
Dissolved Selenium (Se)	ug/L	0.604	0.040	A341524	0.995	0.040	A341524	0.952	0.040	A341524
Dissolved Silicon (Si)	ug/L	3780	50	A341524	2370	50	A341524	2260	50	A341524
Dissolved Silver (Ag)	ug/L	<0.0050	0.0050	A341524	<0.0050	0.0050	A341524	<0.0050	0.0050	A341524
Dissolved Strontium (Sr)	ug/L	253	0.050	A341524	223	0.050	A341524	225	0.050	A341524
Dissolved Tellurium (Te)	ug/L	<0.020	0.020	A341524	<0.020	0.020	A341524	<0.020	0.020	A341524
Dissolved Thallium (TI)	ug/L	<0.0020	0.0020	A341524	<0.0020	0.0020	A341524	<0.0020	0.0020	A341524
Dissolved Thorium (Th)	ug/L	<0.0050	0.0050	A341524	<0.0050	0.0050	A341524	<0.0050	0.0050	A341524
Dissolved Tin (Sn)	ug/L	<0.20	0.20	A341524	<0.20	0.20	A341524	<0.20	0.20	A341524
Dissolved Titanium (Ti)	ug/L	<0.50	0.50	A341524	<0.50	0.50	A341524	<0.50	0.50	A341524
Dissolved Tungsten (W)	ug/L	<0.010	0.010	A341524	<0.010	0.010	A341524	<0.010	0.010	A341524
Dissolved Uranium (U)	ug/L	1.21	0.0020	A341524	1.94	0.0020	A341524	1.79	0.0020	A341524
Dissolved Vanadium (V)	ug/L	<0.20	0.20	A341524	<0.20	0.20	A341524	<0.20	0.20	A341524
Dissolved Zinc (Zn)	ug/L	18.8	0.10	A341524	1.22	0.10	A341524	1.83	0.10	A341524
Dissolved Zirconium (Zr)	ug/L	<0.10	0.10	A341524	<0.10	0.10	A341524	<0.10	0.10	A341524
Dissolved Calcium (Ca)	mg/L	103	0.050	A340086	85.0	0.050	A340086	86.0	0.050	A340086
RDL = Reportable Detection Lir	nit					•	•			



BV Labs ID		AFC784			AFC785			AFC786		
Sampling Date		2021/08/31			2021/08/31			2021/08/31		
Sampling Date		11:30			13:45			14:15		
COC Number		C#644610-01-01			C#644610-01-01			C#644610-01-01		
	UNITS	2021725-03	RDL	QC Batch	2021725-04	RDL	QC Batch	2021725-05	RDL	QC Batch
Dissolved Magnesium (Mg)	mg/L	23.9	0.050	A340086	20.6	0.050	A340086	21.8	0.050	A340086
Dissolved Potassium (K)	mg/L	0.481	0.050	A340086	0.275	0.050	A340086	0.290	0.050	A340086
Dissolved Sodium (Na)	mg/L	1.45	0.050	A340086	0.855	0.050	A340086	0.779	0.050	A340086
Dissolved Sulphur (S)	mg/L	89.1	3.0	A340086	62.0	3.0	A340086	67.8	3.0	A340086
Total Metals by ICPMS										
Total Aluminum (AI)	ug/L	422	0.50	A341316	27.3	3.0	A341287	49.3	0.50	A341316
Total Antimony (Sb)	ug/L	0.156	0.020	A341316	0.119	0.020	A341287	0.131	0.020	A341316
Total Arsenic (As)	ug/L	44.4	0.020	A341316	28.4	0.020	A341287	35.3	0.020	A341316
Total Barium (Ba)	ug/L	11.6	0.020	A341316	11.3	0.050	A341287	10.9	0.020	A341316
Total Beryllium (Be)	ug/L	0.024	0.010	A341316	<0.010	0.010	A341287	<0.010	0.010	A341316
Total Bismuth (Bi)	ug/L	<0.0050	0.0050	A341316	<0.010	0.010	A341287	<0.0050	0.0050	A341316
Total Boron (B)	ug/L	<10	10	A341316	<10	10	A341287	<10	10	A341316
Total Cadmium (Cd)	ug/L	0.203	0.0050	A341316	0.0062	0.0050	A341287	0.0118	0.0050	A341316
Total Chromium (Cr)	ug/L	<0.10	0.10	A341316	<0.10	0.10	A341287	<0.10	0.10	A341316
Total Cobalt (Co)	ug/L	15.6	0.0050	A341316	0.918	0.010	A341287	1.44	0.0050	A341316
Total Copper (Cu)	ug/L	3.98	0.050	A341316	<0.10	0.10	A341287	0.120	0.050	A341316
Total Iron (Fe)	ug/L	3230	1.0	A341316	1380	5.0	A341287	2560	1.0	A341316
Total Lead (Pb)	ug/L	0.0092	0.0050	A341316	<0.020	0.020	A341287	0.0130	0.0050	A341316
Total Lithium (Li)	ug/L	2.55	0.50	A341316	1.24	0.50	A341287	1.36	0.50	A341316
Total Manganese (Mn)	ug/L	84.6	0.050	A341316	36.0	0.10	A341287	56.6	0.050	A341316
Total Molybdenum (Mo)	ug/L	0.091	0.050	A341316	0.150	0.050	A341287	0.147	0.050	A341316
Total Nickel (Ni)	ug/L	9.88	0.020	A341316	1.58	0.10	A341287	2.36	0.020	A341316
Total Phosphorus (P)	ug/L				6.2	5.0	A341287			
Total Selenium (Se)	ug/L	0.602	0.040	A341316	1.04	0.040	A341287	0.961	0.040	A341316
Total Silicon (Si)	ug/L	3930	50	A341316	2450	50	A341287	2270	50	A341316
Total Silver (Ag)	ug/L	<0.0050	0.0050	A341316	<0.010	0.010	A341287	<0.0050	0.0050	A341316
Total Strontium (Sr)	ug/L	255	0.050	A341316	233	0.050	A341287	225	0.050	A341316
Total Tellurium (Te)	ug/L	<0.020	0.020	A341316				<0.020	0.020	A341316
Total Thallium (TI)	ug/L	0.0021	0.0020	A341316	<0.0020	0.0020	A341287	<0.0020	0.0020	A341316
Total Thorium (Th)	ug/L	<0.0050	0.0050	A341316				<0.0050	0.0050	A341316
Total Tin (Sn)	ug/L	<0.20	0.20	A341316	<0.20	0.20	A341287	<0.20	0.20	A341316
Total Titanium (Ti)	ug/L	<0.50	0.50	A341316	<2.0	2.0	A341287	<0.50	0.50	A341316
Total Tungsten (W)	ug/L	<0.010	0.010	A341316				<0.010	0.010	A341316
RDL = Reportable Detection Lir	mit									



BV Labs ID		AFC784			AFC785			AFC786		
Sampling Date		2021/08/31			2021/08/31			2021/08/31		
Sampling Date		11:30			13:45			14:15		
COC Number		C#644610-01-01			C#644610-01-01			C#644610-01-01		
	UNITS	2021725-03	RDL	QC Batch	2021725-04	RDL	QC Batch	2021725-05	RDL	QC Batch
Total Uranium (U)	ug/L	1.22	0.0020	A341316	1.98	0.0050	A341287	1.80	0.0020	A341316
Total Vanadium (V)	ug/L	<0.20	0.20	A341316	<0.20	0.20	A341287	<0.20	0.20	A341316
Total Zinc (Zn)	ug/L	30.0	0.10	A341316	2.4	1.0	A341287	3.36	0.10	A341316
Total Zirconium (Zr)	ug/L	<0.10	0.10	A341316	<0.10	0.10	A341287	<0.10	0.10	A341316
Total Calcium (Ca)	mg/L	105	0.050	A340088	86.3	0.25	A340088	86.5	0.050	A340088
Total Magnesium (Mg)	mg/L	24.4	0.050	A340088	20.5	0.25	A340088	21.8	0.050	A340088
Total Potassium (K)	mg/L	0.482	0.050	A340088	0.27	0.25	A340088	0.290	0.050	A340088
Total Sodium (Na)	mg/L	1.46	0.050	A340088	0.84	0.25	A340088	0.773	0.050	A340088
Total Sulphur (S)	mg/L	90.9	3.0	A340088	61.3	3.0	A340088	66.3	3.0	A340088
RDL = Reportable Detection L	imit									



•

BV Labs ID		AFC787	AFC788	AFC789	AFC790	AFC791		
Sampling Date		2021/08/31 14:30	2021/08/31 15:30	2021/08/31 16:45	2021/08/31	2021/08/31 18:00		
COC Number		C#644610-01-01	C#644610-01-01	C#644610-01-01	C#644610-01-01	C#644610-01-01		
	UNITS	2021725-06	2021725-07	2021725-08	2021725-09	2021725-10	RDL	QC Batch
Dissolved Metals by ICPMS								
Dissolved Aluminum (AI)	ug/L	1.26	1.33	1.00	1.66	6.62	0.50	A341524
Dissolved Antimony (Sb)	ug/L	0.070	0.068	0.100	0.107	0.189	0.020	A341524
Dissolved Arsenic (As)	ug/L	23.5	20.7	22.0	21.4	26.9	0.020	A341524
Dissolved Barium (Ba)	ug/L	10.7	11.1	9.26	8.96	10.0	0.020	A341524
Dissolved Beryllium (Be)	ug/L	<0.010	<0.010	<0.010	<0.010	<0.010	0.010	A341524
Dissolved Bismuth (Bi)	ug/L	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	0.0050	A341524
Dissolved Boron (B)	ug/L	<10	<10	<10	<10	<10	10	A341524
Dissolved Cadmium (Cd)	ug/L	<0.0050	<0.0050	<0.0050	<0.0050	0.0064	0.0050	A341524
Dissolved Chromium (Cr)	ug/L	<0.10	<0.10	<0.10	<0.10	<0.10	0.10	A341524
Dissolved Cobalt (Co)	ug/L	0.0213	0.0195	0.0219	0.0197	0.686	0.0050	A341524
Dissolved Copper (Cu)	ug/L	<0.050	<0.050	0.075	0.086	0.192	0.050	A341524
Dissolved Iron (Fe)	ug/L	<1.0	<1.0	<1.0	<1.0	242	1.0	A341524
Dissolved Lead (Pb)	ug/L	<0.0050	0.0120	<0.0050	<0.0050	<0.0050	0.0050	A341524
Dissolved Lithium (Li)	ug/L	0.86	0.58	0.66	0.64	2.44	0.50	A341524
Dissolved Manganese (Mn)	ug/L	<0.050	<0.050	<0.050	<0.050	48.8	0.050	A341524
Dissolved Molybdenum (Mo)	ug/L	0.138	0.156	0.229	0.223	0.102	0.050	A341524
Dissolved Nickel (Ni)	ug/L	0.129	0.098	0.389	0.341	2.96	0.020	A341524
Dissolved Selenium (Se)	ug/L	0.957	1.21	1.40	1.30	0.680	0.040	A341524
Dissolved Silicon (Si)	ug/L	2420	2070	2050	2010	2650	50	A341524
Dissolved Silver (Ag)	ug/L	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	0.0050	A341524
Dissolved Strontium (Sr)	ug/L	213	199	194	188	264	0.050	A341524
Dissolved Tellurium (Te)	ug/L	<0.020	<0.020	<0.020	<0.020	<0.020	0.020	A341524
Dissolved Thallium (TI)	ug/L	<0.0020	<0.0020	<0.0020	<0.0020	0.0026	0.0020	A341524
Dissolved Thorium (Th)	ug/L	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	0.0050	A341524
Dissolved Tin (Sn)	ug/L	<0.20	<0.20	<0.20	<0.20	<0.20	0.20	A341524
Dissolved Titanium (Ti)	ug/L	<0.50	<0.50	<0.50	<0.50	<0.50	0.50	A341524
Dissolved Tungsten (W)	ug/L	<0.010	<0.010	<0.010	<0.010	<0.010	0.010	A341524
Dissolved Uranium (U)	ug/L	2.04	2.10	2.14	2.07	1.10	0.0020	A341524
Dissolved Vanadium (V)	ug/L	<0.20	<0.20	<0.20	<0.20	<0.20	0.20	A341524
Dissolved Zinc (Zn)	ug/L	<0.10	<0.10	<0.10	<0.10	0.53	0.10	A341524
Dissolved Zirconium (Zr)	ug/L	<0.10	<0.10	<0.10	<0.10	<0.10	0.10	A341524
Dissolved Calcium (Ca)	mg/L	76.1	71.4	83.0	81.1	115	0.050	A340086
RDL = Reportable Detection Li	mit							



ELEMENTS BY ATOMIC SPECTROSCOPY (WATER)

BV Labs ID		AFC787	AFC788	AFC789	AFC790	AFC791		
Sampling Date		2021/08/31 14:30	2021/08/31 15:30	2021/08/31 16:45	2021/08/31	2021/08/31 18:00		
COC Number		C#644610-01-01	C#644610-01-01	C#644610-01-01	C#644610-01-01	C#644610-01-01		
	UNITS	2021725-06	2021725-07	2021725-08	2021725-09	2021725-10	RDL	QC Batch
Dissolved Magnesium (Mg)	mg/L	16.3	16.7	20.0	19.1	29.2	0.050	A340086
Dissolved Potassium (K)	mg/L	0.230	0.206	0.190	0.187	0.477	0.050	A340086
Dissolved Sodium (Na)	mg/L	0.935	0.588	0.596	0.575	0.939	0.050	A340086
Dissolved Sulphur (S)	mg/L	47.0	42.3	57.2	53.6	105	3.0	A340086
Total Metals by ICPMS	•						•	
Total Aluminum (Al)	ug/L	1.11	1.22	1.32	2.00	7.54	0.50	A341316
Total Antimony (Sb)	ug/L	0.072	0.071	0.101	0.098	0.184	0.020	A341316
Total Arsenic (As)	ug/L	24.3	20.9	22.5	21.1	27.7	0.020	A341316
Total Barium (Ba)	ug/L	10.9	11.2	9.17	8.68	10.0	0.020	A341316
Total Beryllium (Be)	ug/L	<0.010	<0.010	<0.010	<0.010	<0.010	0.010	A341316
Total Bismuth (Bi)	ug/L	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	0.0050	A341316
Total Boron (B)	ug/L	<10	<10	<10	<10	<10	10	A341316
Total Cadmium (Cd)	ug/L	<0.0050	<0.0050	<0.0050	<0.0050	0.0073	0.0050	A341316
Total Chromium (Cr)	ug/L	<0.10	<0.10	<0.10	<0.10	<0.10	0.10	A341316
Total Cobalt (Co)	ug/L	0.0180	0.0220	0.0228	0.0219	0.683	0.0050	A341316
Total Copper (Cu)	ug/L	<0.050	<0.050	0.078	0.095	0.163	0.050	A341316
Total Iron (Fe)	ug/L	<1.0	<1.0	<1.0	1.2	246	1.0	A341316
Total Lead (Pb)	ug/L	<0.0050	0.0065	<0.0050	0.0076	0.0058	0.0050	A341316
Total Lithium (Li)	ug/L	0.78	0.50	0.63	0.59	2.23	0.50	A341316
Total Manganese (Mn)	ug/L	0.113	0.097	0.143	0.161	48.1	0.050	A341316
Total Molybdenum (Mo)	ug/L	0.141	0.149	0.228	0.226	0.122	0.050	A341316
Total Nickel (Ni)	ug/L	0.136	0.069	0.389	0.370	2.84	0.020	A341316
Total Selenium (Se)	ug/L	0.963	1.17	1.39	1.27	0.630	0.040	A341316
Total Silicon (Si)	ug/L	2400	2040	1980	1940	2600	50	A341316
Total Silver (Ag)	ug/L	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	0.0050	A341316
Total Strontium (Sr)	ug/L	213	198	191	184	252	0.050	A341316
Total Tellurium (Te)	ug/L	<0.020	<0.020	<0.020	<0.020	<0.020	0.020	A341316
Total Thallium (TI)	ug/L	<0.0020	<0.0020	<0.0020	<0.0020	<0.0020	0.0020	A341316
Total Thorium (Th)	ug/L	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	0.0050	A341316
Total Tin (Sn)	ug/L	<0.20	<0.20	<0.20	<0.20	<0.20	0.20	A341316
Total Titanium (Ti)	ug/L	<0.50	<0.50	<0.50	<0.50	<0.50	0.50	A341316
Total Tungsten (W)	ug/L	<0.010	<0.010	<0.010	<0.010	<0.010	0.010	A341316

RDL = Reportable Detection Limit

N/A = Not Applicable



BV Labs ID		AFC787	AFC788	AFC789	AFC790	AFC791		
Sampling Date		2021/08/31 14:30	2021/08/31 15:30	2021/08/31 16:45	2021/08/31	2021/08/31 18:00		
COC Number		C#644610-01-01	C#644610-01-01	C#644610-01-01	C#644610-01-01	C#644610-01-01		
	UNITS	2021725-06	2021725-07	2021725-08	2021725-09	2021725-10	RDL	QC Batch
Total Uranium (U)	ug/L	2.02	2.11	2.11	2.04	1.07	0.0020	A341316
Total Vanadium (V)	ug/L	<0.20	<0.20	<0.20	<0.20	<0.20	0.20	A341316
Total Zinc (Zn)	ug/L	1.03	1.08	0.80	1.08	1.17	0.10	A341316
Total Zirconium (Zr)	ug/L	<0.10	<0.10	<0.10	<0.10	<0.10	0.10	A341316
Total Calcium (Ca)	mg/L	74.2	71.3	80.8	80.2	112	0.050	A340088
Total Magnesium (Mg)	mg/L	16.1	16.4	19.8	19.2	28.4	0.050	A340088
Total Potassium (K)	mg/L	0.223	0.201	0.192	0.187	0.457	0.050	A340088
Total Sodium (Na)	mg/L	0.916	0.589	0.617	0.579	0.905	0.050	A340088
Total Sulphur (S)	mg/L	46.9	42.6	57.4	53.4	105	3.0	A340088
RDL = Reportable Detection Li	mit							



ELEMENTS BY ATOMIC SPECTROSCOPY (WATER)

BV Labs ID		AFC791		
Sampling Date		2021/08/31 18:00		
COC Number		C#644610-01-01		
	UNITS	2021725-10 Lab-Dup	RDL	QC Batch
Dissolved Metals by ICPMS				
Dissolved Aluminum (AI)	ug/L	6.18	0.50	A341524
Dissolved Antimony (Sb)	ug/L	0.184	0.020	A341524
Dissolved Arsenic (As)	ug/L	26.8	0.020	A341524
Dissolved Barium (Ba)	ug/L	9.99	0.020	A341524
Dissolved Beryllium (Be)	ug/L	<0.010	0.010	A341524
Dissolved Bismuth (Bi)	ug/L	<0.0050	0.0050	A341524
Dissolved Boron (B)	ug/L	<10	10	A341524
Dissolved Cadmium (Cd)	ug/L	0.0068	0.0050	A341524
Dissolved Chromium (Cr)	ug/L	<0.10	0.10	A341524
Dissolved Cobalt (Co)	ug/L	0.693	0.0050	A341524
Dissolved Copper (Cu)	ug/L	0.185	0.050	A341524
Dissolved Iron (Fe)	ug/L	239	1.0	A341524
Dissolved Lead (Pb)	ug/L	<0.0050	0.0050	A341524
Dissolved Lithium (Li)	ug/L	2.32	0.50	A341524
Dissolved Manganese (Mn)	ug/L	48.8	0.050	A341524
Dissolved Molybdenum (Mo)	ug/L	0.124	0.050	A341524
Dissolved Nickel (Ni)	ug/L	2.97	0.020	A341524
Dissolved Selenium (Se)	ug/L	0.679	0.040	A341524
Dissolved Silicon (Si)	ug/L	2630	50	A341524
Dissolved Silver (Ag)	ug/L	<0.0050	0.0050	A341524
Dissolved Strontium (Sr)	ug/L	255	0.050	A341524
Dissolved Tellurium (Te)	ug/L	<0.020	0.020	A341524
Dissolved Thallium (TI)	ug/L	0.0023	0.0020	A341524
Dissolved Thorium (Th)	ug/L	<0.0050	0.0050	A341524
Dissolved Tin (Sn)	ug/L	<0.20	0.20	A341524
Dissolved Titanium (Ti)	ug/L	<0.50	0.50	A341524
Dissolved Tungsten (W)	ug/L	<0.010	0.010	A341524
Dissolved Uranium (U)	ug/L	1.09	0.0020	A341524
Dissolved Vanadium (V)	ug/L	<0.20	0.20	A341524
Dissolved Zinc (Zn)	ug/L	0.52	0.10	A341524
Dissolved Zirconium (Zr)	ug/L	<0.10	0.10	A341524



Report Date: 2021/09/10

Government of Yukon – Dept of ENV Client Project #: 2021-Ketza Sampler Initials: SL

GENERAL COMMENTS

Each temperature is the average of up to three cooler temperatures taken at receipt

Package 1	6.0°C
Package 2	5.7°C

Results relate only to the items tested.



Report Date: 2021/09/10

Government of Yukon – Dept of ENV Client Project #: 2021-Ketza

Sampler Initials: SL

QUALITY ASSURANCE REPORT

QA/QC Batch	Init	OC Type	Parameter	Data Analyzad	Value	Recovery	UNITS	QC Limits
A341287	SOM	QC Type Matrix Spike	Total Aluminum (Al)	Date Analyzed 2021/09/04	value	NC	%	80 - 120
A341207	JOIVI	Width Spike	Total Antimony (Sb)	2021/09/04		99	%	80 - 120
			Total Arsenic (As)	2021/09/04		106	%	80 - 120
			Total Barium (Ba)	2021/09/04		NC	%	80 - 120
			Total Beryllium (Be)	2021/09/04		101	%	80 - 120
			Total Bismuth (Bi)	2021/09/04		97	%	80 - 120
			Total Boron (B)	2021/09/04		NC	%	80 - 120
			Total Cadmium (Cd)	2021/09/04		99	%	80 - 120
			Total Chromium (Cr)	2021/09/04		105	%	80 - 120
			Total Cobalt (Co)	2021/09/04		98	%	80 - 120
			Total Copper (Cu)	2021/09/04		95	%	80 - 120
			Total Iron (Fe)	2021/09/04		NC	%	80 - 120
			Total Lead (Pb)	2021/09/04		101	%	80 - 120
			Total Lithium (Li)	2021/09/04		NC	%	80 - 120
			Total Manganese (Mn)	2021/09/04		NC	%	80 - 120
			Total Molybdenum (Mo)	2021/09/04		NC	%	80 - 120
			Total Nickel (Ni)	2021/09/04		96	%	80 - 120
			Total Phosphorus (P)	2021/09/04		102	%	80 - 120
			Total Selenium (Se)	2021/09/04		97	%	80 - 120
			Total Silicon (Si)	2021/09/04		NC	%	80 - 120
			Total Silver (Ag)	2021/09/04		97	%	80 - 120
			Total Strontium (Sr)	2021/09/04		NC	%	80 - 120
			Total Thallium (TI)	2021/09/04		103	%	80 - 120
		Total Tin (Sn)	2021/09/04		98	%	80 - 120	
		Total Titanium (Ti)	2021/09/04		NC	%	80 - 120	
			Total Uranium (U)	2021/09/04		109	%	80 - 120
			Total Vanadium (V)	2021/09/04		109	%	80 - 120
			Total Zinc (Zn)	2021/09/04		100	%	80 - 120
			Total Zirconium (Zr)	2021/09/04		NC	%	80 - 120
A341287	SOM	Spiked Blank	Total Aluminum (Al)	2021/09/04		97	%	80 - 120
		•	Total Antimony (Sb)	2021/09/04		100	%	80 - 120
			Total Arsenic (As)	2021/09/04		99	%	80 - 120
			Total Barium (Ba)	2021/09/04		97	%	80 - 120
			Total Beryllium (Be)	2021/09/04		103	%	80 - 120
			Total Bismuth (Bi)	2021/09/04		99	%	80 - 120
			Total Boron (B)	2021/09/04		105	%	80 - 120
			Total Cadmium (Cd)	2021/09/04		99	%	80 - 120
			Total Chromium (Cr)	2021/09/04		98	%	80 - 120
			Total Cobalt (Co)	2021/09/04		97	%	80 - 120
			Total Copper (Cu)	2021/09/04		97	%	80 - 120
			Total Iron (Fe)	2021/09/04		102	%	80 - 120
			Total Lead (Pb)	2021/09/04		101	%	80 - 120
			Total Lithium (Li)	2021/09/04		97	%	80 - 120
			Total Manganese (Mn)	2021/09/04		98	%	80 - 120
			Total Molybdenum (Mo)	2021/09/04		100	%	80 - 120
			Total Nickel (Ni)	2021/09/04		98	%	80 - 120
			Total Phosphorus (P)	2021/09/04		97	%	80 - 120
			Total Selenium (Se)	2021/09/04		100	%	80 - 120
			Total Silicon (Si)	2021/09/04		106	%	80 - 120
			Total Silver (Ag)	2021/09/04		98	%	80 - 120
			Total Strontium (Sr)	2021/09/04		97	%	80 - 120
			Total Thallium (TI)	2021/09/04		94	%	80 - 120
			Total Tin (Sn)	2021/09/04		99	%	80 - 120
			Total Titanium (Ti)	2021/09/04		100	%	80 - 120



Sampler Initials: SL

QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
			Total Uranium (U)	2021/09/04		106	%	80 - 120
			Total Vanadium (V)	2021/09/04		98	%	80 - 120
			Total Zinc (Zn)	2021/09/04		100	%	80 - 120
			Total Zirconium (Zr)	2021/09/04		97	%	80 - 120
A341287	SOM	Method Blank	Total Aluminum (AI)	2021/09/04	<3.0		ug/L	
			Total Antimony (Sb)	2021/09/04	<0.020		ug/L	
			Total Arsenic (As)	2021/09/04	<0.020		ug/L	
			Total Barium (Ba)	2021/09/04	<0.050		ug/L	
			Total Beryllium (Be)	2021/09/04	<0.010		ug/L	
			Total Bismuth (Bi)	2021/09/04	<0.010		ug/L	
			Total Boron (B)	2021/09/04	<10		ug/L	
			Total Cadmium (Cd)	2021/09/04	<0.0050		ug/L	
			Total Chromium (Cr)	2021/09/04	<0.10		ug/L	
			Total Cobalt (Co)	2021/09/04	<0.010		ug/L	
			Total Copper (Cu)	2021/09/04	<0.10		ug/L	
			Total Iron (Fe)	2021/09/04	<5.0		ug/L	
			Total Lead (Pb)	2021/09/04	<0.020		ug/L	
			Total Lead (FB) Total Lithium (Li)	2021/09/04	<0.50		ug/L ug/L	
			Total Manganese (Mn)	2021/09/04	<0.10		ug/L	
			Total Maliganese (Mil) Total Molybdenum (Mo)	2021/09/04	<0.10		ug/L	
			Total Nickel (Ni)	2021/09/04	<0.10		ug/L ug/L	
			` '		<5.0			
			Total Phosphorus (P)	2021/09/04			ug/L	
			Total Silican (Si)	2021/09/04	<0.040		ug/L	
			Total Silicon (Si)	2021/09/04	<50		ug/L	
			Total Silver (Ag)	2021/09/04	<0.010		ug/L	
			Total Strontium (Sr)	2021/09/04	<0.050		ug/L	
			Total Thallium (TI)	2021/09/04	<0.0020		ug/L	
			Total Tin (Sn)	2021/09/04	<0.20		ug/L	
			Total Titanium (Ti)	2021/09/04	<2.0		ug/L	
			Total Uranium (U)	2021/09/04	<0.0050		ug/L	
			Total Vanadium (V)	2021/09/04	<0.20		ug/L	
			Total Zinc (Zn)	2021/09/04	<1.0		ug/L	
			Total Zirconium (Zr)	2021/09/04	<0.10		ug/L	
4341287	SOM	RPD	Total Aluminum (Al)	2021/09/04	4.9		%	20
			Total Antimony (Sb)	2021/09/04	6.4		%	20
			Total Arsenic (As)	2021/09/04	3.1		%	20
			Total Barium (Ba)	2021/09/04	2.4		%	20
			Total Beryllium (Be)	2021/09/04	NC		%	20
			Total Bismuth (Bi)	2021/09/04	NC		%	20
			Total Boron (B)	2021/09/04	2.5		%	20
			Total Cadmium (Cd)	2021/09/04	NC		%	20
			Total Chromium (Cr)	2021/09/04	9.2		%	20
			Total Cobalt (Co)	2021/09/04	1.2		%	20
			Total Copper (Cu)	2021/09/04	3.2		%	20
			Total Iron (Fe)	2021/09/04	0.42		%	20
			Total Lead (Pb)	2021/09/04	0.085		%	20
			Total Lithium (Li)	2021/09/04	0.45		%	20
			Total Manganese (Mn)	2021/09/04	0.93		%	20
			Total Molybdenum (Mo)	2021/09/04	0.17		%	20
			Total Nickel (Ni)	2021/09/04	1.5		%	20
			Total Phosphorus (P)	2021/09/04	9.8		%	20
			Total Filosphorus (1) Total Selenium (Se)	2021/09/04	2.3		%	20
			Total Silicon (Si)	2021/09/04	2.5		%	20
			i otai siiicoii (SI)	2021/09/04	۷.5		/0	20



Report Date: 2021/09/10

Government of Yukon – Dept of ENV Client Project #: 2021-Ketza

Sampler Initials: SL

QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limit
			Total Strontium (Sr)	2021/09/04	1.3		%	20
			Total Thallium (TI)	2021/09/04	NC		%	20
			Total Tin (Sn)	2021/09/04	NC		%	20
			Total Titanium (Ti)	2021/09/04	17		%	20
			Total Uranium (U)	2021/09/04	2.1		%	20
			Total Vanadium (V)	2021/09/04	1.8		%	20
			Total Zinc (Zn)	2021/09/04	2.1		%	20
			Total Zirconium (Zr)	2021/09/04	13		%	20
A341316	JLP	Matrix Spike [AFC782-10]	Total Aluminum (Al)	2021/09/07		112	%	80 - 120
			Total Antimony (Sb)	2021/09/07		101	%	80 - 120
			Total Arsenic (As)	2021/09/07		104	%	80 - 120
			Total Barium (Ba)	2021/09/07		101	%	80 - 120
			Total Beryllium (Be)	2021/09/07		98	%	80 - 120
			Total Bismuth (Bi)	2021/09/07		99	%	80 - 120
			Total Boron (B)	2021/09/07		102	%	80 - 120
			Total Cadmium (Cd)	2021/09/07		100	%	80 - 120
			Total Chromium (Cr)	2021/09/07		100	%	80 - 120
			Total Cobalt (Co)	2021/09/07		98	%	80 - 120
			Total Copper (Cu)	2021/09/07		93	% %	80 - 120
			Total Iron (Fe)	2021/09/07 2021/09/07		NC	%	80 - 120
			Total Lishings (Li)			101	%	80 - 120
			Total Lithium (Li)	2021/09/07		98	%	80 - 120
			Total Manganese (Mn)	2021/09/07		NC	%	80 - 120
			Total Molybdenum (Mo)	2021/09/07		107	%	80 - 120
			Total Nickel (Ni)	2021/09/07		96	%	80 - 120
			Total Selenium (Se)	2021/09/07		106	%	80 - 120
			Total Silicon (Si)	2021/09/07		113	%	80 - 120
			Total Silver (Ag)	2021/09/07		99	%	80 - 120
			Total Strontium (Sr)	2021/09/07		NC	%	80 - 120
			Total Tellurium (Te)	2021/09/07		95	%	80 - 120
			Total Thallium (TI)	2021/09/07		100	%	80 - 120
			Total Thorium (Th)	2021/09/07		107	%	80 - 120
			Total Tin (Sn)	2021/09/07		102	%	80 - 120
			Total Titanium (Ti)	2021/09/07		103	%	80 - 120
			Total Tungsten (W)	2021/09/07		105	%	80 - 120
			Total Uranium (U)	2021/09/07		107	%	80 - 120
			Total Vanadium (V)	2021/09/07		103	%	80 - 120
			Total Zinc (Zn)	2021/09/07		NC	%	80 - 120
			Total Zirconium (Zr)	2021/09/07		108	%	80 - 120
A341316	JLP	Spiked Blank	Total Aluminum (Al)	2021/09/03		95	%	80 - 120
			Total Antimony (Sb)	2021/09/03		97	%	80 - 120
			Total Arsenic (As)	2021/09/03		98	%	80 - 120
			Total Barium (Ba)	2021/09/03		96	%	80 - 120
			Total Beryllium (Be)	2021/09/03		98	%	80 - 120
			Total Bismuth (Bi)	2021/09/03		98	%	80 - 120
			Total Boron (B)	2021/09/03		100	%	80 - 120
			Total Cadmium (Cd)	2021/09/03		98	%	80 - 120
			Total Chromium (Cr)	2021/09/03		96	%	80 - 120
			Total Cobalt (Co)	2021/09/03		96	%	80 - 120
			Total Copper (Cu)	2021/09/03		96	%	80 - 120
			Total Iron (Fe)	2021/09/03		101	%	80 - 120
			Total Lead (Pb)	2021/09/03		101	% %	80 - 120
			Total Lithium (Li)	2021/09/03		91	% %	80 - 120 80 - 120
		condition and the	7071/09/03		91	7/0	0U - 1/1	



Sampler Initials: SL

QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
		20.760	Total Molybdenum (Mo)	2021/09/03		99	%	80 - 120
			Total Nickel (Ni)	2021/09/03		97	%	80 - 120
			Total Selenium (Se)	2021/09/03		102	%	80 - 120
			Total Silicon (Si)	2021/09/03		101	%	80 - 120
			Total Silver (Ag)	2021/09/03		97	%	80 - 120
			Total Strontium (Sr)	2021/09/03		95	%	80 - 120
			Total Tellurium (Te)	2021/09/03		101	%	80 - 120
			Total Thallium (TI)	2021/09/03		91	%	80 - 120
			Total Thorium (Th)	2021/09/03		96	%	80 - 120
			Total Tin (Sn)	2021/09/03		98	%	80 - 120
			Total Titanium (Ti)	2021/09/03		98	%	80 - 120
			Total Tungsten (W)	2021/09/03		97	%	80 - 120
			Total Uranium (U)	2021/09/03		102	%	80 - 120
			Total Vanadium (V)	2021/09/03		97	%	80 - 120
			Total Zinc (Zn)	2021/09/03		102	%	80 - 120
			Total Ziric (Zr)	2021/09/03		100	%	80 - 120
A341316	JLP	Method Blank	Total Aluminum (AI)	2021/09/03	<0.50	100	ug/L	00 120
A341310	JLI	WECHOU DIAIR	Total Antimony (Sb)	2021/09/03	<0.020		ug/L	
			Total Artimony (35)	2021/09/03	<0.020		ug/L ug/L	
			Total Barium (Ba)	2021/09/03	<0.020		ug/L	
			Total Baridin (Ba)	2021/09/03	<0.010			
			• • •	2021/09/03	<0.010		ug/L	
			Total Baran (B)	• •	<10		ug/L	
			Total Cadmium (Cd)	2021/09/03			ug/L	
			Total Characians (Cd)	2021/09/03	<0.0050		ug/L	
			Total Cabalt (Ca)	2021/09/03	<0.10		ug/L	
			Total Cobalt (Co)	2021/09/03	<0.0050		ug/L	
			Total Copper (Cu)	2021/09/03	<0.050		ug/L	
			Total Iron (Fe)	2021/09/03	<1.0		ug/L	
			Total Lead (Pb)	2021/09/03	<0.0050		ug/L	
			Total Lithium (Li)	2021/09/03	<0.50		ug/L	
			Total Manganese (Mn)	2021/09/03	<0.050		ug/L	
			Total Molybdenum (Mo)	2021/09/03	<0.050		ug/L	
			Total Nickel (Ni)	2021/09/03	<0.020		ug/L	
			Total Selenium (Se)	2021/09/03	<0.040		ug/L	
			Total Silicon (Si)	2021/09/03	<50		ug/L	
			Total Silver (Ag)	2021/09/03	<0.0050		ug/L	
			Total Strontium (Sr)	2021/09/03	<0.050		ug/L	
			Total Tellurium (Te)	2021/09/03	<0.020		ug/L	
			Total Thallium (Tl)	2021/09/03	0.0025,		ug/L	
					RDL=0.0020 (1)			
			Total Thorium (Th)	2021/09/03	<0.0050		ug/L	
			Total Tin (Sn)	2021/09/03	<0.20		ug/L	
			Total Titanium (Ti)	2021/09/03	<0.50		ug/L	
			Total Tungsten (W)	2021/09/03	<0.010		ug/L	
			Total Uranium (U)	2021/09/03	<0.0020		ug/L	
			Total Vanadium (V)	2021/09/03	<0.20		ug/L	
			Total Zinc (Zn)	2021/09/03	<0.10		ug/L	
			Total Zirconium (Zr)	2021/09/03	<0.10		ug/L	
A341316	JLP	RPD [AFC782-10]	Total Aluminum (Al)	2021/09/03	0.11		%	20
			Total Antimony (Sb)	2021/09/03	1.2		%	20
			Total Arsenic (As)	2021/09/03	1.2		%	20
			Total Barium (Ba)	2021/09/03	2.1		%	20
			Total Beryllium (Be)	2021/09/03	17		%	20
			Total Bismuth (Bi)	2021/09/03	NC		%	20



Sampler Initials: SL

QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
			Total Boron (B)	2021/09/03	NC		%	20
			Total Cadmium (Cd)	2021/09/03	3.2		%	20
			Total Chromium (Cr)	2021/09/03	NC		%	20
			Total Cobalt (Co)	2021/09/03	1.8		%	20
			Total Copper (Cu)	2021/09/03	1.8		%	20
			Total Iron (Fe)	2021/09/03	2.1		%	20
			Total Lead (Pb)	2021/09/03	0.19		%	20
			Total Lithium (Li)	2021/09/03	0.75		%	20
			Total Manganese (Mn)	2021/09/03	0.12		%	20
			Total Molybdenum (Mo)	2021/09/03	0.28		%	20
			Total Nickel (Ni)	2021/09/03	2.4		%	20
			Total Selenium (Se)	2021/09/03	7.0		%	20
			Total Silicon (Si)	2021/09/03	0.77		%	20
			Total Silver (Ag)	2021/09/03	NC		%	20
			Total Strontium (Sr)	2021/09/03	2.3		%	20
			Total Tellurium (Te)	2021/09/03	NC		%	20
			Total Thallium (TI)	2021/09/03	12		%	20
			Total Thorium (Th)	2021/09/03	15		%	20
			Total Tin (Sn)	2021/09/03	NC		%	20
			Total Titanium (Ti)	2021/09/03	NC		%	20
			Total Tungsten (W)	2021/09/03	3.8		%	20
			Total Uranium (U)	2021/09/03	1.0		%	20
			Total Vanadium (V)	2021/09/03	NC		%	20
			Total Zinc (Zn)	2021/09/03	1.2		%	20
			Total Zirconium (Zr)	2021/09/03	NC		%	20
A341524	JLP	Matrix Spike [AFC791-08]	Dissolved Aluminum (Al)	2021/09/04		91	%	80 - 120
			Dissolved Antimony (Sb)	2021/09/04		94	%	80 - 120
			Dissolved Arsenic (As)	2021/09/04		95	%	80 - 120
			Dissolved Barium (Ba)	2021/09/04		92	%	80 - 120
			Dissolved Beryllium (Be)	2021/09/04		90	%	80 - 120
			Dissolved Bismuth (Bi)	2021/09/04		92	%	80 - 120
			Dissolved Boron (B)	2021/09/04		91	%	80 - 120
			Dissolved Cadmium (Cd)	2021/09/04		93	%	80 - 120
			Dissolved Chromium (Cr)	2021/09/04		93	%	80 - 120
			Dissolved Cobalt (Co)	2021/09/04		90	%	80 - 120
			Dissolved Copper (Cu)	2021/09/04		89	%	80 - 120
			Dissolved Iron (Fe)	2021/09/04		96	%	80 - 120
			Dissolved Lead (Pb)	2021/09/04		95	%	80 - 120
			Dissolved Lithium (Li)	2021/09/04		86	%	80 - 120
			Dissolved Manganese (Mn)	2021/09/04		90	%	80 - 120
			Dissolved Molybdenum (Mo)	2021/09/04		101	%	80 - 120
			Dissolved Nickel (Ni)	2021/09/04		89	%	80 - 120
			Dissolved Selenium (Se)	2021/09/04		98	%	80 - 120
			Dissolved Silicon (Si)	2021/09/04		97	%	80 - 120
			Dissolved Silver (Ag)	2021/09/04		91	%	80 - 120
			Dissolved Strontium (Sr)	2021/09/04		NC	%	80 - 120
			Dissolved Tellurium (Te)	2021/09/04		95	%	80 - 120
			Dissolved Thallium (TI)	2021/09/04		89	%	80 - 120
			Dissolved Thorium (Th)	2021/09/04		95	%	80 - 120
			Dissolved Tin (Sn)	2021/09/04		94	%	80 - 120
			Dissolved Titanium (Ti)	2021/09/04		96	%	80 - 120
			Dissolved Tungsten (W)	2021/09/04		94	%	80 - 120
			Dissolved Transum (U)	2021/09/04		101	%	80 - 120
			= .55554 5.41114111 (5)	2021,00,04		101	,,,	20 120



Sampler Initials: SL

QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
			Dissolved Zinc (Zn)	2021/09/04		93	%	80 - 120
			Dissolved Zirconium (Zr)	2021/09/04		100	%	80 - 120
A341524	JLP	Spiked Blank	Dissolved Aluminum (AI)	2021/09/03		96	%	80 - 120
			Dissolved Antimony (Sb)	2021/09/03		98	%	80 - 120
			Dissolved Arsenic (As)	2021/09/03		98	%	80 - 120
			Dissolved Barium (Ba)	2021/09/03		95	%	80 - 120
			Dissolved Beryllium (Be)	2021/09/03		97	%	80 - 120
			Dissolved Bismuth (Bi)	2021/09/03		98	%	80 - 120
			Dissolved Boron (B)	2021/09/03		98	%	80 - 120
			Dissolved Cadmium (Cd)	2021/09/03		98	%	80 - 120
			Dissolved Chromium (Cr)	2021/09/03		98	%	80 - 120
			Dissolved Cobalt (Co)	2021/09/03		96	%	80 - 120
			Dissolved Copper (Cu)	2021/09/03		96	%	80 - 120
			Dissolved Iron (Fe)	2021/09/03		100	%	80 - 120
			Dissolved Lead (Pb)	2021/09/03		100	%	80 - 120
			Dissolved Lithium (Li)	2021/09/03		91	%	80 - 120
			Dissolved Manganese (Mn)	2021/09/03		97	%	80 - 120
			Dissolved Molybdenum (Mo)	2021/09/03		98	%	80 - 120
			Dissolved Nickel (Ni)	2021/09/03		97	%	80 - 120
			Dissolved Mickel (M) Dissolved Selenium (Se)	2021/09/03		99	%	80 - 120
			Dissolved Seleman (Se)	2021/09/03		102	%	80 - 120
			Dissolved Silver (Ag)	2021/09/03		96	% %	80 - 120
			Dissolved Strontium (Sr)	2021/09/03		96 97	% %	80 - 120 80 - 120
			` ,	2021/09/03		102		
			Dissolved Tellurium (Te)	• •			%	80 - 120
			Dissolved Thallium (TI)	2021/09/03		91	%	80 - 120
			Dissolved Thorium (Th)	2021/09/03		97	%	80 - 120
			Dissolved Tin (Sn)	2021/09/03		98	%	80 - 120
			Dissolved Titanium (Ti)	2021/09/03		99	%	80 - 120
			Dissolved Tungsten (W)	2021/09/03		98	%	80 - 120
			Dissolved Uranium (U)	2021/09/03		103	%	80 - 120
			Dissolved Vanadium (V)	2021/09/03		97	%	80 - 120
			Dissolved Zinc (Zn)	2021/09/03		103	%	80 - 120
			Dissolved Zirconium (Zr)	2021/09/03		99	%	80 - 12
A341524	JLP	Method Blank	Dissolved Aluminum (Al)	2021/09/04	<0.50		ug/L	
			Dissolved Antimony (Sb)	2021/09/04	<0.020		ug/L	
			Dissolved Arsenic (As)	2021/09/04	<0.020		ug/L	
			Dissolved Barium (Ba)	2021/09/04	<0.020		ug/L	
			Dissolved Beryllium (Be)	2021/09/04	< 0.010		ug/L	
			Dissolved Bismuth (Bi)	2021/09/04	<0.0050		ug/L	
			Dissolved Boron (B)	2021/09/04	<10		ug/L	
			Dissolved Cadmium (Cd)	2021/09/04	<0.0050		ug/L	
			Dissolved Chromium (Cr)	2021/09/04	<0.10		ug/L	
			Dissolved Cobalt (Co)	2021/09/04	< 0.0050		ug/L	
			Dissolved Copper (Cu)	2021/09/04	<0.050		ug/L	
			Dissolved Iron (Fe)	2021/09/04	<1.0		ug/L	
			Dissolved Lead (Pb)	2021/09/04	< 0.0050		ug/L	
			Dissolved Lithium (Li)	2021/09/04	<0.50		ug/L	
			Dissolved Manganese (Mn)	2021/09/04	<0.050		ug/L	
			Dissolved Molybdenum (Mo)	2021/09/04	<0.050		ug/L	
			Dissolved Nickel (Ni)	2021/09/04	<0.020		ug/L	
			Dissolved Selenium (Se)	2021/09/04	< 0.040		ug/L	
			Dissolved Silicon (Si)	2021/09/04	<50		ug/L	
			Dissolved Silver (Ag)	2021/09/04	<0.0050		ug/L	



Sampler Initials: SL

QUALITY ASSURANCE REPORT(CONTD)									
QA/QC Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits	
			Dissolved Tellurium (Te)	2021/09/04	<0.020		ug/L		
			Dissolved Thallium (TI)	2021/09/04	<0.0020		ug/L		
			Dissolved Thorium (Th)	2021/09/04	<0.0050		ug/L		
			Dissolved Tin (Sn)	2021/09/04	<0.20		ug/L		
			Dissolved Titanium (Ti)	2021/09/04	<0.50		ug/L		
			Dissolved Tungsten (W)	2021/09/04	< 0.010		ug/L		
			Dissolved Uranium (U)	2021/09/04	<0.0020		ug/L		
			Dissolved Vanadium (V)	2021/09/04	<0.20		ug/L		
			Dissolved Zinc (Zn)	2021/09/04	<0.10		ug/L		
			Dissolved Zirconium (Zr)	2021/09/04	< 0.10		ug/L		
A341524	JLP	RPD [AFC791-08]	Dissolved Aluminum (Al)	2021/09/04	6.9		%	20	
			Dissolved Antimony (Sb)	2021/09/04	3.0		%	20	
			Dissolved Arsenic (As)	2021/09/04	0.60		%	20	
			Dissolved Barium (Ba)	2021/09/04	0.51		%	20	
			Dissolved Beryllium (Be)	2021/09/04	NC		%	20	
			Dissolved Bismuth (Bi)	2021/09/04	NC		%	20	
			Dissolved Boron (B)	2021/09/04	NC		%	20	
			Dissolved Cadmium (Cd)	2021/09/04	6.1		%	20	
			Dissolved Chromium (Cr)	2021/09/04	NC		%	20	
			Dissolved Cobalt (Co)	2021/09/04	1.1		%	20	
			Dissolved Copper (Cu)	2021/09/04	3.9		%	20	
				2021/09/04					
			Dissolved Iron (Fe)	• •	1.2 NC		%	20	
			Dissolved Lead (Pb)	2021/09/04	NC		%	20	
			Dissolved Lithium (Li)	2021/09/04	4.9		%	20	
			Dissolved Manganese (Mn)	2021/09/04	0.0057		%	20	
			Dissolved Molybdenum (Mo)	2021/09/04	19		%	20	
			Dissolved Nickel (Ni)	2021/09/04	0.49		%	20	
			Dissolved Selenium (Se)	2021/09/04	0.10		%	20	
			Dissolved Silicon (Si)	2021/09/04	0.71		%	20	
			Dissolved Silver (Ag)	2021/09/04	NC		%	20	
			Dissolved Strontium (Sr)	2021/09/04	3.6		%	20	
			Dissolved Tellurium (Te)	2021/09/04	NC		%	20	
			Dissolved Thallium (Tl)	2021/09/04	12		%	20	
			Dissolved Thorium (Th)	2021/09/04	NC		%	20	
			Dissolved Tin (Sn)	2021/09/04	NC		%	20	
			Dissolved Titanium (Ti)	2021/09/04	NC		%	20	
			Dissolved Tungsten (W)	2021/09/04	NC		%	20	
			Dissolved Uranium (U)	2021/09/04	1.2		%	20	
			Dissolved Vanadium (V)	2021/09/04	NC		%	20	
			Dissolved Zinc (Zn)	2021/09/04	1.3		%	20	
			Dissolved Zirconium (Zr)	2021/09/04	NC		%	20	
A341762	TSO	Matrix Spike [AFC782-02]	Nitrate plus Nitrite (N)	2021/09/03	110	101	%	80 - 120	
A341762	TSO	Spiked Blank	Nitrate plus Nitrite (N)	2021/09/03		101	%	80 - 120	
		Method Blank		2021/09/03	<0.0020	104		80 - 120	
A341762	TSO		Nitrate plus Nitrite (N)				mg/L	25	
A341762	TSO	RPD [AFC782-02]	Nitrate plus Nitrite (N)	2021/09/03	5.9	100	%	25	
A341763	TSO	Matrix Spike [AFC782-02]	Nitrite (N)	2021/09/03		100	%	80 - 120	
A341763	TSO	Spiked Blank	Nitrite (N)	2021/09/03		101	%	80 - 120	
A341763	TSO	Method Blank	Nitrite (N)	2021/09/03	<0.0020		mg/L		
A341763	TSO	RPD [AFC782-02]	Nitrite (N)	2021/09/03	NC		%	25	
A341963	BO3	Spiked Blank	рН	2021/09/04		101	%	97 - 103	
A341963	BO3	RPD	рН	2021/09/04	0.14		%	N/A	
			рН	2021/09/04	0.69		%	N/A	
A341966	BO3	Spiked Blank	Alkalinity (Total as CaCO3)	2021/09/04		95	%	80 - 120	
A341966	BO3	Method Blank	Alkalinity (PP as CaCO3)	2021/09/04	<1.0		mg/L		



Sampler Initials: SL

QUALITY ASSURANCE REPORT(CONT'D)

QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
			Alkalinity (Total as CaCO3)	2021/09/04	<1.0		mg/L	
			Bicarbonate (HCO3)	2021/09/04	<1.0		mg/L	
			Carbonate (CO3)	2021/09/04	<1.0		mg/L	
			Hydroxide (OH)	2021/09/04	<1.0		mg/L	
A341967	BO3	Spiked Blank	Conductivity	2021/09/04		98	%	80 - 120
A341967	BO3	Method Blank	Conductivity	2021/09/04	<2.0		uS/cm	
A342005	BO3	Spiked Blank	рН	2021/09/04		101	%	97 - 103
A342005	BO3	RPD [AFC782-02]	рН	2021/09/04	3.2		%	N/A
A342005	BO3	RPD	рН	2021/09/04	12		%	N/A
A342006	BO3	Spiked Blank	Alkalinity (Total as CaCO3)	2021/09/04		97	%	80 - 120
A342006	BO3	Method Blank	Alkalinity (PP as CaCO3)	2021/09/04	<1.0		mg/L	
			Alkalinity (Total as CaCO3)	2021/09/04	<1.0		mg/L	
			Bicarbonate (HCO3)	2021/09/04	<1.0		mg/L	
			Carbonate (CO3)	2021/09/04	<1.0		mg/L	
			Hydroxide (OH)	2021/09/04	<1.0		mg/L	
A342006	BO3	RPD [AFC782-02]	Alkalinity (PP as CaCO3)	2021/09/04	NC		%	20
			Alkalinity (Total as CaCO3)	2021/09/04	2.7		%	20
			Bicarbonate (HCO3)	2021/09/04	2.7		%	20
			Carbonate (CO3)	2021/09/04	NC		%	20
			Hydroxide (OH)	2021/09/04	NC		%	20
A342007	BO3	Spiked Blank	Conductivity	2021/09/04		100	%	80 - 120
A342007	BO3	Method Blank	Conductivity	2021/09/04	<2.0		uS/cm	
A342007	BO3	RPD [AFC782-02]	Conductivity	2021/09/04	0.68		%	10
A342432	HE1	Matrix Spike	Total Dissolved Solids	2021/09/05		95	%	80 - 120
A342432	HE1	Spiked Blank	Total Dissolved Solids	2021/09/05		96	%	80 - 120
A342432	HE1	Method Blank	Total Dissolved Solids	2021/09/05	<1.0		mg/L	
A342432	HE1	RPD	Total Dissolved Solids	2021/09/05	10		%	20
A342803	TMU	Matrix Spike [AFC785-06]	Strong Acid Dissoc. Cyanide (CN)	2021/09/07		105	%	80 - 120
A342803	TMU	Spiked Blank	Strong Acid Dissoc. Cyanide (CN)	2021/09/07		102	%	80 - 120
A342803	TMU	Method Blank	Strong Acid Dissoc. Cyanide (CN)	2021/09/07	<0.00050		mg/L	
A342803	TMU	RPD [AFC785-06]	Strong Acid Dissoc. Cyanide (CN)	2021/09/07	NC		%	20
A342809	TMU	Matrix Spike [AFC785-06]	Weak Acid Dissoc. Cyanide (CN)	2021/09/07		104	%	80 - 120
A342809	TMU	Spiked Blank	Weak Acid Dissoc. Cyanide (CN)	2021/09/07		103	%	80 - 120
A342809	TMU	Method Blank	Weak Acid Dissoc. Cyanide (CN)	2021/09/07	<0.00050		mg/L	
A342809	TMU	RPD [AFC785-06]	Weak Acid Dissoc. Cyanide (CN)	2021/09/07	NC		%	20
A343019	KWE	Matrix Spike	Dissolved Hex. Chromium (Cr 6+)	2021/09/07		86	%	80 - 120
A343019		Spiked Blank	Dissolved Hex. Chromium (Cr 6+)	2021/09/07		110	%	80 - 120
A343019		Method Blank	Dissolved Hex. Chromium (Cr 6+)	2021/09/07	<0.00099		mg/L	
A343019	KWE	RPD	Dissolved Hex. Chromium (Cr 6+)	2021/09/07	NC		%	20
A343127	CJY	Matrix Spike	Dissolved Mercury (Hg)	2021/09/07		93	%	80 - 120
A343127	CJY	Spiked Blank	Dissolved Mercury (Hg)	2021/09/07		83	%	80 - 120
A343127	CJY	Method Blank	Dissolved Mercury (Hg)	2021/09/07	<0.0019		ug/L	
A343127	CJY	RPD	Dissolved Mercury (Hg)	2021/09/07	NC		%	20
A343244	BTM	Matrix Spike [AFC787-01]	Total Suspended Solids	2021/09/08		107	%	80 - 120
A343244	BTM	Spiked Blank	Total Suspended Solids	2021/09/08		100	%	80 - 120
A343244	BTM	Method Blank	Total Suspended Solids	2021/09/08	<1.0		mg/L	
A343244	BTM	RPD	Total Suspended Solids	2021/09/08	13		%	20
A343312	BTM	Matrix Spike [AFC791-01]	Total Suspended Solids	2021/09/08		107	%	80 - 120
A343312	BTM	Spiked Blank	Total Suspended Solids	2021/09/08		102	%	80 - 120
A343312	BTM	Method Blank	Total Suspended Solids	2021/09/08	<1.0		mg/L	
A343312	BTM	RPD [AFC790-01]	Total Suspended Solids	2021/09/08	NC		%	20
A343419	CJY	Matrix Spike	Total Mercury (Hg)	2021/09/07		86	%	80 - 120
A343419	CJY	Spiked Blank	Total Mercury (Hg)	2021/09/07		83	%	80 - 120
A343419	CJY	Method Blank	Total Mercury (Hg)	2021/09/07	< 0.0019		ug/L	



Government of Yukon – Dept of ENV Client Project #: 2021-Ketza

Sampler Initials: SL

QUALITY ASSURANCE REPORT(CONT'D)

QA/QC Batch	lni+	OC Tuno	Darameter	Data Analyzad	Value	Doggwany	LINUTC	OC Limits
A343419	Init CJY	QC Type RPD [AFC782-11]	Parameter Total Mercury (Hg)	Date Analyzed 2021/09/07	Value NC	Recovery	UNITS %	QC Limits 20
A343419 A343723	KWE	Matrix Spike [AFC791-07]	Dissolved Hex. Chromium (Cr 6+)	2021/09/07	INC	93	% %	80 - 120
A343723 A343723	KWE	Spiked Blank	Dissolved Hex. Chromium (Cr 6+)	2021/09/09		105	%	80 - 120
A343723 A343723	KWE	Method Blank	Dissolved Hex. Chromium (Cr 6+)	2021/09/09	<0.00099	105		60 - 120
			, ,				mg/L	20
A343723	KWE	RPD [AFC791-07]	Dissolved Hex. Chromium (Cr 6+)	2021/09/09	NC	102	%	20
A343769	SKM	Matrix Spike	Total Ammonia (N)	2021/09/09		102	%	80 - 120 80 - 120
A343769	SKM	Spiked Blank	Total Ammonia (N)	2021/09/09	-0.0050	100	%	80 - 120
A343769	SKM	Method Blank	Total Ammonia (N)	2021/09/09	<0.0050		mg/L	20
A343769	SKM	RPD	Total Ammonia (N)	2021/09/09	4.6	101	%	20
A343810	MDO	Matrix Spike [AFC790-03]	Dissolved Organic Carbon (C)	2021/09/10		104	%	80 - 120
A343810	MDO	Spiked Blank	Dissolved Organic Carbon (C)	2021/09/09	.0.20	114	%	80 - 120
A343810	MDO	Method Blank	Dissolved Organic Carbon (C)	2021/09/09	<0.20		mg/L	
A343810	MDO	RPD [AFC790-03]	Dissolved Organic Carbon (C)	2021/09/10	NC		%	20
A343841	TSO	Matrix Spike [AFC787-04]	Total Nitrogen (N)	2021/09/09		101	%	80 - 120
A343841	TSO	Spiked Blank	Total Nitrogen (N)	2021/09/09		100	%	80 - 120
A343841	TSO	Method Blank	Total Nitrogen (N)	2021/09/09	<0.020		mg/L	
A343841	TSO	RPD [AFC787-04]	Total Nitrogen (N)	2021/09/09	0.54		%	20
A344325	FM0	Matrix Spike	Total Phosphorus (P)	2021/09/08		96	%	80 - 120
A344325	FM0	QC Standard	Total Phosphorus (P)	2021/09/08		98	%	80 - 120
A344325	FM0	Spiked Blank	Total Phosphorus (P)	2021/09/08		110	%	80 - 120
A344325	FM0	Method Blank	Total Phosphorus (P)	2021/09/08	<0.0010		mg/L	
A344325	FM0	RPD	Total Phosphorus (P)	2021/09/08	NC		%	20
A344338	FM0	Matrix Spike	Total Phosphorus (P)	2021/09/08		98	%	80 - 120
A344338	FM0	QC Standard	Total Phosphorus (P)	2021/09/08		91	%	80 - 120
A344338	FM0	Spiked Blank	Total Phosphorus (P)	2021/09/08		93	%	80 - 120
A344338	FM0	Method Blank	Total Phosphorus (P)	2021/09/08	<0.0010		mg/L	
A344338	FM0	RPD	Total Phosphorus (P)	2021/09/08	NC		%	20
A344365	FM0	Matrix Spike	Dissolved Phosphorus (P)	2021/09/08		94	%	80 - 120
A344365	FM0	QC Standard	Dissolved Phosphorus (P)	2021/09/08		88	%	80 - 120
A344365	FM0	Spiked Blank	Dissolved Phosphorus (P)	2021/09/08		103	%	80 - 120
A344365	FM0	Method Blank	Dissolved Phosphorus (P)	2021/09/08	<0.0010		mg/L	
A344365	FM0	RPD	Dissolved Phosphorus (P)	2021/09/08	NC		%	20
A346519	MO5	Matrix Spike [AFC782-02]	Dissolved Chloride (Cl)	2021/09/09		102	%	80 - 120
			Dissolved Sulphate (SO4)	2021/09/09		NC	%	80 - 120
A346519	MO5	Spiked Blank	Dissolved Chloride (Cl)	2021/09/09		103	%	80 - 120
			Dissolved Sulphate (SO4)	2021/09/09		108	%	80 - 120
A346519	MO5	Method Blank	Dissolved Chloride (Cl)	2021/09/09	<0.50		mg/L	
			Dissolved Sulphate (SO4)	2021/09/09	<0.50		mg/L	
A346519	MO5	RPD [AFC782-02]	Dissolved Chloride (Cl)	2021/09/09	NC		%	20
			Dissolved Sulphate (SO4)	2021/09/09	1.8		%	20
A346922	CJY	Matrix Spike [AFC791-09]	Dissolved Mercury (Hg)	2021/09/10		88	%	80 - 120
A346922	CJY	Spiked Blank	Dissolved Mercury (Hg)	2021/09/10		83	%	80 - 120
A346922	CJY	Method Blank	Dissolved Mercury (Hg)	2021/09/10	<0.0019		ug/L	
A346922	CJY	RPD [AFC790-09]	Dissolved Mercury (Hg)	2021/09/10	NC		%	20
A346928	CJY	Matrix Spike [AFC787-11]	Total Mercury (Hg)	2021/09/10		99	%	80 - 120
A346928	CJY	Spiked Blank	Total Mercury (Hg)	2021/09/10		96	%	80 - 120
A346928	CJY	Method Blank	Total Mercury (Hg)	2021/09/10	<0.0019		ug/L	
A346928	CJY	RPD [AFC786-11]	Total Mercury (Hg)	2021/09/10	NC		%	20
A347643	MO5	Matrix Spike [AFC782-02]	Fluoride (F)	2021/09/10		100	%	80 - 120
A347643	MO5	Spiked Blank	Fluoride (F)	2021/09/10		100	%	80 - 120
A347643	MO5	Method Blank	Fluoride (F)	2021/09/10	<0.020		mg/L	



Government of Yukon - Dept of ENV Client Project #: 2021-Ketza

Sampler Initials: SL

QUALITY ASSURANCE REPORT(CONT'D)

QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
A347643	MO5	RPD [AFC782-02]	Fluoride (F)	2021/09/10	0		%	20

N/A = Not Applicable

Duplicate: Paired analysis of a separate portion of the same sample. Used to evaluate the variance in the measurement.

Matrix Spike: A sample to which a known amount of the analyte of interest has been added. Used to evaluate sample matrix interference.

QC Standard: A sample of known concentration prepared by an external agency under stringent conditions. Used as an independent check of method accuracy.

Spiked Blank: A blank matrix sample to which a known amount of the analyte, usually from a second source, has been added. Used to evaluate method accuracy.

Method Blank: A blank matrix containing all reagents used in the analytical procedure. Used to identify laboratory contamination.

NC (Matrix Spike): The recovery in the matrix spike was not calculated. The relative difference between the concentration in the parent sample and the spike amount was too small to permit a reliable recovery calculation (matrix spike concentration was less than the native sample concentration)

NC (Duplicate RPD): The duplicate RPD was not calculated. The concentration in the sample and/or duplicate was too low to permit a reliable RPD calculation (absolute difference <= 2x RDL).

(1) Method blank exceeds acceptance limits for TI- 2X RDL acceptable for low level metals determination.



Government of Yukon – Dept of ENV Client Project #: 2021-Ketza Sampler Initials: SL

VALIDATION SIGNATURE PAGE

The analytical data and all QC contained in this report were reviewed and validated by:

David Huang, M.Sc., P.Chem., QP, Scientific Services Manager

BV Labs has procedures in place to guard against improper use of the electronic signature and have the required "signatories", as per ISO/IEC 17025, signing the reports. For Service Group specific validation please refer to the Validation Signature Page.

171.DZ1		INVOICE TO:			Report In	Alemania .		_						Project I	nformatio		- 80		Check to the control of the control	Only
onpany Name	#4977 Gove	rnment of Yukon - Dept of ENV	Company f	MA 844311 C		-		Dept of	ENV		-	ution #		C10319			C1/	# Tall	COC -	Bottle Order #:
ntad Name	Stephanie Ly		Contact No	Ctechnolo	CONTRACTOR DESCRIPTION OF THE PERSON NAMED IN		ed trime	-			F.O.						CI	0000		199340140
Pess	Name and Address of the Owner, where the	roes Branch (V-310) Box 2703	Address	Box 2703							Proj	nd #	2	2021-Ke	tza	_		-	Chain Of Custody Record	644010 Project Manager
	(867) 689-876	17		Whitehors (867) 689-		106		_	_	_	100	xX Name		_		_		-		Project Manager
ne si	refrescuence present properties	ns@yukon.ca	Phone Email	stephanie.	A PROPERTY AND ADDRESS OF THE PARTY AND ADDRES	kon.ca	Fax _				Site San	gled By	,	SW	ma				C#644510-01-01	Customer Solutions
Negutationy Cr	teria .			cial Instructions	december 1	TT	T					Analysis I			historii baydo				Turnaround Time (TAT) Req	uired
	Note: For regulat	od drinking water samples - pluase use the Dr	inking Water Chain o	f Custody Form		Vater 7	ied Febred 7 (7 / N)		& LL-TDS (Group 02)	LL DOC & Dissolved Total Phosphorus (Group 03)	, TKN & LL Total sorus (Group 04)	nia-N Low Level rved)	de SAD & WAD (Grou	ed CR3 & CR5 (Gro	LL Dissolved Metals p 05)	LL Total Metals (Groc		(will be Standa Please days Job Spe Date Re	ntimation Number	
	Sample	must be kapt cool (< 10°C) from time of sample	ng until delivery to th	Labo		date		Z o	6	000	N IN	mode	2	1 2	Ketza L (Group	Ketza L 06)		5000	CONTRACTOR OF THE PARTY OF THE	tud lab Av B)
Sample	Barcode Label	Sample (Location) Identification	Date Sampled	Time Sampled	Matrix	g,	Alk, E	2 5	188	크운	Total	4€	80	800	86	8 8 8 8		# of Dut	ine Comments	
		2021725-1	21/Aug/31	0105	W	N	4 4		X	*	*	*	*	*	X	¥		12		
		2031T25 - 03		0950	1	11	11	4	1	1	1	1	1	1	1	1	_	1		
		2021T25-03		1130	1	Ш	Ш	+	H	\perp	-	4	1	₩	1	1	_	1		
		2021725-04	\vdash	1345	-	Ш	111	+	Н	+	+	1	-	+	H	1	_	Н		
		2021T25-05	-	1415	\vdash	Ш	11	+	H	+	+	+	1	+	Н	H	_	Н	-	
		2021725-06		1430	H	₩	-	Н	\vdash	+	+	-	1	++	\vdash	H		Н		
		2021125 - 07		15:30	H	₩	-	Н	-	+	+	+	-	+	\vdash	\vdash				
		2021T25 - 08		1645	\vdash	#	H		+	+	+	-	-	-	H	H		H	-	
		2021TAS-09			1	₩		,	+	+	+	+		1	\forall	1				
		2021T25-10	- 6	18 00	- 4	1"	V	1	-	~	V	V	V	IV	V	V		4		

Bureau Veritas Canada (2019) Inc.



Your Project #: 2021-Ketza

Your C.O.C. #: 644610-04-01, 644610-05-01

Attention: Stephanie Lyons

Government of Yukon – Dept of ENV Box 2703 Whitehorse, YT Canada Y1A2C6

Report Date: 2021/09/23

Report #: R3075583 Version: 2 - Final

CERTIFICATE OF ANALYSIS

BV LABS JOB #: C165509 Received: 2021/09/03, 15:17

Sample Matrix: Water # Samples Received: 15

# Samples Received: 15					
		Date	Date		
Analyses		Extracted	Analyzed	Laboratory Method	Analytical Method
Alkalinity @25C (pp, total), CO3,HCO3,OH	9	N/A	- , , -	BBY6SOP-00026	SM 23 2320 B m
Alkalinity @25C (pp, total), CO3,HCO3,OH	6	N/A		BBY6SOP-00026	SM 23 2320 B m
Low level chloride/sulphate by AC	14	N/A	2021/09/10	BBY6SOP-00011 / BBY6SOP-00017	SM23-4500-CI/SO4-E m
Low level chloride/sulphate by AC	1	N/A	2021/09/14	BBY6SOP-00011 / BBY6SOP-00017	SM23-4500-CI/SO4-E m
Cyanide SAD (strong acid dissociable) (1)	15	N/A	2021/09/10	CAL SOP-00270	SM 23 4500-CN m
Cyanide WAD (weak acid dissociable) (1)	15	N/A	2021/09/10	CAL SOP-00270	SM 23 4500-CN m
Chromium III (Calc'd) (1, 2)	14	N/A	2021/09/13		Auto Calc
Chromium III (Calc'd) (1, 2)	1	N/A	2021/09/14		Auto Calc
Dissolved Hexavalent Chromium (1)	15	N/A	2021/09/09	AB SOP-00063	SM 23 3500-Cr B m
Carbon (DOC) (1, 3)	11	N/A	2021/09/10	AB SOP-00087	MMCW 119 1996 m
Carbon (DOC) (1, 3)	3	N/A	2021/09/11	AB SOP-00087	MMCW 119 1996 m
Carbon (DOC) (1, 3)	1	N/A	2021/09/13	AB SOP-00087	MMCW 119 1996 m
Conductivity @25C	9	N/A	2021/09/07	BBY6SOP-00026	SM 23 2510 B m
Conductivity @25C	6	N/A	2021/09/08	BBY6SOP-00026	SM 23 2510 B m
Fluoride - Mining Clients	2	N/A	2021/09/10	BBY6SOP-00048	SM 23 4500-F C m
Fluoride - Mining Clients	13	N/A	2021/09/11	BBY6SOP-00048	SM 23 4500-F C m
Hardness Total (calculated as CaCO3) (4)	14	N/A	2021/09/09	BBY WI-00033	Auto Calc
Hardness Total (calculated as CaCO3) (4)	1	N/A	2021/09/13	BBY WI-00033	Auto Calc
Hardness (calculated as CaCO3)	14	N/A	2021/09/13	BBY WI-00033	Auto Calc
Hardness (calculated as CaCO3)	1	N/A	2021/09/14	BBY WI-00033	Auto Calc
Mercury (Dissolved) by CV (2)	1	2021/09/07	2021/09/07	AB SOP-00084	BCMOE BCLM Oct2013 m
Mercury (Dissolved) by CV (2)	14	2021/09/10	2021/09/10	AB SOP-00084	BCMOE BCLM Oct2013 m
Mercury (Total) by CV	1	2021/09/07	2021/09/10	AB SOP-00084	BCMOE BCLM Oct2013 m
Mercury (Total) by CV	14	2021/09/10	2021/09/10	AB SOP-00084	BCMOE BCLM Oct2013 m
Na, K, Ca, Mg, S by CRC ICPMS (diss.)	14	N/A	2021/09/13	BBY WI-00033	Auto Calc
Na, K, Ca, Mg, S by CRC ICPMS (diss.)	1	N/A	2021/09/14	BBY WI-00033	Auto Calc
Elements by ICPMS Low Level (dissolved) (2)	14	N/A	2021/09/11	BBY7SOP-00002	EPA 6020b R2 m
Elements by ICPMS Low Level (dissolved) (2)	1	N/A	2021/09/14	BBY7SOP-00002	EPA 6020b R2 m
Elements by ICPMS Digested LL (total)	1	2021/09/08	2021/09/09	BBY7SOP-00003 / BBY7SOP-00002	EPA 6020b R2 m



Your Project #: 2021-Ketza

Your C.O.C. #: 644610-04-01, 644610-05-01

Attention: Stephanie Lyons

Government of Yukon – Dept of ENV Box 2703 Whitehorse, YT Canada Y1A2C6

Report Date: 2021/09/23

Report #: R3075583 Version: 2 - Final

CERTIFICATE OF ANALYSIS

BV LABS JOB #: C165509 Received: 2021/09/03, 15:17

Sample Matrix: Water # Samples Received: 15

		Date	Date		
Analyses	Quantity	Extracted	Analyzed	Laboratory Method	Analytical Method
Na, K, Ca, Mg, S by CRC ICPMS (total)	14	N/A	2021/09/09	BBY WI-00033	Auto Calc
Na, K, Ca, Mg, S by CRC ICPMS (total)	1	N/A	2021/09/13	BBY WI-00033	Auto Calc
Elements by ICPMS Low Level (total)	13	N/A	2021/09/08	BBY7SOP-00002	EPA 6020b R2 m
Elements by ICPMS Low Level (total)	1	N/A	2021/09/11	BBY7SOP-00002	EPA 6020b R2 m
Nitrogen (Total)	15	N/A	2021/09/09	BBY6SOP-00016	SM 23 4500-N C m
Ammonia-N Low Level (Preserved) (1)	15	N/A	2021/09/11	AB SOP-00007	SM 23 4500 NH3 A G m
Nitrate+Nitrite (N) (low level)	15	N/A	2021/09/04	BBY6SOP-00010	SM 23 4500-NO3- I m
Nitrite (N) (low level)	15	N/A	2021/09/04	BBY6SOP-00010	SM 23 4500-NO3- I m
Nitrogen - Nitrate (as N) Low Level Calc	15	N/A	2021/09/04	BBY WI-00033	Auto Calc
Filter and HNO3 Preserve for Metals	14	N/A	2021/09/03	BBY7 WI-00004	SM 23 3030B m
Filter and HNO3 Preserve for Metals	1	N/A	2021/09/13	BBY7 WI-00004	SM 23 3030B m
pH @25°C (5)	9	N/A	2021/09/07	BBY6SOP-00026	SM 23 4500-H+ B m
pH @25°C (5)	6	N/A	2021/09/08	BBY6SOP-00026	SM 23 4500-H+ B m
Total Dissolved Solids - Low Level (1)	10	2021/09/08	2021/09/08	AB SOP-00065	SM 23 2540 C m
Total Dissolved Solids - Low Level (1)	3	2021/09/09	2021/09/09	AB SOP-00065	SM 23 2540 C m
Total Dissolved Solids - Low Level (1)	1	2021/09/18	2021/09/18	AB SOP-00065	SM 23 2540 C m
Total Dissolved Solids - Low Level (1)	1	2021/09/18	2021/09/22	AB SOP-00065	SM 23 2540 C m
Total Kjeldahl Nitrogen (Total)	15	N/A	2021/09/09	BBY WI-00033	Auto Calc
Total Phosphorus Low Level Dissolved (1, 6)	11	2021/09/10	2021/09/11	AB SOP-00024	SM 23 4500-P A,B,F m
Total Phosphorus Low Level Dissolved (1, 6)	4	2021/09/10	2021/09/12	AB SOP-00024	SM 23 4500-P A,B,F m
Total Phosphorus Low Level Total (1)	10	2021/09/10	2021/09/11	AB SOP-00024	SM 23 4500-P A,B,F m
Total Phosphorus Low Level Total (1)	5	2021/09/10	2021/09/12	AB SOP-00024	SM 23 4500-P A,B,F m
Total Suspended Solids (NFR)	11	2021/09/08	2021/09/09	BBY6SOP-00034	SM 23 2540 D m
Total Suspended Solids (NFR)	4	2021/09/09	2021/09/10	BBY6SOP-00034	SM 23 2540 D m

Remarks:

Bureau Veritas is accredited to ISO/IEC 17025 for specific parameters on scopes of accreditation. Unless otherwise noted, procedures used by Bureau Veritas are based upon recognized Provincial, Federal or US method compendia such as CCME, MELCC, EPA, APHA.

All work recorded herein has been done in accordance with procedures and practices ordinarily exercised by professionals in Bureau Veritas' profession using accepted testing methodologies, quality assurance and quality control procedures (except where otherwise agreed by the client and Bureau Veritas in writing). All data is in statistical control and has met quality control and method performance criteria unless otherwise noted. All method blanks are reported; unless indicated otherwise, associated sample data are not blank corrected. Where applicable, unless otherwise noted, Measurement



Your Project #: 2021-Ketza

Your C.O.C. #: 644610-04-01, 644610-05-01

Attention: Stephanie Lyons

Government of Yukon – Dept of ENV Box 2703 Whitehorse, YT Canada Y1A2C6

Report Date: 2021/09/23

Report #: R3075583 Version: 2 - Final

CERTIFICATE OF ANALYSIS

BV LABS JOB #: C165509 Received: 2021/09/03, 15:17

Uncertainty has not been accounted for when stating conformity to the referenced standard.

Bureau Veritas liability is limited to the actual cost of the requested analyses, unless otherwise agreed in writing. There is no other warranty expressed or implied. Bureau Veritas has been retained to provide analysis of samples provided by the Client using the testing methodology referenced in this report. Interpretation and use of test results are the sole responsibility of the Client and are not within the scope of services provided by Bureau Veritas, unless otherwise agreed in writing. Bureau Veritas is not responsible for the accuracy or any data impacts, that result from the information provided by the customer or their agent.

Solid sample results, except biota, are based on dry weight unless otherwise indicated. Organic analyses are not recovery corrected except for isotope dilution methods.

Results relate to samples tested. When sampling is not conducted by Bureau Veritas, results relate to the supplied samples tested.

This Certificate shall not be reproduced except in full, without the written approval of the laboratory.

Reference Method suffix "m" indicates test methods incorporate validated modifications from specific reference methods to improve performance.

- * RPDs calculated using raw data. The rounding of final results may result in the apparent difference.
- (1) This test was performed by Bureau Veritas Calgary, 4000 19 St., Calgary, AB, T2E 6P8
- (2) Dissolved > Total Imbalance: When applicable, Dissolved and Total results were reviewed and data quality meets acceptable levels unless otherwise noted.
- (3) DOC present in the sample should be considered as non-purgeable DOC. Dissolved > Total Imbalance: When applicable, Dissolved and Total results were reviewed and data quality meets acceptable levels unless otherwise noted.
- (4) "Total Hardness" was calculated from Total Ca and Mg concentrations and may be biased high (Hardness, or Dissolved Hardness, calculated from Dissolved Ca and Mg, should be used for compliance if available).
- (5) The CCME method requires pH to be analysed within 15 minutes of sampling and therefore field analysis is required for compliance. All Laboratory pH analyses in this report are reported past the CCME holding time. Bureau Veritas Laboratories endeavours to analyze samples as soon as possible after receipt.
- (6) Dissolved Phosphorus > Total Phosphorus Imbalance: When applicable, Dissolved Phosphorus and Total Phosphorus results were reviewed and data quality meets acceptable levels unless otherwise noted.

Encryption Key

Kandise Wilson Customer Solutions Representative 23 Sep 2021 18:20:11

Please direct all questions regarding this Certificate of Analysis to your Project Manager.

Customer Solutions, Western Canada Customer Experience Team

Email: customersolutionswest@bureauveritas.com

Phone# (604) 734 7276

BV Labs has procedures in place to guard against improper use of the electronic signature and have the required "signatories", as per ISO/IEC 17025, signing the reports. For Service Group specific validation please refer to the Validation Signature Page.



Government of Yukon – Dept of ENV Client Project #: 2021-Ketza

RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFF263		AFF264			AFF264		
Sampling Date		2021/09/01 09:15		2021/09/01			2021/09/01		
COC Number		644610-04-01		644610-04-01			644610-04-01		
	UNITS	2021T25-11	QC Batch	2021T25-12	RDL	QC Batch	2021T25-12 Lab-Dup	RDL	QC Batch
Misc. Inorganics									
Fluoride (F)	mg/L	0.500	A348726	0.120	0.020	A347643			
Calculated Parameters			I.			<u>I</u>			
Dissolved Chromium III	mg/L	<0.00099	A341719	<0.00099	0.00099	A341719			
Filter and HNO3 Preservation	N/A	FIELD	ONSITE	FIELD		ONSITE			
Dissolved Hardness (CaCO3)	mg/L	404	A341393	352	0.50	A341393			
Total Hardness (CaCO3)	mg/L	380	A341392	330	0.50	A341392			
Nitrate (N)	mg/L	0.451	A341410	0.0768	0.0020	A341410			
Total Total Kjeldahl Nitrogen (Calc)	mg/L	0.067	A341594	0.058	0.020	A341594			
Misc. Inorganics									
Conductivity	uS/cm	750	A345394	630	2.0	A345385	630	2.0	A345385
Strong Acid Dissoc. Cyanide (CN)	mg/L	<0.00050	A346114	<0.00050	0.00050	A346114			
Weak Acid Dissoc. Cyanide (CN)	mg/L	<0.00050	A346121	<0.00050	0.00050	A346121			
Dissolved Organic Carbon (C)	mg/L	0.35	A347315	0.39	0.20	A347315			
рН	рН	8.36	A345387	8.20	N/A	A345379	8.26	N/A	A345379
Total Suspended Solids	mg/L	3.6	A344551	<1.0	1.0	A344551			
Anions									
Alkalinity (PP as CaCO3)	mg/L	4.1	A345389	<1.0	1.0	A345383	<1.0	1.0	A345383
Alkalinity (Total as CaCO3)	mg/L	360	A345389	190	1.0	A345383	190	1.0	A345383
Bicarbonate (HCO3)	mg/L	430	A345389	240	1.0	A345383	240	1.0	A345383
Carbonate (CO3)	mg/L	4.9	A345389	<1.0	1.0	A345383	<1.0	1.0	A345383
Hydroxide (OH)	mg/L	<1.0	A345389	<1.0	1.0	A345383	<1.0	1.0	A345383
Dissolved Chloride (CI)	mg/L	<0.50	A348087	<0.50	0.50	A348087			
Dissolved Sulphate (SO4)	mg/L	85	A348087	160	0.50	A348087			
Metals	•		-		•				
Dissolved Hex. Chromium (Cr 6+)	mg/L	<0.00099	A343723	<0.00099	0.00099	A343723			
Nutrients									
Dissolved Phosphorus (P)	mg/L	<0.0010	A347209	<0.0010	0.0010	A347209			
Total Phosphorus (P)	mg/L	0.0034	A347213	<0.0010	0.0010	A347455			
Total Ammonia (N)	mg/L	<0.0050	A348557	<0.0050	0.0050	A348557			
Nitrate plus Nitrite (N)	mg/L	0.451	A342326	0.0768	0.0020	A342326	0.0776	0.0020	A342326
Nitrite (N)	mg/L	<0.0020	A342330	<0.0020	0.0020	A342330	<0.0020	0.0020	A342330
RDL = Reportable Detection Limit								·	

Lab-Dup = Laboratory Initiated Duplicate

N/A = Not Applicable



Government of Yukon – Dept of ENV Client Project #: 2021-Ketza

RESULTS OF CHEMICAL ANALYSES OF WATER

Sampling Date 2021/09/01 09:15 2021/09/01 2021/09/01 COC Number 644610-04-01 644610-04-01 644610-04-01	
COC Number 644610-04-01 644610-04-01 644610-04-01	
UNITS 2021T25-11 QC Batch 2021T25-12 RDL QC Batch 2021T25-12 Lab-Dup RDL QC Batch 2021T25-12 Lab-Dup	QC Batch
Total Nitrogen (N) mg/L 0.518 A345060 0.134 0.020 A345060	
Physical Properties	
Total Dissolved Solids mg/L 411 (1) A345116 416 (1) 1.1 A345116	

RDL = Reportable Detection Limit

Lab-Dup = Laboratory Initiated Duplicate

⁽¹⁾ Detection limits raised due to insufficient sample volume.



RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFF265		AFF266			AFF267		
Compliant Bata		2021/09/01		2021/09/01			2021/09/01		
Sampling Date		10:45		11:15			12:00		
COC Number		644610-04-01		644610-04-01			644610-04-01		
	UNITS	2021T25-13	QC Batch	2021T25-14	RDL	QC Batch	2021T25-15	RDL	QC Batch
Misc. Inorganics									
Fluoride (F)	mg/L	0.084	A347643	0.160	0.020	A348726	0.120	0.020	A348726
Calculated Parameters	•				•			•	
Dissolved Chromium III	mg/L	<0.00099	A341719	<0.00099	0.00099	A341719	<0.00099	0.00099	A341719
Filter and HNO3 Preservation	N/A	FIELD	ONSITE	FIELD		ONSITE	FIELD		ONSITE
Dissolved Hardness (CaCO3)	mg/L	611	A341393	1120	0.50	A341393	325	0.50	A341393
Total Hardness (CaCO3)	mg/L	580	A341392	1100	0.50	A341392	310	0.50	A341392
Nitrate (N)	mg/L	0.0588	A341410	0.0028	0.0020	A341410	0.0491	0.0020	A341410
Total Total Kjeldahl Nitrogen (Calc)	mg/L	0.055	A341594	0.045	0.020	A341594	0.096	0.020	A341594
Misc. Inorganics									•
Conductivity	uS/cm	1100	A345385	1800	2.0	A345385	610	2.0	A345385
Strong Acid Dissoc. Cyanide (CN)	mg/L	<0.00050	A346114	<0.00050	0.00050	A346114	<0.00050	0.00050	A346114
Weak Acid Dissoc. Cyanide (CN)	mg/L	<0.00050	A346121	<0.00050	0.00050	A346121	<0.00050	0.00050	A346121
Dissolved Organic Carbon (C)	mg/L	0.20	A347315	<0.20	0.20	A347315	0.32	0.20	A347315
рН	рН	8.30	A345379	8.18	N/A	A345379	8.13	N/A	A345379
Total Suspended Solids	mg/L	2.0	A344664	<1.0	1.0	A344685	4.8	1.0	A344551
Anions									
Alkalinity (PP as CaCO3)	mg/L	<1.0	A345383	<1.0	1.0	A345383	<1.0	1.0	A345383
Alkalinity (Total as CaCO3)	mg/L	210	A345383	300	1.0	A345383	140	1.0	A345383
Bicarbonate (HCO3)	mg/L	260	A345383	360	1.0	A345383	180	1.0	A345383
Carbonate (CO3)	mg/L	<1.0	A345383	<1.0	1.0	A345383	<1.0	1.0	A345383
Hydroxide (OH)	mg/L	<1.0	A345383	<1.0	1.0	A345383	<1.0	1.0	A345383
Dissolved Chloride (CI)	mg/L	<0.50	A348087	0.56	0.50	A348087	<0.50	0.50	A348087
Dissolved Sulphate (SO4)	mg/L	370	A348087	830	5.0	A348087	180	0.50	A348087
Metals									
Dissolved Hex. Chromium (Cr 6+)	mg/L	<0.00099	A343723	<0.00099	0.00099	A343723	<0.00099	0.00099	A345891
Nutrients									
Dissolved Phosphorus (P)	mg/L	<0.0010	A347209	<0.0010	0.0010	A347209	<0.0010	0.0010	A347209
Total Phosphorus (P)	mg/L	<0.0010	A347455	<0.0010	0.0010	A347455	<0.0010	0.0010	A347213
Total Ammonia (N)	mg/L	<0.0050	A348557	<0.0050	0.0050	A348557	<0.0050	0.0050	A348557
Nitrate plus Nitrite (N)	mg/L	0.0588	A342326	0.0028	0.0020	A342326	0.0491	0.0020	A342326
Nitrite (N)	mg/L	<0.0020	A342330	<0.0020	0.0020	A342330	<0.0020	0.0020	A342330
Total Nitrogen (N)	mg/L	0.114	A345060	0.048	0.020	A345060	0.145	0.020	A343841
RDL = Reportable Detection Limit									
NI/A Nick Amelicable									

N/A = Not Applicable



BV Labs Job #: C165509 Government of Yukon – Dept of ENV Report Date: 2021/09/23 Client Project #: 2021-Ketza

RESULTS OF CHEMICAL ANALYSES OF WATER

		1	1				I		1
BV Labs ID		AFF265		AFF266			AFF267		
Samuling Data		2021/09/01		2021/09/01			2021/09/01		
Sampling Date		10:45		11:15			12:00		
COC Number		644610-04-01		644610-04-01			644610-04-01		
	UNITS	2021T25-13	QC Batch	2021T25-14	RDL	QC Batch	2021T25-15	RDL	QC Batch
Physical Properties									
Total Dissolved Solids	mg/L	795 (1)	A345116	1520 (1)	1.1	A345116	411 (1)	1.2	A345116
RDL = Reportable Detection Limit									
MDE - Reportable Detection Limit									

⁽¹⁾ Detection limits raised due to insufficient sample volume.



Government of Yukon – Dept of ENV Client Project #: 2021-Ketza

RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFF267			AFF268			AFF268		
Sampling Data		2021/09/01			2021/09/01			2021/09/01		
Sampling Date		12:00			11:45			11:45		
COC Number		644610-04-01			644610-04-01			644610-04-01		
	UNITS	2021T25-15 Lab-Dup	RDL	QC Batch	2021T25-16	RDL	QC Batch	2021T25-16 Lab-Dup	RDL	QC Batch
Misc. Inorganics										
Fluoride (F)	mg/L				<0.020	0.020	A348726			
Calculated Parameters									•	
Dissolved Chromium III	mg/L				<0.00099	0.00099	A341719			
Filter and HNO3 Preservation	N/A				FIELD		ONSITE			
Dissolved Hardness (CaCO3)	mg/L				<0.50	0.50	A341393			
Total Hardness (CaCO3)	mg/L				<0.50	0.50	A341392			
Nitrate (N)	mg/L				<0.0020	0.0020	A341410			
Total Total Kjeldahl Nitrogen (Calc)	mg/L				0.022	0.020	A341594			
Misc. Inorganics										
Conductivity	uS/cm				<2.0	2.0	A345394			
Strong Acid Dissoc. Cyanide (CN)	mg/L				<0.00050	0.00050	A346114			
Weak Acid Dissoc. Cyanide (CN)	mg/L				<0.00050	0.00050	A346121			
Dissolved Organic Carbon (C)	mg/L				<0.20	0.20	A347315	<0.20	0.20	A347315
рН	рН				6.34	N/A	A345387			
Total Suspended Solids	mg/L				<1.0	1.0	A344685			
Anions										
Alkalinity (PP as CaCO3)	mg/L				<1.0	1.0	A345389			
Alkalinity (Total as CaCO3)	mg/L				1.2	1.0	A345389			
Bicarbonate (HCO3)	mg/L				1.5	1.0	A345389			
Carbonate (CO3)	mg/L				<1.0	1.0	A345389			
Hydroxide (OH)	mg/L				<1.0	1.0	A345389			
Dissolved Chloride (CI)	mg/L				<0.50	0.50	A351779	<0.50	0.50	A351779
Dissolved Sulphate (SO4)	mg/L				<0.50	0.50	A351779	<0.50	0.50	A351779
Metals	•								•	
Dissolved Hex. Chromium (Cr 6+)	mg/L				<0.00099	0.00099	A343723			
Nutrients									•	
Dissolved Phosphorus (P)	mg/L				<0.0010	0.0010	A347209			
Total Phosphorus (P)	mg/L	<0.0010	0.0010	A347213	<0.0010	0.0010	A347213			
Total Ammonia (N)	mg/L				<0.0050	0.0050	A348557			
Nitrate plus Nitrite (N)	mg/L				<0.0020	0.0020	A342326			
Nitrite (N)	mg/L				<0.0020	0.0020	A342330			
RDL = Reportable Detection Limit										

Lab-Dup = Laboratory Initiated Duplicate

N/A = Not Applicable



Government of Yukon – Dept of ENV Client Project #: 2021-Ketza

RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFF267			AFF268			AFF268		
Sampling Date		2021/09/01 12:00			2021/09/01 11:45			2021/09/01 11:45		
COC Number		644610-04-01			644610-04-01			644610-04-01		
	UNITS	2021T25-15 Lab-Dup	RDL	QC Batch	2021T25-16	RDL	QC Batch	2021T25-16 Lab-Dup	RDL	QC Batch
Total Nitrogen (N)	mg/L				0.022	0.020	A345060			
Physical Properties										
Total Dissolved Solids	mg/L				2.0 (1)	1.0	A357208			

RDL = Reportable Detection Limit

Lab-Dup = Laboratory Initiated Duplicate

(1) Sample was originally processed within hold time. Data quality required investigation. Re-analysis was completed past recommended hold time.



RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFF269		AFF270			AFF271		
Samuling Data		2021/09/01		2021/09/01			2021/09/01		
Sampling Date		12:30		13:15			14:15		
COC Number		644610-04-01		644610-04-01			644610-04-01		
	UNITS	2021T25-17	QC Batch	2021T25-18	RDL	QC Batch	2021T25-19	RDL	QC Batch
Misc. Inorganics									
Fluoride (F)	mg/L	0.090	A348726	0.027	0.020	A348726	0.170	0.020	A348726
Calculated Parameters			•		•			•	
Dissolved Chromium III	mg/L	<0.00099	A341719	<0.00099	0.00099	A341719	<0.00099	0.00099	A341719
Filter and HNO3 Preservation	N/A	FIELD	ONSITE	FIELD		ONSITE	FIELD		ONSITE
Dissolved Hardness (CaCO3)	mg/L	307	A341393	336	0.50	A341393	343	0.50	A341393
Total Hardness (CaCO3)	mg/L	300	A341392	320	0.50	A341392	330	0.50	A341392
Nitrate (N)	mg/L	0.0592	A341410	0.0352	0.0020	A341410	0.0218	0.0020	A341410
Total Total Kjeldahl Nitrogen (Calc)	mg/L	0.055	A341594	0.037	0.020	A341594	0.048	0.020	A341594
Misc. Inorganics									
Conductivity	uS/cm	590	A345394	600	2.0	A345394	650	2.0	A345394
Strong Acid Dissoc. Cyanide (CN)	mg/L	<0.00050	A346114	<0.00050	0.00050	A346114	<0.00050	0.00050	A346114
Weak Acid Dissoc. Cyanide (CN)	mg/L	<0.00050	A346121	<0.00050	0.00050	A346121	<0.00050	0.00050	A346121
Dissolved Organic Carbon (C)	mg/L	<0.20	A348719	0.38	0.20	A347315	<0.20	0.20	A348719
рН	рН	8.15	A345387	8.34	N/A	A345387	8.00	N/A	A345387
Total Suspended Solids	mg/L	2.8	A344551	1.2	1.0	A344551	12	1.0	A344551
Anions									
Alkalinity (PP as CaCO3)	mg/L	<1.0	A345389	2.0	1.0	A345389	<1.0	1.0	A345389
Alkalinity (Total as CaCO3)	mg/L	150	A345389	220	1.0	A345389	110	1.0	A345389
Bicarbonate (HCO3)	mg/L	190	A345389	260	1.0	A345389	140	1.0	A345389
Carbonate (CO3)	mg/L	<1.0	A345389	2.4	1.0	A345389	<1.0	1.0	A345389
Hydroxide (OH)	mg/L	<1.0	A345389	<1.0	1.0	A345389	<1.0	1.0	A345389
Dissolved Chloride (CI)	mg/L	<0.50	A348087	<0.50	0.50	A348087	<0.50	0.50	A348087
Dissolved Sulphate (SO4)	mg/L	160	A348087	130	0.50	A348087	210	5.0	A348087
Metals									
Dissolved Hex. Chromium (Cr 6+)	mg/L	<0.00099	A345891	<0.00099	0.00099	A345891	<0.00099	0.00099	A345891
Nutrients									
Dissolved Phosphorus (P)	mg/L	<0.0010	A347443	<0.0010	0.0010	A347209	<0.0010	0.0010	A347443
Total Phosphorus (P)	mg/L	<0.0010	A347450	<0.0010	0.0010	A347213	0.0017	0.0010	A347213
Total Ammonia (N)	mg/L	<0.0050	A348557	<0.0050	0.0050	A348557	<0.0050	0.0050	A348557
Nitrate plus Nitrite (N)	mg/L	0.0592	A342326	0.0352	0.0020	A342326	0.0218	0.0020	A342326
Nitrite (N)	mg/L	<0.0020	A342330	<0.0020	0.0020	A342330	<0.0020	0.0020	A342330
Total Nitrogen (N)	mg/L	0.114	A345060	0.073	0.020	A345060	0.069	0.020	A345060
RDL = Reportable Detection Limit									
NI/A Nick Amelicable									

N/A = Not Applicable



BV Labs Job #: C165509 Government of Yukon – Dept of ENV Report Date: 2021/09/23 Client Project #: 2021-Ketza

RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFF269		AFF270			AFF271		
Samuling Data		2021/09/01		2021/09/01			2021/09/01		
Sampling Date		12:30		13:15			14:15		
COC Number		644610-04-01		644610-04-01			644610-04-01		
	UNITS	2021T25-17	QC Batch	2021T25-18	RDL	QC Batch	2021T25-19	RDL	QC Batch
Physical Properties	UNITS	2021T25-17	QC Batch	2021T25-18	RDL	QC Batch	2021T25-19	RDL	QC Batch
Physical Properties Total Dissolved Solids	mg/L	2021T25-17 385 (1)	QC Batch A345116	2021T25-18 354 (1)	1.1	QC Batch A345116	2021T25-19 453 (1)	1.1	QC Batch A345116

⁽¹⁾ Detection limits raised due to insufficient sample volume.



Government of Yukon – Dept of ENV Client Project #: 2021-Ketza

RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFF272			AFF272			AFF273		
		2021/09/01			2021/09/01			2021/09/01		
Sampling Date		15:30			15:30			15:30		
COC Number		644610-04-01			644610-04-01			644610-05-01		
	UNITS	2021T25-20	RDL	QC Batch	2021T25-20 Lab-Dup	RDL	QC Batch	2021T25-21	RDL	QC Batch
Misc. Inorganics										
Fluoride (F)	mg/L	0.040	0.020	A348726	0.038	0.020	A348726	0.810	0.020	A348726
Calculated Parameters						•				
Dissolved Chromium III	mg/L	<0.00099	0.00099	A341719				<0.00099	0.00099	A341719
Filter and HNO3 Preservation	N/A	FIELD		ONSITE				FIELD		ONSITE
Dissolved Hardness (CaCO3)	mg/L	373	0.50	A341393				644	0.50	A341393
Total Hardness (CaCO3)	mg/L	350	0.50	A341392				630	0.50	A341392
Nitrate (N)	mg/L	0.0626	0.0020	A341410				0.438	0.0020	A341410
Total Total Kjeldahl Nitrogen (Calc)	mg/L	0.048	0.020	A341594				0.032	0.020	A341594
Misc. Inorganics										
Conductivity	uS/cm	690	2.0	A345409				1100	2.0	A345385
Strong Acid Dissoc. Cyanide (CN)	mg/L	<0.00050	0.00050	A346114	<0.00050	0.00050	A346114	<0.00050	0.00050	A346114
Weak Acid Dissoc. Cyanide (CN)	mg/L	<0.00050	0.00050	A346121	<0.00050	0.00050	A346121	<0.00050	0.00050	A346121
Dissolved Organic Carbon (C)	mg/L	<0.20	0.20	A348719				0.42	0.20	A347315
рН	рН	7.92	N/A	A345396				8.12	N/A	A345379
Total Suspended Solids	mg/L	<1.0	1.0	A344551				<1.0	1.0	A344546
Anions										
Alkalinity (PP as CaCO3)	mg/L	<1.0	1.0	A345397				<1.0	1.0	A345383
Alkalinity (Total as CaCO3)	mg/L	110	1.0	A345397				200	1.0	A345383
Bicarbonate (HCO3)	mg/L	130	1.0	A345397				250	1.0	A345383
Carbonate (CO3)	mg/L	<1.0	1.0	A345397				<1.0	1.0	A345383
Hydroxide (OH)	mg/L	<1.0	1.0	A345397				<1.0	1.0	A345383
Dissolved Chloride (CI)	mg/L	<0.50	0.50	A348160				0.51	0.50	A348087
Dissolved Sulphate (SO4)	mg/L	250	5.0	A348160				410	5.0	A348087
Metals			•				-		•	
Dissolved Hex. Chromium (Cr 6+)	mg/L	<0.00099	0.00099	A345891	<0.00099	0.00099	A345891	<0.00099	0.00099	A345891
Nutrients										
Dissolved Phosphorus (P)	mg/L	0.0022	0.0010	A347443				0.0077	0.0010	A347209
Total Phosphorus (P)	mg/L	0.0029	0.0010	A347455				0.014	0.0010	A347213
Total Ammonia (N)	mg/L	<0.0050	0.0050	A348552				<0.0050	0.0050	A348557
Nitrate plus Nitrite (N)	mg/L	0.0626	0.0020	A342326				0.438	0.0020	A342326
Nitrite (N)	mg/L	<0.0020	0.0020	A342330				<0.0020	0.0020	A342330
DDI - Donartable Detection Limit			•			•				

RDL = Reportable Detection Limit

Lab-Dup = Laboratory Initiated Duplicate

N/A = Not Applicable



BV Labs Job #: C165509 Government of Yukon – Dept of ENV Report Date: 2021/09/23 Client Project #: 2021-Ketza

RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFF272			AFF272			AFF273		
Sampling Date		2021/09/01			2021/09/01			2021/09/01		
Sampling Date		15:30			15:30			15:30		
COC Number		644610-04-01			644610-04-01			644610-05-01		
	UNITS	2021T25-20	RDL	QC Batch	2021T25-20 Lab-Dup	RDL	QC Batch	2021T25-21	RDL	QC Batch
Total Nitrogen (N)	mg/L	0.111	0.020	A345060				0.470	0.020	A345060
Physical Properties										
					1		1			1
Total Dissolved Solids	mg/L	497 (1)	1.1	A345116				888 (1)	1.1	A34511

RDL = Reportable Detection Limit

Lab-Dup = Laboratory Initiated Duplicate

(1) Detection limits raised due to insufficient sample volume.

RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFF274	AFF275			AFF275		
Sampling Date		2021/09/02	2021/09/02			2021/09/02		
Sampling Date		10:15	11:00			11:00		
COC Number		644610-05-01	644610-05-01			644610-05-01		
	UNITS	2021T25-22	2021T25-23	RDL	QC Batch	2021T25-23 Lab-Dup	RDL	QC Batch
Misc. Inorganics								
Fluoride (F)	mg/L	0.046	0.028	0.020	A348726			
Calculated Parameters								
Dissolved Chromium III	mg/L	<0.00099	<0.00099	0.00099	A341719			
Filter and HNO3 Preservation	N/A	FIELD	FIELD		ONSITE			
Dissolved Hardness (CaCO3)	mg/L	243	136	0.50	A341393			
Total Hardness (CaCO3)	mg/L	220	130	0.50	A341392			
Nitrate (N)	mg/L	0.0263	0.0500	0.0020	A341410			
Total Total Kjeldahl Nitrogen (Calc)	mg/L	0.039	0.039	0.020	A341594			
Misc. Inorganics	l			•	L	•		
Conductivity	uS/cm	460	280	2.0	A345385			
Strong Acid Dissoc. Cyanide (CN)	mg/L	<0.00050	<0.00050	0.00050	A346114			
Weak Acid Dissoc. Cyanide (CN)	mg/L	<0.00050	<0.00050	0.00050	A346121			
Dissolved Organic Carbon (C)	mg/L	0.22	<0.20	0.20	A347315			
рН	рН	8.12	7.73	N/A	A345379			
Total Suspended Solids	mg/L	1.6	2.4	1.0	A346053			
Anions	l			•	L	•		
Alkalinity (PP as CaCO3)	mg/L	<1.0	<1.0	1.0	A345383			
Alkalinity (Total as CaCO3)	mg/L	140	72	1.0	A345383			
Bicarbonate (HCO3)	mg/L	170	88	1.0	A345383			
Carbonate (CO3)	mg/L	<1.0	<1.0	1.0	A345383			
Hydroxide (OH)	mg/L	<1.0	<1.0	1.0	A345383			
Dissolved Chloride (Cl)	mg/L	<0.50	<0.50	0.50	A348087			
Dissolved Sulphate (SO4)	mg/L	110	65	0.50	A348087			
Metals	Į.							
Dissolved Hex. Chromium (Cr 6+)	mg/L	<0.00099	<0.00099	0.00099	A343723			
Nutrients				•				
Dissolved Phosphorus (P)	mg/L	<0.0010	<0.0010	0.0010	A347209	<0.0010	0.0010	A347209
Total Phosphorus (P)	mg/L	<0.0010	<0.0010	0.0010	A347213			
Total Ammonia (N)	mg/L	<0.0050	<0.0050	0.0050	A348557	<0.0050	0.0050	A348557
Nitrate plus Nitrite (N)	mg/L	0.0263	0.0500	0.0020	A342326			
Nitrite (N)	mg/L	<0.0020	<0.0020	0.0020	A342330			
RDL = Reportable Detection Limit				1	1	ı	1	
lah Dun - Laharatan/Initiated Dunli								

Lab-Dup = Laboratory Initiated Duplicate

N/A = Not Applicable



RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFF274	AFF275			AFF275		
Sampling Date		2021/09/02 10:15	2021/09/02 11:00			2021/09/02 11:00		
COC Number		644610-05-01	644610-05-01			644610-05-01		
	UNITS	2021T25-22	2021T25-23	RDL	QC Batch	2021T25-23 Lab-Dup	RDL	QC Batch
Total Nitrogen (N)	mg/L	0.066	0.089	0.020	A345060			
Physical Properties					•			•
Total Dissolved Solids	mg/L	263	178	1.0	A346241			

RDL = Reportable Detection Limit



N/A = Not Applicable

BV Labs Job #: C165509 Government of Yukon – Dept of ENV Report Date: 2021/09/23 Client Project #: 2021-Ketza

RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFF276		AFF277			AFF277		
Sampling Data		2021/09/02		2021/09/02			2021/09/02		
Sampling Date		11:15		12:00			12:00		
COC Number		644610-05-01		644610-05-01			644610-05-01		
	UNITS	2021T25-24	QC Batch	2021T25-25	RDL	QC Batch	2021T25-25 Lab-Dup	RDL	QC Batch
Misc. Inorganics									
Fluoride (F)	mg/L	0.026	A348726	<0.020	0.020	A348726			
Calculated Parameters									
Dissolved Chromium III	mg/L	<0.00099	A341719	<0.00099	0.00099	A341719			
Filter and HNO3 Preservation	N/A	LAB	A349745	FIELD		ONSITE			
Dissolved Hardness (CaCO3)	mg/L	131	A341393	<0.50	0.50	A341393			
Total Hardness (CaCO3)	mg/L	140	A341392	<0.50	0.50	A341392			
Nitrate (N)	mg/L	0.0495	A341410	<0.0020	0.0020	A341410			
Total Total Kjeldahl Nitrogen (Calc)	mg/L	0.084	A341594	<0.020	0.020	A341594			
Misc. Inorganics			•						
Conductivity	uS/cm	280	A345385	<2.0	2.0	A345385			
Strong Acid Dissoc. Cyanide (CN)	mg/L	<0.00050	A346114	<0.00050	0.00050	A346114			
Weak Acid Dissoc. Cyanide (CN)	mg/L	<0.00050	A346121	<0.00050	0.00050	A346121			
Dissolved Organic Carbon (C)	mg/L	<0.20	A347315	<0.20	0.20	A348719	<0.20	0.20	A348719
рН	рН	7.70	A345379	5.66	N/A	A345379			
Total Suspended Solids	mg/L	2.8	A346053	1.6	1.0	A346053			
Anions									
Alkalinity (PP as CaCO3)	mg/L	<1.0	A345383	<1.0	1.0	A345383			
Alkalinity (Total as CaCO3)	mg/L	70	A345383	<1.0	1.0	A345383			
Bicarbonate (HCO3)	mg/L	86	A345383	<1.0	1.0	A345383			
Carbonate (CO3)	mg/L	<1.0	A345383	<1.0	1.0	A345383			
Hydroxide (OH)	mg/L	<1.0	A345383	<1.0	1.0	A345383			
Dissolved Chloride (CI)	mg/L	<0.50	A348087	<0.50	0.50	A348087			
Dissolved Sulphate (SO4)	mg/L	72	A348087	1.2	0.50	A348087			
Metals	•		•		•				
Dissolved Hex. Chromium (Cr 6+)	mg/L	<0.00099	A343723	<0.00099	0.00099	A345891			
Nutrients			•						
Dissolved Phosphorus (P)	mg/L	<0.0010	A347209	<0.0010	0.0010	A347443			
Total Phosphorus (P)	mg/L	<0.0010	A347213	<0.0010	0.0010	A347213			
Total Ammonia (N)	mg/L	<0.0050	A348552	<0.0050	0.0050	A348557			
Nitrate plus Nitrite (N)	mg/L	0.0495	A342326	<0.0020	0.0020	A342326			
Nitrite (N)	mg/L	<0.0020	A342330	<0.0020	0.0020	A342330			
RDL = Reportable Detection Limit									
Lab-Dup = Laboratory Initiated Dupli	icate								
1									



BV Labs Job #: C165509 Government of Yukon – Dept of ENV Report Date: 2021/09/23 Client Project #: 2021-Ketza

RESULTS OF CHEMICAL ANALYSES OF WATER

BV Labs ID		AFF276		AFF277			AFF277		
Sampling Date		2021/09/02 11:15		2021/09/02 12:00			2021/09/02 12:00		
COC Number		644610-05-01		644610-05-01			644610-05-01		
	UNITS	2021T25-24	QC Batch	2021T25-25	RDL	QC Batch	2021T25-25 Lab-Dup	RDL	QC Batch
Total Nitrogen (N)	mg/L	0.133	A343841	<0.020	0.020	A345060			
Physical Properties									
						A362419			

RDL = Reportable Detection Limit

Lab-Dup = Laboratory Initiated Duplicate

⁽¹⁾ Sample was originally processed within hold time. Data quality required investigation. Re-analysis was completed past recommended hold time.



MERCURY BY COLD VAPOR (WATER)

BV Labs ID		AFF263	AFF264	AFF265	AFF266	AFF267	AFF268		
Sampling Date		2021/09/01 09:15	2021/09/01	2021/09/01 10:45	2021/09/01 11:15	2021/09/01 12:00	2021/09/01 11:45		
COC Number		644610-04-01	644610-04-01	644610-04-01	644610-04-01	644610-04-01	644610-04-01		
	UNITS	2021T25-11	2021T25-12	2021T25-13	2021T25-14	2021T25-15	2021T25-16	RDL	QC Batch
Elements									
Elements Dissolved Mercury (Hg)	ug/L	<0.0019	<0.0019	<0.0019	<0.0019	<0.0019	<0.0019	0.0019	A347548
	ug/L ug/L	<0.0019 <0.0019	<0.0019 <0.0019	<0.0019 <0.0019	<0.0019 <0.0019	<0.0019 <0.0019	<0.0019 <0.0019		A347548 A347313

BV Labs ID		AFF269	AFF270	AFF271	AFF272		AFF273		
Sampling Date		2021/09/01 12:30	2021/09/01	2021/09/01	2021/09/01		2021/09/01		
			13:15	14:15	15:30		15:30		
COC Number		644610-04-01	644610-04-01	644610-04-01	644610-04-01		644610-05-01		
	UNITS	2021T25-17	2021T25-18	2021T25-19	2021T25-20	QC Batch	2021T25-21	RDL	QC Batch
Elements									
Dissolved Mercury (Hg)	ug/L	<0.0019	<0.0019	<0.0019	<0.0019	A347548	<0.0019	0.0019	A347548
Total Mercury (Hg)	ug/L	<0.0019	<0.0019	<0.0019	<0.0019	A347313	<0.0019	0.0019	A347795
RDL = Reportable Detection L	imit								

BV Labs ID		AFF273			AFF274		AFF275	AFF276		
Sampling Date		2021/09/01 15:30			2021/09/02 10:15		2021/09/02 11:00	2021/09/02 11:15		
COC Number		644610-05-01			644610-05-01		644610-05-01	644610-05-01		
	UNITS	2021T25-21 Lab-Dup	RDL	QC Batch	2021T25-22	QC Batch	2021T25-23	2021T25-24	RDL	QC Batch
Elements										
Dissolved Mercury (Hg)	ug/L				<0.0019	A343127	<0.0019	<0.0019	0.0019	A347548
Total Mercury (Hg)	ug/L	< 0.0019	0.0019	A347795	<0.0019	A347795	< 0.0019	<0.0019	0.0019	A347795
	∽ <i>6/</i> –	0.00=0	0.00-0							

RDL = Reportable Detection Limit Lab-Dup = Laboratory Initiated Duplicate

BV Labs ID		AFF277		
Sampling Date		2021/09/02 12:00		
COC Number		644610-05-01		
	UNITS	2021T25-25	RDL	QC Batch
Elements				
Dissolved Mercury (Hg)	ug/L	<0.0019	0.0019	A347548
Total Mercury (Hg)	ug/L	<0.0019	0.0019	A347795
Total Mercury (Tig)	~6/ L	0.0015		



ELEMENTS BY ATOMIC SPECTROSCOPY (WATER)

BV Labs ID		AFF263			AFF263			AFF264		
Sampling Date		2021/09/01 09:15			2021/09/01 09:15			2021/09/01		
COC Number		644610-04-01			644610-04-01			644610-04-01		
COC Number		644610-04-01			2021T25-11			644610-04-01		
	UNITS	2021T25-11	RDL	QC Batch	Lab-Dup	RDL	QC Batch	2021T25-12	RDL	QC Batch
Dissolved Metals by ICPMS										
Dissolved Aluminum (AI)	ug/L	1.52	0.50	A346416	1.43	0.50	A346416	1.54	0.50	A346416
Dissolved Antimony (Sb)	ug/L	39.9	0.020	A346416	40.1	0.020	A346416	0.941	0.020	A346416
Dissolved Arsenic (As)	ug/L	24.3	0.020	A346416	24.3	0.020	A346416	0.913	0.020	A346416
Dissolved Barium (Ba)	ug/L	29.8	0.020	A346416	29.6	0.020	A346416	39.1	0.020	A346416
Dissolved Beryllium (Be)	ug/L	<0.010	0.010	A346416	<0.010	0.010	A346416	<0.010	0.010	A346416
Dissolved Bismuth (Bi)	ug/L	<0.0050	0.0050	A346416	<0.0050	0.0050	A346416	<0.0050	0.0050	A346416
Dissolved Boron (B)	ug/L	50	10	A346416	49	10	A346416	<10	10	A346416
Dissolved Cadmium (Cd)	ug/L	0.0180	0.0050	A346416	0.0168	0.0050	A346416	0.0069	0.0050	A346416
Dissolved Chromium (Cr)	ug/L	<0.10	0.10	A346416	<0.10	0.10	A346416	<0.10	0.10	A346416
Dissolved Cobalt (Co)	ug/L	0.119	0.0050	A346416	0.114	0.0050	A346416	0.0284	0.0050	A346416
Dissolved Copper (Cu)	ug/L	1.10	0.050	A346416	1.12	0.050	A346416	0.101	0.050	A346416
Dissolved Iron (Fe)	ug/L	2.3	1.0	A346416	2.2	1.0	A346416	4.5	1.0	A346416
Dissolved Lead (Pb)	ug/L	0.289	0.0050	A346416	0.275	0.0050	A346416	0.0513	0.0050	A346416
Dissolved Lithium (Li)	ug/L	21.4	0.50	A346416	21.5	0.50	A346416	2.09	0.50	A346416
Dissolved Manganese (Mn)	ug/L	1.92	0.050	A346416	1.88	0.050	A346416	3.13	0.050	A346416
Dissolved Molybdenum (Mo)	ug/L	0.514	0.050	A346416	0.487	0.050	A346416	0.225	0.050	A346416
Dissolved Nickel (Ni)	ug/L	0.819	0.020	A346416	0.785	0.020	A346416	0.168	0.020	A346416
Dissolved Selenium (Se)	ug/L	0.182	0.040	A346416	0.159	0.040	A346416	0.734	0.040	A346416
Dissolved Silicon (Si)	ug/L	2660	50	A346416	2660	50	A346416	2020	50	A346416
Dissolved Silver (Ag)	ug/L	<0.0050	0.0050	A346416	<0.0050	0.0050	A346416	<0.0050	0.0050	A346416
Dissolved Strontium (Sr)	ug/L	1130	0.050	A346416	1110	0.050	A346416	299	0.050	A346416
Dissolved Tellurium (Te)	ug/L	<0.020	0.020	A346416	<0.020	0.020	A346416	<0.020	0.020	A346416
Dissolved Thallium (TI)	ug/L	0.0026	0.0020	A346416	0.0025	0.0020	A346416	<0.0020	0.0020	A346416
Dissolved Thorium (Th)	ug/L	<0.0050	0.0050	A346416	<0.0050	0.0050	A346416	<0.0050	0.0050	A346416
Dissolved Tin (Sn)	ug/L	<0.20	0.20	A346416	<0.20	0.20	A346416	<0.20	0.20	A346416
Dissolved Titanium (Ti)	ug/L	<0.50	0.50	A346416	<0.50	0.50	A346416	<0.50	0.50	A346416
Dissolved Tungsten (W)	ug/L	0.170	0.010	A346416	0.172	0.010	A346416	<0.010	0.010	A346416
Dissolved Uranium (U)	ug/L	1.15	0.0020	A346416	1.16	0.0020	A346416	3.02	0.0020	A346416
Dissolved Vanadium (V)	ug/L	<0.20	0.20	A346416	<0.20	0.20	A346416	<0.20	0.20	A346416
Dissolved Zinc (Zn)	ug/L	6.53	0.10	A346416	6.43	0.10	A346416	0.70	0.10	A346416
Dissolved Zirconium (Zr)	ug/L	<0.10	0.10	A346416	<0.10	0.10	A346416	<0.10	0.10	A346416
Dissolved Calcium (Ca)	mg/L	70.9	0.050	A342028				77.8	0.050	A342028
RDI = Reportable Detection Lin	mit									

RDL = Reportable Detection Limit



Government of Yukon – Dept of ENV Client Project #: 2021-Ketza

ELEMENTS BY ATOMIC SPECTROSCOPY (WATER)

BV Labs ID		AFF263			AFF263			AFF264		
Sampling Date		2021/09/01 09:15			2021/09/01 09:15			2021/09/01		
COC Number		644610-04-01			644610-04-01			644610-04-01		
	UNITS	2021T25-11	RDL	QC Batch	2021T25-11 Lab-Dup	RDL	QC Batch	2021T25-12	RDL	QC Batch
Dissolved Magnesium (Mg)	mg/L	55.2	0.050	A342028				38.3	0.050	A342028
Dissolved Potassium (K)	mg/L	3.50	0.050	A342028				0.220	0.050	A342028
Dissolved Sodium (Na)	mg/L	14.2	0.050	A342028				0.406	0.050	A342028
Dissolved Sulphur (S)	mg/L	23.1	3.0	A342028				46.8	3.0	A342028
Total Metals by ICPMS		•					•		•	
Total Aluminum (Al)	ug/L	14.0	3.0	A343719				3.37	0.50	A343687
Total Antimony (Sb)	ug/L	41.1	0.020	A343719				0.923	0.020	A343687
Total Arsenic (As)	ug/L	41.1	0.020	A343719				0.998	0.020	A343687
Total Barium (Ba)	ug/L	29.6	0.050	A343719				38.8	0.020	A343687
Total Beryllium (Be)	ug/L	<0.010	0.010	A343719				<0.010	0.010	A343687
Total Bismuth (Bi)	ug/L	0.028	0.010	A343719				<0.0050	0.0050	A343687
Total Boron (B)	ug/L	49	10	A343719				<10	10	A343687
Total Cadmium (Cd)	ug/L	0.0245	0.0050	A343719				0.0058	0.0050	A343687
Total Chromium (Cr)	ug/L	<0.10	0.10	A343719				<0.10	0.10	A343687
Total Cobalt (Co)	ug/L	0.078	0.010	A343719				0.0219	0.0050	A343687
Total Copper (Cu)	ug/L	3.66	0.10	A343719				0.079	0.050	A343687
Total Iron (Fe)	ug/L	188	5.0	A343719				19.6	1.0	A343687
Total Lead (Pb)	ug/L	13.3	0.020	A343719				0.605	0.0050	A343687
Total Lithium (Li)	ug/L	21.4	0.50	A343719				2.07	0.50	A343687
Total Manganese (Mn)	ug/L	11.1	0.10	A343719				3.70	0.050	A343687
Total Molybdenum (Mo)	ug/L	0.233	0.050	A343719				0.248	0.050	A343687
Total Nickel (Ni)	ug/L	0.94	0.10	A343719				0.190	0.020	A343687
Total Selenium (Se)	ug/L	0.192	0.040	A343719				0.864	0.040	A343687
Total Silicon (Si)	ug/L	2750	50	A343719				2140	50	A343687
Total Silver (Ag)	ug/L	0.061	0.010	A343719				<0.0050	0.0050	A343687
Total Strontium (Sr)	ug/L	1130	0.050	A343719				303	0.050	A343687
Total Tellurium (Te)	ug/L	<0.020	0.020	A343719				<0.020	0.020	A343687
Total Thallium (TI)	ug/L	0.0037	0.0020	A343719				<0.0020	0.0020	A343687
Total Thorium (Th)	ug/L	<0.020	0.020	A343719				<0.0050	0.0050	A343687
Total Tin (Sn)	ug/L	<0.20	0.20	A343719				<0.20	0.20	A343687
Total Titanium (Ti)	ug/L	<2.0	2.0	A343719				<0.50	0.50	A343687
Total Tungsten (W)	ug/L	0.132	0.010	A343719				<0.010	0.010	A343687
Total Uranium (U)	ug/L	1.09	0.0050	A343719				2.85	0.0020	A343687
RDL = Reportable Detection L									•	



ELEMENTS BY ATOMIC SPECTROSCOPY (WATER)

BV Labs ID		AFF263			AFF263			AFF264		
Sampling Date		2021/09/01 09:15			2021/09/01 09:15			2021/09/01		
COC Number		644610-04-01			644610-04-01			644610-04-01		
	UNITS	2021T25-11	RDL	QC Batch	2021T25-11 Lab-Dup	RDL	QC Batch	2021T25-12	RDL	QC Batch
Total Vanadium (V)	ug/L	<0.20	0.20	A343719				<0.20	0.20	A343687
Total Zinc (Zn)	ug/L	8.3	1.0	A343719				0.73	0.10	A343687
Total Zirconium (Zr)	ug/L	<0.10	0.10	A343719				<0.10	0.10	A343687
Total Calcium (Ca)	mg/L	68.1	0.25	A341601				73.7	0.050	A341601
Total Magnesium (Mg)	mg/L	51.1	0.25	A341601				35.8	0.050	A341601
Total Potassium (K)	mg/L	3.28	0.25	A341601				0.214	0.050	A341601
Total Sodium (Na)	mg/L	13.3	0.25	A341601				0.433	0.050	A341601
Total Sulphur (S)	mg/L	23.6	3.0	A341601				50.3	3.0	A341601

RDL = Reportable Detection Limit



s Job #: C165509 Government of Yukon – Dept of ENV
Date: 2021/09/23 Client Project #: 2021-Ketza

ELEMENTS BY ATOMIC SPECTROSCOPY (WATER)

BV Labs ID		AFF264			AFF265		AFF266		
Sampling Date		2021/09/01			2021/09/01		2021/09/01		
Sampling Date		2021/03/01			10:45		11:15		
COC Number		644610-04-01			644610-04-01		644610-04-01		
	UNITS	2021T25-12 Lab-Dup	RDL	QC Batch	2021T25-13	RDL	2021T25-14	RDL	QC Batch
Dissolved Metals by ICPMS									
Dissolved Aluminum (AI)	ug/L				2.11	0.50	3.1	1.0	A346416
Dissolved Antimony (Sb)	ug/L				0.297	0.020	0.231	0.040	A346416
Dissolved Arsenic (As)	ug/L				0.110	0.020	0.239	0.040	A346416
Dissolved Barium (Ba)	ug/L				32.3	0.020	13.9	0.040	A346416
Dissolved Beryllium (Be)	ug/L				<0.010	0.010	<0.020	0.020	A346416
Dissolved Bismuth (Bi)	ug/L				<0.0050	0.0050	<0.010	0.010	A346416
Dissolved Boron (B)	ug/L				<10	10	<20	20	A346416
Dissolved Cadmium (Cd)	ug/L				<0.0050	0.0050	<0.010	0.010	A346416
Dissolved Chromium (Cr)	ug/L				<0.10	0.10	<0.20	0.20	A346416
Dissolved Cobalt (Co)	ug/L				0.0349	0.0050	0.036	0.010	A346416
Dissolved Copper (Cu)	ug/L				0.057	0.050	<0.10	0.10	A346416
Dissolved Iron (Fe)	ug/L				<1.0	1.0	<2.0	2.0	A346416
Dissolved Lead (Pb)	ug/L				0.0134	0.0050	<0.010	0.010	A346416
Dissolved Lithium (Li)	ug/L				4.03	0.50	6.6	1.0	A346416
Dissolved Manganese (Mn)	ug/L				0.365	0.050	<0.10	0.10	A346416
Dissolved Molybdenum (Mo)	ug/L				0.270	0.050	0.80	0.10	A346416
Dissolved Nickel (Ni)	ug/L				0.271	0.020	2.07	0.040	A346416
Dissolved Selenium (Se)	ug/L				0.879	0.040	1.06	0.080	A346416
Dissolved Silicon (Si)	ug/L				2440	50	2300	100	A346416
Dissolved Silver (Ag)	ug/L				<0.0050	0.0050	<0.010	0.010	A346416
Dissolved Strontium (Sr)	ug/L				545	0.050	733	0.10	A346416
Dissolved Tellurium (Te)	ug/L				<0.020	0.020	<0.040	0.040	A346416
Dissolved Thallium (TI)	ug/L				<0.0020	0.0020	<0.0040	0.0040	A346416
Dissolved Thorium (Th)	ug/L				<0.0050	0.0050	<0.010	0.010	A346416
Dissolved Tin (Sn)	ug/L				<0.20	0.20	<0.40	0.40	A346416
Dissolved Titanium (Ti)	ug/L				<0.50	0.50	<1.0	1.0	A346416
Dissolved Tungsten (W)	ug/L				<0.010	0.010	0.073	0.020	A346416
Dissolved Uranium (U)	ug/L				8.07	0.0020	25.1	0.0040	A346416
Dissolved Vanadium (V)	ug/L				<0.20	0.20	<0.40	0.40	A346416
Dissolved Zinc (Zn)	ug/L				1.15	0.10	1.80	0.20	A346416
Dissolved Zirconium (Zr)	ug/L				<0.10	0.10	<0.20	0.20	A346416
Dissolved Calcium (Ca)	mg/L				107	0.050	162	0.10	A342028
RDI = Reportable Detection Li					•		-		

RDL = Reportable Detection Limit

ELEMENTS BY ATOMIC SPECTROSCOPY (WATER)

BV Labs ID		AFF264			AFF265		AFF266		
Sampling Date		2021/09/01			2021/09/01 10:45		2021/09/01 11:15		
COC Number		644610-04-01			644610-04-01		644610-04-01		
	UNITS	2021T25-12 Lab-Dup	RDL	QC Batch	2021T25-13	RDL	2021T25-14	RDL	QC Batch
Dissolved Magnesium (Mg)	mg/L				83.6	0.050	175	0.10	A342028
Dissolved Potassium (K)	mg/L				0.507	0.050	0.55	0.10	A342028
Dissolved Sodium (Na)	mg/L				0.515	0.050	0.43	0.10	A342028
Dissolved Sulphur (S)	mg/L				125	3.0	284	6.0	A342028
Total Metals by ICPMS									
Total Aluminum (AI)	ug/L	3.36	0.50	A343687	8.54	0.50	4.3	1.0	A343687
Total Antimony (Sb)	ug/L	0.902	0.020	A343687	0.284	0.020	0.208	0.040	A343687
Total Arsenic (As)	ug/L	1.01	0.020	A343687	0.135	0.020	0.293	0.040	A343687
Total Barium (Ba)	ug/L	37.8	0.020	A343687	31.2	0.020	13.9	0.040	A343687
Total Beryllium (Be)	ug/L	<0.010	0.010	A343687	<0.010	0.010	<0.020	0.020	A343687
Total Bismuth (Bi)	ug/L	<0.0050	0.0050	A343687	<0.0050	0.0050	<0.010	0.010	A343687
Total Boron (B)	ug/L	<10	10	A343687	<10	10	<20	20	A343687
Total Cadmium (Cd)	ug/L	0.0058	0.0050	A343687	<0.0050	0.0050	<0.010	0.010	A343687
Total Chromium (Cr)	ug/L	<0.10	0.10	A343687	0.12	0.10	<0.20	0.20	A343687
Total Cobalt (Co)	ug/L	0.0259	0.0050	A343687	0.0422	0.0050	0.032	0.010	A343687
Total Copper (Cu)	ug/L	0.079	0.050	A343687	0.064	0.050	<0.10	0.10	A343687
Total Iron (Fe)	ug/L	19.7	1.0	A343687	29.1	1.0	2.7	2.0	A343687
Total Lead (Pb)	ug/L	0.603	0.0050	A343687	0.145	0.0050	0.036	0.010	A343687
Total Lithium (Li)	ug/L	2.06	0.50	A343687	3.84	0.50	6.4	1.0	A343687
Total Manganese (Mn)	ug/L	3.55	0.050	A343687	1.30	0.050	0.56	0.10	A343687
Total Molybdenum (Mo)	ug/L	0.247	0.050	A343687	0.250	0.050	0.85	0.10	A343687
Total Nickel (Ni)	ug/L	0.164	0.020	A343687	0.263	0.020	1.73	0.040	A343687
Total Selenium (Se)	ug/L	0.830	0.040	A343687	0.980	0.040	1.02	0.080	A343687
Total Silicon (Si)	ug/L	2200	50	A343687	2410	50	2190	100	A343687
Total Silver (Ag)	ug/L	<0.0050	0.0050	A343687	<0.0050	0.0050	<0.010	0.010	A343687
Total Strontium (Sr)	ug/L	299	0.050	A343687	516	0.050	724	0.10	A343687
Total Tellurium (Te)	ug/L	<0.020	0.020	A343687	<0.020	0.020	<0.040	0.040	A343687
Total Thallium (TI)	ug/L	<0.0020	0.0020	A343687	<0.0020	0.0020	<0.0040	0.0040	A343687
Total Thorium (Th)	ug/L	<0.0050	0.0050	A343687	0.0059	0.0050	<0.010	0.010	A343687
Total Tin (Sn)	ug/L	<0.20	0.20	A343687	<0.20	0.20	<0.40	0.40	A343687
Total Titanium (Ti)	ug/L	<0.50	0.50	A343687	<0.50	0.50	<1.0	1.0	A343687
Total Tungsten (W)	ug/L	<0.010	0.010	A343687	<0.010	0.010	0.187	0.020	A343687
Total Uranium (U)	ug/L	2.83	0.0020	A343687	7.59	0.0020	24.0	0.0040	A343687
RDL = Reportable Detection Li	mit								

RDL = Reportable Detection Limit



ELEMENTS BY ATOMIC SPECTROSCOPY (WATER)

BV Labs ID		AFF264			AFF265		AFF266		
Sampling Date		2021/09/01			2021/09/01 10:45		2021/09/01 11:15		
COC Number		644610-04-01			644610-04-01		644610-04-01		
	UNITS	2021T25-12 Lab-Dup	RDL	QC Batch	2021T25-13	RDL	2021T25-14	RDL	QC Batch
Total Vanadium (V)	ug/L	<0.20	0.20	A343687	<0.20	0.20	<0.40	0.40	A343687
Total Zinc (Zn)	ug/L	0.76	0.10	A343687	1.14	0.10	1.93	0.20	A343687
Total Zirconium (Zr)	ug/L	<0.10	0.10	A343687	<0.10	0.10	<0.20	0.20	A343687
Total Calcium (Ca)	mg/L				103	0.050	159	0.10	A341601
Total Magnesium (Mg)	mg/L				78.4	0.050	169	0.10	A341601
Total Potassium (K)	mg/L				0.464	0.050	0.54	0.10	A341601
Total Sodium (Na)	mg/L				0.510	0.050	0.43	0.10	A341601
Total Sulphur (S)	mg/L				122	3.0	268	6.0	A341601

RDL = Reportable Detection Limit



ELEMENTS BY ATOMIC SPECTROSCOPY (WATER)

BV Labs ID		AEE267	AEE269	A E E 2 6 0	A E E 2 7 0		A E E 2 7 1		
DV LdDS ID		AFF267	AFF268	AFF269	AFF270		AFF271		
Sampling Date		2021/09/01 12:00	2021/09/01 11:45	2021/09/01 12:30	2021/09/01 13:15		2021/09/01 14:15		
COC Number		644610-04-01	644610-04-01	644610-04-01	644610-04-01		644610-04-01		
COC NUMBER	UNITS	2021T25-15	2021T25-16	2021T25-17	2021T25-18	QC Batch	2021T25-19	RDL	QC Batch
D' I Ind I I I IODAG	ONITS	2021123-13	2021125-10	2021125-17	2021125-10	QC Daten	2021123-13	NDL	QC Daten
Dissolved Metals by ICPMS		_							
Dissolved Aluminum (Al)	ug/L	140	1.17	76.2	1.74	A346416	228	0.50	A346095
Dissolved Antimony (Sb)	ug/L	0.222	<0.020	0.223	0.297	A346416	0.218	0.020	A346095
Dissolved Arsenic (As)	ug/L	4.83	<0.020	6.50	0.345	A346416	2.80	0.020	A346095
Dissolved Barium (Ba)	ug/L	17.7	<0.020	13.6	21.2	A346416	24.8	0.020	A346095
Dissolved Beryllium (Be)	ug/L	<0.010	<0.010	<0.010	<0.010	A346416	<0.010	0.010	A346095
Dissolved Bismuth (Bi)	ug/L	<0.0050	<0.0050	<0.0050	<0.0050	A346416	<0.0050	0.0050	A346095
Dissolved Boron (B)	ug/L	<10	<10	<10	<10	A346416	<10	10	A346095
Dissolved Cadmium (Cd)	ug/L	0.244	<0.0050	0.119	<0.0050	A346416	0.494	0.0050	A346095
Dissolved Chromium (Cr)	ug/L	<0.10	<0.10	<0.10	<0.10	A346416	<0.10	0.10	A346095
Dissolved Cobalt (Co)	ug/L	9.48	<0.0050	8.10	0.0150	A346416	14.1	0.0050	A346095
Dissolved Copper (Cu)	ug/L	0.996	<0.050	0.222	<0.050	A346416	1.62	0.050	A346095
Dissolved Iron (Fe)	ug/L	6.3	<1.0	18.5	<1.0	A346416	<1.0	1.0	A346095
Dissolved Lead (Pb)	ug/L	0.0097	<0.0050	0.0106	<0.0050	A346416	0.0135	0.0050	A346095
Dissolved Lithium (Li)	ug/L	2.77	<0.50	2.29	3.63	A346416	4.27	0.50	A346095
Dissolved Manganese (Mn)	ug/L	268	<0.050	72.8	<0.050	A346416	683	0.050	A346095
Dissolved Molybdenum (Mo)	ug/L	0.221	<0.050	0.230	0.279	A346416	0.214	0.050	A346095
Dissolved Nickel (Ni)	ug/L	14.2	<0.020	5.54	0.049	A346416	32.1	0.020	A346095
Dissolved Selenium (Se)	ug/L	0.739	<0.040	0.682	0.431	A346416	0.853	0.040	A346095
Dissolved Silicon (Si)	ug/L	2970	<50	2750	2330	A346416	3200	50	A346095
Dissolved Silver (Ag)	ug/L	<0.0050	<0.0050	<0.0050	<0.0050	A346416	<0.0050	0.0050	A346095
Dissolved Strontium (Sr)	ug/L	245	<0.050	228	315	A346416	269	0.050	A346095
Dissolved Tellurium (Te)	ug/L	<0.020	<0.020	<0.020	<0.020	A346416	<0.020	0.020	A346095
Dissolved Thallium (TI)	ug/L	<0.0020	<0.0020	<0.0020	<0.0020	A346416	<0.0020	0.0020	A346095
Dissolved Thorium (Th)	ug/L	<0.0050	<0.0050	<0.0050	<0.0050	A346416	<0.0050	0.0050	
Dissolved Tin (Sn)	ug/L	<0.20	<0.20	<0.20	<0.20	A346416	<0.20	0.20	A346095
Dissolved Titanium (Ti)	ug/L	<0.50	<0.50	<0.50	<0.50	A346416	<0.50	0.50	A346095
Dissolved Tungsten (W)	ug/L	0.053	<0.010	0.091	<0.010	A346416	<0.010	0.010	A346095
Dissolved Uranium (U)	ug/L	1.65	0.0024	1.95	1.84	A346416	1.15		A346095
Dissolved Vanadium (V)	ug/L	<0.20	<0.20	<0.20	<0.20	A346416	<0.20	0.20	A346095
Dissolved Zinc (Zn)	ug/L	13.1	0.13	17.3	0.16	A346416	10.7	0.10	A346095
Dissolved Zirconium (Zr)	ug/L	<0.10	<0.10	<0.10	<0.10	A346416	<0.10	0.10	A346095
Dissolved Calcium (Ca)	mg/L	81.9	<0.050	78.6	43.4	A342028	80.0	0.050	A342028
Dissolved Magnesium (Mg)	mg/L	29.2	<0.050	27.0	55.3	A342028	34.6	0.050	A342028
RDL = Reportable Detection Lin		23.2	-0.050	27.0	33.3	. 10 12020	3 7.0	0.000	. 13 12020
NDL - Reportable Detection Li	1111								



BV Labs Job #: C165509 Government of Yukon – Dept of ENV Report Date: 2021/09/23 Client Project #: 2021-Ketza

ELEMENTS BY ATOMIC SPECTROSCOPY (WATER)

BV Labs ID		AFF267	AFF268	AFF269	AFF270		AFF271		
DV 140315		2021/09/01	2021/09/01	2021/09/01	2021/09/01		2021/09/01		
Sampling Date		12:00	11:45	12:30	13:15		14:15		
COC Number		644610-04-01	644610-04-01	644610-04-01	644610-04-01		644610-04-01		
	UNITS	2021T25-15	2021T25-16	2021T25-17	2021T25-18	QC Batch	2021T25-19	RDL	QC Batch
Dissolved Potassium (K)	mg/L	0.355	<0.050	0.362	0.557	A342028	0.378	0.050	A342028
Dissolved Sodium (Na)	mg/L	0.874	<0.050	0.962	0.620	A342028	0.805	0.050	A342028
Dissolved Sulphur (S)	mg/L	58.7	<3.0	52.0	38.3	A342028	74.9	3.0	A342028
Total Metals by ICPMS									
Total Aluminum (AI)	ug/L	987	1.06	262	2.76	A343687	2690	0.50	A343687
Total Antimony (Sb)	ug/L	0.205	<0.020	0.221	0.287	A343687	0.216	0.020	A343687
Total Arsenic (As)	ug/L	13.4	<0.020	15.9	0.361	A343687	13.4	0.020	A343687
Total Barium (Ba)	ug/L	17.8	<0.020	13.8	20.6	A343687	25.3	0.020	A343687
Total Beryllium (Be)	ug/L	0.080	<0.010	0.016	<0.010	A343687	0.206	0.010	A343687
Total Bismuth (Bi)	ug/L	<0.0050	<0.0050	<0.0050	<0.0050	A343687	<0.0050	0.0050	A343687
Total Boron (B)	ug/L	<10	<10	<10	<10	A343687	<10	10	A343687
Total Cadmium (Cd)	ug/L	0.344	<0.0050	0.154	<0.0050	A343687	0.767	0.0050	A343687
Total Chromium (Cr)	ug/L	<0.10	<0.10	<0.10	<0.10	A343687	<0.10	0.10	A343687
Total Cobalt (Co)	ug/L	9.94	<0.0050	7.98	0.0255	A343687	15.4	0.0050	A343687
Total Copper (Cu)	ug/L	6.51	<0.050	0.757	0.052	A343687	18.5	0.050	A343687
Total Iron (Fe)	ug/L	375	<1.0	592	15.5	A343687	46.5	1.0	A343687
Total Lead (Pb)	ug/L	0.229	<0.0050	0.226	0.0392	A343687	0.275	0.0050	A343687
Total Lithium (Li)	ug/L	2.81	<0.50	2.33	3.57	A343687	4.06	0.50	A343687
Total Manganese (Mn)	ug/L	266	<0.050	69.1	0.741	A343687	660	0.050	A343687
Total Molybdenum (Mo)	ug/L	0.203	<0.050	0.231	0.297	A343687	0.195	0.050	A343687
Total Nickel (Ni)	ug/L	14.6	<0.020	5.55	0.071	A343687	33.9	0.020	A343687
Total Selenium (Se)	ug/L	0.744	<0.040	0.747	0.473	A343687	0.953	0.040	A343687
Total Silicon (Si)	ug/L	2960	<50	2830	2410	A343687	3560	50	A343687
Total Silver (Ag)	ug/L	<0.0050	<0.0050	<0.0050	<0.0050	A343687	<0.0050	0.0050	A343687
Total Strontium (Sr)	ug/L	242	0.057	236	316	A343687	269	0.050	A343687
Total Tellurium (Te)	ug/L	<0.020	<0.020	<0.020	<0.020	A343687	<0.020	0.020	A343687
Total Thallium (TI)	ug/L	<0.0020	<0.0020	<0.0020	<0.0020	A343687	<0.0020	0.0020	A343687
Total Thorium (Th)	ug/L	0.0084	<0.0050	0.0052	<0.0050	A343687	0.0104	0.0050	A343687
Total Tin (Sn)	ug/L	<0.20	<0.20	<0.20	<0.20	A343687	<0.20	0.20	A343687
Total Titanium (Ti)	ug/L	<0.50	<0.50	<0.50	<0.50	A343687	<0.50	0.50	A343687
Total Tungsten (W)	ug/L	0.051	<0.010	0.089	<0.010	A343687	<0.010	0.010	A343687
Total Uranium (U)	ug/L	1.77	<0.0020	1.92	1.76	A343687	1.56	0.0020	A343687
Total Vanadium (V)	ug/L	<0.20	<0.20	<0.20	<0.20	A343687	<0.20	0.20	A343687
Total Zinc (Zn)	ug/L	52.2	<0.10	39.4	0.20	A343687	91.4	0.10	A343687
RDL = Reportable Detection Li	mit							-	



Government of Yukon – Dept of ENV Client Project #: 2021-Ketza

ELEMENTS BY ATOMIC SPECTROSCOPY (WATER)

BV Labs ID		AFF267	AFF268	AFF269	AFF270		AFF271		
Sampling Date		2021/09/01	2021/09/01	2021/09/01	2021/09/01		2021/09/01		
Sampling Date		12:00	11:45	12:30	13:15		14:15		
COC Number		644610-04-01	644610-04-01	644610-04-01	644610-04-01		644610-04-01		
	UNITS	2021T25-15	2021T25-16	2021T25-17	2021T25-18	QC Batch	2021T25-19	RDL	QC Batch
Total Zirconium (Zr)	ug/L	<0.10	<0.10	<0.10	<0.10	A343687	<0.10	0.10	A343687
Total Calcium (Ca)	mg/L	78.6	<0.050	78.4	42.7	A341601	78.2	0.050	A341601
Total Magnesium (Mg)	mg/L	28.0	<0.050	25.9	52.4	A341601	33.4	0.050	A341601
Total Potassium (K)	mg/L	0.347	<0.050	0.342	0.532	A341601	0.371	0.050	A341601
Total Sodium (Na)	mg/L	0.863	<0.050	2.44	0.638	A341601	0.774	0.050	A341601
Total Sulphur (S)	mg/L	57.2	<3.0	51.7	40.4	A341601	75.6	3.0	A341601
RDL = Reportable Detection L	imit	•			•				



Government of Yukon – Dept of ENV Client Project #: 2021-Ketza

ELEMENTS BY ATOMIC SPECTROSCOPY (WATER)

BV Labs ID		AFF271			AFF272	AFF273	AFF274	AFF275		
Sampling Date		2021/09/01			2021/09/01	2021/09/01	2021/09/02	2021/09/02		
Jamping Date		14:15			15:30	15:30	10:15	11:00		
COC Number		644610-04-01			644610-04-01	644610-05-01	644610-05-01	644610-05-01		
	UNITS	2021T25-19 Lab-Dup	RDL	QC Batch	2021T25-20	2021T25-21	2021T25-22	2021T25-23	RDL	QC Batch
Dissolved Metals by ICPMS										
Dissolved Aluminum (Al)	ug/L	233	0.50	A346095	1.53	1.56	4.36	43.0	0.50	A346095
Dissolved Antimony (Sb)	ug/L	0.214	0.020	A346095	0.369	0.235	0.386	0.061	0.020	A346095
Dissolved Arsenic (As)	ug/L	2.85	0.020	A346095	37.6	202	12.3	0.992	0.020	A346095
Dissolved Barium (Ba)	ug/L	25.0	0.020	A346095	16.3	4.17	7.85	2.44	0.020	A346095
Dissolved Beryllium (Be)	ug/L	<0.010	0.010	A346095	<0.010	<0.010	<0.010	<0.010	0.010	A346095
Dissolved Bismuth (Bi)	ug/L	<0.0050	0.0050	A346095	<0.0050	<0.0050	<0.0050	<0.0050	0.0050	A346095
Dissolved Boron (B)	ug/L	<10	10	A346095	<10	<10	<10	<10	10	A346095
Dissolved Cadmium (Cd)	ug/L	0.496	0.0050	A346095	0.0085	0.143	0.0091	0.170	0.0050	A346095
Dissolved Chromium (Cr)	ug/L	<0.10	0.10	A346095	<0.10	<0.10	<0.10	<0.10	0.10	A346095
Dissolved Cobalt (Co)	ug/L	14.5	0.0050	A346095	0.0258	0.236	0.0217	1.59	0.0050	A346095
Dissolved Copper (Cu)	ug/L	1.65	0.050	A346095	0.058	0.079	0.105	0.224	0.050	A346095
Dissolved Iron (Fe)	ug/L	<1.0	1.0	A346095	<1.0	4.8	<1.0	2.3	1.0	A346095
Dissolved Lead (Pb)	ug/L	0.0133	0.0050	A346095	<0.0050	<0.0050	0.0061	<0.0050	0.0050	A346095
Dissolved Lithium (Li)	ug/L	4.15	0.50	A346095	0.77	3.69	0.99	1.09	0.50	A346095
Dissolved Manganese (Mn)	ug/L	683	0.050	A346095	0.133	20.3	0.083	32.7	0.050	A346095
Dissolved Molybdenum (Mo)	ug/L	0.235	0.050	A346095	0.251	0.692	0.210	0.169	0.050	A346095
Dissolved Nickel (Ni)	ug/L	32.7	0.020	A346095	0.910	2.23	0.474	9.23	0.020	A346095
Dissolved Selenium (Se)	ug/L	0.867	0.040	A346095	1.80	0.638	0.339	0.058	0.040	A346095
Dissolved Silicon (Si)	ug/L	3150	50	A346095	1880	5570	1760	940	50	A346095
Dissolved Silver (Ag)	ug/L	<0.0050	0.0050	A346095	<0.0050	<0.0050	<0.0050	<0.0050	0.0050	A346095
Dissolved Strontium (Sr)	ug/L	263	0.050	A346095	263	775	186	108	0.050	A346095
Dissolved Tellurium (Te)	ug/L	<0.020	0.020	A346095	<0.020	<0.020	<0.020	<0.020	0.020	A346095
Dissolved Thallium (TI)	ug/L	<0.0020	0.0020	A346095	<0.0020	0.0092	<0.0020	0.0046	0.0020	A346095
Dissolved Thorium (Th)	ug/L	<0.0050	0.0050	A346095	<0.0050	0.0059	<0.0050	<0.0050	0.0050	A346095
Dissolved Tin (Sn)	ug/L	<0.20	0.20	A346095	<0.20	<0.20	<0.20	<0.20	0.20	A346095
Dissolved Titanium (Ti)	ug/L	<0.50	0.50	A346095	<0.50	<0.50	<0.50	<0.50	0.50	A346095
Dissolved Tungsten (W)	ug/L	<0.010	0.010	A346095	<0.010	0.012	<0.010	<0.010	0.010	A346095
Dissolved Uranium (U)	ug/L	1.13	0.0020	A346095	2.24	4.26	1.81	1.16	0.0020	A346095
Dissolved Vanadium (V)	ug/L	<0.20	0.20	A346095	<0.20	<0.20	<0.20	<0.20	0.20	A346095
Dissolved Zinc (Zn)	ug/L	11.0	0.10	A346095	1.20	47.2	0.56	7.04	0.10	A346095
Dissolved Zirconium (Zr)	ug/L	<0.10	0.10	A346095	<0.10	<0.10	<0.10	<0.10	0.10	A346095
Dissolved Calcium (Ca)	mg/L				94.4	188	67.8	35.8	0.050	A342028

RDL = Reportable Detection Limit



Government of Yukon – Dept of ENV Client Project #: 2021-Ketza

ELEMENTS BY ATOMIC SPECTROSCOPY (WATER)

BV Labs ID		AFF271			AFF272	AFF273	AFF274	AFF275		
		2021/09/01			2021/09/01	2021/09/01	2021/09/02	2021/09/02		
Sampling Date		14:15			15:30	15:30	10:15	11:00		
COC Number		644610-04-01			644610-04-01	644610-05-01	644610-05-01	644610-05-01		
	UNITS	2021T25-19 Lab-Dup	RDL	QC Batch	2021T25-20	2021T25-21	2021T25-22	2021T25-23	RDL	QC Batch
Dissolved Magnesium (Mg)	mg/L				33.2	42.4	17.8	11.5	0.050	A342028
Dissolved Potassium (K)	mg/L				0.288	0.990	0.151	0.120	0.050	A342028
Dissolved Sodium (Na)	mg/L				0.539	3.52	0.305	0.164	0.050	A342028
Dissolved Sulphur (S)	mg/L				83.4	144	32.2	20.9	3.0	A342028
Total Metals by ICPMS	•									
Total Aluminum (Al)	ug/L				4.09	3.22	5.54	63.6	0.50	A343687
Total Antimony (Sb)	ug/L				0.377	0.241	0.399	0.051	0.020	A343687
Total Arsenic (As)	ug/L				39.7	269	13.0	2.05	0.020	A343687
Total Barium (Ba)	ug/L				15.8	4.11	7.47	2.44	0.020	A343687
Total Beryllium (Be)	ug/L				<0.010	<0.010	<0.010	<0.010	0.010	A343687
Total Bismuth (Bi)	ug/L				<0.0050	0.0059	<0.0050	<0.0050	0.0050	A343687
Total Boron (B)	ug/L				<10	<10	<10	<10	10	A343687
Total Cadmium (Cd)	ug/L				0.0065	0.154	0.0091	0.165	0.0050	A343687
Total Chromium (Cr)	ug/L				<0.10	<0.10	<0.10	<0.10	0.10	A343687
Total Cobalt (Co)	ug/L				0.0309	0.250	0.0213	1.46	0.0050	A343687
Total Copper (Cu)	ug/L				0.107	0.158	0.165	0.405	0.050	A343687
Total Iron (Fe)	ug/L				13.3	256	7.8	82.1	1.0	A343687
Total Lead (Pb)	ug/L				0.0198	0.0056	0.0348	0.0297	0.0050	A343687
Total Lithium (Li)	ug/L				0.75	3.48	0.92	1.08	0.50	A343687
Total Manganese (Mn)	ug/L				0.565	20.5	0.650	30.2	0.050	A343687
Total Molybdenum (Mo)	ug/L				0.211	0.685	0.243	0.156	0.050	A343687
Total Nickel (Ni)	ug/L				0.843	2.13	0.415	8.64	0.020	A343687
Total Selenium (Se)	ug/L				1.95	0.611	0.352	0.074	0.040	A343687
Total Silicon (Si)	ug/L				1980	5290	1700	924	50	A343687
Total Silver (Ag)	ug/L				<0.0050	<0.0050	<0.0050	<0.0050	0.0050	A343687
Total Strontium (Sr)	ug/L				253	754	175	108	0.050	A343687
Total Tellurium (Te)	ug/L				<0.020	<0.020	<0.020	<0.020	0.020	A343687
Total Thallium (TI)	ug/L				<0.0020	0.0092	<0.0020	0.0034	0.0020	A343687
Total Thorium (Th)	ug/L				<0.0050	<0.0050	<0.0050	0.0060	0.0050	A343687
Total Tin (Sn)	ug/L				<0.20	<0.20	<0.20	<0.20	0.20	A343687
Total Titanium (Ti)	ug/L				<0.50	<0.50	<0.50	<0.50	0.50	A343687
Total Tungsten (W)	ug/L				<0.010	0.010	<0.010	<0.010	0.010	A343687
Total Uranium (U)	ug/L				2.09	4.03	1.69	1.13	0.0020	A343687
				•	•	•				•

RDL = Reportable Detection Limit



Government of Yukon – Dept of ENV Client Project #: 2021-Ketza

ELEMENTS BY ATOMIC SPECTROSCOPY (WATER)

BV Labs ID		AFF271			AFF272	AFF273	AFF274	AFF275		
Sampling Date		2021/09/01			2021/09/01	2021/09/01	2021/09/02	2021/09/02		
Sampling Date		14:15			15:30	15:30	10:15	11:00		
COC Number		644610-04-01			644610-04-01	644610-05-01	644610-05-01	644610-05-01		
	UNITS	2021T25-19 Lab-Dup	RDL	QC Batch	2021T25-20	2021T25-21	2021T25-22	2021T25-23	RDL	QC Batch
Total Vanadium (V)	ug/L				<0.20	<0.20	<0.20	<0.20	0.20	A343687
Total Zinc (Zn)	ug/L				1.17	50.7	1.47	9.47	0.10	A343687
Total Zirconium (Zr)	ug/L				<0.10	<0.10	<0.10	<0.10	0.10	A343687
Total Calcium (Ca)	mg/L				90.9	183	62.8	34.8	0.050	A341601
Total Magnesium (Mg)	mg/L				29.8	40.7	16.5	10.5	0.050	A341601
Total Potassium (K)	mg/L				0.258	0.943	0.135	0.112	0.050	A341601
Total Sodium (Na)	mg/L				0.511	3.29	0.275	0.145	0.050	A341601
Total Sulphur (S)	mg/L				82.3	147	31.7	21.4	3.0	A341601

RDL = Reportable Detection Limit



BV Labs Job #: C165509 Government of Yukon – Dept of ENV Report Date: 2021/09/23 Client Project #: 2021-Ketza

ELEMENTS BY ATOMIC SPECTROSCOPY (WATER)

BV Labs ID		AFF276			AFF276			AFF277		
Campling Data		2021/09/02			2021/09/02			2021/09/02		
Sampling Date		11:15			11:15			12:00		
COC Number		644610-05-01			644610-05-01			644610-05-01		
	UNITS	2021T25-24	RDL	QC Batch	2021T25-24 Lab-Dup	RDL	QC Batch	2021T25-25	RDL	QC Batch
Dissolved Metals by ICPMS										
Dissolved Aluminum (AI)	ug/L	48.0	0.50	A351252				<0.50	0.50	A346095
Dissolved Antimony (Sb)	ug/L	0.049	0.020	A351252				<0.020	0.020	A346095
Dissolved Arsenic (As)	ug/L	1.27	0.020	A351252				<0.020	0.020	A346095
Dissolved Barium (Ba)	ug/L	2.58	0.020	A351252				<0.020	0.020	A346095
Dissolved Beryllium (Be)	ug/L	<0.010	0.010	A351252				<0.010	0.010	A346095
Dissolved Bismuth (Bi)	ug/L	<0.0050	0.0050	A351252				<0.0050	0.0050	A346095
Dissolved Boron (B)	ug/L	<10	10	A351252				<10	10	A346095
Dissolved Cadmium (Cd)	ug/L	0.159	0.0050	A351252				<0.0050	0.0050	A346095
Dissolved Chromium (Cr)	ug/L	<0.10	0.10	A351252				<0.10	0.10	A346095
Dissolved Cobalt (Co)	ug/L	1.56	0.0050	A351252				<0.0050	0.0050	A346095
Dissolved Copper (Cu)	ug/L	0.147	0.050	A351252				<0.050	0.050	A346095
Dissolved Iron (Fe)	ug/L	1.1	1.0	A351252				<1.0	1.0	A346095
Dissolved Lead (Pb)	ug/L	<0.0050	0.0050	A351252				<0.0050	0.0050	A346095
Dissolved Lithium (Li)	ug/L	1.02	0.50	A351252				<0.50	0.50	A346095
Dissolved Manganese (Mn)	ug/L	31.0	0.050	A351252				<0.050	0.050	A346095
Dissolved Molybdenum (Mo)	ug/L	0.173	0.050	A351252				<0.050	0.050	A346095
Dissolved Nickel (Ni)	ug/L	9.01	0.020	A351252				<0.020	0.020	A346095
Dissolved Selenium (Se)	ug/L	0.060	0.040	A351252				<0.040	0.040	A346095
Dissolved Silicon (Si)	ug/L	894	50	A351252				<50	50	A346095
Dissolved Silver (Ag)	ug/L	<0.0050	0.0050	A351252				<0.0050	0.0050	A346095
Dissolved Strontium (Sr)	ug/L	112	0.050	A351252				0.058	0.050	A346095
Dissolved Tellurium (Te)	ug/L	<0.020	0.020	A351252				<0.020	0.020	A346095
Dissolved Thallium (TI)	ug/L	0.0028	0.0020	A351252				<0.0020	0.0020	A346095
Dissolved Thorium (Th)	ug/L	<0.0050	0.0050	A351252				<0.0050	0.0050	A346095
Dissolved Tin (Sn)	ug/L	<0.20	0.20	A351252				<0.20	0.20	A346095
Dissolved Titanium (Ti)	ug/L	<0.50	0.50	A351252				<0.50	0.50	A346095
Dissolved Tungsten (W)	ug/L	<0.010	0.010	A351252				<0.010	0.010	A346095
Dissolved Uranium (U)	ug/L	1.12	0.0020	A351252				<0.0020	0.0020	A346095
Dissolved Vanadium (V)	ug/L	<0.20	0.20	A351252				<0.20	0.20	A346095
Dissolved Zinc (Zn)	ug/L	5.76	0.10	A351252				0.17	0.10	A346095
Dissolved Zirconium (Zr)	ug/L	<0.10	0.10	A351252				<0.10	0.10	A346095
Dissolved Calcium (Ca)	mg/L	34.3	0.050	A342028				<0.050	0.050	A342028
RDI = Reportable Detection Lin	mit									

RDL = Reportable Detection Limit



ELEMENTS BY ATOMIC SPECTROSCOPY (WATER)

BV Labs ID		AFF276			AFF276			AFF277		
Sampling Date		2021/09/02			2021/09/02			2021/09/02		
Sampling Date		11:15			11:15			12:00		
COC Number		644610-05-01			644610-05-01			644610-05-01		
	UNITS	2021T25-24	RDL	QC Batch	2021T25-24 Lab-Dup	RDL	QC Batch	2021T25-25	RDL	QC Batch
Dissolved Magnesium (Mg)	mg/L	11.0	0.050	A342028				<0.050	0.050	A342028
Dissolved Potassium (K)	mg/L	0.111	0.050	A342028				<0.050	0.050	A342028
Dissolved Sodium (Na)	mg/L	0.154	0.050	A342028				<0.050	0.050	A342028
Dissolved Sulphur (S)	mg/L	21.4	3.0	A342028				<3.0	3.0	A342028
Total Metals by ICPMS			ē	•	•	ē		•	•	
Total Aluminum (AI)	ug/L	70.7	0.50	A347639	68.0	0.50	A347639	<0.50	0.50	A343687
Total Antimony (Sb)	ug/L	0.056	0.020	A347639	0.050	0.020	A347639	<0.020	0.020	A343687
Total Arsenic (As)	ug/L	1.84	0.020	A347639	1.79	0.020	A347639	<0.020	0.020	A343687
Total Barium (Ba)	ug/L	2.75	0.020	A347639	2.75	0.020	A347639	<0.020	0.020	A343687
Total Beryllium (Be)	ug/L	<0.010	0.010	A347639	<0.010	0.010	A347639	<0.010	0.010	A343687
Total Bismuth (Bi)	ug/L	<0.0050	0.0050	A347639	<0.0050	0.0050	A347639	<0.0050	0.0050	A343687
Total Boron (B)	ug/L	<10	10	A347639	<10	10	A347639	<10	10	A343687
Total Cadmium (Cd)	ug/L	0.183	0.0050	A347639	0.175	0.0050	A347639	<0.0050	0.0050	A343687
Total Chromium (Cr)	ug/L	<0.10	0.10	A347639	<0.10	0.10	A347639	<0.10	0.10	A343687
Total Cobalt (Co)	ug/L	1.78	0.0050	A347639	1.75	0.0050	A347639	<0.0050	0.0050	A343687
Total Copper (Cu)	ug/L	0.372	0.050	A347639	0.390	0.050	A347639	<0.050	0.050	A343687
Total Iron (Fe)	ug/L	80.4	1.0	A347639	81.2	1.0	A347639	<1.0	1.0	A343687
Total Lead (Pb)	ug/L	0.0277	0.0050	A347639	0.0270	0.0050	A347639	<0.0050	0.0050	A343687
Total Lithium (Li)	ug/L	1.14	0.50	A347639	1.11	0.50	A347639	<0.50	0.50	A343687
Total Manganese (Mn)	ug/L	36.5	0.050	A347639	36.2	0.050	A347639	<0.050	0.050	A343687
Total Molybdenum (Mo)	ug/L	0.175	0.050	A347639	0.156	0.050	A347639	<0.050	0.050	A343687
Total Nickel (Ni)	ug/L	9.67	0.020	A347639	9.39	0.020	A347639	<0.020	0.020	A343687
Total Selenium (Se)	ug/L	0.072	0.040	A347639	0.063	0.040	A347639	<0.040	0.040	A343687
Total Silicon (Si)	ug/L	1020	50	A347639	1020	50	A347639	<50	50	A343687
Total Silver (Ag)	ug/L	<0.0050	0.0050	A347639	<0.0050	0.0050	A347639	<0.0050	0.0050	A343687
Total Strontium (Sr)	ug/L	117	0.050	A347639	115	0.050	A347639	0.059	0.050	A343687
Total Tellurium (Te)	ug/L	<0.020	0.020	A347639	<0.020	0.020	A347639	<0.020	0.020	A343687
Total Thallium (TI)	ug/L	0.0057	0.0020	A347639	0.0054	0.0020	A347639	<0.0020	0.0020	A343687
Total Thorium (Th)	ug/L	0.0071	0.0050	A347639	0.0074	0.0050	A347639	<0.0050	0.0050	A343687
Total Tin (Sn)	ug/L	<0.20	0.20	A347639	<0.20	0.20	A347639	<0.20	0.20	A343687
Total Titanium (Ti)	ug/L	<0.50	0.50	A347639	<0.50	0.50	A347639	<0.50	0.50	A343687
Total Tungsten (W)	ug/L	0.029	0.010	A347639	0.032	0.010	A347639	<0.010	0.010	A343687
Total Uranium (U)	ug/L	1.22	0.0020	A347639	1.21	0.0020	A347639	<0.0020	0.0020	A343687
RDL = Reportable Detection Li				•	-		-	-	•	-

Lab-Dup = Laboratory Initiated Duplicate



BV Labs Job #: C165509 Government of Yukon – Dept of ENV Report Date: 2021/09/23 Client Project #: 2021-Ketza

ELEMENTS BY ATOMIC SPECTROSCOPY (WATER)

BV Labs ID		AFF276			AFF276			AFF277		
Sampling Date		2021/09/02			2021/09/02			2021/09/02		
Sampling Date		11:15			11:15			12:00		
COC Number		644610-05-01			644610-05-01			644610-05-01		
	UNITS	2021T25-24	RDL	QC Batch	2021T25-24 Lab-Dup	RDL	QC Batch	2021T25-25	RDL	QC Batch
Total Vanadium (V)	ug/L	<0.20	0.20	A347639	<0.20	0.20	A347639	<0.20	0.20	A343687
Total Zinc (Zn)	ug/L	9.63	0.10	A347639	9.31	0.10	A347639	0.81	0.10	A349611
Total Zirconium (Zr)	ug/L	<0.10	0.10	A347639	<0.10	0.10	A347639	<0.10	0.10	A343687
Total Calcium (Ca)	mg/L	36.7	0.050	A341601				<0.050	0.050	A341601
Total Magnesium (Mg)	mg/L	11.4	0.050	A341601				<0.050	0.050	A341601
Total Potassium (K)	mg/L	0.125	0.050	A341601				<0.050	0.050	A341601
Total Sodium (Na)	mg/L	0.154	0.050	A341601				<0.050	0.050	A341601
Total Sulphur (S)	mg/L	21.9	3.0	A341601				<3.0	3.0	A341601

RDL = Reportable Detection Limit

Lab-Dup = Laboratory Initiated Duplicate



BV Labs Job #: C165509 Government of Yukon – Dept of ENV Report Date: 2021/09/23 Client Project #: 2021-Ketza

GENERAL COMMENTS

Each temperature is the average of up to three cooler temperatures taken at receipt

Package 1	6.0°C
Package 2	4.0°C
Package 3	7.0°C

Sample AFF268 [2021T25-16]: Sample was analyzed past method specified hold time for Total Dissolved Solids - Low Level. Exceedance of hold time increases the uncertainty of test results but does not necessarily imply that results are compromised.

Sample AFF276 [2021T25-24]: The sample for dissolved metals was filtered and preserved at the lab. Values may not reflect concentrations at the time of sampling.

Sample AFF277 [2021T25-25]: Sample was analyzed past method specified hold time for Total Dissolved Solids - Low Level. Exceedance of hold time increases the uncertainty of test results but does not necessarily imply that results are compromised.

Sample AFF277, Elements by ICPMS Low Level (total): Test repeated.

Results relate only to the items tested.



Government of Yukon – Dept of ENV Client Project #: 2021-Ketza

QUALITY ASSURANCE REPORT

BANCH Rist CType Parameter Date Analyzed Value Recovery UNITS Oct Linds A342326 TSO Makris Spike [AFZ64-02] Nitrate plus Nitrite (N) 2021/09/94 102 % 80 - 120 A34226 TSO Method Blank Nitrate plus Nitrite (N) 2021/09/94 0.0000 mg/L A34236 TSO Method Blank Nitrite (N) 2021/09/94 0.0000 mg/L A342380 TSO Spiked Blank Nitrite (N) 2021/09/94 0.0000 mg/L A342380 TSO Method Blank Nitrite (N) 2021/09/97 0.0000 mg/L A343237 CP Method Blank Dissolved Methorury (Ng) 2021/09/97 0.0019 mg/L A343237 CP Repol Jambiner Dissolved Methorury (Ng) 2021/09/97 0.0019 mg/L A343237 CP Repol Jambiner Dissolved Methorury (Ng) 2021/09/97 0.0019 mg/L A343237 CP RPO) Jambiner Dissolved Methorury (Ng)		QUALITY ASSURANCE REPORT											
A342328 1750 Spiked Blank Niritare plus Niriter (N) 2021/09/04 d. 0.0020 mg/L mg	-	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits				
Mart	A342326	TSO	Matrix Spike [AFF264-02]	Nitrate plus Nitrite (N)	2021/09/04		102	%	80 - 120				
1842-138 780 8P0 [AP78-4-02] Mirate glus Mirite [N] 2011/69/04 100 5 80 50 1842-138 780 Solked Blank Mirite (N) 2011/69/04 0.0020 mg/L 1842-138 780 Solked Blank Mirite (N) 2011/69/04 0.0020 mg/L 1842-138 780 Solked Blank Mirite (N) 2011/69/04 0.0020 mg/L 1842-138 780 SP0 [AP78-402] Mirite (N) 2011/69/04 0.0020 mg/L 1842-138 780 SP0 [AP78-402] Mirite (N) 2011/69/07 0.0039 3 5 80 120 1842-138 780 Mirite Splite Mirite (N) 2011/69/07 0.0039 mg/L 1842-138 780 Mirite Splite Mirite (N) 2011/69/07 0.0039 mg/L 1842-138 780 Mirite Splite Mirite (N) 2011/69/07 0.0039 mg/L 1842-138 Mirite Splite AP78-404 Mirite (N) 2011/69/07 0.0039 mg/L 1842-138 Mirite Splite AP78-404 Mirite (N) 2011/69/07 0.0039 mg/L 1842-138 Mirite Splite AP78-404 Mirite (N) 2011/69/07 0.0039 mg/L 1842-138 Mirite Splite AP78-404 Mirite (N) 2011/69/08 0.0039 mg/L 1842-138 Mirite Splite AP78-404 Mirite (N) 2011/69/08 0.0039 mg/L 1842-138 Mirite Splite AP78-404 Mirite (N) 2011/69/08 0.0039 mg/L 1842-138 Mirite Splite AP78-404 Mirite (N) 2011/69/08 0.0039 mg/L 1842-138 Mirite Splite AP78-404 Mirite (N) 2011/69/08 0.0039 mg/L 1842-138 Mirite Splite AP78-404 Mirite (N) 2011/69/08 0.0039 mg/L 1842-138 Mirite Splite AP78-404 Mirite (N) 2011/69/08 0.0039 mg/L 1842-138 Mirite Splite AP78-404 Mirite (N) 2011/69/08 0.0039 mg/L 1842-138 Mirite Splite AP78-404 Mirite (N) 2011/69/08 0.0039 mg/L 1842-138 Mirite Splite AP78-404 Mirite (N) 2011/69/08 0.0039 mg/L 1842-138 Mirite Splite AP78-404 Mirite Mirite (N) 2011/69/08 0.0039 mg/L 1842-138 Mirite Splite AP78-404 Mirite Mirite Mirite (N) 2011/69/08 0.0039 mg/L 1842-138 Mirite Splite AP78-404 mg/L 1842-138 Mirite Splite AP78-404 mg/L 184	A342326	TSO	Spiked Blank	Nitrate plus Nitrite (N)	2021/09/04		105	%	80 - 120				
Martin Spike Martin Spike Martin Spike Martin Ke No. 2011/89/04 0.0020 mg No. 100 Mg 80 - 120 Mg Mg Mg Mg Mg Mg Mg M	A342326	TSO	Method Blank	Nitrate plus Nitrite (N)	2021/09/04	<0.0020		mg/L					
Math Mintro Min	A342326	TSO	RPD [AFF264-02]	Nitrate plus Nitrite (N)	2021/09/04	1.0		%	25				
May 13, 13, 13, 13, 14, 15, 16, 16, 16, 16, 17, 17, 18, 18, 18, 18, 18, 18, 18, 18, 18, 18	A342330	TSO	Matrix Spike [AFF264-02]		2021/09/04		100	%	80 - 120				
May Mark Spin Rep Merke Rep Mirtie N) 201/89/06 NC 18 18 18 18 19 19 19 18 18	A342330	TSO	Spiked Blank	Nitrite (N)	2021/09/04		102	%	80 - 120				
A343127 CV Matrix Spike Dissolved Mercury (Hg) 2021/09/07 38 % 80-120 A343127 CV Method Blank Dissolved Mercury (Hg) 2021/09/07 <0.0019	A342330	TSO	Method Blank	Nitrite (N)	2021/09/04	<0.0020		mg/L					
A343127 CV Spiked Blank Dissolved Mercury (Hg) 2021/09/07 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.0019 <0.001	A342330	TSO	RPD [AFF264-02]	• •	2021/09/04	NC		%	25				
A343127 CJV MeD Dissolved Mercury (Hg) 2021/09/07 NC % 2014 NA43687 A343147 CJV RD Dissolved Mercury (Hg) 2021/09/08 100 % 80-120 NA54587 A343687	A343127	CJY	Matrix Spike	Dissolved Mercury (Hg)	2021/09/07		93	%	80 - 120				
A343127 V. M. PRD Dissolved Mercury (Hg) 2021/09/098 NC % 20.1 A34587 AA1 Matrix Spike (AFF264-03) Total Alminum (Hd) 2021/09/08 100 % 80-120 Total Artseinc (As) 2021/09/08 105 % 80-120 Total Barlum (Ba) 2021/09/08 99 % 80-120 Total Barlum (Ba) 2021/09/08 92 % 80-120 Total Bernill (Bi) 2021/09/08 92 % 80-120 Total Gardium (Gd) 2021/09/08 93 % 80-120 Total Cadmium (Cd) 2021/09/08 93 % 80-120 Total Cobalt (Co) 2021/09/08 93 % 80-120 Total Cobalt (Co) 2021/09/08 93 % 80-120 Total Cobalt (Co) 2021/09/08 90 % 80-120 Total Cobalt (Co) 2021/09/08 90 % 80-120 Total Cobalt (Co) 2021/09/08 90 % 80-120	A343127	CJY	Spiked Blank		2021/09/07		83	%	80 - 120				
A343 887 B. A3 B. A B. A B. A B. A B. A B. A B.	A343127	CJY	Method Blank	Dissolved Mercury (Hg)	2021/09/07			ug/L					
Total Antimony (Sb)	A343127	CJY	RPD	Dissolved Mercury (Hg)	2021/09/07	NC		%	20				
Total Arsenic (As) 2021/09/08 90 % 80 - 120 Total Barium (Ba) 2021/09/08 99 % 80 - 120 Total Barium (Ba) 2021/09/08 100 % 80 - 120 Total Barium (Ba) 2021/09/08 100 % 80 - 120 Total Born (B) 2021/09/08 94 % 80 - 120 Total Born (B) 2021/09/08 94 % 80 - 120 Total Born (B) 2021/09/08 97 % 80 - 120 Total Chromium (Cr) 2021/09/08 97 % 80 - 120 Total Chromium (Cr) 2021/09/08 97 % 80 - 120 Total Chromium (Cr) 2021/09/08 99 % 80 - 120 Total Copper (Cu) 2021/09/08 99 % 80 - 120 Total Lotal (Total Lotal (Pb) 2021/09/08 97 % 80 - 120 Total Lotal (Total Lotal (Pb) 2021/09/08 97 % 80 - 120 Total Lotal (Unit (Library (Libr	A343687	AA1	Matrix Spike [AFF264-03]	Total Aluminum (Al)	2021/09/08		100	%	80 - 120				
Total Barium (Ba) 2021/09/08 99				Total Antimony (Sb)	2021/09/08		105	%	80 - 120				
Total Benyllium (Re)				Total Arsenic (As)	2021/09/08		109	%	80 - 120				
Total Bismuth (Bi)				Total Barium (Ba)	2021/09/08		99	%	80 - 120				
Total Boron (B)				Total Beryllium (Be)	2021/09/08		100	%	80 - 120				
Total Cadmium (Cd)					2021/09/08		92	%	80 - 120				
Total Chromium (Cr)				Total Boron (B)	2021/09/08		94	%	80 - 120				
Total Cobalt (Co)				Total Cadmium (Cd)	2021/09/08		103	%	80 - 120				
Total Copper (Cu)				Total Chromium (Cr)	2021/09/08		97	%	80 - 120				
Total Iron (Fe)				Total Cobalt (Co)	2021/09/08		93	%	80 - 120				
Total Lead (Pb) 2021/09/08 103 % 80 - 120				Total Copper (Cu)	2021/09/08		90	%	80 - 120				
Total Manganese (Mn)				Total Iron (Fe)	2021/09/08		101	%	80 - 120				
Total Manganese (Mn) 2021/09/08 96 % 80 - 120 Total Mickel (Ni) 2021/09/08 92 % 80 - 120 Total Nickel (Ni) 2021/09/08 92 % 80 - 120 Total Sileenium (Se) 2021/09/08 112 % 80 - 120 Total Sileenium (Se) 2021/09/08 112 % 80 - 120 Total Sileenium (Se) 2021/09/08 106 % 80 - 120 Total Sileenium (Sr) 2021/09/08 96 % 80 - 120 Total Sirontium (Sr) 2021/09/08 NC % 80 - 120 Total Total Trontium (Te) 2021/09/08 104 % 80 - 120 Total Trontium (Th) 2021/09/08 103 % 80 - 120 Total Trontium (Th) 2021/09/08 103 % 80 - 120 Total Trontium (Th) 2021/09/08 103 % 80 - 120 Total Trontium (Th) 2021/09/08 103 % 80 - 120 Total Trontium (Ti) 2021/09/08 104 % 80 - 120 Total Trantium (Ti) 2021/09/08 101 % 80 - 120 Total Trantium (U) 2021/09/08 102 % 80 - 120 Total Vanadium (V) 2021/09/08 105 % 80 - 120 Total Ziric (Zh) 2021/09/08 100 % 80 - 120 Total Ziric (Zh) 2021/09/08 109 % 80 - 120 Total Ziric (Zh) 2021/09/08 109 % 80 - 120 Total Ziric (Zh) 2021/09/08 109 % 80 - 120 Total Ziric (Zh) 2021/09/08 100 % 80 - 120 Total Ziric (Zh) 2021/09/08 100 % 80 - 120 Total Ziric (Zh) 2021/09/08 100 % 80 - 120 Total Artsenic (As) 2021/09/08 99 % 80 - 120 Total Artsenic (As) 2021/09/08 99 % 80 - 120 Total Barium (Ba) 2021/09/08 99 % 80 - 120 Total Barium (Ba) 2021/09/08 99 % 80 - 120 Total Barium (Ba) 2021/09/08 99 % 80 - 120 Total Barium (Ba) 2021/09/08 99 % 80 - 120 Total Cadmium (Cd) 2021/09/08 99 % 80 - 120 Total Cadmium (Cd) 2021/09/08 99 % 80 - 120 Total Cadmium (Cd) 2021/09/08 99 % 80 - 120 Total Cadmium (Cd) 2021/09/08 99 % 80 - 120 Total Cadmium (Cd) 2021/09/08 99 % 80 - 120 Total Cadmium (Cd) 2021/09/08 99 % 80 - 120 To				Total Lead (Pb)	2021/09/08		103	%	80 - 120				
Total Molybdenum (Mo) 2021/09/08 108				Total Lithium (Li)	2021/09/08		97	%	80 - 120				
Total Nickel (Ni)				Total Manganese (Mn)	2021/09/08		96	%	80 - 120				
Total Selenium (Se)				Total Molybdenum (Mo)	2021/09/08		108	%	80 - 120				
Total Silicon (Si) 2021/09/08 106 % 80 - 120				Total Nickel (Ni)	2021/09/08		92	%	80 - 120				
Total Silver (Ag) 2021/09/08 96				Total Selenium (Se)	2021/09/08		112	%	80 - 120				
Total Strontium (Sr) 2021/09/08 NC				• •	2021/09/08		106	%	80 - 120				
Total Tellurium (Te)				Total Silver (Ag)	2021/09/08		96	%	80 - 120				
Total Thallium (Ti)				Total Strontium (Sr)	2021/09/08		NC	%	80 - 120				
Total Thorium (Th) 2021/09/08 103				Total Tellurium (Te)	2021/09/08		104	%	80 - 120				
Total Tin (Sn) 2021/09/08 104				Total Thallium (TI)	2021/09/08		103	%	80 - 120				
Total Titanium (Ti) 2021/09/08 101				Total Thorium (Th)	2021/09/08		103	%	80 - 120				
Total Uranium (U) 2021/09/08 102 % 80 - 120				Total Tin (Sn)	2021/09/08		104	%	80 - 120				
Total Uranium (U) 2021/09/08 105 % 80 - 120				Total Titanium (Ti)	2021/09/08		101	%	80 - 120				
Total Vanadium (V) 2021/09/08 100 % 80 - 120 Total Zinc (Zn) 2021/09/08 99 % 80 - 120 Total Zinc (Zn) 2021/09/08 109 % 80 - 120 Total Zinconium (Zr) 2021/09/08 109 % 80 - 120 Total Aluminum (Al) 2021/09/08 99 % 80 - 120 Total Antimony (Sb) 2021/09/08 100 % 80 - 120 Total Arsenic (As) 2021/09/08 100 % 80 - 120 Total Barium (Ba) 2021/09/08 100 % 80 - 120 Total Barium (Ba) 2021/09/08 98 % 80 - 120 Total Barium (Ba) 2021/09/08 98 % 80 - 120 Total Bismuth (Bi) 2021/09/08 99 % 80 - 120 Total Boron (B) 2021/09/08 99 % 80 - 120 Total Cadmium (Cd) 2021/09/08 99 % 80 - 120 Total Cadmium (Cd) 2021/09/08 99 % 80 - 120 Total Cadmium (Cd) 2021/09/08 99 % 80 - 120 Total Cobalt (Co) 2021/09/08 97 % 80 - 120 Total Cobalt (Co) 2021/09/08 96 % 80 - 120 Total Cobalt (Co) 2021/09/08 96 % 80 - 120 Total Copper (Cu) 2021/09/08 96 % 80 - 120 Total Copper (Cu) 2021/09/08 96 % 80 - 120 Total Copper (Cu)				Total Tungsten (W)	2021/09/08		102	%	80 - 120				
Total Zinc (Zn) Z021/09/08 99				Total Uranium (U)	2021/09/08		105	%	80 - 120				
A343687 AA1 Spiked Blank Total Zirconium (Zr) 2021/09/08 99 % 80 - 120 Total Aluminum (Al) 2021/09/08 99 % 80 - 120 Total Antimony (Sb) 2021/09/08 100 % 80 - 120 Total Arsenic (As) 2021/09/08 100 % 80 - 120 Total Barium (Ba) 2021/09/08 98 % 80 - 120 Total Beryllium (Be) 2021/09/08 99 % 80 - 120 Total Bismuth (Bi) 2021/09/08 99 % 80 - 120 Total Boron (B) 2021/09/08 99 % 80 - 120 Total Cadmium (Cd) 2021/09/08 99 % 80 - 120 Total Cadmium (Cr) 2021/09/08 99 % 80 - 120 Total Cobalt (Co) 2021/09/08 97 % 80 - 120 Total Cobalt (Co) 2021/09/08 96 % 80 - 120 Total Copper (Cu) 2021/09/08 96 % 80 - 120				Total Vanadium (V)	2021/09/08		100	%	80 - 120				
A343687 AA1 Spiked Blank Total Aluminum (Al) 2021/09/08 99 % 80 - 120 Total Antimony (Sb) 2021/09/08 100 % 80 - 120 Total Arsenic (As) 2021/09/08 100 % 80 - 120 Total Barium (Ba) 2021/09/08 98 % 80 - 120 Total Beryllium (Be) 2021/09/08 99 % 80 - 120 Total Bismuth (Bi) 2021/09/08 99 % 80 - 120 Total Boron (B) 2021/09/08 99 % 80 - 120 Total Cadmium (Cd) 2021/09/08 99 % 80 - 120 Total Chromium (Cr) 2021/09/08 99 % 80 - 120 Total Cobalt (Co) 2021/09/08 96 % 80 - 120 Total Copper (Cu) 2021/09/08 96 % 80 - 120				Total Zinc (Zn)	2021/09/08		99	%	80 - 120				
Total Antimony (Sb) 2021/09/08 100 % 80 - 120 Total Arsenic (As) 2021/09/08 100 % 80 - 120 Total Barium (Ba) 2021/09/08 98 % 80 - 120 Total Beryllium (Be) 2021/09/08 99 % 80 - 120 Total Bismuth (Bi) 2021/09/08 97 % 80 - 120 Total Boron (B) 2021/09/08 99 % 80 - 120 Total Cadmium (Cd) 2021/09/08 99 % 80 - 120 Total Chromium (Cr) 2021/09/08 97 % 80 - 120 Total Cobalt (Co) 2021/09/08 96 % 80 - 120 Total Copper (Cu) 2021/09/08 96 % 80 - 120				Total Zirconium (Zr)	2021/09/08		109	%	80 - 120				
Total Arsenic (As) 2021/09/08 100 % 80 - 120 Total Barium (Ba) 2021/09/08 98 % 80 - 120 Total Beryllium (Be) 2021/09/08 99 % 80 - 120 Total Bismuth (Bi) 2021/09/08 97 % 80 - 120 Total Boron (B) 2021/09/08 99 % 80 - 120 Total Cadmium (Cd) 2021/09/08 99 % 80 - 120 Total Chromium (Cr) 2021/09/08 97 % 80 - 120 Total Cobalt (Co) 2021/09/08 96 % 80 - 120 Total Copper (Cu) 2021/09/08 96 % 80 - 120	A343687	AA1	Spiked Blank	Total Aluminum (Al)	2021/09/08		99	%	80 - 120				
Total Barium (Ba) 2021/09/08 98 % 80 - 120 Total Beryllium (Be) 2021/09/08 99 % 80 - 120 Total Bismuth (Bi) 2021/09/08 97 % 80 - 120 Total Boron (B) 2021/09/08 99 % 80 - 120 Total Cadmium (Cd) 2021/09/08 99 % 80 - 120 Total Chromium (Cr) 2021/09/08 97 % 80 - 120 Total Cobalt (Co) 2021/09/08 96 % 80 - 120 Total Copper (Cu) 2021/09/08 96 % 80 - 120				Total Antimony (Sb)	2021/09/08		100	%	80 - 120				
Total Beryllium (Be) 2021/09/08 99 % 80 - 120 Total Bismuth (Bi) 2021/09/08 97 % 80 - 120 Total Boron (B) 2021/09/08 99 % 80 - 120 Total Cadmium (Cd) 2021/09/08 99 % 80 - 120 Total Chromium (Cr) 2021/09/08 97 % 80 - 120 Total Cobalt (Co) 2021/09/08 96 % 80 - 120 Total Copper (Cu) 2021/09/08 96 % 80 - 120				Total Arsenic (As)	2021/09/08		100	%	80 - 120				
Total Bismuth (Bi) 2021/09/08 97 % 80 - 120 Total Boron (B) 2021/09/08 99 % 80 - 120 Total Cadmium (Cd) 2021/09/08 99 % 80 - 120 Total Chromium (Cr) 2021/09/08 97 % 80 - 120 Total Cobalt (Co) 2021/09/08 96 % 80 - 120 Total Copper (Cu) 2021/09/08 96 % 80 - 120				Total Barium (Ba)	2021/09/08		98	%	80 - 120				
Total Boron (B) 2021/09/08 99 % 80 - 120 Total Cadmium (Cd) 2021/09/08 99 % 80 - 120 Total Chromium (Cr) 2021/09/08 97 % 80 - 120 Total Cobalt (Co) 2021/09/08 96 % 80 - 120 Total Copper (Cu) 2021/09/08 96 % 80 - 120				Total Beryllium (Be)	2021/09/08		99	%	80 - 120				
Total Cadmium (Cd) 2021/09/08 99 % 80 - 120 Total Chromium (Cr) 2021/09/08 97 % 80 - 120 Total Cobalt (Co) 2021/09/08 96 % 80 - 120 Total Copper (Cu) 2021/09/08 96 % 80 - 120				Total Bismuth (Bi)	2021/09/08		97	%	80 - 120				
Total Chromium (Cr) 2021/09/08 97 % 80 - 120 Total Cobalt (Co) 2021/09/08 96 % 80 - 120 Total Copper (Cu) 2021/09/08 96 % 80 - 120				Total Boron (B)	2021/09/08		99	%	80 - 120				
Total Cobalt (Co) 2021/09/08 96 % 80 - 120 Total Copper (Cu) 2021/09/08 96 % 80 - 120				Total Cadmium (Cd)	2021/09/08		99	%	80 - 120				
Total Copper (Cu) 2021/09/08 96 % 80 - 120				Total Chromium (Cr)	2021/09/08		97	%	80 - 120				
				Total Cobalt (Co)	2021/09/08		96	%	80 - 120				
Total Iron (Fe) 2021/09/08 101 % 80 - 120				Total Copper (Cu)	2021/09/08		96	%	80 - 120				
				Total Iron (Fe)	2021/09/08		101	%	80 - 120				



QA/QC Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
			Total Lead (Pb)	2021/09/08		99	%	80 - 120
			Total Lithium (Li)	2021/09/08		96	%	80 - 120
			Total Manganese (Mn)	2021/09/08		98	%	80 - 120
			Total Molybdenum (Mo)	2021/09/08		102	%	80 - 120
			Total Nickel (Ni)	2021/09/08		98	%	80 - 120
			Total Selenium (Se)	2021/09/08		99	%	80 - 120
			Total Silicon (Si)	2021/09/08		102	%	80 - 120
			Total Silver (Ag)	2021/09/08		98	%	80 - 120
			Total Strontium (Sr)	2021/09/08		100	%	80 - 120
			Total Tellurium (Te)	2021/09/08		98	%	80 - 120
			Total Thallium (TI)	2021/09/08		96	%	80 - 120
			Total Thorium (Th)	2021/09/08		96	%	80 - 120
			Total Tin (Sn)	2021/09/08		99	%	80 - 120
			Total Titanium (Ti)	2021/09/08		100	%	80 - 120
			Total Tungsten (W)	2021/09/08		99	%	80 - 120
			Total Uranium (U)	2021/09/08		101	%	80 - 120
			Total Vanadium (V)	2021/09/08		99	%	80 - 120
			Total Zinc (Zn)	2021/09/08		99	%	80 - 120
			Total Zirconium (Zr)	2021/09/08		100	%	80 - 120
A343687	AA1	Method Blank	Total Aluminum (AI)	2021/09/08	<0.50		ug/L	
			Total Antimony (Sb)	2021/09/08	<0.020		ug/L	
			Total Arsenic (As)	2021/09/08	<0.020		ug/L	
			Total Barium (Ba)	2021/09/08	<0.020		ug/L	
			Total Beryllium (Be)	2021/09/08	<0.010		ug/L	
			Total Bismuth (Bi)	2021/09/08	<0.0050		ug/L	
			Total Boron (B)	2021/09/08	<10		ug/L	
			Total Cadmium (Cd)	2021/09/08	<0.0050		ug/L	
			Total Chromium (Cr)	2021/09/08	<0.10		ug/L	
			Total Cobalt (Co)	2021/09/08	<0.0050		ug/L	
			Total Copper (Cu)	2021/09/08	<0.050		ug/L	
			Total Iron (Fe)	2021/09/08	<1.0		ug/L	
			Total Lead (Pb)	2021/09/08	<0.0050		ug/L	
			Total Lithium (Li)	2021/09/08	<0.50		ug/L	
			Total Manganese (Mn)	2021/09/08	<0.050		ug/L	
			Total Molybdenum (Mo)	2021/09/08	<0.050		ug/L	
			Total Nickel (Ni)	2021/09/08	<0.020		ug/L	
			Total Selenium (Se)	2021/09/08	<0.040		ug/L	
			Total Silicon (Si)	2021/09/08	<50		ug/L	
			Total Silver (Ag)	2021/09/08	<0.0050		ug/L	
			Total Strontium (Sr)	2021/09/08	<0.050		ug/L	
			Total Tellurium (Te)	2021/09/08	<0.020		ug/L	
			Total Thallium (TI)	2021/09/08	<0.0020		ug/L	
			Total Thorium (Th)	2021/09/08	<0.0050		ug/L	
			Total Tin (Sn)	2021/09/08	<0.20		ug/L	
			Total Titanium (Ti)	2021/09/08	<0.50		ug/L	
			Total Tungsten (W)	2021/09/08	<0.010		ug/L	
			Total Transum (U)	2021/09/08	<0.0020		ug/L	
			Total Vanadium (V)	2021/09/08	<0.20		ug/L	
			Total Zinc (Zn)	2021/09/08	<0.10		ug/L	
			Total Ziric (Zri) Total Zirconium (Zr)	2021/09/08	<0.10		ug/L ug/L	
A343687	AA1	RPD [AFF264-03]	Total Aluminum (Al)	2021/09/08	0.10		ug/L %	20
MJ-13007	~~1	M D [Al 1 204-03]	Total Antimony (Sb)	2021/09/08	2.3		% %	20
			Total Artimony (Sb) Total Arsenic (As)	2021/09/08	2.3 0.72		% %	20
			Total Barium (Ba)	2021/09/08	2.6		% %	
			Total Barium (Ba) Total Beryllium (Be)	2021/09/08	NC		% %	20 20

			QUALITY ASSURANCE					
QA/QC Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
			Total Bismuth (Bi)	2021/09/08	NC		%	20
			Total Boron (B)	2021/09/08	NC		%	20
			Total Cadmium (Cd)	2021/09/08	0.69		%	20
			Total Chromium (Cr)	2021/09/08	NC		%	20
			Total Cobalt (Co)	2021/09/08	17		%	20
			Total Copper (Cu)	2021/09/08	0.83		%	20
			Total Iron (Fe)	2021/09/08	0.46		%	20
			Total Lead (Pb)	2021/09/08	0.35		%	20
			Total Lithium (Li)	2021/09/08	0.25		%	20
			Total Manganese (Mn)	2021/09/08	4.1		%	20
			Total Molybdenum (Mo)	2021/09/08	0.38		%	20
			Total Nickel (Ni)	2021/09/08	14		%	20
			Total Selenium (Se)	2021/09/08	4.0		%	20
			Total Silicon (Si)	2021/09/08	2.5		%	20
			Total Silver (Ag)	2021/09/08	NC		%	20
			Total Strontium (Sr)	2021/09/08	1.4		%	20
			Total Tellurium (Te)	2021/09/08	NC		%	20
			Total Thallium (TI)	2021/09/08	NC		%	20
			Total Thorium (Th)	2021/09/08	NC		%	20
			Total Tin (Sn)	2021/09/08	NC		%	20
			Total Titanium (Ti)	2021/09/08	NC		%	20
			Total Tungsten (W)	2021/09/08	NC		%	20
			Total Uranium (U)	2021/09/08	0.67		%	20
			Total Vanadium (V)	2021/09/08	NC		%	20
			Total Zinc (Zn)	2021/09/08	4.6		%	20
			Total Zinc (Zin)	2021/09/08	NC		%	20
A343687	AA1	RPD	Total Aluminum (Al)	2021/09/09	1.5		%	20
A343007	AAI	IVED	Total Antimony (Sb)	2021/09/09	NC		%	20
			• • • •	2021/09/09	NC			
			Total Parium (Pa)		NC NC		% %	20
			Total Barium (Ba)	2021/09/09				20
			Total Bisserth (Bi)	2021/09/09	NC		%	20
			Total Bismuth (Bi)	2021/09/09	NC		%	20
			Total Boron (B)	2021/09/09	NC		%	20
			Total Cadmium (Cd)	2021/09/09	NC		%	20
			Total Chromium (Cr)	2021/09/09	NC		%	20
			Total Cobalt (Co)	2021/09/09	NC		%	20
			Total Copper (Cu)	2021/09/09	NC		%	20
			Total Iron (Fe)	2021/09/09	NC		%	20
			Total Lead (Pb)	2021/09/09	NC		%	20
			Total Lithium (Li)	2021/09/09	NC		%	20
			Total Manganese (Mn)	2021/09/09	NC		%	20
			Total Molybdenum (Mo)	2021/09/09	7.5		%	20
			Total Nickel (Ni)	2021/09/09	NC		%	20
			Total Selenium (Se)	2021/09/09	NC		%	20
			Total Silicon (Si)	2021/09/09	NC		%	20
			Total Silver (Ag)	2021/09/09	NC		%	20
			Total Strontium (Sr)	2021/09/09	NC		%	20
			Total Thallium (TI)	2021/09/09	NC		%	20
			Total Tin (Sn)	2021/09/09	NC		%	20
			Total Titanium (Ti)	2021/09/09	NC		%	20
			Total Uranium (U)	2021/09/09	NC		%	20
			Total Vanadium (V)	2021/09/09	NC		%	20
			Total Zinc (Zn)	2021/09/09	14		%	20
			Total Ziric (Zr)	2021/09/09	6.7		%	20
A343719	AA1	Matrix Spike	Total Aluminum (AI)	2021/09/09		101	%	80 - 120



QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
		ζο./ρο	Total Antimony (Sb)	2021/09/09	74.40	104	%	80 - 120
			Total Arsenic (As)	2021/09/09		107	%	80 - 120
			Total Barium (Ba)	2021/09/09		NC	%	80 - 120
			Total Beryllium (Be)	2021/09/09		96	%	80 - 120
			Total Bismuth (Bi)	2021/09/09		95	%	80 - 120
			Total Boron (B)	2021/09/09		NC	%	80 - 120
			Total Cadmium (Cd)	2021/09/09		96	%	80 - 120
			Total Chromium (Cr)	2021/09/09		96	%	80 - 120
			Total Cobalt (Co)	2021/09/09		94	%	80 - 120
			Total Copper (Cu)	2021/09/09		91	%	80 - 120
			Total Iron (Fe)	2021/09/09		NC	%	80 - 120
			Total Lead (Pb)	2021/09/09		96	%	80 - 120
			Total Lead (Fb) Total Lithium (Li)	2021/09/09		NC	%	80 - 120
			Total Manganese (Mn)	2021/09/09		NC	%	80 - 120
				• •		NC		
			Total Miskel (Ni)	2021/09/09			%	80 - 120
			Total Salanium (Sa)	2021/09/09		92	%	80 - 120
			Total Selenium (Se)	2021/09/09		107	%	80 - 120
			Total Silicon (Si)	2021/09/09		107	%	80 - 120
			Total Silver (Ag)	2021/09/09		94	%	80 - 120
			Total Strontium (Sr)	2021/09/09		NC	%	80 - 120
			Total Tellurium (Te)	2021/09/09		108	%	80 - 120
			Total Thallium (TI)	2021/09/09		98	%	80 - 120
			Total Thorium (Th)	2021/09/09		99	%	80 - 120
			Total Tin (Sn)	2021/09/09		99	%	80 - 120
			Total Titanium (Ti)	2021/09/09		102	%	80 - 120
			Total Tungsten (W)	2021/09/09		107	%	80 - 120
			Total Uranium (U)	2021/09/09		104	%	80 - 120
			Total Vanadium (V)	2021/09/09		102	%	80 - 120
			Total Zinc (Zn)	2021/09/09		96	%	80 - 120
			Total Zirconium (Zr)	2021/09/09		107	%	80 - 120
A343719	AA1	Spiked Blank	Total Aluminum (Al)	2021/09/09		99	%	80 - 120
			Total Antimony (Sb)	2021/09/09		102	%	80 - 120
			Total Arsenic (As)	2021/09/09		102	%	80 - 120
			Total Barium (Ba)	2021/09/09		100	%	80 - 120
			Total Beryllium (Be)	2021/09/09		101	%	80 - 120
			Total Bismuth (Bi)	2021/09/09		100	%	80 - 120
			Total Boron (B)	2021/09/09		98	%	80 - 120
			Total Cadmium (Cd)	2021/09/09		100	%	80 - 120
			Total Chromium (Cr)	2021/09/09		98	%	80 - 120
			Total Cobalt (Co)	2021/09/09		95	%	80 - 120
			Total Copper (Cu)	2021/09/09		96	%	80 - 120
			Total Iron (Fe)	2021/09/09		102	%	80 - 120
			Total Lead (Pb)	2021/09/09		101	%	80 - 120
			Total Lithium (Li)	2021/09/09		97	%	80 - 120
			Total Manganese (Mn)	2021/09/09		97	%	80 - 120
			Total Molybdenum (Mo)	2021/09/09		103	%	80 - 120
			Total Nickel (Ni)	2021/09/09		97	%	80 - 120
			Total Selenium (Se)	2021/09/09		100	%	80 - 120
			Total Silicon (Si)	2021/09/09		105	%	80 - 120
			Total Silver (Ag)	2021/09/09		98	%	80 - 120
			Total Strontium (Sr)	2021/09/09		101	%	80 - 120
			Total Tellurium (Te)	2021/09/09		103	%	80 - 120
			Total Thallium (TI)	2021/09/09		100	%	80 - 120
			Total Thailidin (11)	2021/09/09				
			Lotal Thorium (Th)	/(1/1/19/19		99	%	80 - 120



QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
		•	Total Titanium (Ti)	2021/09/09		100	%	80 - 120
			Total Tungsten (W)	2021/09/09		102	%	80 - 120
			Total Uranium (U)	2021/09/09		103	%	80 - 120
			Total Vanadium (V)	2021/09/09		99	%	80 - 120
			Total Zinc (Zn)	2021/09/09		100	%	80 - 120
			Total Zirconium (Zr)	2021/09/09		103	%	80 - 120
A343719	AA1	Method Blank	Total Aluminum (AI)	2021/09/09	<3.0		ug/L	
			Total Antimony (Sb)	2021/09/09	<0.020		ug/L	
			Total Arsenic (As)	2021/09/09	<0.020		ug/L	
			Total Barium (Ba)	2021/09/09	<0.050		ug/L	
			Total Beryllium (Be)	2021/09/09	< 0.010		ug/L	
			Total Bismuth (Bi)	2021/09/09	< 0.010		ug/L	
			Total Boron (B)	2021/09/09	<10		ug/L	
			Total Cadmium (Cd)	2021/09/09	<0.0050		ug/L	
			Total Cadmum (Cu)	2021/09/09	<0.10		ug/L	
			Total Cobalt (Co)		<0.10		-	
			` '	2021/09/09			ug/L	
			Total Copper (Cu)	2021/09/09	<0.10		ug/L	
			Total Iron (Fe)	2021/09/09	<5.0		ug/L	
			Total Lead (Pb)	2021/09/09	<0.020		ug/L	
			Total Lithium (Li)	2021/09/09	<0.50		ug/L	
			Total Manganese (Mn)	2021/09/09	<0.10		ug/L	
			Total Molybdenum (Mo)	2021/09/09	<0.050		ug/L	
			Total Nickel (Ni)	2021/09/09	<0.10		ug/L	
			Total Selenium (Se)	2021/09/09	<0.040		ug/L	
			Total Silicon (Si)	2021/09/09	<50		ug/L	
			Total Silver (Ag)	2021/09/09	<0.010		ug/L	
			Total Strontium (Sr)	2021/09/09	<0.050		ug/L	
			Total Tellurium (Te)	2021/09/09	<0.020		ug/L	
			Total Thallium (Tl)	2021/09/09	<0.0020		ug/L	
			Total Thorium (Th)	2021/09/09	<0.020		ug/L	
			Total Tin (Sn)	2021/09/09	<0.20		ug/L	
			Total Titanium (Ti)	2021/09/09	<2.0		ug/L	
			Total Tungsten (W)	2021/09/09	< 0.010		ug/L	
			Total Uranium (U)	2021/09/09	< 0.0050		ug/L	
			Total Vanadium (V)	2021/09/09	<0.20		ug/L	
			Total Zinc (Zn)	2021/09/09	<1.0		ug/L	
			Total Zirconium (Zr)	2021/09/09	<0.10		ug/L	
A343719	AA1	RPD	Total Aluminum (Al)	2021/09/09	NC		%	20
			Total Antimony (Sb)	2021/09/09	NC		%	20
			Total Arsenic (As)	2021/09/09	0.52		%	20
			Total Barium (Ba)	2021/09/09	0.92		%	20
			Total Beryllium (Be)	2021/09/09	NC		%	20
			Total Bismuth (Bi)	2021/09/09	NC		% %	20
							% %	
			Total Boron (B)	2021/09/09	0.18			20
			Total Characters (Cd)	2021/09/09	NC		%	20
			Total Chromium (Cr)	2021/09/09	NC		%	20
			Total Cobalt (Co)	2021/09/09	5.7		%	20
			Total Copper (Cu)	2021/09/09	4.5		%	20
			Total Iron (Fe)	2021/09/09	1.3		%	20
			Total Lead (Pb)	2021/09/09	5.7		%	20
			Total Lithium (Li)	2021/09/09	1.9		%	20
			Total Manganese (Mn)	2021/09/09	3.2		%	20
			Total Molybdenum (Mo)	2021/09/09	0.67		%	20
			Total Nickel (Ni)	2021/09/09	4.7		%	20
			Total Selenium (Se)	2021/09/09	9.1		%	20



Government of Yukon – Dept of ENV Client Project #: 2021-Ketza

QA/QC Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
		. //	Total Silicon (Si)	2021/09/09	2.4	•	%	20
			Total Silver (Ag)	2021/09/09	NC		%	20
			Total Strontium (Sr)	2021/09/09	1.7		%	20
			Total Thallium (TI)	2021/09/09	NC		%	20
			Total Tin (Sn)	2021/09/09	NC		%	20
			Total Titanium (Ti)	2021/09/09	NC		%	20
			Total Uranium (U)	2021/09/09	2.3		%	20
			Total Vanadium (V)	2021/09/09	NC		%	20
			Total Zinc (Zn)	2021/09/09	1.0		%	20
			Total Zirconium (Zr)	2021/09/09	14		%	20
A343723	KWE	Matrix Spike	Dissolved Hex. Chromium (Cr 6+)	2021/09/09		93	%	80 - 120
A343723	KWE	Spiked Blank	Dissolved Hex. Chromium (Cr 6+)	2021/09/09		105	%	80 - 120
A343723	KWE	Method Blank	Dissolved Hex. Chromium (Cr 6+)	2021/09/09	<0.00099	103	mg/L	00 120
A343723	KWE	RPD	Dissolved Hex. Chromium (Cr 6+)	2021/09/09	NC		// // // // // // // // // // // // //	20
A343841	TSO	Matrix Spike	Total Nitrogen (N)	2021/09/09	IVC	101	%	80 - 120
A343841		•		2021/09/09			% %	80 - 120 80 - 120
	TSO	Spiked Blank	Total Nitrogen (N)	2021/09/09	40 O2O	100		80 - 120
A343841	TSO	Method Blank	Total Nitrogen (N)		<0.020		mg/L	20
A343841	TSO	RPD	Total Suggest ded Salida	2021/09/09	0.54	402	%	20
A344546	BTM	Matrix Spike	Total Suspended Solids	2021/09/09		103	%	80 - 120
A344546	BTM	Spiked Blank	Total Suspended Solids	2021/09/09		102	%	80 - 120
A344546	BTM	Method Blank	Total Suspended Solids	2021/09/09	<1.0		mg/L	
A344546	BTM	RPD	Total Suspended Solids	2021/09/09	NC		%	20
A344551	BTM	Matrix Spike	Total Suspended Solids	2021/09/09		103	%	80 - 120
A344551	BTM	Spiked Blank	Total Suspended Solids	2021/09/09		101	%	80 - 120
A344551	BTM	Method Blank	Total Suspended Solids	2021/09/09	<1.0		mg/L	
A344551	BTM	RPD	Total Suspended Solids	2021/09/09	NC		%	20
A344664	BTM	Matrix Spike	Total Suspended Solids	2021/09/09		102	%	80 - 120
A344664	BTM	Spiked Blank	Total Suspended Solids	2021/09/09		102	%	80 - 120
A344664	BTM	Method Blank	Total Suspended Solids	2021/09/09	<1.0		mg/L	
A344664	BTM	RPD	Total Suspended Solids	2021/09/09	NC		%	20
A344685	BTM	Matrix Spike [AFF268-01]	Total Suspended Solids	2021/09/09		104	%	80 - 120
A344685	BTM	Spiked Blank	Total Suspended Solids	2021/09/09		102	%	80 - 120
A344685	BTM	Method Blank	Total Suspended Solids	2021/09/09	<1.0		mg/L	
A344685	BTM	RPD	Total Suspended Solids	2021/09/09	NC		%	20
A345060	TSO	Matrix Spike	Total Nitrogen (N)	2021/09/09		103	%	80 - 120
A345060	TSO	Spiked Blank	Total Nitrogen (N)	2021/09/09		108	%	80 - 120
A345060	TSO	Method Blank	Total Nitrogen (N)	2021/09/09	<0.020		mg/L	
A345060	TSO	RPD	Total Nitrogen (N)	2021/09/09	1.2		%	20
A345116	AP1	Spiked Blank	Total Dissolved Solids	2021/09/08		104	%	80 - 120
A345116	AP1	Method Blank	Total Dissolved Solids	2021/09/08	<1.0		mg/L	
A345379	BB3	Spiked Blank	pH	2021/09/07		101	%	97 - 103
A345379	BB3	RPD	pH	2021/09/07	0.13		%	N/A
A345379	BB3	RPD [AFF264-02]	pH	2021/09/07	0.73		%	N/A
A345383	BB3	Matrix Spike [AFF264-02]	Alkalinity (Total as CaCO3)	2021/09/07		NC	%	80 - 120
A345383	BB3	Spiked Blank	Alkalinity (Total as CaCO3)	2021/09/07		96	%	80 - 120
A345383	BB3	Method Blank	Alkalinity (PP as CaCO3)	2021/09/07	<1.0		mg/L	
	-		Alkalinity (Total as CaCO3)	2021/09/07	<1.0		mg/L	
			Bicarbonate (HCO3)	2021/09/07	<1.0		mg/L	
			Carbonate (CO3)	2021/09/07	<1.0		mg/L	
			Hydroxide (OH)	2021/09/07	<1.0		mg/L	
A345383	BB3	RPD [AFF264-02]	Alkalinity (PP as CaCO3)	2021/09/07	NC		// // // // // // // // // // // // //	20
, 13-3303	כטט	111 2 [A11 207-02]	Alkalinity (Fr as CaCO3) Alkalinity (Total as CaCO3)	2021/09/07	0.0052		%	20
			Bicarbonate (HCO3)	2021/09/07	0.0052		% %	20
			Carbonate (CO3)	2021/09/07	0.0052 NC		% %	20
			Carbonate (COS)	2021/09/07	INC		70	20



Government of Yukon – Dept of ENV Client Project #: 2021-Ketza

QA/QC	I-a.!+	OC Tuno	Darameter	Data Analisasal	Value	D	LINUTC	OC Livelite
Batch A345385	Init BB3	QC Type Spiked Blank	Parameter Conductivity	Date Analyzed 2021/09/07	Value	Recovery 100	UNITS %	QC Limits 80 - 120
		•	•		-2.0	100		80 - 120
A345385	BB3 BB3	Method Blank RPD	Conductivity	2021/09/07 2021/09/07	<2.0 0.097		uS/cm %	10
A345385			Conductivity					10
A345385	BB3	RPD [AFF264-02]	Conductivity	2021/09/07	0.16	101	%	10
A345387	BB3	Spiked Blank	pH	2021/09/07	0.12	101	%	97 - 103
A345387	BB3	RPD	pH	2021/09/08	0.13		%	N/A
4245200	222		pH	2021/09/08	0	NG	%	N/A
A345389	BB3	Matrix Spike	Alkalinity (Total as CaCO3)	2021/09/08		NC	%	80 - 120
A345389	BB3	Spiked Blank	Alkalinity (Total as CaCO3)	2021/09/07		84	%	80 - 120
A345389	BB3	Method Blank	Alkalinity (PP as CaCO3)	2021/09/07	<1.0		mg/L	
			Alkalinity (Total as CaCO3)	2021/09/07	<1.0		mg/L	
			Bicarbonate (HCO3)	2021/09/07	<1.0		mg/L	
			Carbonate (CO3)	2021/09/07	<1.0		mg/L	
			Hydroxide (OH)	2021/09/07	<1.0		mg/L	
A345389	BB3	RPD	Alkalinity (PP as CaCO3)	2021/09/08	NC		%	20
			Alkalinity (Total as CaCO3)	2021/09/08	1.2		%	20
			Bicarbonate (HCO3)	2021/09/08	1.2		%	20
			Carbonate (CO3)	2021/09/08	NC		%	20
			Hydroxide (OH)	2021/09/08	NC		%	20
A345394	BB3	Spiked Blank	Conductivity	2021/09/07		98	%	80 - 120
A345394	BB3	Method Blank	Conductivity	2021/09/07	<2.0		uS/cm	
A345396	BB3	Spiked Blank	рН	2021/09/07		98	%	97 - 103
A345397	BB3	Matrix Spike [AFF272-02]	Alkalinity (Total as CaCO3)	2021/09/08		NC	%	80 - 120
A345397	BB3	Spiked Blank	Alkalinity (Total as CaCO3)	2021/09/08		92	%	80 - 120
A345397	BB3	Method Blank	Alkalinity (PP as CaCO3)	2021/09/08	<1.0		mg/L	
			Alkalinity (Total as CaCO3)	2021/09/08	<1.0		mg/L	
			Bicarbonate (HCO3)	2021/09/08	<1.0		mg/L	
			Carbonate (CO3)	2021/09/08	<1.0		mg/L	
			Hydroxide (OH)	2021/09/08	<1.0		mg/L	
A345409	BB3	Spiked Blank	Conductivity	2021/09/08		99	%	80 - 120
A345409	BB3	Method Blank	Conductivity	2021/09/08	<2.0		uS/cm	
A345891	KWE	Matrix Spike [AFF272-11]	Dissolved Hex. Chromium (Cr 6+)	2021/09/09		94	%	80 - 120
A345891	KWE	Spiked Blank	Dissolved Hex. Chromium (Cr 6+)	2021/09/09		107	%	80 - 120
A345891	KWE	Method Blank	Dissolved Hex. Chromium (Cr 6+)	2021/09/09	<0.00099		mg/L	
A345891	KWE	RPD [AFF272-11]	Dissolved Hex. Chromium (Cr 6+)	2021/09/09	NC		%	20
A346053	втм	Matrix Spike	Total Suspended Solids	2021/09/10		105	%	80 - 120
A346053	втм	Spiked Blank	Total Suspended Solids	2021/09/10		101	%	80 - 120
A346053	втм	Method Blank	Total Suspended Solids	2021/09/10	<1.0		mg/L	
A346053	втм	RPD	Total Suspended Solids	2021/09/10	18		%	20
A346095	AA1	Matrix Spike [AFF271-05]	Dissolved Aluminum (AI)	2021/09/11		100	%	80 - 120
			Dissolved Antimony (Sb)	2021/09/11		102	%	80 - 120
			Dissolved Arsenic (As)	2021/09/11		101	%	80 - 120
			Dissolved Barium (Ba)	2021/09/11		97	%	80 - 120
			Dissolved Beryllium (Be)	2021/09/11		98	%	80 - 120
			Dissolved Bismuth (Bi)	2021/09/11		98	%	80 - 120
			Dissolved Bismath (B)	2021/09/11		99	%	80 - 120
			Dissolved Cadmium (Cd)	2021/09/11		101	%	80 - 120
			Dissolved Chromium (Cr)	2021/09/11		98	%	80 - 120
			Dissolved Cobalt (Co)	2021/09/11		93	%	80 - 120
			Dissolved Copper (Cu)	2021/09/11		92	%	80 - 120
			Dissolved Copper (Cu) Dissolved Iron (Fe)	2021/09/11		103	% %	80 - 120
			Dissolved Iron (Fe) Dissolved Lead (Pb)	2021/09/11		98	% %	80 - 120
			Dissolved Lead (PD) Dissolved Lithium (Li)	2021/09/11		98 95	% %	80 - 120 80 - 120
			` '					
			Dissolved Malyhdanum (Ma)	2021/09/11		NC 106	% %	80 - 120 80 - 120
<u> </u>			Dissolved Molybdenum (Mo)	2021/09/11		106	%	80 - 120



QA/QC Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limit
			Dissolved Nickel (Ni)	2021/09/11		92	%	80 - 120
			Dissolved Selenium (Se)	2021/09/11		104	%	80 - 120
			Dissolved Silicon (Si)	2021/09/11		106	%	80 - 120
			Dissolved Silver (Ag)	2021/09/11		96	%	80 - 120
			Dissolved Strontium (Sr)	2021/09/11		NC	%	80 - 120
			Dissolved Tellurium (Te)	2021/09/11		100	%	80 - 120
			Dissolved Thallium (TI)	2021/09/11		101	%	80 - 120
			Dissolved Thorium (Th)	2021/09/11		105	%	80 - 120
			Dissolved Tin (Sn)	2021/09/11		102	%	80 - 120
			Dissolved Titanium (Ti)	2021/09/11		103	%	80 - 120
			Dissolved Tungsten (W)	2021/09/11		101	%	80 - 120
			Dissolved Uranium (U)	2021/09/11		107	%	80 - 120
			Dissolved Vanadium (V)	2021/09/11		102	%	80 - 120
			Dissolved Zinc (Zn)	2021/09/11		99	%	80 - 120
			Dissolved Zirconium (Zr)	2021/09/11		108	%	80 - 120
A346095	AA1	Spiked Blank	Dissolved Aluminum (Al)	2021/09/11		103	%	80 - 120
A340033	771	Spiked blank	Dissolved Antimony (Sb)	2021/09/11		103	%	80 - 120
			Dissolved Antimony (3b) Dissolved Arsenic (As)	2021/09/11		100	%	80 - 120
			Dissolved Arsenic (As) Dissolved Barium (Ba)	2021/09/11				
			,	• •		101	%	80 - 120
			Dissolved Beryllium (Be)	2021/09/11		100	%	80 - 120
			Dissolved Bismuth (Bi)	2021/09/11		102	%	80 - 120
			Dissolved Boron (B)	2021/09/11		99	%	80 - 120
			Dissolved Cadmium (Cd)	2021/09/11		102	%	80 - 120
			Dissolved Chromium (Cr)	2021/09/11		101	%	80 - 120
			Dissolved Cobalt (Co)	2021/09/11		99	%	80 - 120
			Dissolved Copper (Cu)	2021/09/11		99	%	80 - 120
			Dissolved Iron (Fe)	2021/09/11		104	%	80 - 120
			Dissolved Lead (Pb)	2021/09/11		101	%	80 - 120
			Dissolved Lithium (Li)	2021/09/11		97	%	80 - 120
			Dissolved Manganese (Mn)	2021/09/11		101	%	80 - 120
			Dissolved Molybdenum (Mo)	2021/09/11		104	%	80 - 120
			Dissolved Nickel (Ni)	2021/09/11		101	%	80 - 120
			Dissolved Selenium (Se)	2021/09/11		102	%	80 - 120
			Dissolved Silicon (Si)	2021/09/11		107	%	80 - 120
			Dissolved Silver (Ag)	2021/09/11		99	%	80 - 120
			Dissolved Strontium (Sr)	2021/09/11		102	%	80 - 120
			Dissolved Tellurium (Te)	2021/09/11		103	%	80 - 120
			Dissolved Thallium (TI)	2021/09/11		100	%	80 - 120
			Dissolved Thorium (Th)	2021/09/11		102	%	80 - 120
			Dissolved Tin (Sn)	2021/09/11		103	%	80 - 120
			Dissolved Titanium (Ti)	2021/09/11		105	%	80 - 120
			Dissolved Tungsten (W)	2021/09/11		102	%	80 - 120
			Dissolved Uranium (U)	2021/09/11		106	%	80 - 120
			Dissolved Vanadium (V)	2021/09/11		102	%	80 - 120
			Dissolved Zinc (Zn)	2021/09/11		104	%	80 - 120
			Dissolved Zirconium (Zr)	2021/09/11		103	%	80 - 120
A346095	AA1	Method Blank	Dissolved Aluminum (AI)	2021/09/11	<0.50		ug/L	
			Dissolved Antimony (Sb)	2021/09/11	<0.020		ug/L	
			Dissolved Arsenic (As)	2021/09/11	<0.020		ug/L	
			Dissolved Barium (Ba)	2021/09/11	<0.020		ug/L	
			Dissolved Baridin (Ba) Dissolved Beryllium (Be)	2021/09/11	<0.020		ug/L ug/L	
			Dissolved Beryllulli (Be) Dissolved Bismuth (Bi)	2021/09/11				
			Dissolved Bismuth (BI) Dissolved Boron (B)		<0.0050 <10		ug/L	
			` '	2021/09/11			ug/L	
			Dissolved Cadmium (Cd)	2021/09/11	<0.0050		ug/L	



QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
		• • • • • • • • • • • • • • • • • • • •	Dissolved Cobalt (Co)	2021/09/11	<0.0050	•	ug/L	
			Dissolved Copper (Cu)	2021/09/11	<0.050		ug/L	
			Dissolved Iron (Fe)	2021/09/11	<1.0		ug/L	
			Dissolved Lead (Pb)	2021/09/11	<0.0050		ug/L	
			Dissolved Lithium (Li)	2021/09/11	<0.50		ug/L	
			Dissolved Manganese (Mn)	2021/09/11	<0.050		ug/L	
			Dissolved Molybdenum (Mo)	2021/09/11	<0.050		ug/L	
			Dissolved Nickel (Ni)	2021/09/11	<0.020		ug/L	
			Dissolved Selenium (Se)	2021/09/11	<0.040		ug/L	
			Dissolved Silicon (Si)	2021/09/11	<50		ug/L	
			Dissolved Silver (Ag)	2021/09/11	<0.0050		ug/L	
			Dissolved Strontium (Sr)	2021/09/11	0.056,		ug/L	
			, ,		RDL=0.050 (1)		O,	
			Dissolved Tellurium (Te)	2021/09/11	<0.020		ug/L	
			Dissolved Thallium (TI)	2021/09/11	<0.0020		ug/L	
			Dissolved Thorium (Th)	2021/09/11	<0.0050		ug/L	
			Dissolved Tin (Sn)	2021/09/11	<0.20		ug/L	
			Dissolved Titanium (Ti)	2021/09/11	<0.50		ug/L	
			Dissolved Tungsten (W)	2021/09/11	<0.010		ug/L	
			Dissolved Uranium (U)	2021/09/11	<0.0020		ug/L	
			Dissolved Vanadium (V)	2021/09/11	<0.20		ug/L	
			Dissolved Zinc (Zn)	2021/09/11	<0.10		ug/L	
			Dissolved Zirconium (Zr)	2021/09/11	<0.10		ug/L	
A346095	AA1	RPD [AFF271-05]	Dissolved Aluminum (Al)	2021/09/11	2.0		%	20
		[]	Dissolved Antimony (Sb)	2021/09/11	1.9		%	20
			Dissolved Arsenic (As)	2021/09/11	1.9		%	20
			Dissolved Barium (Ba)	2021/09/11	1.0		%	20
			Dissolved Beryllium (Be)	2021/09/11	NC		%	20
			Dissolved Bismuth (Bi)	2021/09/11	NC		%	20
			Dissolved Boron (B)	2021/09/11	NC		%	20
			Dissolved Cadmium (Cd)	2021/09/11	0.29		%	20
			Dissolved Chromium (Cr)	2021/09/11	NC		%	20
			Dissolved Cobalt (Co)	2021/09/11	2.2		%	20
			Dissolved Copper (Cu)	2021/09/11	2.1		%	20
			Dissolved Iron (Fe)	2021/09/11	NC		%	20
			Dissolved Lead (Pb)	2021/09/11	1.9		%	20
			Dissolved Lithium (Li)	2021/09/11	2.9		%	20
			Dissolved Manganese (Mn)	2021/09/11	0.040		%	20
			Dissolved Molybdenum (Mo)	2021/09/11	9.3		%	20
			Dissolved Nickel (Ni)	2021/09/11	2.0		%	20
			Dissolved Selenium (Se)	2021/09/11	1.6		%	20
			Dissolved Silicon (Si)	2021/09/11	1.6		%	
			Dissolved Silver (Ag)	2021/09/11	NC		% %	20 20
			Dissolved Strontium (Sr)	2021/09/11	2.2		%	20
			Dissolved Tellurium (Te)	2021/09/11	NC		%	20
			, ,	2021/09/11				
			Dissolved Thallium (Tl)	2021/09/11	NC NC		%	20
			Dissolved Thorium (Th)		NC NC		% %	20 20
			Dissolved Titanium (Ti)	2021/09/11	NC NC		%	20
			Dissolved Titanium (Ti)	2021/09/11	NC NC		%	20
			Dissolved Tungsten (W)	2021/09/11	NC		%	20
			Dissolved Uranium (U)	2021/09/11	1.3		%	20
			Dissolved Vanadium (V)	2021/09/11	NC		%	20
			Dissolved Zinc (Zn)	2021/09/11	2.1		%	20
			Dissolved Zirconium (Zr)	2021/09/11	NC	40.	%	20
A346114	TMU	Matrix Spike [AFF272-10]	Strong Acid Dissoc. Cyanide (CN)	2021/09/10		104	%	80 - 120



Government of Yukon – Dept of ENV Client Project #: 2021-Ketza

04/00			· · · · · · · · · · · · · · · · · · ·					
QA/QC Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
A346114	TMU	Spiked Blank	Strong Acid Dissoc. Cyanide (CN)	2021/09/10		101	%	80 - 120
A346114	TMU	Method Blank	Strong Acid Dissoc. Cyanide (CN)	2021/09/10	<0.00050		mg/L	
A346114	TMU	RPD [AFF272-10]	Strong Acid Dissoc. Cyanide (CN)	2021/09/10	NC		%	20
A346121	TMU	Matrix Spike [AFF272-10]	Weak Acid Dissoc. Cyanide (CN)	2021/09/10		102	%	80 - 120
A346121	TMU	Spiked Blank	Weak Acid Dissoc. Cyanide (CN)	2021/09/10		104	%	80 - 120
A346121	TMU	Method Blank	Weak Acid Dissoc. Cyanide (CN)	2021/09/10	<0.00050		mg/L	
A346121	TMU	RPD [AFF272-10]	Weak Acid Dissoc. Cyanide (CN)	2021/09/10	NC		%	20
A346241	KGA	Matrix Spike	Total Dissolved Solids	2021/09/13		109	%	80 - 120
A346241	KGA	Spiked Blank	Total Dissolved Solids	2021/09/09		100	%	80 - 120
A346241	KGA	Method Blank	Total Dissolved Solids	2021/09/09	<1.0		mg/L	
A346241	KGA	RPD	Total Dissolved Solids	2021/09/13	2.0		%	20
A346416	AA1	Matrix Spike [AFF263-05]	Dissolved Aluminum (AI)	2021/09/11	0	101	%	80 - 120
7.5 .5 .12			Dissolved Antimony (Sb)	2021/09/11		NC	%	80 - 120
			Dissolved Arsenic (As)	2021/09/11		102	%	80 - 120
			Dissolved Barium (Ba)	2021/09/11		100	%	80 - 120
			Dissolved Beryllium (Be)	2021/09/11		98	%	80 - 120
			Dissolved Bismuth (Bi)	2021/09/11		97	%	80 - 120
			Dissolved Bismuth (B)	2021/09/11		98	%	80 - 120
			Dissolved Cadmium (Cd)	2021/09/11		100	%	80 - 120
			Dissolved Chromium (Cr)	2021/09/11		97	%	80 - 120
			Dissolved Cobalt (Co)	2021/09/11		92	%	80 - 120
			• •	2021/09/11		92 91	%	80 - 120 80 - 120
			Dissolved Copper (Cu)					
			Dissolved Iron (Fe)	2021/09/11		102	%	80 - 120
			Dissolved Lead (Pb)	2021/09/11		98	%	80 - 120
			Dissolved Lithium (Li)	2021/09/11		93	%	80 - 120
			Dissolved Manganese (Mn)	2021/09/11		96	%	80 - 120
			Dissolved Molybdenum (Mo)	2021/09/11		108	%	80 - 120
			Dissolved Nickel (Ni)	2021/09/11		92	%	80 - 120
			Dissolved Selenium (Se)	2021/09/11		103	%	80 - 120
			Dissolved Silicon (Si)	2021/09/11		95	%	80 - 120
			Dissolved Silver (Ag)	2021/09/11		97	%	80 - 120
			Dissolved Strontium (Sr)	2021/09/11		NC	%	80 - 120
			Dissolved Tellurium (Te)	2021/09/11		99	%	80 - 120
			Dissolved Thallium (TI)	2021/09/11		101	%	80 - 120
			Dissolved Thorium (Th)	2021/09/11		105	%	80 - 120
			Dissolved Tin (Sn)	2021/09/11		104	%	80 - 120
			Dissolved Titanium (Ti)	2021/09/11		102	%	80 - 120
			Dissolved Tungsten (W)	2021/09/11		108	%	80 - 120
			Dissolved Uranium (U)	2021/09/11		109	%	80 - 120
			Dissolved Vanadium (V)	2021/09/11		101	%	80 - 120
			Dissolved Zinc (Zn)	2021/09/11		96	%	80 - 120
			Dissolved Zirconium (Zr)	2021/09/11		107	%	80 - 120
A346416	AA1	Spiked Blank	Dissolved Aluminum (Al)	2021/09/11		104	%	80 - 120
			Dissolved Antimony (Sb)	2021/09/11		102	%	80 - 120
			Dissolved Arsenic (As)	2021/09/11		99	%	80 - 120
			Dissolved Barium (Ba)	2021/09/11		100	%	80 - 120
			Dissolved Beryllium (Be)	2021/09/11		101	%	80 - 120
			Dissolved Bismuth (Bi)	2021/09/11		102	%	80 - 120
			Dissolved Boron (B)	2021/09/11		100	%	80 - 120
			Dissolved Cadmium (Cd)	2021/09/11		100	%	80 - 120
			Dissolved Chromium (Cr)	2021/09/11		102	%	80 - 120
			Dissolved Cobalt (Co)	2021/09/11		100	%	80 - 120
			Dissolved Copper (Cu)	2021/09/11		101	%	80 - 120
			Dissolved Iron (Fe) Dissolved Lead (Pb)	2021/09/11 2021/09/11		105 99	% %	80 - 120 80 - 120
			Pissolved read (Ln)	2021/09/11		<u> </u>	/0	00 - 120



QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
		. 71	Dissolved Lithium (Li)	2021/09/11		98	%	80 - 120
			Dissolved Manganese (Mn)	2021/09/11		103	%	80 - 120
			Dissolved Molybdenum (Mo)	2021/09/11		103	%	80 - 120
			Dissolved Nickel (Ni)	2021/09/11		101	%	80 - 120
			Dissolved Selenium (Se)	2021/09/11		101	%	80 - 120
			Dissolved Silicon (Si)	2021/09/11		111	%	80 - 120
			Dissolved Silver (Ag)	2021/09/11		98	%	80 - 120
			Dissolved Strontium (Sr)	2021/09/11		102	%	80 - 120
			Dissolved Tellurium (Te)	2021/09/11		102	%	80 - 120
			Dissolved Thallium (TI)	2021/09/11		100	%	80 - 120
			Dissolved Thorium (Th)	2021/09/11		102	%	80 - 120
			Dissolved Tin (Sn)	2021/09/11		104	%	80 - 120
			Dissolved Titanium (Ti)	2021/09/11		107	%	80 - 120
			Dissolved Tungsten (W)	2021/09/11		100	%	80 - 120
			Dissolved Uranium (U)	2021/09/11		106	%	80 - 120
			Dissolved Vanadium (V)	2021/09/11		103	%	80 - 120
			Dissolved Zinc (Zn)	2021/09/11		105	%	80 - 120
			Dissolved Zirconium (Zr)	2021/09/11		105	%	80 - 120
A346416	AA1	Method Blank	Dissolved Aluminum (Al)	2021/09/11	<0.50		ug/L	
			Dissolved Antimony (Sb)	2021/09/11	<0.020		ug/L	
			Dissolved Arsenic (As)	2021/09/11	<0.020		ug/L	
			Dissolved Barium (Ba)	2021/09/11	<0.020		ug/L	
			Dissolved Beryllium (Be)	2021/09/11	<0.010		ug/L	
			Dissolved Bismuth (Bi)	2021/09/11	<0.0050		ug/L	
			Dissolved Boron (B)	2021/09/11	<10		ug/L	
			Dissolved Cadmium (Cd)	2021/09/11	<0.0050		ug/L	
			Dissolved Chromium (Cr)	2021/09/11	<0.10		ug/L	
			Dissolved Cobalt (Co)	2021/09/11	<0.0050		ug/L	
			Dissolved Copper (Cu)	2021/09/11	< 0.050		ug/L	
			Dissolved Iron (Fe)	2021/09/11	<1.0		ug/L	
			Dissolved Lead (Pb)	2021/09/11	<0.0050		ug/L	
			Dissolved Lithium (Li)	2021/09/11	<0.50		ug/L	
			Dissolved Manganese (Mn)	2021/09/11	<0.050		ug/L	
			Dissolved Molybdenum (Mo)	2021/09/11	<0.050		ug/L	
			Dissolved Nickel (Ni)	2021/09/11	<0.020		ug/L	
			Dissolved Selenium (Se)	2021/09/11	<0.040		ug/L	
			Dissolved Silicon (Si)	2021/09/11	<50		ug/L	
			Dissolved Silver (Ag)	2021/09/11	<0.0050		ug/L	
			Dissolved Strontium (Sr)	2021/09/11	<0.050		ug/L	
			Dissolved Tellurium (Te)	2021/09/11	<0.020		ug/L	
			Dissolved Thallium (TI)	2021/09/11	<0.0020		ug/L	
			Dissolved Thorium (Th)	2021/09/11	<0.0050		ug/L	
			Dissolved Tin (Sn)	2021/09/11	<0.20		ug/L	
			Dissolved Titanium (Ti)	2021/09/11	<0.50		ug/L	
			Dissolved Tungsten (W)	2021/09/11	< 0.010		ug/L	
			Dissolved Translum (U)	2021/09/11	0.0021,		ug/L	
				2021/03/11	RDL=0.0020 (2)		ug/ L	
			Dissolved Vanadium (V)	2021/09/11	<0.20		ug/L	
			Dissolved Zinc (Zn)	2021/09/11	0.14, RDL=0.10 (3)		ug/L	
			Dissolved Zirconium (Zr)	2021/09/11	<0.10		ug/L	
A346416	AA1	RPD [AFF263-05]	Dissolved Aluminum (Al)	2021/09/11	6.3		%	20
		-	Dissolved Antimony (Sb)	2021/09/11	0.41		%	20
			Dissolved Arsenic (As)	2021/09/11	0.027		%	20
			Dissolved Barium (Ba)	2021/09/11	0.81		%	20



QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
			Dissolved Beryllium (Be)	2021/09/11	NC		%	20
			Dissolved Bismuth (Bi)	2021/09/11	NC		%	20
			Dissolved Boron (B)	2021/09/11	0.29		%	20
			Dissolved Cadmium (Cd)	2021/09/11	6.5		%	20
			Dissolved Chromium (Cr)	2021/09/11	NC		%	20
			Dissolved Cobalt (Co)	2021/09/11	4.7		%	20
			Dissolved Copper (Cu)	2021/09/11	1.8		%	20
			Dissolved Iron (Fe)	2021/09/11	4.5		%	20
			Dissolved Lead (Pb)	2021/09/11	5.0		%	20
			Dissolved Lithium (Li)	2021/09/11	0.43		%	20
			Dissolved Manganese (Mn)	2021/09/11	2.5		%	20
			Dissolved Molybdenum (Mo)	2021/09/11	5.4		%	20
			Dissolved Nickel (Ni)	2021/09/11	4.3		%	20
			Dissolved Selenium (Se)	2021/09/11	13		%	20
			Dissolved Silicon (Si)	2021/09/11	0.13		%	20
			Dissolved Silver (Ag)	2021/09/11	NC		%	20
			Dissolved Strontium (Sr)	2021/09/11	1.7		%	20
			Dissolved Tellurium (Te)	2021/09/11	NC		%	20
			Dissolved Thallium (TI)	2021/09/11	1.2		%	20
			Dissolved Thailidin (Tr) Dissolved Thorium (Th)	2021/09/11	NC		%	20
			` ,	2021/09/11	NC			
			Dissolved Tin (Sn) Dissolved Titanium (Ti)	· ·			% %	20
			Dissolved Titalium (T) Dissolved Tungsten (W)	2021/09/11 2021/09/11	NC 1.2			20
			Dissolved Tungsten (w) Dissolved Uranium (U)	2021/09/11	1.2		%	20
			, ,	• •	0.15 NG		%	20
			Dissolved Vanadium (V)	2021/09/11	NC 1.F		%	20
			Dissolved Zinc (Zn)	2021/09/11	1.5		%	20
4247200	EN 40	Ma-tuin Cuite [AFF27F 00]	Dissolved Zirconium (Zr)	2021/09/11	NC	407	%	20
A347209	FM0	Matrix Spike [AFF275-08]	Dissolved Phosphorus (P)	2021/09/11		107	%	80 - 120
A347209	FM0	QC Standard	Dissolved Phosphorus (P)	2021/09/11		90	%	80 - 120
A347209	FM0	Spiked Blank	Dissolved Phosphorus (P)	2021/09/11	0.0040	113	%	80 - 120
A347209	FM0	Method Blank	Dissolved Phosphorus (P)	2021/09/11	<0.0010		mg/L	
A347209	FM0	RPD [AFF275-08]	Dissolved Phosphorus (P)	2021/09/11	NC		%	20
A347213	FM0	Matrix Spike [AFF267-07]	Total Phosphorus (P)	2021/09/11		100	%	80 - 120
A347213	FM0	QC Standard	Total Phosphorus (P)	2021/09/11		90	%	80 - 120
A347213	FM0	Spiked Blank	Total Phosphorus (P)	2021/09/11		115	%	80 - 120
A347213	FM0	Method Blank	Total Phosphorus (P)	2021/09/11	<0.0010		mg/L	
A347213	FM0	RPD [AFF267-07]	Total Phosphorus (P)	2021/09/11	NC		%	20
A347313	CJY	Matrix Spike	Total Mercury (Hg)	2021/09/10		87	%	80 - 120
A347313	CJY	Spiked Blank	Total Mercury (Hg)	2021/09/10		96	%	80 - 120
A347313	CJY	Method Blank	Total Mercury (Hg)	2021/09/10	<0.0019		ug/L	
A347313	CJY	RPD	Total Mercury (Hg)	2021/09/10	3.2		%	20
A347315	ZWU	Matrix Spike [AFF268-08]	Dissolved Organic Carbon (C)	2021/09/10		111	%	80 - 120
A347315	ZWU	Spiked Blank	Dissolved Organic Carbon (C)	2021/09/10		111	%	80 - 120
A347315	ZWU	Method Blank	Dissolved Organic Carbon (C)	2021/09/10	<0.20		mg/L	
A347315	ZWU	RPD [AFF268-08]	Dissolved Organic Carbon (C)	2021/09/10	NC		%	20
A347443	STI	Matrix Spike	Dissolved Phosphorus (P)	2021/09/12		76 (4)	%	80 - 120
A347443	STI	QC Standard	Dissolved Phosphorus (P)	2021/09/12		87	%	80 - 120
A347443	STI	Spiked Blank	Dissolved Phosphorus (P)	2021/09/12		111	%	80 - 120
A347443	STI	Method Blank	Dissolved Phosphorus (P)	2021/09/12	< 0.0010		mg/L	
A347443	STI	RPD	Dissolved Phosphorus (P)	2021/09/12	1.5		%	20
A347450	STI	Matrix Spike	Total Phosphorus (P)	2021/09/12		92	%	80 - 120
A347450	STI	QC Standard	Total Phosphorus (P)	2021/09/12		90	%	80 - 120
A347450	STI	Spiked Blank	Total Phosphorus (P)	2021/09/12		98	%	80 - 120
A347450	STI	Method Blank	Total Phosphorus (P)	2021/09/12	<0.0010		mg/L	
A347450	STI	RPD	Total Phosphorus (P)	2021/09/12	NC		%	20



Government of Yukon – Dept of ENV Client Project #: 2021-Ketza

QA/QC	lus in	OC Turns	Davamakan	Data Analysed	Value	Dagayamı	LINUTC	OC Limita
Batch A347455	Init STI	QC Type Matrix Spike	Parameter Total Phosphorus (P)	Date Analyzed 2021/09/12	Value	Recovery 69 (4)	UNITS %	QC Limits 80 - 120
A347455 A347455		•		2021/09/12		69 (4) 87	%	
	STI	QC Standard Spiked Blank	Total Phosphorus (P) Total Phosphorus (P)	2021/09/12		87 97		80 - 120 80 - 120
A347455	STI	•	Total Phosphorus (P)		<0.0010	97	% ma/l	80 - 120
A347455	STI	Method Blank	1	2021/09/12	<0.0010		mg/L	20
A347455	STI	RPD	Total Phosphorus (P)	2021/09/12	NC	00	%	20
A347548	CJY	Matrix Spike	Dissolved Mercury (Hg)	2021/09/10		98	%	80 - 120
A347548	CJY	Spiked Blank	Dissolved Mercury (Hg)	2021/09/10	.0.0040	98	%	80 - 120
A347548	CJY	Method Blank	Dissolved Mercury (Hg)	2021/09/10	<0.0019		ug/L	20
A347548	CJY	RPD	Dissolved Mercury (Hg)	2021/09/10	NC	0.2	%	20
A347639	AA1	Matrix Spike [AFF276-04]	Total Aluminum (Al)	2021/09/11		93	%	80 - 120
			Total Antimony (Sb)	2021/09/11		98	%	80 - 120
			Total Arsenic (As)	2021/09/11		95	%	80 - 120
			Total Barium (Ba)	2021/09/11		97	%	80 - 120
			Total Beryllium (Be)	2021/09/11		91	%	80 - 120
			Total Bismuth (Bi)	2021/09/11		96	%	80 - 120
			Total Boron (B)	2021/09/11		89	%	80 - 120
			Total Cadmium (Cd)	2021/09/11		96	%	80 - 120
			Total Chromium (Cr)	2021/09/11		91	%	80 - 120
			Total Cobalt (Co)	2021/09/11		88	%	80 - 120
			Total Copper (Cu)	2021/09/11		87	%	80 - 120
			Total Iron (Fe)	2021/09/11		98	%	80 - 120
			Total Lead (Pb)	2021/09/11		98	%	80 - 120
			Total Lithium (Li)	2021/09/11		90	%	80 - 120
			Total Manganese (Mn)	2021/09/11		88	%	80 - 120
			Total Molybdenum (Mo)	2021/09/11		101	%	80 - 120
			Total Nickel (Ni)	2021/09/11		89	%	80 - 120
			Total Selenium (Se)	2021/09/11		94	%	80 - 120
			Total Silicon (Si)	2021/09/11		104	%	80 - 120
			Total Silver (Ag)	2021/09/11		89	%	80 - 120
			Total Strontium (Sr)	2021/09/11		NC	%	80 - 120
			Total Tellurium (Te)	2021/09/11		97	%	80 - 120
			Total Thallium (Tl)	2021/09/11		100	%	80 - 120
			Total Thorium (Th)	2021/09/11		100	%	80 - 120
			Total Tin (Sn)	2021/09/11		100	%	80 - 120
			Total Titanium (Ti)	2021/09/11		97	%	80 - 120
			Total Tungsten (W)	2021/09/11		95	%	80 - 120
			Total Uranium (U)	2021/09/11		106	%	80 - 120
			Total Vanadium (V)	2021/09/11		95	%	80 - 120
			Total Zinc (Zn)	2021/09/11		93	%	80 - 120
			Total Zirconium (Zr)	2021/09/11		102	%	80 - 120
A347639	AA1	Spiked Blank	Total Aluminum (Al)	2021/09/11		104	%	80 - 120
			Total Antimony (Sb)	2021/09/11		105	%	80 - 120
			Total Arsenic (As)	2021/09/11		100	%	80 - 120
			Total Barium (Ba)	2021/09/11		102	%	80 - 120
			Total Beryllium (Be)	2021/09/11		101	%	80 - 120
			Total Bismuth (Bi)	2021/09/11		103	%	80 - 120
			Total Boron (B)	2021/09/11		101	%	80 - 120
			Total Cadmium (Cd)	2021/09/11		102	%	80 - 120
			Total Chromium (Cr)	2021/09/11		101	%	80 - 120
			Total Cobalt (Co)	2021/09/11		100	%	80 - 120
			Total Copper (Cu)	2021/09/11		100	%	80 - 120
			Total Iron (Fe)	2021/09/11		106	%	80 - 120
			Total Lead (Pb)	2021/09/11		102	%	80 - 120
			Total Lithium (Li)	2021/09/11		98	%	80 - 120
			Total Manganese (Mn)	2021/09/11		103	%	80 - 120



QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
		••	Total Molybdenum (Mo)	2021/09/11		104	%	80 - 120
			Total Nickel (Ni)	2021/09/11		101	%	80 - 120
			Total Selenium (Se)	2021/09/11		101	%	80 - 120
			Total Silicon (Si)	2021/09/11		109	%	80 - 120
			Total Silver (Ag)	2021/09/11		99	%	80 - 120
			Total Strontium (Sr)	2021/09/11		102	%	80 - 120
			Total Tellurium (Te)	2021/09/11		105	%	80 - 120
			Total Thallium (TI)	2021/09/11		102	%	80 - 120
			Total Thorium (Th)	2021/09/11		103	%	80 - 120
			Total Tin (Sn)	2021/09/11		104	%	80 - 120
			Total Titanium (Ti)	2021/09/11		106	%	80 - 120
			Total Tungsten (W)	2021/09/11		100	%	80 - 120
			Total Uranium (U)	2021/09/11		107	%	80 - 120
			Total Vanadium (V)	2021/09/11		102	%	80 - 120
			Total Variadidii (V) Total Zinc (Zn)	2021/09/11		102	%	80 - 120
						103	% %	
A 2 47C20	A A 1	Mathad Dlaul	Total Aluminum (Zr)	2021/09/11	40 FO	102		80 - 120
A347639	AA1	Method Blank	Total Auminum (AI)	2021/09/11	<0.50		ug/L	
			Total Antimony (Sb)	2021/09/11	<0.020		ug/L	
			Total Arsenic (As)	2021/09/11	<0.020		ug/L	
			Total Barium (Ba)	2021/09/11	<0.020		ug/L	
			Total Beryllium (Be)	2021/09/11	<0.010		ug/L	
			Total Bismuth (Bi)	2021/09/11	<0.0050		ug/L	
			Total Boron (B)	2021/09/11	<10		ug/L	
			Total Cadmium (Cd)	2021/09/11	<0.0050		ug/L	
			Total Chromium (Cr)	2021/09/11	<0.10		ug/L	
			Total Cobalt (Co)	2021/09/11	<0.0050		ug/L	
			Total Copper (Cu)	2021/09/11	<0.050		ug/L	
			Total Iron (Fe)	2021/09/11	<1.0		ug/L	
			Total Lead (Pb)	2021/09/11	<0.0050		ug/L	
			Total Lithium (Li)	2021/09/11	<0.50		ug/L	
			Total Manganese (Mn)	2021/09/11	< 0.050		ug/L	
			Total Molybdenum (Mo)	2021/09/11	< 0.050		ug/L	
			Total Nickel (Ni)	2021/09/11	<0.020		ug/L	
			Total Selenium (Se)	2021/09/11	< 0.040		ug/L	
			Total Silicon (Si)	2021/09/11	<50		ug/L	
			Total Silver (Ag)	2021/09/11	<0.0050		ug/L	
			Total Strontium (Sr)	2021/09/11	<0.050		ug/L	
			Total Tellurium (Te)	2021/09/11	<0.020		ug/L	
			Total Thallium (TI)	2021/09/11	<0.0020		ug/L	
			Total Thorium (Th)	2021/09/11	<0.0050		ug/L	
			Total Tin (Sn)	2021/09/11	<0.20		ug/L	
			Total Titanium (Ti)	2021/09/11	<0.50		ug/L	
			Total Triallium (Tr) Total Tungsten (W)	2021/09/11	<0.010		ug/L	
			Total Uranium (U)	2021/09/11	0.0027, RDL=0.0020 (2)		ug/L	
			Total Vanadium (V)	2021/09/11	<0.20		ug/L	
			Total Zinc (Zn)	2021/09/11	<0.10		ug/L	
			Total Zirconium (Zr)	2021/09/11	<0.10		ug/L	
A347639	AA1	RPD [AFF276-04]	Total Aluminum (Al)	2021/09/11	3.8		%	20
			Total Antimony (Sb)	2021/09/11	11		%	20
			Total Arsenic (As)	2021/09/11	2.4		%	20
			Total Barium (Ba)	2021/09/11	0.13		%	20
			Total Beryllium (Be)	2021/09/11	NC		%	20
			Total Bismuth (Bi)	2021/09/11	NC		%	20
			Total Boron (B)	2021/09/11	NC		%	20

			QUALITY ASSURANCE					
QA/QC Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
			Total Cadmium (Cd)	2021/09/11	4.5		%	20
			Total Chromium (Cr)	2021/09/11	NC		%	20
			Total Cobalt (Co)	2021/09/11	1.6		%	20
			Total Copper (Cu)	2021/09/11	4.7		%	20
			Total Iron (Fe)	2021/09/11	1.0		%	20
			Total Lead (Pb)	2021/09/11	2.6		%	20
			Total Lithium (Li)	2021/09/11	2.3		%	20
			Total Manganese (Mn)	2021/09/11	1.1		%	20
			Total Molybdenum (Mo)	2021/09/11	11		%	20
			Total Nickel (Ni)	2021/09/11	2.9		%	20
			Total Selenium (Se)	2021/09/11	13		%	20
			Total Silicon (Si)	2021/09/11	0.60		%	20
			Total Silver (Ag)	2021/09/11	NC		%	20
			Total Strontium (Sr)	2021/09/11	1.4		%	20
			Total Tellurium (Te)	2021/09/11	NC		%	20
			Total Thallium (TI)	2021/09/11	4.7		%	20
			Total Thorium (Th)	2021/09/11	4.0		%	20
			Total Tin (Sn)	2021/09/11	NC		%	20
			Total Titanium (Ti)	2021/09/11	NC		%	20
			Total Tungsten (W)	2021/09/11	11		%	20
			Total Uranium (U)	2021/09/11	0.35		%	20
			Total Vanadium (V)	2021/09/11	NC		%	20
			Total Zinc (Zn)	2021/09/11	3.4		%	20
			Total Zirconium (Zr)	2021/09/11	NC		%	20
A347643	MO5	Matrix Spike	Fluoride (F)	2021/09/10	110	100	%	80 - 120
A347643	MO5	Spiked Blank	Fluoride (F)	2021/09/10		100	%	80 - 120
A347643	MO5	Method Blank	Fluoride (F)	2021/09/10	<0.020	100	mg/L	00 - 120
A347643	MO5	RPD	Fluoride (F)	2021/09/10	0.020		111g/ L %	20
A347043			` '	2021/09/10	U	104	% %	80 - 120
A347795	CJY	Matrix Spike [AFF274-04]	Total Mercury (Hg)			104		
	CJY	Spiked Blank	Total Mercury (Hg)	2021/09/10	-0.0010	106	% /I	80 - 120
A347795	CJY	Method Blank	Total Mercury (Hg)	2021/09/10	<0.0019		ug/L	20
A347795	CJY	RPD [AFF273-04]	Total Mercury (Hg)	2021/09/10	NC	400	%	20
A348087	MO5	Matrix Spike	Dissolved Chloride (Cl)	2021/09/10		100	%	80 - 120
			Dissolved Sulphate (SO4)	2021/09/10		NC	%	80 - 120
A348087	MO5	Spiked Blank	Dissolved Chloride (CI)	2021/09/10		103	%	80 - 120
			Dissolved Sulphate (SO4)	2021/09/10		99	%	80 - 120
A348087	MO5	Method Blank	Dissolved Chloride (CI)	2021/09/10	<0.50		mg/L	
			Dissolved Sulphate (SO4)	2021/09/10	<0.50		mg/L	
A348087	MO5	RPD	Dissolved Chloride (Cl)	2021/09/10	NC		%	20
			Dissolved Sulphate (SO4)	2021/09/10	2.5		%	20
A348160	MO5	Matrix Spike	Dissolved Chloride (CI)	2021/09/10		84	%	80 - 120
			Dissolved Sulphate (SO4)	2021/09/10		NC	%	80 - 120
A348160	MO5	Spiked Blank	Dissolved Chloride (CI)	2021/09/10		103	%	80 - 120
			Dissolved Sulphate (SO4)	2021/09/10		101	%	80 - 120
A348160	MO5	Method Blank	Dissolved Chloride (CI)	2021/09/10	<0.50		mg/L	
			Dissolved Sulphate (SO4)	2021/09/10	0.98, RDL=0.50		mg/L	
A348160	MO5	RPD	Dissolved Chloride (CI)	2021/09/10	5.1		%	20
. 13 13100	05	5	Dissolved Sulphate (SO4)	2021/09/10	1.6		%	20
A348552	JFH	Matrix Spike	Total Ammonia (N)	2021/09/11	1.0	96	%	80 - 120
A348552	JFH	Spiked Blank	Total Ammonia (N)	2021/09/11		96	% %	80 - 120 80 - 120
A348552 A348552	JFH	Method Blank	Total Ammonia (N) Total Ammonia (N)	2021/09/11	<0.0050	30	% mg/L	00 - 120
								20
A348552	JFH	RPD	Total Ammonia (N)	2021/09/11	1.3	101	%	20
A348557	JFH	Matrix Spike [AFF275-09]	Total Ammonia (N)	2021/09/11		101	%	80 - 120
A348557	JFH	Spiked Blank	Total Ammonia (N)	2021/09/11		97	%	80 - 120



Government of Yukon – Dept of ENV Client Project #: 2021-Ketza

QA/QC								
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
A348557	JFH	Method Blank	Total Ammonia (N)	2021/09/11	<0.0050		mg/L	
A348557	JFH	RPD [AFF275-09]	Total Ammonia (N)	2021/09/11	NC		%	20
A348719	ZWU	Matrix Spike [AFF277-08]	Dissolved Organic Carbon (C)	2021/09/13		112	%	80 - 120
A348719	ZWU	Spiked Blank	Dissolved Organic Carbon (C)	2021/09/11		115	%	80 - 120
A348719	ZWU	Method Blank	Dissolved Organic Carbon (C)	2021/09/11	<0.20		mg/L	
A348719	ZWU	RPD [AFF277-08]	Dissolved Organic Carbon (C)	2021/09/13	NC		%	20
A348726	TL9	Matrix Spike [AFF272-02]	Fluoride (F)	2021/09/11		104	%	80 - 120
A348726	TL9	Spiked Blank	Fluoride (F)	2021/09/11		106	%	80 - 120
A348726	TL9	Method Blank	Fluoride (F)	2021/09/11	<0.020		mg/L	
A348726	TL9	RPD [AFF272-02]	Fluoride (F)	2021/09/11	5.1	400	%	20
A349611	AA1	Matrix Spike	Total Zinc (Zn)	2021/09/14		102	%	80 - 120
A349611	AA1	Spiked Blank	Total Zinc (Zn)	2021/09/14	.0.40	102	%	80 - 120
A349611	AA1	Method Blank	Total Zinc (Zn)	2021/09/14	<0.10		ug/L	20
A349611	AA1	RPD	Total Zinc (Zn)	2021/09/14	1.9	F7 (4)	%	20
A351252	AA1	Matrix Spike	Dissolved Auminum (Al)	2021/09/14		57 (4)	%	80 - 120
			Dissolved Arcania (As)	2021/09/14 2021/09/14		105 101	% %	80 - 120 80 - 120
			Dissolved Arsenic (As) Dissolved Barium (Ba)	2021/09/14		97	% %	80 - 120 80 - 120
			Dissolved Baridin (Ba) Dissolved Beryllium (Be)	2021/09/14		92	%	80 - 120
			Dissolved Berymann (Be) Dissolved Bismuth (Bi)	2021/09/14		93	%	80 - 120
			Dissolved Bismath (B)	2021/09/14		91	%	80 - 120
			Dissolved Cadmium (Cd)	2021/09/14		103	%	80 - 120
			Dissolved Chromium (Cr)	2021/09/14		91	%	80 - 120
			Dissolved Cobalt (Co)	2021/09/14		95	%	80 - 120
			Dissolved Copper (Cu)	2021/09/14		87	%	80 - 120
			Dissolved Iron (Fe)	2021/09/14		45 (4)	%	80 - 120
			Dissolved Lead (Pb)	2021/09/14		96	%	80 - 120
			Dissolved Lithium (Li)	2021/09/14		83	%	80 - 120
			Dissolved Manganese (Mn)	2021/09/14		NC	%	80 - 120
			Dissolved Molybdenum (Mo)	2021/09/14		107	%	80 - 120
			Dissolved Nickel (Ni)	2021/09/14		94	%	80 - 120
			Dissolved Selenium (Se)	2021/09/14		101	%	80 - 120
			Dissolved Silicon (Si)	2021/09/14		NC	%	80 - 120
			Dissolved Silver (Ag)	2021/09/14		100	%	80 - 120
			Dissolved Strontium (Sr)	2021/09/14		NC	%	80 - 120
			Dissolved Tellurium (Te)	2021/09/14		103	%	80 - 120
			Dissolved Thallium (TI)	2021/09/14		95	%	80 - 120
			Dissolved Thorium (Th)	2021/09/14		99	%	80 - 120
			Dissolved Tin (Sn)	2021/09/14		101	%	80 - 120
			Dissolved Titanium (Ti)	2021/09/14		87	%	80 - 120
			Dissolved Tungsten (W)	2021/09/14		99	%	80 - 120
			Dissolved Uranium (U)	2021/09/14		99	%	80 - 120
			Dissolved Vanadium (V)	2021/09/14		92	%	80 - 120
			Dissolved Zinc (Zn)	2021/09/14		101	%	80 - 120
			Dissolved Zirconium (Zr)	2021/09/14		107	%	80 - 120
A351252	AA1	Spiked Blank	Dissolved Aluminum (AI)	2021/09/14		98	%	80 - 120
			Dissolved Antimony (Sb)	2021/09/14		104	%	80 - 120
			Dissolved Arsenic (As)	2021/09/14		101	%	80 - 120
			Dissolved Barium (Ba)	2021/09/14		102	%	80 - 120
			Dissolved Beryllium (Be)	2021/09/14		102	%	80 - 120
			Dissolved Bismuth (Bi)	2021/09/14		99	%	80 - 120
			Dissolved Boron (B)	2021/09/14		101	%	80 - 120
			Dissolved Cadmium (Cd)	2021/09/14		102	%	80 - 120
			Dissolved Chromium (Cr)	2021/09/14		93	%	80 - 120
<u> </u>			Dissolved Cobalt (Co)	2021/09/14		96	%	80 - 120

04/06			QUALITY ASSURANCE					
QA/QC Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
			Dissolved Copper (Cu)	2021/09/14		92	%	80 - 120
			Dissolved Iron (Fe)	2021/09/14		103	%	80 - 120
			Dissolved Lead (Pb)	2021/09/14		99	%	80 - 120
			Dissolved Lithium (Li)	2021/09/14		99	%	80 - 120
			Dissolved Manganese (Mn)	2021/09/14		93	%	80 - 120
			Dissolved Molybdenum (Mo)	2021/09/14		103	%	80 - 120
			Dissolved Nickel (Ni)	2021/09/14		98	%	80 - 120
			Dissolved Selenium (Se)	2021/09/14		99	%	80 - 120
			Dissolved Silicon (Si)	2021/09/14		103	%	80 - 120
			Dissolved Silver (Ag)	2021/09/14		100	%	80 - 120
			Dissolved Strontium (Sr)	2021/09/14		96	%	80 - 120
			Dissolved Tellurium (Te)	2021/09/14		104	%	80 - 120
			Dissolved Thallium (TI)	2021/09/14		99	%	80 - 120
			Dissolved Thorium (Th)	2021/09/14		101	%	80 - 120
			Dissolved Tin (Sn)	2021/09/14		103	%	80 - 120
			Dissolved Titanium (Ti)	2021/09/14		103	%	80 - 120
			Dissolved Tungsten (W)	2021/09/14		98	%	80 - 120
			Dissolved Uranium (U)	2021/09/14		100	%	80 - 120
			Dissolved Vanadium (V)	2021/09/14		92	%	80 - 120
			Dissolved Zinc (Zn)	2021/09/14		101	%	80 - 120
			Dissolved Zirconium (Zr)	2021/09/14		103	%	80 - 120
A351252	AA1	Method Blank	Dissolved Aluminum (AI)	2021/09/14	<0.50		ug/L	
			Dissolved Antimony (Sb)	2021/09/14	<0.020		ug/L	
			Dissolved Arsenic (As)	2021/09/14	<0.020		ug/L	
			Dissolved Barium (Ba)	2021/09/14	<0.020		ug/L	
			Dissolved Beryllium (Be)	2021/09/14	<0.010		ug/L	
			Dissolved Bismuth (Bi)	2021/09/14	<0.0050		ug/L	
			Dissolved Boron (B)	2021/09/14	<10		ug/L	
			Dissolved Cadmium (Cd)	2021/09/14	< 0.0050		ug/L	
			Dissolved Chromium (Cr)	2021/09/14	<0.10		ug/L	
			Dissolved Cobalt (Co)	2021/09/14	<0.0050		ug/L	
			Dissolved Copper (Cu)	2021/09/14	<0.050		ug/L	
			Dissolved Iron (Fe)	2021/09/14	<1.0		ug/L	
			Dissolved Lead (Pb)	2021/09/14	<0.0050		ug/L	
			Dissolved Lithium (Li)	2021/09/14	<0.50		ug/L	
			Dissolved Manganese (Mn)	2021/09/14	<0.050		ug/L	
			Dissolved Molybdenum (Mo)	2021/09/14	<0.050		ug/L	
			Dissolved Nickel (Ni)	2021/09/14	<0.020		ug/L	
			Dissolved Selenium (Se)	2021/09/14	<0.040		ug/L	
			Dissolved Silicon (Si)	2021/09/14	<50		ug/L	
			Dissolved Silver (Ag)	2021/09/14	< 0.0050		ug/L	
			Dissolved Strontium (Sr)	2021/09/14	<0.050		ug/L	
			Dissolved Tellurium (Te)	2021/09/14	<0.020		ug/L	
			Dissolved Thallium (TI)	2021/09/14	<0.0020		ug/L	
			Dissolved Thorium (Th)	2021/09/14	<0.0050		ug/L	
			Dissolved Tin (Sn)	2021/09/14	<0.20		ug/L	
			Dissolved Titanium (Ti)	2021/09/14	<0.50		ug/L	
			Dissolved Tungsten (W)	2021/09/14	<0.010		ug/L	
			Dissolved Uranium (U)	2021/09/14	<0.0020		ug/L	
			Dissolved Vanadium (V)	2021/09/14	<0.20		ug/L	
			Dissolved Zinc (Zn)	2021/09/14	<0.10		ug/L	
			Dissolved Zirconium (Zr)	2021/09/14	<0.10		ug/L	
A351252	AA1	RPD	Dissolved Antimony (Sb)	2021/09/14	3.6		%	20
			Dissolved Arsenic (As)	2021/09/14	3.0		%	20
			Dissolved Barium (Ba)	2021/09/14	1.4		%	20



Government of Yukon – Dept of ENV Client Project #: 2021-Ketza

QUALITY ASSURANCE REPORT(CONT'D)

QA/QC	1	00 T:	Paramatan.	Data Analis I	Malica	D	LINUTC	001::
Batch	Init	QC Type	Parameter	Date Analyzed	Value	Recovery	UNITS	QC Limits
			Dissolved Beryllium (Be)	2021/09/14	NC		%	20
			Dissolved Bismuth (Bi)	2021/09/14	NC		%	20
			Dissolved Boron (B)	2021/09/14	0.17		%	20
			Dissolved Cadmium (Cd)	2021/09/14	4.6		%	20
			Dissolved Chromium (Cr)	2021/09/14	1.5		%	20
			Dissolved Lithium (Li)	2021/09/14	1.1		%	20
			Dissolved Molybdenum (Mo)	2021/09/14	0.21		%	20
			Dissolved Nickel (Ni)	2021/09/14	1.2		%	20
			Dissolved Selenium (Se)	2021/09/14	10		%	20
			Dissolved Silicon (Si)	2021/09/14	1.9		%	20
			Dissolved Silver (Ag)	2021/09/14	NC		%	20
			Dissolved Strontium (Sr)	2021/09/14	0.34		%	20
			Dissolved Thallium (TI)	2021/09/14	NC		%	20
			Dissolved Tin (Sn)	2021/09/14	NC		%	20
			Dissolved Uranium (U)	2021/09/14	1.3		%	20
			Dissolved Vanadium (V)	2021/09/14	2.4		%	20
			Dissolved Zinc (Zn)	2021/09/14	4.1		%	20
			Dissolved Zirconium (Zr)	2021/09/14	NC		%	20
A351779	MO5	Matrix Spike [AFF268-02]	Dissolved Chloride (CI)	2021/09/14		100	%	80 - 120
			Dissolved Sulphate (SO4)	2021/09/14		102	%	80 - 120
A351779	MO5	Spiked Blank	Dissolved Chloride (CI)	2021/09/14		103	%	80 - 120
			Dissolved Sulphate (SO4)	2021/09/14		99	%	80 - 120
A351779	MO5	Method Blank	Dissolved Chloride (CI)	2021/09/14	<0.50		mg/L	
			Dissolved Sulphate (SO4)	2021/09/14	<0.50		mg/L	
A351779	MO5	RPD [AFF268-02]	Dissolved Chloride (CI)	2021/09/14	NC		%	20
			Dissolved Sulphate (SO4)	2021/09/14	NC		%	20
A357208	AP1	Matrix Spike	Total Dissolved Solids	2021/09/18		82	%	80 - 120
A357208	AP1	Spiked Blank	Total Dissolved Solids	2021/09/18		96	%	80 - 120
A357208	AP1	Method Blank	Total Dissolved Solids	2021/09/18	<1.0		mg/L	
A357208	AP1	RPD	Total Dissolved Solids	2021/09/18	0.29		%	20
A362419	HE1	Spiked Blank	Total Dissolved Solids	2021/09/22		92	%	80 - 120
A362419	HE1	Method Blank	Total Dissolved Solids	2021/09/22	<1.0		mg/L	

N/A = Not Applicable

Duplicate: Paired analysis of a separate portion of the same sample. Used to evaluate the variance in the measurement.

Matrix Spike: A sample to which a known amount of the analyte of interest has been added. Used to evaluate sample matrix interference.

QC Standard: A sample of known concentration prepared by an external agency under stringent conditions. Used as an independent check of method accuracy.

Spiked Blank: A blank matrix sample to which a known amount of the analyte, usually from a second source, has been added. Used to evaluate method accuracy.

Method Blank: A blank matrix containing all reagents used in the analytical procedure. Used to identify laboratory contamination.

NC (Matrix Spike): The recovery in the matrix spike was not calculated. The relative difference between the concentration in the parent sample and the spike amount was too small to permit a reliable recovery calculation (matrix spike concentration was less than the native sample concentration)

NC (Duplicate RPD): The duplicate RPD was not calculated. The concentration in the sample and/or duplicate was too low to permit a reliable RPD calculation (absolute difference <= 2x RDL).

- (1) Method blank exceeds acceptance limits for Srl- 2X RDL acceptable for low level metals determination.
- (2) Method blank exceeds acceptance limits for U- 2X RDL acceptable for low level metals determination.
- (3) Method blank exceeds acceptance limits for Zn- 2X RDL acceptable for low level metals determination.
- (4) Recovery or RPD for this parameter is outside control limits. The overall quality control for this analysis meets acceptability criteria.



VALIDATION SIGNATURE PAGE

The analytical data and all QC contained in this report were reviewed and validated by:

Ghayasuddin Khan, M.Sc., P.Chem., QP, Scientific Specialist, Inorganics

Sandy Yuan, M.Sc., QP, Scientific Specialist

BV Labs has procedures in place to guard against improper use of the electronic signature and have the required "signatories", as per ISO/IEC 17025, signing the reports. For Service Group specific validation please refer to the Validation Signature Page.

EXCDA1		INVOICE TO:				Report Inf	french	-		_		-	_		Project l	nformatio		-		590000000000000000000000000000000000000	nly
-	#4977 Goues	mment of Yukon - Dept of ENV	-		#44311 Go	-	_	-	- Deo	t of EN	v				C10319			-	C165	509 COC	Bottle Order #:
ripany Name riaci Name	Stephanie Lyc			ompany Name ontact Name	Stephanie L	AND RESIDENCE TO SHARE S		-	- Dep		-	P.0	ration#					_			100000000
Pass	Water Resour	ces Branch (V-310) Box 2703		50'ess	Box 2703								ed#		2021-Ke	tza			-		644610
	Whitehorse Y	AND DESCRIPTION OF THE PERSON			Whitehorse	_	C6					Pro	ect.Name							Chain Of Custody Record	Project Manager
ne	(867) 689-876	CONTRACTOR OF THE PARTY OF THE		none	(867) 689-8	-		_Fax	_			SM				_	_	_	-		Customer Solutions
ei .	Stephanie lyo	ns@yukon.ca	0	nai	stephanie.ly	onsgyu	ton.ca	_			_	far	Analysis	Was alte	_	_	_		_	C#644610-04-01	
Regulatory Crit	eria			Specials	netructions		ê	1					Armyss	I	Ta					Turnaround Time (TAT) Re Please provide advance notice for r	
	Note: For regulate	of drinking water samples - phease use the i	Orinking Wate	r Chain of Cu	stody Form		3	Spered 2 (Y7)	EC. F, pH & LL.Cl. SO4, 7, NO3 (Group 01)	TSS & LL-TDS (Group 02)	LL DOC & Dissolved Total Phosphorus (Group 03)	, TKN & LL Total ionus (Group 04)	nia-N Low Level	SAD & WAD (Group	ed CR3 & CR5 (Grou	u LL Dissolved Metals up 05)	LL Total Metals (Group		(will be a Standar Flease a Geys - 0 Job Spec Date Rec	r (Standard) TAT a not specified) of TAT is not specified) of TAT is 5.7 Working days for most tests: none: Standard TAT for certain fests such as 8 contact your Project Manager for details; othe Standard TAT of applies to entire submissions) otherwise than TAT (if applies to entire submissions) of the Standard Tatle of the Stan	00 and Downs/Furant are 1
	Samples	must be kept cool (< 10°C) from time of same	pling until deliv	ery to BV Lab	me in		8	tans Fi	AR, EC NO2, N	*6 52	8 6	Total N. Phosph	9.3	anide	8	Ketza L (Group	Ketza L 06)		711000		goal no for #)
Sample	Bartode Label	Sangle (Location) Identification	Date Sa	ngled Ti	ine Sangled	Matrix	Re	2	25	20	35	26	Amm	99	8 8	30	28	-	# of Butte	Comments	
		3031725-11	0150	1510	0915	SW	N	Y	Х	X	X	*	X	Х	χ	X	X	_	13		
		2021T25 -12	1			1	1	1	1	1	1	1	1	1	11	1	1		1		
		2021T35-13			1045		Ш			1	Ц	Ш	Ш	Ц	11				Ш		
		3021725 -14			1115		Ш	1		\perp	Ш	Ш	Ш	Ц	11		Ц		11		
		2021 T 25 -15			1200		Ш	1	Ш	\perp	Ш	Ш	Ш	Ш	11		Ш	_	11		
		2621T25-16			1145	\perp	Ш	Ш	\perp		Ш	Ш	Ш	Ш		Ш	Ш		11		
		2021725-17			1230		Ш	1						Ш					1		
		2021T25-18			13 15		11							Ш							
		2021Ta5 - 19			14:15	1	Ш	Ш		1				Ш							
		2021T 25 - 20	1		15:30	+	4	4	*	4	4	4	+	4	4	4	4		4		
	USHED BY: (Slove	The second secon	CALWWIDGE	Time	1. 12	7	-	-	nature/Pri	M)			ete: (YYAM		Time	# jar	s used and submitted	Time Se	-	Lab Use Only	ty Seal Intect on Coder?
de place	rechouse	o Styrms 121/0	2018	COFL	1 Ven	are l	any	13V	-		_	10	10310	5	15:17	-		[1 /	6,6/4,4,4/2,7,7	at annua

Bureau Veritas Canada (2019) Inc.

		Bureau Wintes Laboratories 4000 19st N.E. Calgary, Alberta (Conside T2E 6P6 T	wi (403) 291-	3077 Toll-free 800-	563-6266 Fax	(403) 2	191-0	HOS www	bvistes oc	pm										People 2
		INVOICE TO:				Raport in	formati	on.							Project	nformatio	in.		mill #- 7-2	FOR ANY AND MANAGEMENT OF THE	nly
mpany Name	#4977 Gover	nment of Yukon - Dept of EN	N .	Company No	me #44311 (Sovernmen	t of Y	uko	n – Dep	at of EN	N.	Que	tation#		C10319				C16556	09_COC	Bottle Order #:
ntact Name	Stephanie Lyo			Contact Nan		Lyons						P.0			-						THE RESIDENCE
0111		ces Branch (V-310) Box 2703		Address	Box 2703							Pro	ect#		2021-Ke	tza			-		644610
- 3	Whitehorse Y				Whitehors		C6	_	_			Proj	ect Name				_		-	Chain Of Custody Record	Project Manager
one .	(867) 689-876	Chicago Paris Control of the Control	-	Phone	(867) 689	of the party of the last		"Fa	K	_	_	She			_	_			_		Customer Solutions
al	Stephanie.lyor	nsgyuxon.ca		Enail	No. of Concession, Name of Street, or other Persons, Name of Street, Name of S	lyons@yu	con.ca	_	_	_		Sar	Analysis I		_	_				C#644\$10-05-01	
Regulatory Crit			(1)		al Instructions		nking Water 7 (Y / N.)	Stered ? (Y/N)	pH & LL-Ct, SO4, (Group 01)	DS (Group 02)	Dissolved Total is (Group 03)	(Group 04)	nia-N Low Level	& WAD (Group	CR3 & CR6 (Group	Dissolved Metals 5)	Total Metals (Group		(will be ap Standard I Please not days - con Jee Specifi	Turnaround Time (TAT) Req Passes provide Britana exists for re Standard) YAT plind if Rish TAT is not specified) YAT = 5-7 Working days for most tests is the "Standard TAT for certain tests such as 80 foot your Project Manager for Outsile." In Rush TAT (if applies to entire submission)	o and Dissins Furance are > 1
- 3	Note: For regulate	d drinking water samples - please us	se the Orinking Wa	ter Chain of	Custody Form		100	eld F	C. F.	LL-TDS	45 €	TKN Norus	Ned)	e SAD	8	40	11.70		Date Requir Rush Cordin	nation Number	
3000	Samples	must be kept cool (< 10°C) from time	of sampling until de	livery to BV I	301		8	8		+6	DOC	N dd	Ammon (Presen	nide	1.6	12 9	122		Carrier II	Control of the second	set no tyriti
Samole	Baroode Label	Sample (Location) Identification	n Date 1	Sampled	Time Sampled	Matrix	18	N Sc	AK. E	155	3.6	Phos	A Se	Oya Cya	86	Ketza (Group	Ketza 06)		For Duties	Conments	
		SOTIES		eprá	15 30	SW	N	Y	Х	Х	Χ	Х	X	X	X	X	X		13		
		2021725-22	035	וב' דקפ	1015		1	1	1	1		1	1	1	1	1	1		1		
		2021725-23	> 1		1100	Ш	11	4		1	Ш			Ц	11	Ш	Ш		4	and and to be still a	
		2021725 -24		_	1115	+	+	4	+		\perp				\perp				4	han on of posses	
		2021725 - 25	5	-	1200	4	+	4	÷	+	4	+	+	+	4	4	1		13	-this blank	
							Ш													<u> </u>	
0							П														
* RELING	CISHED BY ISIGNAL		Date: (YYMM50)	-			VEDBY	1.(5)	produceith	(MQ		-	de: (YYAM	_	Time	# jar	s used and submitted	-		Lab Use Only	
repran	ierym	o Sums is	E011011E	170	O XX	regre 6	m	-				10	1/04/07	3	15:17	-	-	Timedan	700	specialize (,**) on selected	Seel Intact on Cooler?

Bureau Veritax Canada (2019) Inc.

Project: 2021 Ketza Mine Audit (Contract # C00061500)

			l	-18	Result	Donast	- 211						1 F
#	Sample	Date	Lab#	δ ¹⁸ Ο		Repeat	$\delta^2 H$	Result	Repeat		pН	EC	AZD
				H ₂ O	VSMOV		H ₂ O	VSMOW			_	uS/cm	!
1	2021T24-01	2021-08-04	461319	Х	-22.00	-22.02	Х	-167.88	-168.06		7.59	597.0	. L
2	2021T24-02	2021-08-03	461320	Х	-20.75		Х	-161.82		1x30mL	7.30	686.0	!
3	2021T24-03	2021-08-03	461321	Х	-21.91		Х	-168.43		1x30mL	7.70	493.0	!
4	2021T24-04	2021-08-03	461322	Х	-21.37		Х	-164.72		1x30mL	7.49	444.0	. L
5	2021T24-05	2021-08-05	461323	Х	-21.40	-21.42	Х	-163.71	-163.54		7.72	300.0	. L
6	2021T24-06	2021-08-04	461324	X	-21.53		Х	-163.04		1x30mL	7.47	826.0	!
7	2021T24-07	2021-08-05	461325	Х	-21.07		Х	-161.81		1x30mL	12.19	1,999.0	. L
8	2021T24-08	2021-08-05	461326	Х	-21.50		Х	-163.56		1x30mL	7.21	610.0	. L
9	2021T24-09	2021-08-05	461327	Х	-20.98	24.00	Х	-160.71	100.10	1x30mL	7.17	529.0	!
10	2021T24-10	2021-08-04	461328	Х	-21.35	-21.30	Х	-162.40	-162.43		7.03	333.0	. L
11	2021T24-11	2021-08-04	461329	Х	-21.22		Х	-161.90		1x30mL	7.36	694.0	. L
12	2021T24-12	2021-08-05	461330	Х	-21.68		Х	-164.85		1x30mL	7.36	1,125.0	. L
13	2021T24-13	2021-08-03	461331	Х	-21.01		Х	-159.58		1x30mL	6.02	670.0	. L
14	2021T24-14	2021-08-04	461332	Х	-22.47		Х	-170.20		1x30mL	5.09	465.0	!
15	2021T24-15	2021-08-04	461333	Х	-21.50	-21.48	Х	-162.90	-162.80		2.68	1,012.0	. L
16	2021T24-16	2021-08-05	461334	Х	-21.90		Х	-166.74		1x30mL	3.74	491.0	↓
17	2021T24-17	2021-08-05	461335	X	-20.86		X	-159.53		1x30mL	6.82	554.0	↓
18	2021T24-18	2021-08-04	461336	Х	-21.38		Х	-164.68		1x30mL	7.26	814.0	. L
19	2021T24-19	2021-08-05	461337	Х	-21.28		Х	-162.94		1x30mL	7.46	469.1	. L
20	2021T24-20	2021-08-03	461338	Х	-21.49	-21.60	Х	-164.58	-164.55	1x30mL	7.64	208.0	!
21	2021T24-21	2021-08-03	461339	Х	-18.79		Х	-146.14		1x30mL	7.49	509.0	!
22	2021T24-22	2021-08-03	461340	Х	-22.04		Х	-167.14		1x30mL	7.48	514.0	!
23	2021T24-23	2021-08-03	461341	Χ	-21.72		Х	-165.44		1x30mL	7.59	563.0	!
24	2021T24-24	-											!
25	2021T24-25	2021-08-06	461342	Χ	-21.41		Х	-161.52		1x30mL	8.29	304.6	!
26	2021T24-26	2021-08-05	461343	Х	-21.59	-21.57	Х	-165.11	-165.24	1x30mL	7.69	709.0	!
27	2021T24-27	2021-08-05	461344	Х	-21.44		Х	-164.98		1x30mL	8.01	650.0	!
28	2021T24-28	2021-08-05	461345	Х	-19.99		Х	-157.47		1x30mL	7.96	424.2	!
29	2021T24-29	2021-08-05	461346	Х	-21.25		Х	-162.64		1x30mL	7.90	438.7	!
30	2021T24-30	2021-08-06	461347	Х	-21.06	-21.00	Х	-161.41	-161.33		8.37	436.0	!
31	2021T24-31	2021-08-06	461348	Χ	-19.86	-19.99	Χ	-157.61	-158.29		8.23	643.0	!
32	2021T24-32	2021-08-06	461349	Х	-20.06		Х	-158.82		1x30mL	7.84	639.0	!
33	2021T24-33	2021-08-06	461350	Χ	-21.39		Х	-162.76		1x30mL	8.40	517.0	!
34	2021T24-34	2021-08-06	461351	Х	-21.12		Х	-161.51		1x30mL	8.38	451.7	!
35	2021T24-35	2021-08-06	461352	Χ	-21.31		Х	-162.86		1x30mL	8.30	489.1	!
36	2021T24-36	2021-08-05	461353	Х	-21.74	-21.71	Х	-164.87		1x30mL	8.40	418.4	!
37	2021T24-37	2021-08-06	461354	Χ	-21.28	-21.22	Χ	-162.33	-161.79	1x30mL	8.40	536.0	!
38	2021T24-38	2021-08-05	461355	Х	-21.93		Х	-166.81		1x30mL	7.70	660.0	!
39	2021T24-39	2021-08-05	461356	Χ	-21.57		Χ	-162.33		1x30mL	8.36	497.0	!
40	2021T24-40	2021-08-06	461357	Х	-21.76		Х	-166.60		1x30mL	8.38	759.0	!
41	2021T24-41	2021-08-06	461358	Х	-20.99		Х	-161.22		1x30mL	8.27	413.3	↓
42	2021T24-42	2021-08-03	461359	Х	-21.52	-21.55	Х		-165.49		7.59	563.0	↓
43	2021T24-43	2021-08-03	461360	Χ	-21.63	-21.79	Х		-168.68		7.70	493.0	ı ∟
44	2021T24-44	2021-08-06	461361	Х	-19.68		Х	-156.74		1x30mL	8.23	643.0	↓
45	2021T24-45	2021-08-31	461362	Х	-21.25		Х	-160.90		1x30mL	8.08	587.0	↓
46	2021T24-46	2021-08-31	461363	Х	-21.11		Х	-160.76		1x30mL	8.18	528.0	↓
47	2021T24-47	2021-08-31	461364	Х	-21.46	-21.49	Х	-164.77	-165.00		7.71	715.0	↓
48	2021T24-48	2021-08-31	461365	Х	-21.62		Х	-164.53		1x30mL	7.73	579.0	↓
49	2021T24-49	2021-08-31	461366	Χ	-21.65		Х	-164.29		1x30mL	7.71	609.0	↓
50	2021T24-50	2021-08-31	461367	Х	-21.64		Χ	-164.39		1x30mL	7.35	500.0	↓
51	2021T24-51	2021-08-31	461368	Х	-21.76		Х	-164.97		1x30mL	7.40	505.0	↓
52	2021T24-52	2021-08-31	461369	Х	-21.75	-21.82	Х	-165.36	-165.87	1x30mL	7.53	569.0	↓
53	2021T24-53	2021-08-31	461370	Х	-21.88		Х	-165.55		1x30mL	7.53	569.0	↓
54	2021T24-54	2021-08-31	461371	Χ	-21.48		Χ	-163.65		1x30mL	7.44	796.0	J



ISO# 2021422 Location: 5-A 67 for 18O, 2H Environmental Isotope Lab 2021-09-23 2 of 2

Project: 2021 Ketza Mine Audit (Contract # C00061500)

_							_			•
#	Sample	Date	Lab#	$\delta^{18} O$	Result	Repeat	$\delta^2 H$	Result	Repeat	
				H ₂ O	VSMOV	V ± 0.2‰	H ₂ O	VSMOW	± 0.8‰	
55	2021T24-55	2021-09-01	461372	Х	-21.27		Χ	-163.83		1x30mL
56	2021T24-56	2021-09-01	461373	Х	-21.43		Χ	-163.52		1x30mL
57	2021T24-57	2021-09-01	461374	Х	-21.47	-21.33	Χ	-165.70	-165.31	1x30mL
58	2021T24-58	2021-09-01	461375	Х	-21.70		Χ	-165.72		1x30mL
59	2021T24-59	2021-09-01	461376	Х	-21.52		Χ	-163.45		1x30mL
60	2021T24-60	2021-09-01	461377	Х	-13.53	-13.49	Χ	-95.90	-95.34	1x30mL
61	2021T24-61	2021-09-01	461378	Х	-21.40		Χ	-163.67		1x30mL
62	2021T24-62	2021-09-01	461379	Х	-21.54	-21.64	Χ	-164.84	-164.29	1x30mL
63	2021T24-63	2021-09-01	461380	Х	-21.82		Х	-164.67		1x30mL
64	2021T24-64	2021-09-01	461381	Х	-21.58		Χ	-160.74		1x30mL
65	2021T24-65	2021-09-01	461382	Х	-21.79		Χ	-166.74		1x30mL
66	2021T24-66	2021-09-02	461383	Х	-21.10		Χ	-160.62		1x30mL
67	2021T24-67	2021-09-02	461384	Х	-21.00	-21.02	Χ	-159.11	-159.37	1x30mL
68	2021T24-68	2021-09-02	461385	Х	-20.93		Χ	-159.37		1x30mL

рН	EC	
	uS/cm	
7.93	759.0	
8.29	623.0	
8.36	1,044.0	
8.34	1,767.0	
8.23	597.0	
5.86	2.6	
8.25	574.0	
8.50	586.0	
8.22	634.0	
7.74	685.0	
7.87	1,145.0	
8.29	450.3	
8.00	274.4	
8.00	274.4	

NOTES

No sample #24



Appendix E – 2021 Audit Field Notes – Hemmera and Water Resources Branch

		10 mg			1
Station ID:		Date: 31 Sup	الله (الله على الله	er: Sunned y	no breeze; 3.3:
Sample ID:	2021T25-1	Coordinates:	N101543	37 W 130.	23592
Sample Class:	SW	Site Description:	D/S Peel 4 (Coche Costi	00012
	· •	- 4		Car 17 W	ence
Time:	0905	Field Crew (circ	cle sampler):	SDCE	
Air Temp (°C):	3.3		Meter Used:	1 Y 234 bal	0/
H2O Temp (°C):	3,7/3.6		7	51 422568	10. TTO SIGNATURE 1
DO (mg/L):	11.59/11.85	QA/QC Sample ID	<u></u>)s	01 122368	
DO (%):	- /89.5	Duplicate:		Time:	
Cond (µs/cm):	57352.2	Trip Blank:		Time:	
SPC (µs/cm):	587/597	Field Blank:		Time:	
pH:	8.08/7.35				
ORP (mV):	- / -93.6	Picture #s:	Feld Notes /	45/55/54b/	1001,0
Furbidity (NTU): _	2.06/1.22	Comments:	Brown precipit	ate Fo ?	DDILO
		Troster V	= 20 U1 = 2 > 20 U2 =		12504 AL Endpoint
368.0M	0	0	1. 10 42		Rete in the Run.

			100	breeze; 3.6°C
Station ID:	KR-08-1			sunny, nocloud,
Sample ID:	2021T25-02	Coordinates: _	N 61.54294°1	N132. 03607"
Sample Class:		Site Description:	Cache Ck. UK Per	el Creek
	09:50	Field Crew (circl	e sampler): SI	/CF
Air Temp (°C):		Ticle I		29.2689
H2O Temp (°C):	4.2/4.1			3 3001
DO (mg/L):	11.45/11.72	QA/QC Sample IDs		
DO (%):	-/89.9	Duplicate:		Time:
	-/322.8	Trip Blank:		Time:
SPC (µs/cm):	528/537	Field Blank:	<i></i>	Time: _/
pH:	8.18/7.72			
	F.(F)-	Picture #s:	US/DS/suk	O/RB/LB
Turbidity (NTU):	0.50/-0.65		I black bear w	
		Titrasti	on VIT = 20	
			V2/2= 20	4, = 333

*		
Station ID:	KR-15-1	Date: 31 Aug 2021 Weather: Sunny, Siclauds; Ight
Sample ID:	2021725-03	Coordinates: U/S culvert on Poel creek and came
Sample Class:	SW	Site Description: NOI. 54209 W 132. 24698 Food
Time:	11:30	Field Crew (circle sampler): (SL)(CF
Air Temp (°C):	12.7	Field Meter Used: 1234626/1225689
H2O Temp (°C):	34/3.3	-31000/
DO (mg/L):	11.60/11.93	QA/QC Sample IDs
DO (%):	-/89.4	Duplicate: Time:
Cond (µs/cm):		Trip Blank: Time:
SPC (µs/cm):	715/726	Field Blank: Time:
pH:	7.71/7.13	
	-122.0	Picture #s: U/S/DS/SMb/Rb/Lb
urbidity (NTU):	2.98/2.34	Comments: iron exide precipitate on substrate and
		vegetation in stream bed.
		Tetration: U-20 U. = 18B

368.0N

	JL	DAR	LING	LLC	
Tacoma,	WA	, USA	• Ritei	ntheRa	in.com

v. light breeze.

	Station ID:	PS3-D5_	Date: 31 Aug à	Weather	er: <u>sonny</u> ~5%	o cloud
	Sample ID:	RODIT25-04	Coordinates:	N61.54270	0°W 132.268	110
Sa	mple Class:		Site Description:	Reel Cr D/S	Seep 3	
	Time:	1345	Field Crew (circ	de sampler): 🤇	SL)/CF	
Ai	r Temp (°C):	12.5	Field	Meter Used: 🛶	234626/ 4225	689
H20	Temp (°C):	3.7/3.5		3		
		11.28/15.64	QA/QC Sample ID	<u>)s</u>		
- 9.	DO (%):	- /87.F	Duplicate:		Time:	
C	ond (µs/cm):	- /345.8	Trip Blank:		Time:	
	SPC (µs/cm):	579 /588	Field Blank:	/	Time:	/Site
	pH:	773/7.28				and a
	ORP (mV):	- /1870	Picture #s:	US/DS/S	ub/RB/LB	
Turl		2.44/0.90		Iron oxide or	ecip coveriu 41	eam
V1=20	U1=336	O.KN Hasoy	Su	betrove 100%		
Va=20	U2=234	Grad. Cyl. measure LP end point	ement			
	210	LP end point	٢			

	1. 19					
Station ID: Sample ID: Sample Class:	2021T25-05	Date: 31 Aug c Coordinates: Site Description:	9021 Weather: (61:54280 Peck Ck D/	Sunny; 5% o 132 2690 Seep 2	cloud; v light be	18024
Time: Air Temp (°C): H2O Temp (°C):	1415 14.3 4.2/4.2	Field Crew (circl Field N	e sampler): (leter Used: Yas	SL)/CF 34626/422	<u>568</u> 9	
DO (mg/L):	What control are the same and t	QA/QC Sample IDs			-	
DO (%):	CALLS TO STANDARD BY THE STANDARD	Duplicate:		Time:		
Cond (µs/cm):	- /372.	子 Trip Blank:	STEELING TO STEEL	Time:		
SPC (µs/cm):	609/619	Field Blank:	100	Time:		
pH:	7.71/7.19					
ORP (mV):	-1'99.4	Picture #s:	US/DS/sub	188118		
Furbidity (NTU):	1.48 /0.94			s precip on sta		
* 4		V1:20 V.	:930 016	N HASOU	TW SOBHORE	
366.0M	0			endpoint	Kitte in the Kain.	

	PCS3		light breeze
Station ID: ((Seep 3)	Date: 31 Aug 2021	Weather: Sonry 10% cloud
	2021T25-06	Coordinates: NG1.5	54087 W132. 26822°
Sample Class:		Site Description: Sec	& Slaylighting
		The state of the s	
Time:	14:30	Field Crew (circle sam	
Air Temp (°C):	17.7/	Field Meter	Used:
H2O Temp (°C):	1,4/1.3		<u> </u>
DO (mg/L):	11.20/ 12.01	QA/QC Sample IDs	
DO (%):	- /85.3	Duplicate:	Time:
Cond (µs/cm):	- /279.		Time:
SPC (µs/cm):	500 / 513	Field Blank:	Time:
pH:	7.35/7.09		
ORP (mV):	- /81,6	Picture #s:	15/15/ substrate
Turbidity (NTU):	9.62/ 10.45		eops (Imain 3 2 side)
V: 20	Ui:251	DUIGH HOUTH NO 100	n precipan substrate.
N7: 90	17: 949	-P endpoint	

	200	1 9		1 5					
Station ID: Sample ID:	2021	2)	The state of the s	31 Aug a	<u>3021</u> 1	Weather:	v. light Sunncy	15%clo	
Sample Class:	SW					Z day	ighting.		as PCS 3?
Time: Air Temp (°C): H2O Temp (°C):	13	1.3	Field (le sample Meter Use		F, AB		A.
DO (mg/L): DO (%):	1092	W.74		ample IDs	5		The second second	•	
Cond (µs/cm):		280.5	F.	iplicate: _ o Blank: _	1.7		Time:		
SPC (µs/cm):	505 7.40	513	Field	d Blank: _			Time:	1000	
ORP (mV):		130.9	Pic	ture #s: _	US/1	5/508	OIRB/	LB	
urbidity (NTU):	0-15	-139	Com	nments:		C VV	11 00		
0	()	A7:90	.:.О : Вісеіпіредзії гіме ггс	SU, AW, amos	D.16N		0	

seed daylights @NOI. 54328 W 132	FG.1	46	Ŧ
----------------------------------	------	----	---

	Sin, few clouds, ice
Station ID: KR17	Date: Aug 31/2021 Weather: Sun, few clouds, 150
Sample ID: 2021 T25 -08	1/09 Coordinates: N 61.54302 W 132. 07417
Sample Class: 5w	Site Description: Kel7, daylighting 50m upstream
Time: 16:45	Field Crew (circle sampler): (SLICF / AB
Air Temp (°C):	Field Meter Used: YS1 PRO Y225689
H20 Temp (°C): 4.8 3.2	1234626
DO (mg/L): 10.05 10.83	QA/QC Sample IDs
DO (%): 80.6	Duplicate: <u>2021735-09</u> Time: 17:115
Cond (µs/cm): 336.1	Trip Blank:
SPC (µs/cm): 5/39 5 83	Field Blank: Time:
pH: 7.53 7.2	
ORP (mV): 161.4	Picture #s: US/SS/SUB/ RB/LB
Turbidity (NTU): -0.13 -1.49	Comments: no staining on rocks/substrate.
The state of the s	Comments: no staining on rocks/substrate. Ji: 248 -seep daylights ~50m 45
V2: 20 (Ja: 245

	KRI7 DS	N 61: 36	1.563 WH	32°16,266'	
Station ID:	Seep-1	Date: 31 Aug 2		er: Sunny a59	aland Ent
Sample ID:	2021 T25-10	TO A STREET THE THE PASSES OF LABOUR AND A SECOND	161. 54328°	W138.8746	breeze
Sample Class:	SW			nt from Bight Bonk	~2m D/S + ~10m D/S
T	10.00		noticable on	stream substre	de
Time:	1800	Field Crew (circl		9/CF/AB	
Air Temp (°C):	10.1	Field N	Neter Used:		
H2O Temp (°C):	3.6/3.5				
DO (mg/L):	11.28/11.57	QA/QC Sample IDs		900	
DO (%):	- 187.4	Duplicate:	Log 9744	Time:	> \
Cond (µs/cm):	- /485.2	Trip Blank:		Time:	
SPC (µs/cm):	708\0PF	Field Blank:	41	Time:	
pH: _	7.44/7.00				
ORP (mV):	- 1-2.0	Picture #s:	USIDS SOL	O RB LB SPE	22 V/S
urbidity (NTU): _	6.32/-0.83	Comments:	àw seen de	glighting from 1	201+ 1- 10
POSEN NOILO	N::90	U:18)	dictorbed 80	Time alone	signi donk
LP endpoint	N7:90		exposed		
0	0	Moo.nisheRain.com	RAG JL Tacoma, AW, USA		0

				V. light	presse
Station ID:	KR-23	Date: 01 Sept &	000) We		
Sample ID:	2021725-11	Coordinates: N	61.5576	25° W 132, 15'	392.
Sample Class:		Site Description:	ischarge	DIS of old a	dit
			0	. <u>(D</u>	
Time:	0915	Field Crew (circl	e sampler):	(SO KCF)	SL
Air Temp (°C):	10.2	Field M	leter Used:	1234626/	1225629
H2O Temp (°C):	4.1/40				
DO (mg/L):	11.31 11.65	QA/QC Sample IDs	ž		_
DO (%):	-/89.1	Duplicate: _		Time	
Cond (µs/cm):	-/461.8	Trip Blank:		Time: _	-275
SPC (µs/cm):	759/771	Field Blank:		* Time:	41 (3)
pH:	7 93/6 73				adi
ORP (mV):	-/ 255 P	Picture #s:	USIN	5/8Ub/18B	JLB/disch-
Turbidity (NTU):	0.00/-0.82	Comments:	. DS ditch	along road/o	anchioning.
			- 11	On	occers uppy

Station ID:	COTI 1 6		15 restance of a constant	- 1 All 22	
		Date: 01 Sept	2021 Weather	Sunny <5%	cloud, light
Sample ID:	2021725-12	Coordinates:	161.55725	W132.1708	8° breeze
Sample Class:	SW	Site Description:	Tributary to	Carlo Crook 1	15 of mad
	- F()	r / 1817	The state of the	agree acce, c	2088H2.
Time:	1005	Field Crew (cir	cle sampler):	SUCE	· · ·
Air Temp (°C):	8.3	Field	Meter Used: 723	4626 / 12256	89
H2O Temp (°C):	24/23	4 3	y in design of the first		
DO (mg/L):	12.23/12.54	QA/QC Sample II	<u></u>		
DO (%):	-/91.6	Duplicate:		Time:	1
Cond (µs/cm):	-/358.7	Trip Blank:		Time:	
SPC (µs/cm):	623 633	Field Blank:		Time:	
pH:	8,29/7.45				
ORP (mV):	-/225,7	Picture #s:	US/108/501	/RB/LB	:
Turbidity (NTU):	0.44/-6.31	Comments:	no abnormal col	lour on solostmate.	long state sheep
		and the second second	wass during en w	uks ; lg- sm cobble :	periphyton substrate.
.0	0	CONTROL TO A SERVICE CASE AND	Tacoma, WA, USA	0	0

Rite in the Rain.

Station ID:	CCITÀ	Date: 1- Sept-	-dod Weather: Since breeze,
Sample ID: 2	4021T25-13	Coordinates: N	N61.55496, W132, 17478
Sample Class:	SW		Tributory to coche (t. US of
	142	Ō	road culvert
Time:	10:45		cle sampler): CF, GD
Air Temp (°C):	12.2	Field N	Meter Used: Y274626 / Y225689
H2O Temp (°C):	3.5/3.4		
DO (mg/L):	11.78/12.12	QA/QC Sample ID:	<u>)s</u>
DO (%):	= /91.3	Duplicate:	Time:
Cond (µs/cm):	- /6aH	Trip Blank:	Fime:
SPC (µs/cm):	1044/1062	Field Blank:	Time:
pH:	8.36/7.53		
ORP (mV):	- /195.6	Picture #s:	US DS SUB RB LB
Turbidity (NTU):			brownish green sediment no
		c	odour, 5m-ly cobbles

Station ID:	CCT3	Date: 1-Sept 2021 Weather: Sunny 45% Clouds	
Sample ID:	2021T25-14	Coordinates: N61.55 149 W [32, 19676]	e lide
Sample Class:	_ SW	Site Description: Tributary to cache of us of ro	but
		Chreck	
Time:		Field Crew (circle sampler):	
Air Temp (°C):	4.9/4.8	Field Meter Used: Y324636 / Y335689	
H2O Temp (°C):	12.3	of the state of th	
	11.34/11.59	QA/QC Sample IDs	
DO (%):	-/90.8	Duplicate: Time:	1
Cond (µs/cm):	767/1700	Trip Blank: Time:	
SPC (µs/cm):	1767/1794	Field Blank: Time:	No.
pH:	8.34/7.54		
	-/209.5	Picture #s: US DS SUB, RB, LB	
urbidity (NTU):	0.33/0.38	Comments: brownish green sadiment, no odow	
		5m-med cobbles	
0	0	Tacoma, WA, USA • RiteintheRain.com	0

Rite in the Rain.

Station ID:	KR-28		Weather: Sunny 2011 Clouds
Sample ID:	2021792-12	Coordinates: NSI	1,54962 W132,20453
Sample Class:	5W	Site Description:	ch Creek
Time:	12:00	Field Crew (circle sam	
Air Temp (°C):	13.4	Field Meter	Used: Y234626/Y225689
H2O Temp (°C):	7.2/7.1		
DO (mg/L):	10.70/10.89	QA/QC Sample IDs	
DO (%):	-/90.1	Duplicate:	Time:
Cond (µs/cm):	-/399.0	Trip Blank:	Time:
	517/606	Field Blank: 2021	T25-16 Time: 11:45
pH:	8.23/7.51		
ORP (mV):	-/197.6	Picture #s: <u> </u>	, DS SUB RB, LB
Turbidity (NTU):	1.83/0.07	Comments: Large	e-med cobbles
	The second second		

	KR-27 2021745-17 SW	Pate: 1 SEPT- 2021 Coordinates: N 61. S Site Description: Cache	Weather: Clear 51 chouds 4959 W 182.22078 Ck DS of bridge
Time:	12:30	Field Crew (circle sample Field Meter Use	er): CEKD
Air Temp (°C):	14.4	Field Meter Use	ed: YA346A6/Y225689
H2O Temp (°C):	7.0/6.9		100007 120007
DO (mg/L):	10.72/10.94	QA/QC Sample IDs	
DO (%):	- 190.1	_ Duplicate:	Time:
Cond (µs/cm):	- /382.2	Trip Blank:	Time:
SPC (µs/cm):	574/583	Field Blank:	Time:
pH:	8.25/7.54		
ORP (mV):	- /176.4	Picture #s: \) \> \	s Sub RB, LB
urbidity (NTU):	1.41/-0.14	Comments: Jonge -	ned Colles some hown
		and lea	red colles some hown

JL DARLING LLC
Tacoma, WA, USA • RiteintheRain.com

Rite in the Rain.

Station ID: KR-26	Date: -SEPT-202 Weather: Sunny, 10% Clouds
Sample ID: 2021725-18	Coordinates: 61.54755 W132.22208
Sample Class: 5W	Site Description: Erib. Cache Creek, US of
	Fjord
Time: \3:15	Field Crew (circle sampler):
Air Temp (°C): 6.4	Field Meter Used: 4234 626/ 4222 5689
H2O Temp (°C): 4.4/4.3	
DO (mg/L): (1).18/10.33	QA/QC Sample IDs
DO (%): - /90.2	Duplicate: Time:
Cond (µs/cm): - /417.4	Trip Blank:Time:
SPC (µs/cm): 586/596	Field Blank: Time:
pH: 8.50/7.91	
ORP (mV): - /179,5	Picture #s: US, DS SUB RBLB
Turbidity (NTU): [.16 /-0.17	Comments: clear no odour, med. Gobbles
	/

Station ID:	KR-22	Date: 1-500t	- 2021 Wes	ather: Clear	me, X
Sample ID:	2021TAS-19	Coordinates:	N64.55	154 W 132	21600
Sample Class:	_SW	Site Description:			US of
Time:	14:15	Field Crew (cir	Confluence	656	
Air Temp (°C):				C1-109	
H2O Temp (°C):		riela	Meter Used:	(yz4896V)	7772889
DO (mg/L):	10.45/10.70	QA/Q€ Sample I	<u>-</u> <u>)s</u>		The state of the s
DO (%):	- 190.1	Duplicate:		Time:	77.10
Cond (µs/cm):		Trip Blank:	AT PERSON OF STREET	Time:	-9.7
SPC (µs/cm):	634/645	Field Blank:		Time:	
pH:	8,22/7.64		A STATE OF THE STA		* /·
ORP (mV):	- / 185.1	Picture #s:	USASS	il ek 18	
Turbidity (NTU):	272/0.93		white pec	i pitute, sligh	Ely Milky
		име сес Вітеіптіре Ваіп. соп		0 0	0

Rite in the Rain.

Station ID: KR-al	Date: - Sept-2021 Weather: hight Clouds
Sample ID: 2021745-20	Coordinates: N 61.5573 W 132, 28545
	Site Description: Misery Creek US of
Sample Class:	tions.
Time: 15-30	Field Crew (circle sampler):
Air Temp (°C): 13.7	Field Meter Used: 4234626/42225689
H20 Temp (°C): 3,9/3,7	
DO (mg/L): 10.77/11.40	QA/QC Sample IDs
DO (%): - / 86.5	Duplicate: Time:
Cond (µs/cm): -/4 2.4	Trip Blank: Time:
SPC (µs/cm): 685/696	Field Blank: Time:
pH: 7.74 / 7.28	
ORP (mV): -/ 189.3	Picture #s: VS DS SUB RB LB
Turbidity (NTU): 0.86/-0.14	Comments: clear No Odour. Some by
	racks on road, not occessible
	by truck

Station ID:	MCSI	Date: 01 Sec	H 2021 Weather:	v 1, ght breeze	
Sample ID:	- n/s	Coordinates	NO1.557389°	sunny overce	est; 90% crouds
Sample Class:	SW	Site Description	seep; milky	white precip	~300 m up
Time: Air Temp (°C):	16:05	Field Crew (ci Field		Present Present	access road from RR-21
H2O Temp (°C): _	V				
DO (mg/L): _		QA/QC Sample II	<u>Ds</u>		
DO (%):		Duplicate:		Time:	
Cond (µs/cm): _	. He	Trip Blank:	PARTITION OF A STATE OF	Time:	
SPC (µs/cm):		Field Blank:		Time:	
pH:		71		Time.	
ORP (mV):		Picture #s:		11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	SKT SILVE
Turbidity (NTU):		Comments:	Looks undestoned	ched on Uph	Il sole of
					DIED.

395.oV

JL DARLING LLC
Tacoma, WA, USA • RiteintheRain.com

Date: Stpt-2021 Weather: TS/CIDUS
Coordinates: 61.55502 132.24800
Site Description: Cache Crek trib US of
Field Crew (circle sampler): Field Meter Used: \(\frac{1}{234626}\) \(\frac{1}{2}\)
QA/QC Sample IDs
Duplicate: Time:
Trip Blank:
Field Blank: Time:
Picture #s: US DS JUB RB LB DDS Comments: Some bown staining

		lower portal C	site 10 confirmed by	site man
	1430	Portal Pipe	outcland	
Station ID:	PS +5+0-82	Date: -SEPT-3031	Weather: Sunny Citt	strature
Sample ID:	not sampled	Coordinates:	- Johny Citt	3)04(03)
Sample Class:	SW	Site Description: Pipe	Coming Know wine	portal
Time:	17:15	Field Crew (circle sam	pler): C5 10 (3)	
Air Temp (°C):	16.8	Field Meter I	Jsed: V) Subjections	c()d
H2O Temp (°C):	2.9/2.5	1 - 1	10,7000/1000	DEAT
DO (mg/L):	[1.35 / la.d]	QA/QC Sample IDs	No.	
	- / 98.6	Duplicate:	Time:	1.5
Cond (µs/cm):		Trip Blank:	Time:	1.4
SPC (µs/cm):	1165/1160	Field Blank:	Time:	
pH:	7.68 /5.84	· · · · · · · · · · · · · · · · · · ·		
ORP (mV):	- /286.3	Picture #s: pipe		Transfer of
Turbidity (NTU): 2	1.11 / 1.48	Comments:	A POP	

	DARLING LLC A, USA • RiteintheRain.com
before PS 1430 OWR	- bolgal
Station ID: PS15 10	Date: 1-SEP-2021 Weather: Sunny, Some Clouds
Sample ID: 2021TAS-21	Coordinates: 61.53587 132.26451
Sample Class: 5W	Site Description: water flowing out of
	boleal
Time: 15:30	Field Crew (circle sampler): CF(SL)
Air Temp (°C): 18.8	Field Meter Used: Y2346x6/Y2225629
H2O Temp (°C): 1,8 / 1,7	
DO (mg/L): 11.61 / 12.07	QA/QC Sample IDs
DO (%): - /86.9	Duplicate: Time:
Cond (µs/cm): - / 646	Trip Blank:
SPC (µs/cm): 1145/1163	Field Blank: Time:
pH: 7.87 / 6.56	
ORP (mV): - /233.2	Picture #s: Portal Outflow
Turbidity (NTU): 1.76/0.23	Comments:
VIII 2	

			10 mm 20 mm	Op at		
		10	FICUS SHIW	ened 10's		
Uf	oper portel	confirmed site now	tono show	ened 10's	opposta	
Station ID:	PS 1430 %	Date: 01 Sopt	نان Wear	ther: < \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	مالم ماده الأملان	
Sample ID:			N 61,537		~40% clouds	s (wisp
Sample Class:	N/S	Site Description:	upper por	tel tan	I no wower	
Time:		Field Crew (circ	cle sampler):	discharge x	or at end	9
Air Temp (°C):			Meter Used:			
H20 Temp (°C): _		· 45	A PROPERTY.			
DO (mg/L):		QA/QC Sample ID	—) <u>s</u>			
DO (%):		Duplicate:	14000	Time:	ran district	
Cond (µs/cm):		Trip Blank:		Time:		
SPC (µs/cm):		Field Blank:	/	Time:		
pH:				1000		
ORP (mV): /	(F)	Picture #s:	David e	who were	d 4 3 3 6 6 1	
Furbidity (NTU).		Comments:	Princi	many en	a or pipe.	

368.0N

Station ID: R-0	Date: 2-SEPT-202) Weather: Over (456
Sample ID: 2021725-22	Coordinates: 61.53978 132.27/24
Sample Class: 5 W	Site Description: Upper Cache Ck, VS of
Sumple class.	diversion
Time: 10:15	Field Crew (circle sampler):
Air Temp (°C):	Field Meter Used: 734636 7325629
H2O Temp (°C): 5.4 /5.3	
DO (mg/L): [0.69/11,08	QA/QC Sample IDs
DO (%): - 187.4	Duplicate: Time:
Cond (µs/cm): -/284.3	Trip Blank:Time:
SPC (µs/cm): 450,3/456,5	Field Blank: Time:
pH: 829/7.27	
ORP (mV): - / [3]. [5]	Picture #s: US DS SUB RB LB
Turbidity (NTU): -0.02/-1.30	Comments: (lear no adout sm-la cabbles

Station ID: Sample ID: Sample Class:	2011 AS-23	Date: 2-SEPT-2021 Weather: Overcost winly Coordinates: 61.52730 132.29988 Site Description: Torn Leke outflow
Time:	11:00	Field Crew (circle sampler): CF.GD
Air Temp (°C):	6.5	Field Meter Used:
H20 Temp (°C):	6.2/6.1	12 11 12 Tag 4000/ 1200 1607
	10.53/10.78	QA/QC Sample IDs
DO (%):	- 186.8	Duplicate: 202(725-24 Time: 11:15
Cond (µs/cm):		Trip Blank: Time:
SPC (µs/cm):	274.4/278.2	Field Blank: Time:
pH:	8.00/7.09	
	-/185.1	Ficture #s: US D5 50b, RB, LB
urbidity (NTU):	1.31/-0.24	Comments: clar brown organics on sub
		No odove

365.0N

lite in the Rain.

JL DARLING LLC
Tacoma, WA, USA • RiteintheRain.com

Station ID: Tora Lyke	Date: d-SEP7- 2021 Weather: Cloudy
Sample ID:	Coordinates: 61.52732 132.30333
Sample Class:	Site Description: Tarn Late-white pecip
_	0.00
Time: 11-15	Field Crew (circle sampler): CF, SL
Air Temp (°C): 6.5	Field Meter Used:
H2O Temp (°C): 6 · \(\lambda / 6 \cdot \)	
DO (mg/L): 10.35/10.64	QA/QC Sample IDs
DO (%): -/85.8	Duplicate: Time:
Cond (µs/cm): - /80 2	Trip Blank:Time:
SPC (µs/cm): 276.8/2825	Field Blank: Time:
pH: 8.02/7.15	
ORP (mV):/1728	Picture #s: Pecip aco
Turbidity (NTU): 1.78/0.64	Comments:

Station ID:	Torn Loke	Date: 2-SEP-2021 Weather: Chudy	
Sample ID:		Coordinates: 61.52728 132.30353	
Sample Class:		Site Description: Fin Lake brown pricip area	
Time: Air Temp (°C): H2O Temp (°C):		Field Crew (circle sampler): Field Meter Used:	La de la companya de
	0.41/ 10.99	QA/QC Sample IDs	
DO (%):	84.4/84.4	_ Duplicate: Time:	
The state of the s	- /179.9	Trip Blank:	
	295.4/398.2	Field Blank: Time:	
pH:	7.42/6.25		
	-/199.5	Picture #s: Precip area	
urbidity (NTU):	1.44/3.88	Comments:	***

JL DARLING LLC
Tacoma, WA, USA • RiteintheRain.com

Station ID: Trip Blan Sample ID: 303/1725-2 Sample Class:	
Time: 1200 Air Temp (°C):	Field Crew (circle sampler): Field Meter Used:
DO (mg/L): DO (%): Cond (µs/cm): SPC (µs/cm): pH:	OA/OC Sample IDs Duplicate: Time: Time: Same Field Blank: Time: Time: Same
ORP (mV):	Picture #s:Comments:

Sample Time (24 hr) Sample Method Field Filtered & Preserved OAQC Sample Collected OAQC	Vell Name	wine?	LlyD-9	201 A		Project Number			4822
Veather 17i, overcest statelogger Details flownload info, etc.) Monitoring Well Details Well casing height (magl) D.20 Peth to Water (m) 9.860 Well casing height (magl) D.20 Purge Well casing height (magl) Field Readings Field Readings Time Purge Water Level (m) Temp (°C) DO (mg/L) Conductivity (us/cm) PH Redox (mV) Appearan Caseur, etc. DASS 2L G.O. 3.58 Colo. 7.21 H/6.0 24. Sample Time (24 hr) Sample Method Field Filtered & Preserved QAQC Sample Collected Pur is deficitual leaving an open hole open Austh Mant. M. Cours. Organics in Well.	ate		Aug S			Client		YG	EMR
NAME A SAMPLE TIME (24 hr) Sample Time (24 hr) Sample Method Sample Time (24 hr) Sample Time (24 hr) Sample Method	Sampler		JIYA			Project Name		Ke	etza
Monitoring Well Details Pepth to Water (m) 9.860 Well casing height (magl) Details Pepth to Bottom (m) SULL Estimated Water Volume (L) Purge Method Field Readings Time Purge Water Level (m) DO (mg/L) Conductivity (us/cm) PH Redox (mV) Appearan Odeur, 61 CA35 2L Sample Time (24 hr) Sample Method Field Filtered & Preserved QAQC Sample Collected OPUO General Notes, Calculations: Well broken off: Ca3ing laying an grown and phs Purge I solve to the laying an open hole open hush Manh-Put. Mo cours. Organics in well.	Veather		172	, overca	52				
Depth to Water (m) 9.860 Well casing height (magl) SU.(e) Tubing Depth (m) Field Readings Time Purge Water Level (m) Field Readings Time Volume (m) Appearan Octor, et (m) Sample Time (24 hr) Sample Method Field Filtered & Preserved OAQC Sample Collected			Í	J/A					
Depth to Bottom (m) SY. (e) Tubing Depth (m) SY. (e) Tubing Depth (m) Estimated Water Volume (L) Field Readings Time Purge Water Level (m) Temp (°C) DO (mg/L) Conductivity pH Redox (mV) Appearan odear, etc. CASS 2L CO. 3.58 (010 7.21 //6.0 7.4) Sample Time (24 hr) Sample Method Field Filtered & Preserved QAQC Sample Collected OPYO Field Filtered & Pre					Monitoring We	ell Details			
Field Readings Time Purge Water Level (m) Temp (°C) DO (mg/L) Conductivity (µs/cm) pH Redox (mV) Appearan Oderur, et (µs/cm) pH Redox (mV) Oderur, et (µs/cm) pH Red	epth to Wate	er (m)				Well casing hei	ight (magl)	0.20	
Estimated Water Volume (L) Field Readings Time Purge Volume (m) Temp (°C) DO (mg/L) Conductivity (µs/cm) pH Redox (mV) Appearance of the	epth to Botto	om (m)	54.	61	1	Tubing Depth (m)		
Field Readings Time Purge Volume (m) Temp (°C) DO (mg/L) Conductivity (µs/cm) pH Redox (mV) Appearan odeur, 81 A35 2L 6.0 3.58 (010 7.21 //6.0 24.) Sample Time (24 hr) Sample Method Field Filtered & Preserved QAQC Sample Collected OQUO (see Name: Lell Goker off: Ca Jing (quing on grown) and phs Pur is detached leaving an open hole lopen hosh Mant. Pur. No cours. Organics in well.			11.1.			Estimated Wate	er Volume (L)		
Sample Time (24 hr) Sample Method Field Filtered & Preserved OAQC Sample Collected OGUO Seneral Notes, Calculations: Well broken off. Ca 3: ng laying on grand and plas Puc is detached leaving an open hole lopen hosh Mant. Puc. No cover. Organics in well.			13400	osleve	Field Read	dings		W - 167	
Sample Time (24 hr) Sample Method Field Filtered & Preserved OAQC Sample Collected Oaquarity Oaquarit	Time			Temp (°C)	DO (mg/L)		pH	Redox (mV)	Appearance, odeur, etc.
O940 Seneral Notes, Calculations: Well broken off. Casing laying on grown and plus for love is defacted leaving an open hole lopen Rush marnt. pre. No cover. Organics in well.	0935	ZL		5.0	3.58	(010	7.21	116.0	٦4.7 <u>5</u>
Jayour (es) No Yes Name: Well broken off. Casing laying on grown and phos Our is defacted leaving an open hole open Rush Mount. Pr. No cover. Organics in well.							> 11		
Well broken off. Casing laying on grown and plus for leaving an open hole lopen Rush mant. pre. No cover. Organics in well.	Sample Tir	me (24 hr)	Sample	Method	Field Filtere	ed & Preserved	Q	AQC Sample Co	llected
Well broken off. Casing laying on grown and phis for is detached leaving an open hole lopen Rush mant.pv. No cover. Organics in well.	094	0	Ludwick	eve	es) No	Yes _A	lame:	
mant. pvc. No cover. Organies in well.	3eneral Notes	s, Calculation	a		Casi	ing layin	y on c	grand or	of plastic
mount. pvc. No cover. Organics in well.		Puc	is deta	chiel	leaving	an ope	in hole	open 1	WS4
Color of the color of the color of the		mant.	ov. //	1/2 0000	. Dra-	e de la circa	44 ll.	FEL	
		0	70	i cover	· · ·	rien in			
full pulc casing ce-aboached after sample		full puc	casing	ce-atora	ched at	for sam	ple		

Well Name		MW 10-0	1 /MWIO.	-07	Project Number 104822			1822			
Date		Aug 3/		ş-i	Client YG EN		EMR				
Sampler		JE /	4_		Project Name		Ke	etza			
Weather		172, Su	2				-				
Datalogger D (download in		N/	4 M	IJIO-0Z Monitoring We	Nad logge	C. No	1 downlos	del.			
Depth to Wa	ter (m)	MW10-01:	2 /mw10-	nz: 3.395	Well casing heig	ght (magl)					
Depth to Bott	tom (m)				Tubing Depth (n		,				
Well Diamete	er	2"	11.	, , , , , , , , , , , , , , , , , , ,							
Purge Metho	d	-	-		Estimated Wate	r Volume (L)					
			PIEN PER	Field Read	lings						
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	рН	Redox (mV)	Appearance, odour, etc.			
					>						
							A.				
Sample T	ime (24 hr)	Sample	Method	Field Filtere	d & Preserved	Q	AQC Sample Col	lected			
1700		-		Yes	No	Yes N	ame:				
General Note	s, Calculation		Not in	Scope	. No	Samp	eler.				
		MW10-C	1 19	arte	(in						
		MW10-0	MW10-02 Solmist Carologger at well. Not downloaded.								
)		L609	ed belo	w fally	pand	loat.					



Well Name	1 441	P90-01	4 /B		Project Number		104	1 822
Date		Ava 3/	21		Client		YG EMR	
Sampler		TI /A	-		Project Name		Ke	etza
Weather		12%	Sundy					
Datalogger De (download info			NIA					
				Monitoring We	II Details			The surface
Depth to Wate	r (m)	A:6.76	5 B:	15.845	Well casing heig	jht (magl)	Flush	
Depth to Botto	m (m)	A: 9.996	B:	28.239	Tubing Depth (m	1)		
Well Diameter Purge Method		2"			Estimated Water	r Volume (L)		
Turge Method				Field Read	tings			North State
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	рН	Redox (mV)	Appearance, odour, etc.
	_							
	=							
٠,		1						
Sample Tin	ne (24 hr)	Sample	Method	Field Filtere	d & Preserved	Q	AQC Sample Co	llected
16:45	,	-		Yes	No	Yes N	lame:	
General Notes		s: \	1.1 :0	5,000		ما م	Lilia	Oard
		. 4	105 14	scope	· LQ(4+	en or	tailing	6 461
		Qm6.	nkment	(000,				
)								

Well Name	X 1-74	P90-	. cj		Project Number		104	1822
Date		Aug 3/21			Client		YG	EMR
Sampler		A	- /-	FT.	Project Name		Ke	etza
Weather	8, 5 (2)	19	1/Sun	1.1				
Datalogger D (download int			ŇΑ	Monitoring We	ell Details	This was	District Control	
Depth to Wat	er (m)	-			Well casing heig	ht (magl)	_	_
Depth to Bott	om (m)				Tubing Depth (m	1)		
Well Diamete	er		Z"		F-10-1-120/-1-1			
Purge Metho	d	_			Estimated Water	r Volume (L)	_	
		1 1 1		Field Read	dings			Bee
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	pН	Redox (mV)	Appearance, odour, etc.
				55				
1				ē				
-								
Sample T	ime (24 hr)	Sample	Method	Field Filtere	d & Preserved	C	AQC Sample Co	llected
	-			Yes	No	Yes	Name:	
General Note	s, Calculation	s:				_		
		1						
		1 4 1	Lin	~ ().40m	down		
		P	SKO.			G. C.	•	
		À /	,					
	2),	No	1 10	Sign	2	3	,	
		/	(1	1.1	pul	D.		
Ĵ		LOCE	th on	40-11-9	Park	Koul	(



Well Name	10 mm 10 m	P89-	.(Project Number 104822			
Date		Aug 3/21			Client		YG	EMR
Sampler		JI /	JE A				Ke	etza
Weather		17 8	Sunul				70	
Datalogger D (download in		ρÌ	14					
				Monitoring We	ell Details		والالتالية	1 7 7 7 1
Depth to Wa	ter (m)	Day			Well casing hei	ght (magl)	0 /A	ush
Depth to Bot	tom (m)	1.8-	tu.		Tubing Depth (r	n)		
Well Diamete	er	1" -			Estimated Wate	er Volume (L		
Purge Metho	od	NIA	ł		Estimated vvate	, voidine (2,		
			J J== ' u	Field Read		4000		V MATE TO SE
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	pН	Redox (mV)	Appearance, odour, etc.
0						41		
<i>j</i>					and the state of t			
	= = ±1		Section Section 18 Section 18					
								194
	Ī							
Sample T	ime (24 hr)	Sample	Method	Field Filtere	ed & Preserved		QAQC Sample Co	llected
1641				Yes	es No Yes Name:			
General Note	es, Calculatior	ns:	10.11	007	in C.	•		
		`	N/E/II	110	in Scol	OR		
D)		1 1011	(
2 = 4		Med	dref					
		/		1	1			
		60	ded a	fs:11-	s paul	7.1		
)		LOC			, for	tory		



Vell Name		Pga-	3		Project Number		104	1822		
Date		Aug 3	121		Client		YG	EMR		
Sampler		T	/A-		Project Name		Ke	etza		
Weather		172	Sugar	K	gin last	244	/			
Datalogger D (download in		3 2 7	N	A Monitoring We		NS 2000		No. (Property)		
Depth to Wat	ter (m)	P	RY		Client YG EMR Project Name Ketza Retza Re					
Depth to Bott	tom (m)	3.4	195		Tubing Depth (n	n)				
Well Diamete	er	116			Fatimated Moto	s Valuma (L)	7)21	/		
Purge Metho	d		*		Estimated vvate	r volume (L)				
				Field Read	Readings					
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)		pH	Redox (mV)	Appearance, odour, etc.		
		OR .								
			-							
)								-		
		:						-		
	8									
Sample T	ime (24 hr)	Sample	Method	Field Filtere	d & Preserved	Q.	AQC Sample Co	lected		
145	7			Yes	No	Yes N	ame:			
General Note	s, Calculation	S:					E D	1 1		
		No	Sample	,	Dry.	Well 1	broken	off		
		at a16	ound le	vet. Ca	e placed	100/14	ou tob	0,		
Well. Not in Scope - located as to Road										



Well Name	1,000	Palo-1	24		Project Number		104	1822
Date		AIX S	h		Client		YG	EMR
Sampler		TI	AS		Project Name		Ke	etza
Weather	4	17:	, Sam	J	Rain lost	246		
Datalogger D (download inf		N	1/A	Monitoring We				
Depth to Wat	ter (m)	DR	4	#	Well casing heig	ht (magl)	1.641	
Depth to Bott	tom (m)	9,158			Tubing Depth (m	1)		
Well Diamete		2"			Estimated Water	r Volume (L)	DAV	
Purge Metho	d	12 Tab	82 T Tu	Field Read	dings		1/1	
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	рН	Redox (mV)	Appearance, odour, etc.
			Į.					
)——				><				
						_		
Sample T	ime (24 hr)	Sample	Method	Field Filtere	ed & Preserved	C	AQC Sample Co	llected
154				Yes	No	Yes I	Name:	
General Note	es, Calculation	ns:	. (,				
		Ity	Wel	The state of the s				
		Puc o	:08 5	Julai a	about	metal	Cosing	
		1 6		7+1,000	16000	1.0	3	
5								



Well Name		Pau-	114	_	Project Number		104	1822			
Date		Ava 3	121		Client		YG	EMR			
Sampler	THE STATE	AT/	TI		Project Name		Ke	etza			
Weather	31,450	14°	1006GS	. R	in (65) .	24h					
Datalogger D (download in		1		nge/ Monitoring We		- 277	200	C Sample Collected			
Depth to Wa	ter (m)	Dry			Well casing hei	ght (magl)	0.953	M			
Depth to Bot	tom (m)	3.114			Tubing Depth (r	n)					
Well Diamete	er_	2"			Estimated Wate	vr. Volumo (L.)					
Purge Metho	d	N/A			Estillated vvale	i volume (L)	· Dry				
			1 1	Field Read		W.A	Sun ANDE				
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	рН	Redox (mV)				
7											
			1:								
					1						
			4								
			<u>-</u>								
Sample T	ime (24 hr)	Sample	Method	Field Filtere	ed & Preserved	Q	AQC Sample Co	llected			
0837	-	N/A	7	Yes	No	Yes_N	ame:				
	es, Calculation	ns:					K	5 8			
		No	Sample	Wel	11 day	<u>.</u>					
		Wel	lin	good	condit	ion. N	s materia	e			
		neede	ġ.	•							
		9									
1					11	N					



Well Name	35 151	P9(0-11	<u>B</u>		Project Number		104	1822
Date		Aun 3/2	1		Client		YG	EMR
Sampler		A 1:	jī		Project Name		Ke	etza
Weather		142	, Outras	t. <	Rain lest	24 hou	l'	
Datalogger D (download in		11/0						
(download ii)	10, 516.)	MIT		Monitoring We	ell Details	113		
Depth to Wa	ter (m)	Dey	19		Well casing heiตุ	ght (magl)	1.313	
Depth to Bott	tom (m)	4.227			Tubing Depth (r	n)		_
Well Diamete								
Purge Metho	od			- 31	Estimated Water Volume (L)			
				Field Read	dings			
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	рН	Redox (mV)	Appearance, odour, etc.
				The state of the s				
-	y = 8.8							
Sample T	ime (24 hr)	Sample	Mathad	Field Filters	ed & Preserved		AQC Sample Co	llected
	ine (24 m)	Sample	Metriou					ilected
General Note	es, Calculation	e.		Yes	No	Yes N	allie.	
General Note			ig Stie	King up	above me	tal casi	-d	
*	. (J					
	Well &	ary. No	Sample					
		,	v					
				5				
(



Well Name		P96 -	110		Project Number		104	4822	
Date		P96 - Aug 3/2	21		Client		YG	EMR	
Sampler	- 11	JT /A	_	8	Project Name		Ke	etza	
Weather		14'6.	(Nelcas)	30					
Datalogger D (download in	etails fo etc)	A 30	gger	Monitoring We	ell Details	"5 11			
Depth to Wa	ter (m)	17.88		J	Well casing heig	ght (magl)	1,311 00		
Depth to Bot	om (m)	17.90			Tubing Depth (n	n)			
Well Diamete	er	2"			Estimated Water Volume (L)			1 m	
Purge Metho	d	NA							
				Field Read					
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	рН	Redox (mV)	Appearance, odour, etc.	
								_	
				* 17					
				-			n		
						/			
Sample 1	ime (24 hr)	Sample	Method	Field Filtere	ed & Preserved	Q	AQC Sample Co	llected	
0849		_		Yes	No	Yes1	lame:	-	
General Note	es, Calculation	is: Well	ovc. Sti	cks up	allowe w	ell metal	casivel		
		losuf	ficient	Volum	2. No.	Sample	or parame	ters.	
		111241							
					lę.				



Well Name	10 2 1	P90.7F	\		Project Number	104822				
Date		Ava 3/	2.1	0	Client		YG	EMR		
Sampler		51/1	1		Project Name		Ke	tza		
Weather	Stranding	14°.	DUMAd	Ra:	n Isst	24h				
Datalogger Datalogger Datalogger Datalogger			/A	Monitoring We				m 755W 75 H		
Depth to Wat	er (m)	DRY		volitioning vvo	Well casing heig	ght (magl)	0.064	YG EMR Ketza Appearance, odour, etc.		
Depth to Botte	om (m)	8.210	1		Tubing Depth (n	1)		-		
Well Diamete		2"	A	Estimated Water Volume (L)						
Purge Method	d ————————————————————————————————————	NI	A	Field Read	dings					
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	рН	Redox (mV)			
	and the same									
ĺ						No. of the last of	4132			
			-							
	-			and definition of the state of		/				
Sample T	ime (24 hr)	Sample	Method	Field Filter	ed & Preserved	Q	AQC Sample Co	llected		
090	5			Yes	. No	Yes N	lame:			
General Note	es, Calculation	is:	:)	da	Puc co	ising ha	s no me	tel		
	Cali		Jo Fem		1000					
	Carli		10 1 cm	·						
I_{χ}										
7										



Well Name		090-7	<u> </u>		Project Number		10-	4822		
Date		Ava 3	121		Client		YG	EMR		
Sampler		2E //	97		Project Name		Ke	etza		
Weather		142,	Turni	7.	n lock	246				
Datalogger D (download in:		1	NIA	A		3				
Depth to Wat	ter (m)	0.2-		Monitoring We	Well casing hei	ght (magl)	0,046			
Depth to Bott	tom (m)	9.20	4		Tubing Depth (r	m)				
Well Diamete	ər	2"	, ,			EN PLES	0.005 m			
Purge Metho	d		-		Estimated VVate	nated Water Volume (L)				
				Field Read	dings		10 S 10 T 10 T 10	10 20 -		
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	pН	Redox (mV)	Appearance, odour, etc.		
	4		_							
	-		-1	i e			and the second second second second			
			The state of the s							
						_				
				-						
Sample T	ime (24 hr)	Sample	Method	Field Filtere	d & Preserved	Q,	AQC Sample Co	llected		
09	34			Yes	No	Yes N	lame:			
General Note	es, Calculation	s: (N	sufficien	nt wet	er for	parameter	"S or Sq	mph.		
	2		^ ®			e: (%)				
			25							
)	- 12									



Well Name		76	8-04A		Project Number	ect Number 104822				
Date		Aug (+ /21	α.	Client		YG	EMR		
Sampler	1 1 1	37	14		Project Name		. Ke	Ketza		
Weather		152	Ducca	s t						
Datalogger D (download int		N	A					1		
Depth to Wat	er (m)	23.0		Monitoring We	ell Details Well casing hei	ght (magl)	1.32	7		
Depth to Bott	om (m)		462		Tubing Depth (r	n)	-			
Well Diamete	r	2'	1				195.	 J 94		
Purge Metho		Hydro	1:81		4.5	Estimated Water Volume (L)				
	Purge	Water Level		Field Read	dings Conductivity			Appearance,		
Time	Volume	(m)	Temp (°C)	DO (mg/L)	(µs/cm)	рН	Redox (mV)	odour, etc.		
12:56	10		3.9	5.96	694	9.11	347.2	71.5		
1>:28	26		3.9	5,65	694	7.25	323.5	76.0		
1:01	30		3.9	5.96	693	7.28	307	120		
1:03	40		4.0	5.44	694	7.32	293	130		
1:06	50		4./	5.35	694	7.36	283	133		
Sample Ti	me (24 hr)	Sample	Method	Field Filtere	d & Preserved	Q	AQC Sample Co	llected		
(3:1		1-goro	ift	es	No	Yes	lame:			
General Note	s, Calculation	s: \				1				
	77	xged c	nay 6	arameter.	s Stoler	1.Zex.				
	1 1)01	ni 7:1	good	condi	fice.					
. tlan	1.11	(4 .		1140-09	8-044.	-> D7	B:53	65~		
Well: s in good condition. Unidentiful Well immediately beside HYD-08-044 -> DTB: 5.365 - dry well										
	driller's sludge in the well									



Well Name		Core sho	ick well		Project Number	w Table	104	4822
Date		Core sho	- 21		Client		YG	EMR
Sampler		AT , J.	I		Project Name		. Ke	etza
Weather		16°C,	overca	st	Ta .		8	
Datalogger De (download inf		NIA						
				Monitoring We	No.	- 2		arest 250
Depth to Wate	er (m)	16.640	2		Well casing hei	ght (magl)	0	
Depth to Botto	om (m)	34.870	>		Tubing Depth (m)			
Well Diamete		4"			Estimated Wate	er Volume (L)		
Purge Method		bailer						
	Purge	Water Level	- 0-	Field Read	Conductivity			Appearance,
Time	Volume	(m)	Temp (°C)	DO (mg/L)	(µs/cm)	pH	Redox (mV)	odour, etc.
0846			8.7	9.37	300	7.72	100.2	0
					9			
	4							
				å				
			8 Ft 2				ч	
Sample Ti	me (24 hr)	Sample	Method	Field Filtere	d & Preserved	Q	AQC Sample Col	lected
0845	_	Bailes		<u></u>	No	Yes -N	lame:	
General Notes			Sec. of six					
			Well	in	Careshaols	hut.	has own	
	(non-	operation	-9/		1		has pum	r
	N.	6		171	† ·			
*								
)								



	- Au	,		Project Number 1				
		5/21		Client		YG	EMR	
	JI	AT	-	Project Name		K	etza	
44.8	19:	ougst				4		
5		NI	2					
	344		Monitoring We	II Details		North Arthur	وني باش	
)	5,5	42		Well casing hei	ght (magl)	0.94		
n)	20.	. 77	53	Tubing Depth (r	n)			
	2"		Estimated Water Volume (L)		27.456			
	(Jath	Cre/AMio	Field Read	dings				
	and the second s	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	рН	Redox (mV)	Appearance, odour, etc.	
		3.4	2.95		7.18	19.5	349.53	
54+		7.4	3.38	.1179	7.30	2.6	231.8	
521	12	1	3.69	1125		-9,6	189,7	
		χ.						
						2		
	-			,				
24 hr)	Sample	Method	Field Filtere	d & Preserved	Q <i>F</i>	AQC Sample Co	llected	
	Late		Yes	No	Yes N	ame:		
ılculations:	VIA 110				/	VA 6		
- 2	6,5	Y2		hel h	9000	cardilon	le _w .	
	20.23				V			
_	13,7-	78	x 2	- Z7.	456	· 7 2 82	7 3-	
	Purge olume 2 7 L 3 2 L 24 hr)	Purge Water Level (m) 24 hr) Sample Includations:	20. 77 20. 77 24 24 hr) Sample Method 10/16 24 hr) Sample Method 10/16 27. 3.4 24 hr) Sample Method	Monitoring We 5, 54Z 70, 77 70 70 70 70 70 70 70 70 70	Monitoring Well Details Well casing heir Tubing Depth (r Tubing Depth (r Estimated Water Field Readings Purge olume (m) Temp (°C) Tomp (°C) Temp	Monitoring Well Details Well casing height (magl) Zo. ZZ Tubing Depth (m) Zu Estimated Water Volume (L) Field Readings Purge olume (m) 3.4 2.9 1256 7.18 3.4 3.8 1179 7.30 3.4 3.6 1125 7.36 3.4 3.6 1125 7.36 Well casing height (magl) Field Readings Purge olume (L) Field Readings A	Monitoring Well Details 6, 547 Well casing height (magl) 70, 77 Tubing Depth (m) Estimated Water Volume (L) Field Readings Orge Olume Water Level Temp (°C) OO (mg/L) Conductivity (µs/cm) Purge Olume 3,4 2,97 1256 7,18 19,5 3,4 3,48 1179 7,30 2,6 3,14 3,64 1175 7,36 20,6 Purge No Yes Name: OAQC Sample Conductions:	



Well Name		P90-	7B		Project Numbe	GITHILL.	10)4822	1	
Date		Ava 3/	21		Client	N 11 T	YG	Appearance, odour, etc. 1.5 56.97 3.8 63.8 Sample Collected Meedec fo purge		
Sampler	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	TT /			Project Name		K	etza		
Weather		14°	Suppl	Ryin	1951	246		V The	-	
Datalogger E (download in			,	V/A	1931			142	4	
		North Con-		Monitoring We			1119 2011			
Depth to Wa		6.26	8		Well casing hei	ght (magl)	O.			
Depth to Bot	tom (m)	17.00	3		Tubing Depth (i	m)	040			
Purge Method Valkea 1 Hydroliff Estimated Water Volume (L)				\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \						
r drye Metrio		Wate	sa 3 Hyo	Field Readings						
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	рН	Redox (mV)		NT	
0946	15 L	13.004	15.5	8.13	214	7.92	31.5			
1440	24L	*	9,8	5.90	208	7.04	133.8	activities.		
Ì					1		4	100	1	
					240	E 1			1	
	- I 9		C114.						1	
		, *·		ſ		-			1	
Sample Ti	ime (24 hr)	Sample	Method	Field Filtere	d & Preserved	QA	AQC Sample Co	llected		
144	0	Watters		Yes	No	Yes N	ame:			
General Note	s, Calculations		01.	7 7	h concr	ple				
	le		13 +11	0) L W1	V. (())(011					
17.003 10.735 X2 Z1.470 X 3 64.41 L needed to purge										
	M	rged dr	y after	22L.	direct s	ample af	ter ZZL			
_ Deb					purging -		2			
	-	- 01		J	, 0					



Well Name		HYD-0	8-02		Project Numbe		10	104822	
Date		Aug 4,	/21		Client		YG	EMR	
Sampler			4 T		Project Name		K	etza	
Weather		16.0	over	cxt					
Datalogger Do (download inf		NIA	ł.						
		The state	1 10g n	Monitoring We	ell Details				
Depth to Wate	er (m)	137.899			Well casing hei	ght (magl)			
Depth to Botto	om (m)	164.35			Tubing Depth (i	m)			
Well Diameter		2"					umo (I.)		
Purge Method		1-140/0	Slover		Estimated Wate	er Volume (L)			
			W 4 - 5 -	Field Read	dings				
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	рН	Redox (mV)	Appearance, odour, etc.	
1745	21		6.7	6.83	333	7.03	148.1	56.65	
1, ,						7.0			
						5.0			
					-				
Sample Tir	me (24 hr)	Sample	Method	Field Filtere	d & Preserved		AQC Sample Co	llected	
17:5		Hurbos	leve	(fes) No	Yes N	ame:		
General Notes	s, Calculation	s: \ ()			1 (1	1 .		
			6	VC)	hielting g	ibae 1	utal cas	im.	
			Well .	A COL	od Shepa			/ =	
				The good	- orapi	•			
¥1									
)									



Well Name	184	GT-	10-01		Project Number		104	4822	
Date		Aug d	,		Client		YG	EMR	
Sampler		五	/A	-	Project Name		Ke	etza	
Weather		15		enast		8			
Datalogger D (download int			- ,	NA				8	
	30.70			Monitoring We	Tubing Depth (m) Estimated Water Volume (L) eld Readings (mg/L) Conductivity (µs/cm) PH Redox (mV) Appeadodu				
Depth to Wat	er (m)	45	15/	727	Well casing hei	ght (magl)	1.200		
Depth to Bott	Bottom (m) Tubing Depth (m)								
Well Diamete	er	2							
Purge Metho	d	Hydro	Seene		45 17 17 18 18 18 18 18				
			Stirley,	Field Read		JE LA HILL			
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)		pН	Redox (mV)	Appearance, odour, etc.	
16:00	2		7.1	1.95	826	7.47	24.9	17.28	
							10	-	
	8			4				/4	
			-		-				
Sample T	ime (24 hr)	Sample	Method	Field Filtere	d & Preserved	Q/	AQC Sample Col	lected	
15:38	9	144/10	sleeve	(es) No	Yes N	ame:		
	s, Calculation	s: "			- (
	W	ell Cos:	ng (003	e in c	fround-				
					Cancre	1			
	36		1 6034	CP of	(ancre	K.			
				22			10		
)		×							



Well Name		HYD-0	8-10		Project Numbe		10	4822	7		
Date		Aug 4/	21		Client		YG EMR Ketza				
Sampler		31/A			Project Name		Ketza		1		
Weather		IHC.	Overcaje	,	·				1		
Datalogger [(download in			MA	Monitoring We	ell Details	2, - 1 1	VID - 1-7-7-1				
Depth to Wa	ter (m)	65.2			Well casing hei	ight (magl)					
Depth to Bot	tom (m)	111.97	15		Tubing Depth (m)			1		
Well Diamete	ell Diameter 2				155				1		
Purge Metho	ge Method HydroSleeve			Estimated Wate	er Volume (L)						
illi ett ja		1-11-1	7	Field Read	dings		1 1 1 1 1				
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	рН	Redox (mV)	Appearance, odour etc.	1		
1100	21		8.2	5.36	1012	7.68	581.2	39.65			
	a a		34								
			-								
			÷								
							-		-		
Sample Ti	me (24 hr)	Sample	Method	Field Filtere	d & Preserved	Q.A	QC Sample Col	lected	ĺ		
1100)	Hydrosle	eve	Yes) No	Yes—N	ame:				
	s, Calculations		ا امه				v-1 (-				
	Λ 01 10	jen ala 1	nor Nave	-)-61	of on it	, ecb	o feel to				
	Elemon.	b. Or	jan-c A	natter of	og on it	of ove					
	_				wer meta						
1	\\ 0\cl	Colin	48	ن ماهما	A (10)	(· ~)					
	1~ (2014)	CATING	J-1	100 JC 11	Stelled.	. — > (wor ply				



Well Name		440-0	8-098		Project Number		10-	4822		
Date		Aug 4/	21		Client	- M - M - 1	YG	EMR		
Sampler		21/	A		Project Name		Ke	etza		
Weather		14'2	outrest	L	7		- 			
Datalogger D (download inf					724					
1102 31 31	a 1	911, 411		Monitoring We				the state of		
Depth to Wat					Project Name Ketza Sell Details Well casing height (magl) Tubing Depth (m) Estimated Water Volume (L) Sings Conductivity (µs/cm) PH Redox (mV) Appearan odour, etc. Appearan odour, etc.					
Depth to Botto	om (m)	3.350	1		Tubing Depth (r	n)	YG EMR Ketza 1.150 Redox (mV) Appearance odour, etc QAQC Sample Collected Name: SGM COWN.			
Well Diamete	r	1''		V	Estimated Water	er Volume (L.)				
Purge Method	Purge Method					-volatile (L)	Redox (mV) Appearance, odour, etc. AQC Sample Collected ame:			
				Field Read						
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)		pH	Redox (mV)			
•										
7 14										
Sample Tir	me (24 hr)	Sample	Method	Field Filtere	d & Preserved	Q	AQC Sample Col	lected		
0910				Yes	No	Yes N	Name:			
General Notes	s, Calculation	s:	Nell	block	ed 3	3.356	m dow	'v -		
			No wa	fa.			1			
		F)	Well	Casing	(00 % ·	r degr	nol.			
)										



GROG	NOVA	TEIX OF	(IVII EE	OOLL		OTTLE	•		
Well Name		tIND-0	8-09A		Project Number		104	1822	
Date		10g 4	/21		Client		YG	EMR	
Sampler		TI	1	-	Project Name		Ke	etza	
Weather			7						
Datalogger D (download in									
				Monitoring We	II Details	W. Tr		45-5-179	
Depth to Wat	ter (m)	13.960)		Well casing hei	ght (magl)	YG EMR Ketza L.OZO Redox (mV) Appearanged odour, et al. 20 QAQC Sample Collected		
Depth to Bottom (m)		13.960	.000		Tubing Depth (i	n)			
	Well Diameter				Estimated Water Volume (L)				
Purge Method		Hydros	leve						
التناييا	, 1			Field Read			A Partie of		
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	рН	Redox (mV)	Appearance, odour, etc.	
9:26	2		6.9	10.59	465	5.09	146.2	0	
		80							
								v.	
							2.5	-	
Sample T	ime (24 hr)	Sample	Method	Field Filtere	ed & Preserved	Q	AQC Sample Co	llected	
9:4	5	Hudros	leeve	Yes	No	Yes -1	lame:		
General Note	es, Calculation	ns:				•) (5	
		1061	1-00	N -	mand				
		VVC	(00%	"	giores.				
			•				6		
2			je.						
Ļ	8								
ŕ									



GROU	NDWA	VIER S	AMPLE	: COLL	ECHON	SHEE	T			
Vell Name		KR-05	- 688		Project Number		10-	4822		
ate		Aug 4	121		Client		YG	EMR		
Sampler		TI	AT		Project Name		K	etza		
Veather			lli nu	krast					1	
Datalogger De download inf		AVA	100							
		THE PERSON	14 14 E.L.	Monitoring We	Well Details					
Depth to Wate	er (m)	47.	472		Well casing height (magl)					
Depth to Botto	om (m)	72.	42		Tubing Depth (m)					
Well Diamete	r	2"				111000				
Purge Method	,	Hydro	1: F4		Estimated Water Volume (L) 49.894					
		310 111	WEST T	Field Read			R VAL	Bu 5 70		
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	рН	Redox (mV)	Appearance, odour, etc.	N	
1630	(OL		5.3	6.23	828	7.28	153.0	0	,	
1637	204		4.6	6.20	418	7.27	152.8	0		
140	25		4.6	6.21	814	7.26	152.2	0	1	
126			* * *			. ~			1	
									1	
							-		1	
	A									
Sample Tir	me (24 hr)	Sample	Method	Field Filtere	d & Preserved	0/	AQC Sample Col	lected		
		المراجبية ا		Yes	- 15 EM			ected .		
Peneral Notes		Hydrolia s:	<i>:/</i>	res	/ NO	N	ame: F. S	ν,		
					, . ×	10/0	1/	. /		
4	47	.472				VVC.	l'ing	oof		
	- 72	.420					and,	lia		
	24.	948	メフ・	49	901					
	4	1		. , , , ,	0-16					
	Puge	30L	\$ 59	impled.	Paramet	les de	66			
	. 0			()	THEME	المحرر راب	1046			



Well Name		1510	prtal m	د اا	Project Number	" I'E'T'S	YG EMR Ketza Appearance, odour, etc.			
Date		Aug U	71		Client		YG	EMR		
Sampler		TH	IA.		Project Name		Ke	etza		
Weather		Bi	nverce	.ct	W					
Datalogger Do (download inf			N/a							
1 1			May a William	Monitoring We	ll Details		g ni jilika ni y			
Depth to Wate	er (m)	62	870	Κ.	Well casing hei	ght (magl)	0			
Depth to Botto	om (m)	96	. 344		Tubing Depth (r	n)				
Well Diamete	r .	1	t"		Cotymated Mate	or Volume (L)				
Purge Method			Hydrostee	vi	Estimated Wate	er volume (L)	Appearance			
				Field Read	dings			- * Ph		
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	pH	Redox (mV)	Appearance, odour, etc.		
14:09	2		8.0	8.72	597	7.59	157.5	1.72		
					4		II.			
		181								
	me (24 hr)	Sample	Method	Field Filtere	d & Preserved	QA	AQC Sample Col	lected		
14:1		-yacos	ler/e	Yes) No	Yes N	ame:			
General Note	s, Calculation	s: ()	1		11.	. 1. 7.	- 0			
	1	Nell	4" in d	lianeter.	dict	10+ Ne	we Cap	on it		
	and	we	201	Ar U"	0	, 01				
	1.		V VALV	77	Caps.	16/1	open			
	1250	n apo	indoned	7+1	ucturk.					
		8								
)		-					300			

GROU	NUVA	ILIX OF	ZIVII EE	OOLL	LOTTON			1. 20	
Well Name		Vole	Milly	vell	Project Number		104822		
Date		Aug 5	18		Client		YG	EMR	
Sampler	in the	A	SI		Project Name		Ke	etza	
Weather		160	c. Ou	rest				, , , , , , , , , , , , , , , , , , ,	
Datalogger De (download info		TO I	MA				* *		
download into	0, 0.0.)	TEPELA		Monitoring We	ell Details				
Depth to Wate	er (m)				Well casing heig	ht (magl)	0		
Depth to Botto	om (m)	-			Tubing Depth (m	1)			
Well Diamete	r	4	Estimated Water Volume (L)						
Purge Method	Purge Method		0			3 353		37.2	
	LIL SHE	Weterlevel		Field Rea	dings Conductivity			Appearance,	
Time	Purge Volume	(m)	Temp (⁰ C)	DO (mg/L)	(µs/cm)	pH	Redox (mV)	odour, etc.	
1885	500		6.2	5.20	582	7.83	-78.9	0	
					14 1525 - 14		je.		
		-	251	-: "					
					5-11				
Sample T	ime (24 hr)	Sample	: Method	Field Filter	ed & Preserved	C	AQC Sample Co	ollected	
	00	Ana		Ve:	s) No	Yes	Name:		
	es, Calculatio	ons:			,				
		14	A Pro	m hos	e O pom	e Thack	/ - ×		
		191	1	*		1 -			
		4.	101	214	nin Gefe	ne San	rple.		
		4 %	1						
) .									



Well Name		LIYE	08-1	7	Project Number		10-	4822
Date		Aug C	-/21	191	Client		YG	EMR
Sampler		74/	9	4.6	Project Name		Ke	etza
Weather		12/	16e	Octras	1			
Datalogger [(download in	Details ifo, etc.)	搜	NIA	Monitoring We	4. 1			Sa Televisia
Depth to Wa	ter (m)	3.17		vioritioning vvo	Well casing hei	ght (magl)	0.99	
Depth to Bot	tom (m)	41.4		4 3 NO	Tubing Depth (r	n)	- , Y	
Well Diamete		- 7	2"		Estimated Water Volume (L)			
Purge Metho	od	-43	and the	Field Read				
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	рН	Redox (mV)	Appearance, odour, etc.
1100	80		3.4	1.10	554.	6.82	-55.9	147,97
	l' s	. 2	1=1		V .		u ji e	10
							7 +	
1 6		14			1 1	* · · · · · · · · · · · · · · · · · · ·	5 14	
		100			3 18	*		
	- it	*				1970		
Sample 1	Time (24 hr)	Sample	Method	Field Filtere	ed & Preserved	Q	AQC Sample Co	llected
1100)	LOWF	low	Yes	No	Ye <u>s</u>	lame:	
General Not	es, Calculation					,		
				- ku		1		
		noty	- 801	2	vell vlear	all.		AL IN
		ampled	after	(2 cha	eged		, s , w a	
A			1.50	3 to PV	· Cl	,e***		
		A: 0.	of L	3 70 1	0			11



Well Name	Mend Comp	Well	Project Number	7 5 5	10	C Sample Collected			
Date	Aug 5/2	1	Client		YG	EMR			
Sampler	A America	/ Suppose	Project Name		K	YG EMR Ketza Appearance, odour, etc.			
Weather	42 = 0) Wester	11	100					
Datalogger Details (download info_etc)	MA	Monitoring We				· ·			
Depth to Water (m)	NAME OF TAXABLE PARTY.	Morntoning VVC	Well casing hei	ght (magl)	N	Appearance, odour, etc.			
Depth to Bottom (m)	THE PERSON NAMED IN		Tubing Depth (r	n)		3.			
Well Diameter	4								
Purge Method	Pump		Estimated Wate	er Volume (L)					
		Field Read	dings		1 1 3	L - T L T - W			
Time Purge Volume	Water Level (m) Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	рН	Redox (mV)				
60	29.5	5.71	460	7.46	72.6	0			
	1				u .				
= 1	FA.			5 ec					
	1 2 4								
	V.								
		12	0						
Sample Time (24 hr)	Sample Method	Field Filtere	d & Preserved	QA	AQC Sample Col	lected			
2020	PUMP	Yes	No	Yes Na	ame:				
General Notes, Calculations	S	Al A							
a a		ý	V.,	20	\$)	≅			
	9								



Vell Name		Pale.	-12B		Project Number		10)4822			
ate		Aug 3	3/21		Client		YG	EMR			
Sampler		7-	(A-		Project Name		К	0.944 Appearance,			
Veather		17:	Sonne	(Rain	· (ast	246 .				
atalogger D download inf			NIA			1,000					
				Monitoring We	ell Details	100		10 X 15 11			
epth to Wat	0.600			M-							
epth to Botte	om (m)	9.072	2		Tubing Depth (r	n)					
Vell Diamete	r	7"			Estimated Wate	er Volume (L)	· 0.1	,			
urge Method	1	Bailer	Estimated Water Volume (L) 0, 944			4					
	Purge	Water Level		Field Read	dings Conductivity			Annearance			
Time	Volume	(m)	Temp (°C)	DO (mg/L)	(µs/cm)	pН		odour, etc.			
1512	IL		6.6	2.95	559	7.54	92.3	1.87			
1515	2L	×	4.8	3.30	566	7,58	67.7	4.29			
1518	3L		4.4	3.69	563	7.59	47.8	7.70			
7.	1	<u> </u>	1)7								
	9										
				-		-		×			
Sample Ti	me (24 hr)	Sample	Method	Field Filtere	ed & Preserved	Q.F	AQC Sample Co	llected			
152	D	Bailer		Yes	No	(Yes) N	ame: P96-1	12.D			
	s, Calculations	s:			18.						
		8.60				()	uplicate	Ac west			
		9.0	f2 ——								
		0.4	72	x2 =1	0.444	X 3	= 2.8	32 L Progr			
	Q	VC 0	00 54	idring	960UL M	1/-1		Tuege			
	\		, (C),		101	the Ca	Sing				



Well Name		GT-	10-66	A	Project Number		104	4822		
Date	3, 3,27	Aun	5/21		Client		YG	EMR		
Sampler	"(8" X - V	JE	100		Project Name	All property	Ke	etza		
Weather	1 1 1 5	150	, oulcel	l						
Datalogger D (download in		NI	A	Monitoring We	ell Details			7 7 7 1 1 1		
Depth to Wa	ter (m)	39	.650		Well casing hei	ght (magl)	1.08			
Depth to Bot	tom (m)	(4	3.54		Tubing Depth (i	m)				
	Well Diameter Purge Method		FRE		Estimated Wate	er Volume (L)		Redox (mV) Appearance odour, etc. 41, 0 48.6		
Purge Metho			(Field Read						
Time	Purge Volume	Water Level	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	рН	Redox (mV)	Appearance, odour, etc.		
1(:44			6.8	7.36	(१११	12.19	-41.0	4		
)				ж						
2		27	*							
-	1									
			2							
Sample T	ime (24 hr)	Sample	Method	Field Filtere	d & Preserved	Q	AQC Sample Col	llected		
)1./ (50	Bailer)(e)s	No	Yes N	ame:	-		
	es, Calculation	is: M	1							
	Only	1/4	of las	40 1	2025/		11111	2		
1	11/0/1	-1-1	191	se g	erus i	soule f	Net octa	-(
	,,,,,	Vent dry	Wif	dr	echarge.					
							a F 100			
)										



Well Name		HYD-C	8-08)	Project Numbe		10	104822 YG EMR Ketza			
Date		Auc 31	121		Client		YG	EMR			
Sampler		TE	/A	4	Project Name		K	etza			
Weather		Hº.	NJOSCO	12							
Datalogger D (download inf			NIA					9			
Depth to Wat	er (m)	. Q12	18	Monitoring We	ell Details Well casing hei	aht (maal)	Law	YG EMR Ketza (mV) Appearance, odour, etc. 7 -2-95 0			
Depth to Botte	om (m)			-	Tubing Depth (i		1,410)			
Well Diamete	104, 375										
			¥		Estimated Wate	er Volume (L)					
Purge Method		Hydros	(eve	Field Read	No ac		odour, etc.				
Time	Purge	Water Level	Temp (°C)	DO (mg/L)	Conductivity	рН	Redox (mV)				
12:36	Volume 2)	(m)	5.5	學3.32	(µs/cm)	6.02		odour, etc.			
	7	1	34 5	10.3172	070	0.2	115,T	200			
)						2					
			0								
37 = =				* T				- E			
	7		-			· ·		× ~			
- 4			- 14	2			2				
Sample Tii	me (24 hr)	Sample	Method	Field Filtere	d & Preserved	0.0	ACC Cample Co	Vocate d			
				Yes				liected			
\325 General Notes		Hydrosla	Je	Yes	No	Yes N	ame:	->-			
4	, calculation	Dela	odor.	n water	1'R	i 'y lei	1 color.				
)	We'			er to 1	Loose	in gro	ind, co	acked			



Depth to Water (m) Depth to Bottom (m) Nell Diameter Datalogger Details NA B. 8666 15.597	Monitoring We	ell Details Well casing he Tubing Depth (Estimated Wat	m) er Volume (L) pH 7. 46 7.39	13.447 Redox (mV) 100.6	Appearance, odour, etc.
Veather Depth to Water (m) Depth to Bottom (m) Vell Diameter Purge Method Purge Volume 15.597 Time Purge Volume 16.20 17.20 18.8666 18.8666 18.8666 18.8666 18.8666 18.8666 18.8666 18.8666 18.8666 18.8666 18.8666 18.8666 18.8666 18.8666 18.8666 18.866666 18.8666666 18.866666 18.866666 18.866666 18.866666 18.866666 18.866666 18.866666 18.866666 18.866666 18.866666 18.866666 18.866666 18.866666 18.866666 18.8666666 18.8666666 18.8666666 18.8666666 18.8666666 18.866666666 18.86666666666	Field Read DO (mg/L) 3-05	Rein (a) ell Details Well casing he Tubing Depth (Estimated Wate dings Conductivity (µs/cm) 519	ight (magl) m) er Volume (L) pH 7. 46 7.39	1.220 13.442 Redox (mV)	Appearance, odour, etc.
Depth to Water (m) Depth to Water (m) Depth to Bottom (m) Vell Diameter Purge Method Purge Water Level (m) Time Purge (m) Purge (m) Temp (°C) 1012 13L 4.4 10120 26L 3.9	Field Read DO (mg/L) 3-05	Well casing he Tubing Depth (Estimated Wate dings Conductivity (µs/cm) 519	ight (magl) m) er Volume (L) pH 7. 46 7.39	1,220 13.447 Redox (mV)	Appearance, odour, etc.
Depth to Water (m) Depth to Water (m) Depth to Bottom (m) Vell Diameter Purge Method Purge Water Level (m) Time Purge (m) Purge (m) Temp (°C) 10,20 202 3.9	Field Read DO (mg/L) 3-05	Well casing he Tubing Depth (Estimated Wate dings Conductivity (µs/cm) 519	m) er Volume (L) pH 7. 46 7.39	13.447 Redox (mV) 120.6	Appearance, odour, etc.
Depth to Bottom (m) 15.597 Nell Diameter Purge Method Purge Water Level (m) 10,20 20L 3.9	Field Read C) DO (mg/L) 3-0 5	Well casing he Tubing Depth (Estimated Wate dings Conductivity (µs/cm) 519	m) er Volume (L) pH 7. 46 7.39	13.447 Redox (mV) 120.6	Appearance, odour, etc.
Depth to Bottom (m) 15.597 Vell Diameter Purge Method Purge Water Level (m) 10.20 202 3.9	3-05 2,55	Tubing Depth (Estimated Water dings Conductivity (µs/cm) 519	m) er Volume (L) pH 7. 46 7.39	13.447 Redox (mV) 120.6	Appearance, odour, etc.
Veil Diameter Purge Method Purge Water Level (m) Time Purge (%C) 1012 13L 4.4 10120 26L 3.9	3-05 2,55	Estimated Water dings Conductivity (µs/cm) 519	pH 7. 46 7.39	Redox (mV)	Appearance, odour, etc.
Purge Method Purge Water Level Temp (°C 10/20 26L 3.9	3-05 2,55	Conductivity (µs/cm) 519	рн 7. 46 7.39	Redox (mV)	Appearance, odour, etc.
Time Purge Volume (m) Temp (°C 10.7.20 20.4.4 3.9	3-05 2,55	Conductivity (µs/cm) 519	рн 7. 46 7.39	Redox (mV)	Appearance, odour, etc.
Time Purge Volume (m) Temp (°C 10.7.20 206 / 3.9	3-05 2,55	Conductivity (µs/cm) 519 516	7.46 7.39	120.6	odour, etc.
Volume (m) Temp (°C 1012 13L 4.4 1012 3.9	3.05	(µs/cm) 519 516	7.46 7.39	120.6	odour, etc.
10:20 266 / 3.9	2,55	516	7.39	119.1	
10:20 266 / 3.9		516	7.31	119.1	35.6/
10:33 39 4 3.8	3.07	114	-		
			7.48	124.3	93,13
		-21.1	. 10		
			Ψ.	· ·	
			-	Jan 1918	
County Time (24 h.)					
Sample Time (24 hr) Sample Method		ed & Preserved		AQC Sample Co	llected
General Notes, Calculations:	(Yes)	No	Yes_N	lame:	THE
				2	10
8.866 15.597				100	
	10 11				
6.731 X2	13.4	62 X	3 40	.386L1	weeks purged
Puc Sticks at	have said	2000	u.	reach.	



Well Name		BH-10	-DIB		Project Number		104	1822
Date			3/21		Client		YG	EMR
Sampler		A= 1	(JI		Project Name		Ke	etza
Weather		176	CUMAN					
Datalogger De (download info	etails o, etc)	7	NA				.5	
			1	Monitoring We		4		
Depth to Wate		ry			Well casing heig		0.96	
Depth to Botto	om (m)	3.39			Tubing Depth (m	1)		
Well Diameter	· L.V.	t "			Estimated Water	· Volume (L)		
Purge Method	1 1							
	Purge	Water Level		Field Read	lings Conductivity			Appearance,
Time	Volume	(m)	Temp (°C)	DO (mg/L)	(µs/cm)	pН	Redox (mV)	odour, etc.
		The last and the second districts			a			
.8								
	1							
	V.							
	v							K.
Sample Ti	me (24 hr)	Sample	Method	Field Filtere	d & Preserved		QAQC Sample Co	llected
				Yes	No		Name:	() S (80)
1710 General Note	s, Calculations	s:		19152	100000	(NSE(N))	YOTH NEW YORK OF THE PARTY OF T	
		dry. 1	Jo Farn	00				
	Voc			P.C.				
)		141						



Vell Name		RH-10	-01A		Project Number		10-	4822
Date		Aug '	3/21		Client		YG	EMR
Sampler		TI /	4		Project Name		K	etza
Weather		17%	Sunni	/				*
Datalogger D download in		1.77	NIA					
	1 1 1		E-1-191	Monitoring We				era PSEATE
Depth to Wat	er (m)	10.98	5		Well casing heigh	ght (magl)	0.94	
Depth to Bott	om (m)	11.59	2		Tubing Depth (r	n)		
Well Diamete	er	2	υ -		Estimated Wate	or Volume (L)		,
Purge Metho	d	B5.60		Z	Estimated vvale	i volume (E)	1.214	1
1000	P. C.			Field Read				Appearance;
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	рН	Redox (mV)	odour, etc.
1713	1.2		Ce.1	7.45	714	7,43	64.2	710
1715	2.4		4.3	7,60	703	7.35	68.9	091
1717	3.6		5.5	6,47	686	7.30	72.3	784
91	* v :							
		. · · · · · ·						
E .	1.		_				N &	
							7	
Sample T	ime (24 hr)	Sample	Method	Field Filtere	ed & Preserved	Q	AQC Sample Co	llected
100			Medica	Ves	No		lame:	
General Note) es, Calculation	Bailes 1s:		l es) 140	160	iaino.	
		10.985		9		*		
		0.00		1 7	214 ×	7 3.	642 to	purge
		0.607	XZ	; 1. 2	X)		V
	Qu	0000	Class		1 1			
	100	Libral	24-CKZ	96006	Melal	casing.	(8)	
	Nell	Stindu						



GROO	NOTTA							
Well Name		BH-10	05		Project Number		104	1822
Date		Α.	5/21		Client	" The S	YG	EMR
Sampler		7	I Ar		Project Name		Ke	etza
Weather		170	. Sur	14				
Datalogger De (download inf			(\)	A'		9		
(NEW YORK		Monitoring We	II Details	1-1 - 5-	S - Hug	71 2 1 2 1 1 2 1 1 1
Depth to Wate	er (m)	4.41	ø5		Well casing hei	ght (magl)	0.7	53
Depth to Botto	om (m)	9.48	,2		Tubing Depth (r	m)		
Well Diamete	r	7"			Estimated Wate	or Volume (L)	(1)	201
Purge Method	d William	Hydro	(: f1		Estimated Water	or volume (L)	10	.034
				Field Read	dings			
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	рН	Redox (mV)	Appearance, odour, etc.
1960	(0		3.1	5.40	476	7.60	30.3	457.0
1903	220		2.5	7.40	451	759	91.0	484.0
1906	30		2.4	7.35	944	7.49	46.9	618.0
	-							
					- 11			
			8					
						14		
Sample T	ime (24 hr)	Sample	Method	Field Filtere	ed & Preserved	Q	AQC Sample Co	llected
19:19	5	Lyclo	1:A.	(es) No	-¥es N	ame:	
General Note	es, Calculation	15.						
	4.	465						
	d	482						
	5	.017	x2	: 10.0	osy x	3 : 30	0.102	
	. 1		A	4	1.			
1	W	ell in	E) 000 (3	cano	litien			>
1			•	4				



GROL	INDWA	ATER S	AMPLE	COLL	ECTION	SHEE	:T	
Well Name		BH10-	02		Project Numbe	r - 10	10	14822
Date		Au 3/22			Client	The Late	YG	EMR
Sampler	13.00	A	-1		Project Name		К	etza
Weather		176,	Sunau					
Datalogger [(download in		Nol	- (Monded			71	
COMMODITION OF	110, 010.)	100,		Monitoring VV	ell Details	17 KE		
Depth to Wa	ter (m)	5.39	5		Well casing he	ight (magl)	0.88	5
Depth to Bot	tom (m)	14.0	52		Tubing Depth (m)		
Well Diamete	er	z"					40 1 1	
Purge Metho	od .	Grant Land	Hydr	.	Estimated Wate	er Volume (L)	19.11	1
	1 1	ESING	11 700	Field Read	dings		1277	5-11 L
Time	Purge Volume	Water Level (m)	Temp (⁰ C)	DO (mg/L)	Conductivity (µs/cm)	pH	Redox (mV)	Appearance, odour, etc.
	19		3.8	3.65	489	7.81	-108	35.67
	38		2.8	2.96	492	7.71	-104.9	47.71
	57		2.6	2.53	493	7.70	-101.5	
	2				,	,,,,		
			_					
Sample T	ime (24 hr)	Sample	Method	Field Filtere	ed & Preserved	Q	AQC Sample Co	llected
.0		II lost	M	(es			lame: BH-10	
18:15 General Note	es, Calculation	HYAIOI.	++					-000
		5.395				(1	242 }	o ourde
	\	4.952		0 19	.114 ×	Dr.	,	()
	-/	9.50	of X	-				
	> 0							×



Vell Diameter 2	Vell Name		P90-9	8;		Project Number		104	1822
Vealiner ITY Survey Nationager Details N/A Monitoring Well Details Well casing height (magl) Depth to Water (m) 8.185 Well casing height (magl) Tubing Depth (m) Vell Diameter 11'' Estimated Water Volume (L) Purge Mater Level (m) Field Readings Time Purge Water Level (m) Temp (°C) DO (mg/L) Conductivity pH Redox (mv) Appearance odour, etc. NoT IL 9.6 7.47 -139.1 360 NoT IL 9.6 7.49 -140.6 380 NOT IL 9.6 7.49 509 7.49 -142.7 586	ate	Shirte	Aug 3/1	21		Client		YG	EMR
Depth to Water (m) B.185 Well casing height (magl) Depth to Bottom (m) B. (a B Tubing Depth (m)	Sampler	H-WCZ	TI/	1	£.	Project Name		Ke	etza
Monitoring Well Details Depth to Water (m) 8.185 Well casing height (magl) Depth to Bottom (m) 8.168 Tubing Depth (m) Well casing height (magl) Depth to Bottom (m) 8.168 Tubing Depth (m) Estimated Water Volume (L) Purge Method Field Readings Fi	Veather		174 S	jong.		Rain La	st 29L	-	
Depth to Water (m) 8.185 Well casing height (magl) Depth to Bottom (m) 8.608 Tubing Depth (m) Purge Method Becaler Field Readings Time Purge Volume (m) Purge Water Level (m) Temp (°C) 1406 1407 14			N/s	4		r.			
Depth to Bottom (m) B 6 B Tubing Depth (m)	1000				Monitoring We				le garge of the say
Nell Diameter 1	Depth to Wate	er (m)	8.185					0	
Purge Water Level Temp (°C) DO (mg/L) Conductivity pH Redox (mV) Appearance Ap	Depth to Botto	om (m)	8.618	3		Tubing Depth (r	n)		
Purge Water Level Temp (°C) DO (mg/L) Conductivity pH Redox (mV) Appearance Redox (mV) Appearance Redox (mV) Appearance Redox (mV) Redox (mV) Redox (mV) Appearance Re	Well Diametei		-			Estimated Wate	er Volume (L)	0.866	26
Field Readings Time Purge Volume Water Level (m) Temp (°C) DO (mg/L) Conductivity (μs/cm) pH Redox (mV) Appearance octour, etc. Ileole 0.5 L 9.2 7.47 505 7.47 -139.1 360 Ileo7 1 L 9.6 7.40 500 7.47 -140.6 380 Ileo4 2 L 9.6 2.48 509 7.49 -142.7 386	Purge Method	i .	Baile	- =					
	Time			Temp (°C)		Conductivity	pН	Redox (mV)	Appearance,
1607 1L 9.6 2.40 500 7.47 -140.6 380 1609 ZL 9.6 2.48 509 7.49 -142.7 386	1606		(11)	9.2	2.47		7.47	-139.1	
1609 ZL 9.6 2.48 509 7.49 -142.7 386	102	16			2.40				
		ZL	-	0		509	7.49	-142.7	
			¥.						-
			*	= 1/		- 4			
Sample Time (24 hr) Sample Method Field Filtered & Preserved QAQC Sample Collected						ev*			
	Sample Ti	me (24 hr)	Sample	Method	Field Filtere	ed & Preserved	Q,	AQC Sample Co	llected
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Nelo	114			Yes	· No	⇔Yès₀ N	ame:	+ 1 -
	•		8.618		0,21	10 2 2	- 2	598LP	ila 6
8.185 8.618			0.433	16 11 S		15.1		1. 60 a	Au.
8.618 0.433 x2 : 0.816 x3 = 25986 pure	mo-	hrong o	proken	"Death Si at gra	ned level	Mell 13	es not	to be a	
Strong odor > "Death Smed!". Well is broken to be a flich mount of broken at grand level and was not covered	suff;	well.	Mal is	in a	deppress	iun. Roa	d wolf	going di	creetly into



ate ampler		1					4	
ampler		1/20 5	n		Client		YG	EMR
		TI /A	-		Project Name		К	etza
eather		14'01	overcust	,				
atalogger Det ownload info		*	NIF	t			a a	
te start	No. of	Mary John		Monitoring We	ll Details			
epth to Water	r (m)	2.28	1		Well casing heig	jht (magl)	1.40	
epth to Bottor	m (m)	6.46			Tubing Depth (n	n)		
ell Diameter		("			Estimated Wate	r Voluma (L)	X	c =
urge Method		Lberl	Flow		Estimated vvale	r volume (L)		
				Field Read			وكارواك	HOE!
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	рН	Redox (mV)	Appearance, adour, etc.
1950	500ml	3.235	6.3	1.19	£ 521	7.70	-21.5	68.28
0951		3.25Ce	7.2	0.55	525	7.17	-30.8	68.40
0956	1400m1	3.255	7.6	0.37	529	7.17	-34.6	62.00
	= W	÷1						
		l ki						
					×			
Sample Tim	ie (24 hr)	Sample	Method	Field Filtere	d & Preserved	Q.	AQC Sample Co	llected
1000		1001	From	Yes	No	Yes N	ame	
eneral Notes,	Calculations		1.3					
	2	No ca	6 justa	Ked on	well.	Mehl	casing fell	over.
		Puc st	944:19	مرامه	N.		,	
	41	100 5	, ,	Mance				



Vell Name		HYD	-08-1	IA	Project Number		10	4822
Date		Aug	5/21		Client		YG	EMR
Sampler		20	AT		Project Name		К	etza
Veather		116	Merca	4				
Datalogger De download infe		100		* 4	V			
	95.00		e MR BY	Monitoring We	II Details	100	15 79 1977	
epth to Wate	er (m)	12.6	45		Well casing hei	ght (magi)	a t	
epth to Botto	om (m)	37	2.130	,	Tubing Depth (r	n)		
Vell Diameter		2"					740	·
ourge Method	1	West	ea /h	varol: A	Estimated Wate	er Volume (L)	38.9	t
			A TO HAIL	Field Read				
Time	Purge Volume	Water Level (m)	Temp (°C)	DO (mg/L)	Conductivity (µs/cm)	рН	Redox (mV)	Appearance odour, etc.
1415	38L	w	3.7	7.30	419	3.81	457.6	25.05
1423	76L		3.4	7.63	414	3.75	469.3	23.20
1435	1161		3.7	7.59	491	3.74	474.9	114.85
	-	4				×		
17)								
	-							
	* *		-+1	E				
Sample Tir	me (24 hr)	Sample	Method	Field Filtere	d & Preserved	Q.A	AQC Sample Co	llected
144	12	Water		Res	No	Yes N	ame:	_
	() s, Calculation							
	4		_					10 T
X		32.130			2.			
			11	-	799	9 47	1/69	P
		19:1	10)	XL	30.1	' /)	1.0.1	
	E 1	vell in-	door	randi	38.9 fin	,		
	> n * (/	VCL //	good	(00,100)		20.		



Hemm 'a

100
-17
- 11
#
1
U.
7
7
$\underline{}$
C
Ш
URFACE WATER SAMPLE COLLECTION SHEET
\mathcal{L}
O
ш
\overline{a}
E
Q
S
~

ш
5
3
3
щ
U
1
4
Y

Site Name	101					
	Netza KKIG Project Number	104822-01	Site Name	Ketza KP	Ketza KPIS Project Number	104822-0
Uate	Asy 5/21 Client	YG EMR	Date	Die 6/71		0 V
Sampler	ST /A Project Name	Ketza	1 2 0 7	11000		ים בושא
Geographic			0.00 miles	31/187	Project Name	Ketza
Weather.			Coordinates			
Field Parameters (note)	Fed Parameters (note units if office in the contract of the co	Q.	Westher	13, oxecat		
Water Doneh (m)	TOPING STORY TO SEE STORY		Fleid Parameters (note	Fleid Parameters (note units if different man those stated)	(pa	
maret Ceptul (m)	52.0		Water Depth (m)	2		
Temperature (°C)	11.0		Temperature (°C)	2:0		
DO (mg/L)	4.57	x	DO (ma/L)			
Conductivity (µs/cm)	497		Conductivity fusion	00.00		
Ŧ	0.36			000	").5	ā
Redox (mV)	02 .		E.	7.72	(40)	
Treebleite, farren	1.65		Redox (mV)	,		
(MID)	0	100	Turbidity (NTU)	(C)		
Appearance / Odour	Clad		Appearance / Odour			
Sample Time (24 hr)	Field Preserved & GAGC Sample Collected Filtered if Required	S 5, 500	Sample Time (24 m)	רופטע	DATE COVERAGE	
	-	ر			to call pile Colatting	Anavs s
0417	Yes Name:) De coc	1550	(Yes No Yes Name.	ame:	00
General Notes:)		General Notes:		D	3
Stream	tan clear.		Salt Flow	Soll	C-11-2	
			-	THA	7 150	
				TS: 16:04	TS: (6:09	
			200		TE. (6:11)	
	, ,		430. 1864 430. 1960	×	R G6	
		, (4 , (4) , (4)	62. 129.5		\\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\	
		#:			0 . 0	
			4		1	
2 2 4000	5					





Site Maine	KR-10	Project Number	104822-01	Site Name
Date	100 6/21	Otent	YG EMR	Date
Sampler	XXXX	Project Name	Ketza	Sample
Geographic Coordinates				Geographic
Weather	Dein			Weather
Field Parameters (note units if different than those stated)	units if different than the	ose stated)		Field Paran
Water Depth (m)	52.0		30	Water Dept
Temperature (°C)	120			Temperatu
DO (mg/L)	42.D			DO (mg/L)
Conductivity (µs/cm)	415			Conductivi
F4	9.40			Hd
Redox (mV)	82.1			Redox (mV
Turbidity (NTU)	75			Turbidity (1
Appearance / Odour	SI:OFF	Cloudy		Appearanc
Sample Time (24 hr)	Field Preserved & Filtered it Required	OAQC Sample Collected	Analysis	Sample Ti
9	Veg No	Yes Name:	Specol	
		General Notes:		

Site Name		Project Number	104822-01
Date		Client	YG EMR
Sampler		Project Name	Ketza
Geographic Combinates			<
Weather			
Field Parameters (note units if different than those stated)	mis it different than th	cose stated)	
Water Depth (m)			
Temperature (°C)			
DO (mg/L)			
Conductivity (µs/cm)			
Ą			
Redox (mV)			
Turbidity (NTU)			
Appearance / Odour			
Sample Time (24 hr)	Fleid Preserved & Filtered if Required	QAQC Sample Collected	Analysis
	Yes No	Yes Name:	
		General Notes:	
		*	
-			





Site Name	KR-12	Project Number	104822-01	Site Name
Date	6-Ang-21	Olent	YG EMR	Date
Sampler	AT/77	Project Name	Ketza	Sampler
Geographic Coordinates				Geographi
Weamer	(7.C, No	Mostly clouds		Weather
Field Parameters (note	Field Parameters (note units it different than those stated)	ose stated)		Freid Parar
Water Depth (m)	840,08	24		Water Dep
Temperature (°C)	11 -			Temperatu
DO (mg/L)	9.0			DO (mg/L)
Conductivity (µs/cm)	489.1			Conductiv
Hd	8.30			F
Redox (mV)	93.1			Redox (m)
Turbidity (NTU)	14.96			Turbidity (
Appearance / Odour	-hirbid			Appearance
Sample Time (24 nm)	Field Preserved & Entered if Required	QAQC Sample Collected	Ånalysis	Sample T
16:45	Yes No	Yes Name:	Sep (a	175
		General Notes:		
	84			

Site Name	() に に い	Designed Misseshore	404822 04
	8	inclination indicate	10-220401
Date	(2/9 dy	Glient	YG EMR
Sampler	JA M	Project Name	Ketza
Geographic Coordinates			
Weather	PC, Somy	<	
Field Parameters (note	Field Parameters (note units if different than those stated)		
Water Depth (m)	52.0		
Temperature (°C)	101		
DO (mg/L)	6.0		
Conductivity (us/cm)	759		
Н	2.38		
Redox (mV)	GH.C		
Turbidity (NTU)	Q		
Appearance / Odour	Sul		
Sample Time (24 hr)	Field Preserved & GAGC &	QAQC Sample Collected	Analysis
SSLI	_	Je:	See Ge
	General Notes:	otes:	
			3





•	Sile Name	KZ01	Project Number	104822-01	Site Name
	Date	12/6 6/21	Client	YG EMR	Date
	Sampler	AT/TI	Project Name	Ketza	Sample:
	Seographic Coordinates				Geographic
	Meather	17° onless	(esc)		Weather
	Field Parameters (note t	Freid Parameters (note units if different than those stated)	(0)		Fleid Parame
	Water Depth (m)	22.0			Water Depth
	Temperature (°C)	11.5			Temperature
	DO (mg/L)	9.03			DO (mg/L)
	Conductivity (µs/cm)	304.6			Conductivity
	Н	8.29			표
	Redox (mV)	25.1			Redox (mV)
	Turbidity (NTU)	0	1		Turbidity (N
	Appearance / Odour	clear		~	Appearance
	Sample Time (24 hr)	ઝ જ	QAQC Sample Collected	Analysis	Sample Tim
	<u>S</u>	Yes No Yes N	Yes Name: 78	Section	6:9/
	Salt kul	General Notes:	Notes:	2	
	J. 702. 6		75 75	カルー	
# 1	1 522	当	70	4:19	
	3 956	& *	304.7	2/2	
	×	0 7	(075 /	1	
		D 150	100 nosi	000	
	_				

Sun Name	KR-11	Project Number	104822-01
Date	(5-Aux-11	// Otent	YG EMR
Sample	サノオ	Project Name	Ketza
Geographic Coordinates			11
Weather	17.61	mostly cloudy	
Field Parameters (note units if different than those stated)	units it different than th	hose stated)	
Water Depth (m)	0.25		×
Temperature (°C)	8://		
DO (mg/L)	9.23		
Conductivity (µs/cm)	481.7		
Н	8.38		i i
Redox (mV)	83.9		
Turbidity (NTU)	Ø		
Appearance / Odour	clesr		
Sample Time (24 hr)	Field Preserved & Filtered if Reguired	QAQC Sample Collected	Analysis
(6:30	(es) No	Yes Name:	See Coc
		General Notes:	
			(2



LI Hemmera An Ausenco Company

Site Name	ITAIMN	Project Number	104822-01	Site Neise	
Date	10-Aug-21	Chent	YGEMR	Dain	-
,	& Suite			Date	
od ripie.	JT /AT	Project Name	Ketza	Sampler	
Goordinates				Geographic	
Aeather	- July	7		SOUTHERNOON	
Field Parameters (note u	Field Parameters (note units if different than those stated)	357		Wealher	
Water Depth (m)				ried Parameters (note units	5_
Temperature (°C)				water Depth (m)	_
				Temperature (°C)	
DO (mg/L)	939			DO (mg/L)	_
Conductivity (µs/cm)	843			Conductivity (µs/cm)	_
Æ	7:96			Hd	
Redox (mV)	74.4			Redox (mV)	-
Turbidity (NTU)	D, d			Turbidity (NTU)	_
Appearance / Odour	(had)			Appearance / Odour	-
Sample Time (24 hr)	Field Preserved & CACC Pillered if Required	DADC Sample Collected	Analysis	Sample Time (24 m)	<u> </u>
1300	Yes No Yes Name:		The Coll	1275	
	/ General N			1363	
1808	29 (+	-		SOF	
	0		,,,	,	
77 85.4	4	_	74/4	Kal	
1801	75 1769	75 120	2	543	
2 1295	TE 1305	408 37	00	1748	
3 (82	ond O	S8 2		2 933	
		N 120	2	2 1100	
9	9791 V	1	^		
	25 D	で マ		. W.	
X					

	Site Name	1101	Project Ni-mas	10,000000	L
		X		10-228401	
	Date	6-AUR, /21	Client	YG EMR	
	Sampler	12/4	Project Name	Ketza	
	Geographic Coordinates				1
	Weather	(Te, Som	Jan 60	752	1
	Field Parameters (note	Froid Parameters (note units if different than those stated)			
T	Water Depth (m)	SG: 0.215			
	Temperature (°C)	\$ 00.			1
	DO (mg/L)	9,55			1
	Conductivity (µs/cm)	536	-	.4	
	Hd	05.8			1
	Redox (mV)	76.5			1
	Turbidity (NTU)	b		Te	10
	Appearance / Odour	clesy		3	1
	Sample Time (24 hr)		GAGC Sample Collected	Analysis	
	1325	Yes Name:		36	
	Sr (+.	General Notes:	tes:	3	
-	5 -	スティー	X	7.	
_	Kel	15 13.20	15 6	6:30	
\rightarrow	E 54%	TE 13:36	TE 13:41	15:3	
_	748	8 536	53	23.8	
_)	A 1050	<)	
	2 = 94	1606	82017	78	
		905	Q 1566	٠	
		-			





2 11/02 15 15 04 15 05 15 05 15 15 05 15 0	777	Sample Time (24 hr)	Appearance / Odour	Turbidity (NTU)	Redox (mV)	H	Conductivity (µs/cm)	DO (mg/L)	Temperature (°C)	Water Depth (m)	Field Paranleters (note u	Meamer	Geographic Coordinates	Sampler	Date	Site Name
General Notes Francisco TE 7226 TE 7230 TE 7230 TE 7230	Yes No Yes Name	Filtered if Required QAQ	Cham	0	715	6.70	67	9,70	11.9	6-1	rent than those st	140 Ohn		177/4	Aug, 6/21	EDIMIN
		QAQC Sample Collected		1,						9	2)	1605/		Project Name	Client	Project Number
	Ha DOW	Analysis	Ą	Tu	Z.	pt	ç	DO	Те	- W	20	W	ଦୁ ଦୁ	Ketza	YG EMR	104822-01

104822-01	Sie Name	NWID-2 Project Number	104822-01	
YG EMR	Sec	AUG 6 /21 CIEM	YG EMR	
le Ketza	Sampler	T. M. Project Name	Ketza	
[6]	Geographic Geordinales			
	Westier	Ohmes Al	HQ.	
	Field Parameters (note u	en:		
74.	Water Depth (m)	(Su)		
	Temperature (°C)	I. &		
· •	DO (mg/L)	- Ch'C	A	
	Conductivity (µs/cm)	583		
	рН	21.8		
	Redox (mV)	1 日 / の	7	
	Turbidity (NTU)	(0)		
*	Appearance / Odour	Chas		
ted Analysis	Sample Time (24 hr)	Fillered if Required QAQC Sample Collected	d Analysis	
- Fow Only	1240	1 2 18	- Flow Ohly	
Set 2	25		7577	
1121 JE 1270	15 de 150	\$25.57 \$2.57 \$2.57	P 581	
D 1381	2 1250	1	D 785	
0 5/9	25/11 6			
	×			



104822-01 YG EMR Keiza Flau On (

36 2	Flowardy	Analysis	Į.	2				X.				1		Ketza	YG EMR	104822-01
Fav. St. 1 K G. 1 8 430 1 638 2 854 3 1041	120g	Sample Time (24 hr)	Appearance / Odour	Turbidity (NTU)	Redox (mV)	PH	Conductivity (µs/cm)	DO (mg/L)	Temperature (°C)	Water Depth (m)	Field Parameters (note t	Weather	Geographic Coordinates	Sampler	Date	Site Name
General Notes: 527 1 527 1 75 1768 75 1268 76 12:12 10 426:7 10 509	Yes No Yes Name	Fileid Preserved & QAC	Class	0	69.9	6:30	425-8	11.5	5.9	0	Field Parameters (note units if different than those stated)	14°C. Over		TILLAT	AD6 6/21	7166
	1	QAQC Sample Collected		8		26					ed)	Diverce St.		Project Name	Client	Project Number
257 2005 2005 2005 2005 2005	Town on the	Analysis	· ·	× ·				4	40				*	Ketza	YG EMR	104822-01





2 893 2 1720	Far C	5	Sample Time (24 hr)	Appearance / Odour	Turbidity (NTU)	Redox (mV)	рН	Conductivity (µs/cm)	DO (mg/L)	Temperature (°C)	Water Depth (m)	Field Parameters (note u	Weather	Geographic Coordinates	Sampler	Date	Site Name
555 V St. 12.	General Notes		Filtered if Required QAQC	Cha	0	2.17	8.22	425.4	9.42	Dis.	0.10	Field Parameters (note units if different than those stated)	14° Kain		TE 14-	Aug - 6/21	15cD-3
515 O 2545 B 11.52 B 1	8	ime:	QAQC Sample Collected	ve.	3		a				a K			4	Project Name	Client	Project Number
	. 2	Flow	Analysis				F,		3					21	Ketza	YG EMR	104822-01

	2 868	1 650	ב ברון ק	7.00	Flow and	138	Sample Time (24 hr)	Appearance / Odour	Turbidity (NTU)	Redox (mV)	РН	Conductivity (µs/cm)	DO (mg/L)	Temperature (°C)	Water Depth (m)	Field Parameters (note	Weather	Geographic Coordinales	Sampler	Date	Site Name
Q 50	D 633	0 76	\	12 N	General Notes:	Yes No Yes Name:	Field Preserved & QAQC Sample Collected	(but	5.87	71.9	8.21	1/26.	9.34	10.6	0.15	Field Parameters (note units if different than those stated)	57 3M		77./AT Pro.	AUG 6/21 CHENT	LSCD-2 PRO
0	h29 0	15-14 S	151151	1 ST		Flow Only	le Collected Analysis						40	100					Project Name Ketza	YG EMR	Project Number 104822-01





2	200	1045	Sample Time (24 hr)	Appearance / Odour	Turbidity (NTU)	Redox (mV)	рн	Conductivity (µs/cm)	DO (mg/L)	Temperature (°C)	Water Depth (m)	Field Parameters (note units if different than those stated)	Weather	Geographic Coordinates	Sampler	Date	Site Name
	Pier. Jaken for	Yes No	Filtered if Required	Che	0	82.9	7,80	639	20	(A)		units if different than th	271	1 10	シネ	AUA 6	KR-601
	alson from	Yes Name:	QAQC Sample Collected									iose slated)			Project Name	/2 Client	Project Number
# **	of some sil	See con	Analysis			•	8				le S				Ketza	YG EMR	104822-01
,			Sa	App	Turl	Red	рН	Con	DO	Теп	Wat	Fie	Wea	Gec Coo	San	Date	Site

 Scharge	ce coc	Analysis								19				Ketza	YG EMR	104822-01
90	1100	Sample Time (24 hr)	Appearance / Odour	Turbidity (NTU)	Redox (mV)	PH	Conductivity (µs/cm)	DO (mg/L)	Temperature (°C)	Water Depth (m)	Field Parameters (note	Weather	Geographic Coordinates	Sampler	Date	Site Name
General Notes:	-	Field Preserved & QA Filtered if Required	Cluer	9	4,58	8,23	543	8.53	16.60	1759	Field Parameters (note units if different than those stated)	1400	14	一种一个	AUG 6/21	100-20
General Notes:	Yes Name:	QAQC Sample Collected									ed)	6.5		Project Name	Client	Project Number
KR-090	Der 1000	Analysis					F	*					æ	Ketza	YG EMR	104822-01





		101000 01
Site Name	KR-08 Project Number	104822-01
Date	AUG G/Z) Cient	YG EMR
Sampler	TIA. Project Name	Ketza
Geographic Coordinates		
Weather	15 K	
Field Parameters (note un	Field Parameters (note units if different than those stated)	
Water Depth (m)	56:0.190	
Temperature (°C)	6.4	
DO (mg/L)	9.65	
Conductivity (µs/cm)	436.0	
PH	C 2.3	
Redox (mV)	41.9	
Turbidity (NTU)	59.00	·
Appearance / Odour	Cloudit	
Sample Time (24 hr)	Filtered if Required A DAGE 5) maken
5610		See Oc
6	General Notes:	
1 1 Lang /a	tool.	aghing
	2	Salt 2
Ka		TE: 643,06
210016 1250 1250 1250 127.2	B 138.8	B: 440.2

See Marie	Project Number	104822-01
	121	YG EMR
Sampler	A Project Name	Ketza
Geographic Coordinales		
Weather	THE KOS	
Field Parameters (note to	Field Parameters (note units if different than those stated)	
Water Depth (m)	6.25	
Temperature (°C)	a J	
DO (mg/L)	9,49	
Conductivity (µs/cm)	414 3	
P	20 27	
Redox (mV)	A2 6	
Turbidity (NTU)		
- TOdour	Char	
is Sample Time (24 hr)	Field Preserved & QAQC Sample Collected	Analysis
080	Yes No Yes Name:	Se Cor
	General Notes:	pouring
000	to p of weir.	
) 7 6 6	22	

Project Name Project Name Project Name Sample Collected Sample Collected Sample Collected	4.50 4.50 4.50 1.50 1.50 1.50 1.50 1.50 1.50 1.50 1	16:00 Yes	Sample Time (24 hr) Field P	Appearance / Odour C/ear	Turbidity (NTU)	Redox (mV) 74	Ø.	Conductivity (µs/cm)	DO (mg/L)	Temperature (°C)	Water Depth (m)	Field Parameters (note units if different than those stated)	Weather 14	Geographic Coordinates	Sampler	Date 27	Sta Varie 大が
	General Notes Collected Flaw	No	Field Preserved & OAOC Sample Collected	, w/ brown al		, ,	0/	50	4	N .	0,10	fferent than those stated)			7 T Project Name	2	-04-7V3 Project Number
			Analysis	2 50						€					Ketza	YG EMR	104822-01

. 6

00000000000000000000000000000000000000	0	1810	Sample Time (24 hr)	Appearance / Odour	Turbidity (NTU)	Redox (mV)	PH	Conductivity (µs/cm)	DO (mg/L)	Temperature (°C)	Water Depth (m)	Field Parameters (note	Weather	Geographic Coordinates	Sample	Date	Site Name
00 2 60 0 V 2 60 0	Johnson Com		Filed Preserved & C	(likey	О	56.1	8.27	ななた	H0.8	14.	0.10	Field Parameters (note units if different than those stated)	THE DWG	1.0	TT/A	Aug 5/21	Wier 3
	General Notes:	Yes Name:	QAQC Sample Collected			-	×					sta(ed)	(5.5)		Project Name	Client	Project Number
	*	*	Analysis			2		4	4		3	1			Ketza	YG EMR	104822-01



16.30	Meir in	1705	Sample Time (24 Fr)	Appearance / Odour	Turbidity (NTU)	Redox (mV)	Hq	Conductivity (µs/cm)	DO (mg/L)	Temperature (°C)	Water Depth (m)	Field Parameters (note u	Weather	Geographic Coordinates	Sampler	Date	Site Name
@ 152 -> Volumetic the	collected Condition	Yes No Yes Name:	Field Preserved & GAGC Sample Collegied Filtered if Required	ولسما	O	664	7.90	t.88h	9.28	14.1	0.15	Field Parameters (note units if different than those stated)	This, Ren		T AT Project Name	Aug S/2) Client	KR-05-52 Project Number
c How	7	See Cac	Analysis				3.00								Ketza	YG EMR	104822-01

	G,	15.15				8								Za	MR	2-01
3	1740	Sample Time (24 hr)	Appearance / Odour	Turbidity (NTU)	Redox (mV)	рН	Conductivity (µs/cm)	DO (mg/L)	Temperature (°C)	Water Depth (m)	Field Parameters (note)	Weather	Geographic Coordinates	Sampler	Dale.	Site Name
	Yes No Wes Name:	Fireto Preserved & QAQC Sample Collected	The	D	89,9	7.69	709	9.11	11.8	56:0.629	Field Parameters (note units if different than those stated)	(5°, 720, 125)	× / × /	A TI Project Name	AG 5/7 Clent	Project Number
	See (01	Analysis												Ketza	YG EMR	104822-01
	20	VS18												za	:MR	:2-01





104822-01 YG EMR

Project Name

Compared to last August, water OAGC Sample Collected clear, alase on rocks Yes Name: leid Parameters (note units if different than those stated) Field Preserved & Fitered if Required 8 Y K- 5- S Ketza 9 50.50 0 (se) 7.4 TOH 0 Sample Time (24 rm) Appearance / Odour Conductivity (µs/cm) (6:50 (emperature (°C) Nater Depth (m) rurbidity (NTU) General Notes: Redox (mV) DO (mg/L) 3eograph. Site Name Weather Samper SURFACE WATER SAMPLE COLLECTION SHEET BB 104822-01 YG EMR Ketza OAGC Sample Collected KR13 Ketza Project Name Yes Name: ers (note units if different than those stated) 5/21 7 Field Preserved & Filtered if Required ž 9.82 418.4 927 8.40 0.10 (3) Sample Time (24 hr) Conductivity (µs/cm) Appearance / Odour 16 25 General Notes: emperature (°C) Vater Depth (m) (UTU) eld Paramete Redox (mV) Geographic Coordinates DO (mg/L) Veather Sampler

(0C



Appendix F - Flow Measurements Datasheets

KR-15 Peel Creek at Road

Station ID & Name:	KR-15	Peel Creek at Road	
GPS (WGS 84 Lat Long D.D)	61.5422	-132.2475	1301 m a.s.l.

Gauging comments

Date: 2021-08-31

Best flow estimate available for KR-15 is using the difference in discharge from velocity-area cross-sections (FlowTracker 2 instrument) above and below Peel Creek - Cache Creek confluence, i.e. PCC-1 flow (downstream) minus KR-08 flow (upstream):

0.044 m³/s around 10:00 on 2021-08-31.

Visual flow estimate during KR-15 site visit: 40 L/s at 12:00.

Salt dilution gauging conducted on 2021-08-31 around 11:55 but result was rejected.

Discharge result was suspect due to inadequate mixing range. Selected measurement reach was too short and tracer plume passed too fast, likely leading to a discharge overestimate by the QiQuac instrument (conductivity probes).



KR-15 Gauging pool looking across from left downstream bank, upstream of road crossing

PC-DS3 Peel Creek d/s of Seep 3

Station ID & Name:	PC-DS3	Peel Creek d/	's of Seep 3
GPS (WGS 84 Lat Long D.D)	61.5427	-132.2681	1499 m a.s.l.
Salt Dilution - Slug Injection M	ethod – Two Hi-Res Co	nductivity Probes	Weather
Parameter	Value	Unit	Dry - Clear
Date	2021-08-31	YYYY-MM-DD	Instrument - S/N
Start Trace Time	13:50:26	HH:MM	QiQuac
End Trace Time	13:55:47	HH:MM	QM5.24
Mass of salt (dry)	0.100	kg	Firmware Version
Mixing reach length	50	m	QQF0.3.5
Mixing potential	good	Y/N	NaCl Brand
Field Calibration? [NaCl] 5.0 g/l	Υ	[NaCl](g/l)	Sifto (Pool)
	Ch0	Probe	Ch1
Probe S/N	TM7.206		TM7.144
Field Q	0.035	m³/sec	0.036
Field Grade	Α	QUnc. & %DQ	Α
Discharge (post-processed)	0.035	m³/sec	0.036
Background EC.T (avg, n=20)	559.37	μS/cm	572.08
Peak EC.T	654.77	μS/cm	665.15
Peak above BG EC.T in %	+ 17 %		+ 16 %
Salt pulse duration	00:05:21	HH:MM:SS	00:05:10
QUnc. (95% conf. intrvl.)	5.4	%	5.4
CF.T (field cal.)	0.514	(mg/L)/(μS/cm)	0.492



PC-DS3 Conductivity probe locations looking downstream

PC-DS2 Peel Creek d/s of Seep 2

Station ID & Name:	PC-DS2 Peel Creek d/s of Seep 2		d/s of Seep 2
GPS (WGS 84 Lat Long D.D)	61.5428	-132.2701	1519 m a.s.l.
Salt Dilution - Slug Injection Me	thod – Two Hi-Res Condo	uctivity Probes	Weather
Parameter	Value	Unit	Dry - Clear
Date	2021-08-31	YYYY-MM-DD	Instrument - S/N
Start Trace Time	14:31:07	HH:MM	QiQuac
End Trace Time	14:37:42	HH:MM	QM5.24
Mass of salt (dry)	0.100	kg	Firmware Version
Mixing reach length	70	m	QQF0.3.5
Mixing potential	good	Y/N	NaCl Brand
Field Calibration? [NaCl] 5.0 g/l	Y	[NaCl](g/l)	Sifto (Pool)
	Ch0	Probe	Ch1
Probe S/N	TM7.206		TM7.144
Field Q	0.021	m³/sec	0.021
Field Grade	Α	QUnc. & %DQ	Α
Discharge (post-processed)	0.021	m³/sec	0.021
Background EC.T (avg, n=20)	593.12	μS/cm	607.30
Peak EC.T	688.78	μS/cm	707.36
Peak above BG EC.T in %	+ 16 %		+ 16 %
Salt pulse duration	00:06:55	HH:MM:SS	00:06:35
QUnc. (95% conf. intrvl.)	5.3	%	5.6
CF.T (field cal.)	0.497	(mg/L)/(μS/cm)	0.478



PC-DS2 Conductivity probe locations looking upstream

PC-DS1 Peel Creek d/s of Seep 1

Station ID & Name:	PC-DS1 Peel Creek d/s of Seep 1		d/s of Seep 1
GPS (WGS 84 Lat Long D.D)	61.5427	-132.2681	1525 m a.s.l.
Salt Dilution - Slug Injection Me	thod – Two Hi-Res Condu	uctivity Probes	Weather
Parameter	Value	Unit	Dry - Clear
Date	2021-08-31	YYYY-MM-DD	Instrument - S/N
Start Trace Time	18:11:20	HH:MM	QiQuac
End Trace Time	18:19:55	HH:MM	QM5.24
Mass of salt (dry)	0.100	kg	Firmware Version
Mixing reach length	45	m	QQF0.3.5
Mixing potential	fair	Y/N	NaCl Brand
Field Calibration? [NaCl] 5.0 g/l	Υ	[NaCl](g/l)	Sifto (Pool)
	Ch0	Probe	Ch1
Probe S/N	TM7.206		TM7.144
Field Q	0.008	m³/sec	0.007
Field Grade	С	QUnc. & %DQ	С
Discharge (post-processed)	0.008	m³/sec	0.007
Background EC.T (avg, n=20)	746.51	μS/cm	767.75
Peak EC.T	989.23	μS/cm	1069.45
Peak above BG EC.T in %	+ 33 %		+ 39 %
Salt pulse duration	00:08:35	HH:MM:SS	00:08:00
QUnc. (95% conf. intrvl.)	6.6	%	6.3
CF.T (field cal.)	0.488	(mg/L)/(μS/cm)	0.473

Gauging conditions comments:

Subpar channel conditions, steep gradient of steps/pools, coarse streambed, flow in substrate.



PC-DS1 Conductivity probe locations looking downstream

KR-08 Cache Creek (upstream of Peel confluence)

Station ID & Name:	KR-08	Cacl	no Crook u/s Pool
			ne Creek u/s Peel
GPS (WGS 84 Lat Long D.D)	61.543	-132.236	1242 m a.s.l.
Wading –Velocity	/-Area Method – Acc	oustic Doppler Velocii	metry (ADV)
Parameter	Value	Unit	Instrument
Date	2021-08-31	YYYY-MM-DD	Sontek FlowTracker2
Start Time	10:00	HH:MM	Handheld/Probe Serial #
End Time	10:49	HH:MM	FT2H2048013
Stations	25	#	FT2P2050002
Discharge	0.388	m³/sec	Operator
Section Width	2.95	m	AM & SL
Section Area	0.644	m²	Q location relative to SG
Mean Velocity	0.602	m/sec	Downstream
Highest Panel % of Q	7.3	%	Q Dist. to SG (m)
Uncertainty (IVE)	3.2	%	2
Staff Gauge (SG) Reading / Time	0.130	m / HH:MM	10:34
Stage-Discharge Control	Туре	Effectiveness	Control distance to SG (m)
Natural	Section	Partial	4
Condition:	Clear	Time cleaned:	Not cleaned



 $KR-08\ Velocity-area\ cross-section-looking\ downstream$

PCC-1 Cache Creek downstream of Peel Creek confluence

Station ID & Name:	PCC-1	Cach	ie Creek d/s Peel
GPS (WGS 84 Lat Long D.D)	61.556	-132.236	1241 m a.s.l.
Wading –Velocity	Wading –Velocity-Area Method – Acoustic Doppler Velocimetry (ADV)		
Parameter	Value	Unit	Instrument
Date	2021-08-31	YYYY-MM-DD	Sontek FlowTracker2
Start Time	09:06	нн:ММ	Handheld/Probe Serial #
End Time	09:40	HH:MM	FT2H2048013
Stations	22	#	FT2P2050002
Discharge	0.432	m³/sec	Operator
Section Width	3.05	m	AM
Section Area	0.750	m²	Q location relative to SG
Mean Velocity	0.576	m/sec	N/A
Highest Panel % of Q	8.6	%	Q distance to SG (m)
Uncertainty (IVE)	6.0	%	N/A
Staff Gauge (SG) Reading / Time	N/A	m / HH:MM	N/A
Stage-Discharge Control	Туре	Effectiveness	Control distance to SG (m)
Natural	Section	Partial	N/A
Condition:	Clear	Time cleaned:	Not cleaned



PCC-1 Velocity-area cross-section – looking upstream

KR-22 Misery Creek

KR-22	Misery Creek	
61.545	-132.220	1221 m a.s.l.
Area Method – Acou	ustic Doppler Velocim	etry (ADV)
Value	Unit	Instrument
2021-09-01	YYYY-MM-DD	Sontek FlowTracker2
15:18	HH:MM	Handheld/Probe Serial #
15:50	HH:MM	FT2H2048013
24	#	FT2P2050002
0.337	m³/sec	Operator
3.40	m	AM
0.725	m²	Q location relative to SG
0.466	m/sec	Downstream
8.5	%	Q distance to SG (m)
5.9	%	300
0.285	m / HH:MM	15:00
Туре	Effectiveness	Distance to SG (m)
Section	Partial	2
Clear	Time cleaned:	Not cleaned
	61.545 Area Method – Acou Value 2021-09-01 15:18 15:50 24 0.337 3.40 0.725 0.466 8.5 5.9 0.285 Type Section	61.545 -132.220 Area Method – Acoustic Doppler Velocim Value Unit 2021-09-01 YYYY-MM-DD 15:18 HH:MM 15:50 HH:MM 24 # 0.337 m³/sec 3.40 m 0.725 m² 0.466 m/sec 8.5 % 5.9 % 0.285 m / HH:MM Type Effectiveness Section Partial



KR-22 Velocity-area cross-section – looking upstream

Appendix G - Hydrometric Network Assessment

KR-12 Ketza River

Station name	KR-12 Ketza River downs	tream of Cache Creek confluence	
Location	61.575544°, -132.172186° (WGS84), 1,086 m asl		
	The hydrometric station is located on the right bank of the Ketza River about 80		
	metres west of the Ketza camp access	road at a point along the road 1.2 kilometers	
	north of the	Ketza creek bridge.	
Watershed Area		s the most downstream station in existing	
	monitoring network. Maximum	elevation in watershed is 2,168 m asl.	
Flow Range	Low:	Annual maximum:	
	2011-2012 Winter average: 0.155	2012-06-22 Freshet peak: 12.120 m ³ /s	
	m³/s	2012-00-22 Heshet peak. 12.120 III-75	
Rationale	EBA chose this location close to the Project boundary to monitor flows leaving the		
	property.		
	Ketza River is the receiving water for Cache Creek.		
	Primary purpose is to estimate % of discharge from Cache Creek that contributes		
	to Ketza River flow.		
Photos	The state of the s		
	KR-12 looking upstream	KR-12 looking downstream	

Station name	KR-12 Ketza River downs	tream of Cache Creek confluence
Sketch		1
		. N
		la i
		V /
	- GA	ueine
	TR.	ANSECT
	BMZ 4m	
	(Rebar in soil)	
		1
	Housing	⁷ m 1.
	0	<u> </u>
	₹ •} \	
	861	\
	2012 Sketch of the	layout of KR12 – Ketza R.
	Source: EBA. 2013. Ketza Rive	er Project 2012 Hydrological Report.
Channel	_	ollapsed at stilling well location.
conditions		stream of S.G. but fair at the S.G. location.
		riffle downstream of left bend.
		eam draining adjacent wetland. Gravel bar otential for braiding at certain stages.
		currently located in the middle of a wetland
		r flood plain.
Satellite		<u>+</u> . V
imagery	The state of the s	
	KR-12 hydro new	
	\sim	
	≪R-12 hydro eid	
	image © 2221 Maari Tec	
	Imagery date: 2005-08-09	KR-12 current location in wetland (2019-
		06)

	KR-12 Ketza R	liver downstream of Cache Creek confluence	
	https://caltopo.com/ma	ap.html#ll=61.57694,-132.17319&z=16&b=imagery	
Current infra-	EBA (2013): "A 2.5 m long, 5 cm diameter Schedule 40 galvanized steel pipe was		
structure	attached to a large boulder located near the right bank of the creek by means		
	two heavy duty mounting	tabs secured to the boulder with 3/8 inch by 6 inch long	
		re/temperature instrumentation located within the pipe	
		tre of water depth near the edge of the right bank of the	
	nodoling is in about 1.0ine	river.	
	The staff saves was year		
		tically mounted to a 2" x 4" by 8' long pressure treated	
		the river bed to depth of 0.7 metres. The gauge is further	
	secured by attaching the k	pack of the stake to a 3 cm diameter rebar 2meters long,	
	driv	ven one meter into the river bed."	
		Hydrometric Station Key Elevations	
	6/14/2012 2:30 PM	Date and time of the elevation survey	
	1086.000 metres MSL 1086.631 metres MSL	Assumed elevation of the primary benchmark BM1 (from Google Earth) Elevation of the secondary benchmark (BM2)	
	1084.821 metres MSL	Elevation of the pressure / temperature sensor located within the housing	
	1084.920 metres MSL	Elevation of the zero reading on the staff gauge	
	1085.538 metres MSL 0.120 metres	Water surface elevation near the housing at the time of the survey Correction to staff gauge reading to obtain pressure transducer water level	
		elevations in 2012 at KR-12 (EBA 2013)	
	Stilling well location nov Benchmark boulder shatt	staff gauge is slightly loose, tilted and damaged. w inadequate. Boulder supporting sensor housing has collapsed into river. ered and will collapse in river with further bank erosion. BM1 unreliable. BM2 not found.	
Recommended	The existing KR-12 location in the middle of a wetland and/or flood plain is not		
infrastructure	adequate for hydrometric monitoring.		
	WRB suggests to relocate	the station downstream (61.57907°, -132.17929°) as it	
		each with no sign of gravel bars, braiding or flood plain.	
		at shoreline suggest elevated banks and confinement	
		There also appears to be a rocky outcropping on LDB	
	_	e suitable for a bedrock bolt or staff plate benchmark.	
	Thalweg is on the left downstream bank		
	Installa	ation as per R.I.S.C. 2018 guidelines:	
		ation as per R.I.S.C. 2018 guidelines: auge with adequate support structure	
	Staff Ga		
	Staff Ga 3 elevation benchmarks	auge with adequate support structure s (rock bolt in boulder or ground rod driven to refusal)	
	Staff Ga 3 elevation benchmarks Stilling well or mid-s	auge with adequate support structure s (rock bolt in boulder or ground rod driven to refusal) tream anchor deployment (pending site inspection)	
	Staff Ga 3 elevation benchmarks Stilling well or mid-s Pressure tr	auge with adequate support structure s (rock bolt in boulder or ground rod driven to refusal)	
Monitoring	Staff Ga 3 elevation benchmarks Stilling well or mid-s Pressure tr Cable way hardware (f	auge with adequate support structure s (rock bolt in boulder or ground rod driven to refusal) tream anchor deployment (pending site inspection) ansducer (continuous water level logger).	

Station name	KR-12 Ketza River downstream of Cache Creek confluence
	Pre-spring freshet (late April – early May) to ensure loggers are synchronized and
	in working order
	Spring freshet (late May – early June snowmelt peak)
	Late melt (late June, early July)
	Significant rain event(s)
	Summer low flow
	Pre-freeze-up (September) to winterize loggers (protect from freezing damage)
	Early winter (November)
	Late winter/winter low flow (March)
	Survey stage (water surface elevation) on each visit.
	Develop rating curve and derive continuous discharge from corrected stage time-
	series.
Measurement	High flow: cross section standard measurement with ADCP (i.e. cableway and boat
methods	deployment)
	Moderate – low flow: cross section standard measurement with ADV or equivalent
	(i.e. wading)
	Winter flow: salt dilution gauging following R.I.S.C. 2018 best practices.
	Alternative if high flow measurements are unsafe: collect discharge measurement
	from bridge at KR-11 (upstream of Cache Creek confluence) and estimate
	discharge by adding Q from KR-10 and KR-11.
Priority rank	1 – Essential

KR-10 Cache Creek (upstream of Ketza River confluence)

Station name KR-10 Cache Creek (upstream of Ketza River confluence) 61.564608°, -132.16450° The hydrometric station is located on the right bank of Cache Creek about 70 metres east of the camp access road at a point along the road 200 metres south of the Ketza River bridge. The si located about 20metres south east of an old camper/trailer located near the abandoned airstream Area Flow Range Low: 2011-2012 Winter average: 0.060 m³/s EBA chose this location as the most downstream option along Cache Creek to quantify flows let the property before the stream reaches a floodplain and its confluence with the upper branch of River. Primary purpose is to estimate % of discharge from Cache Creek that contributes to Ketza River KR-10 looking upstream KR-10 looking at well on RDB	te is rip.	
The hydrometric station is located on the right bank of Cache Creek about 70 metres east of the camp access road at a point along the road 200 metres south of the Ketza River bridge. The si located about 20metres south east of an old camper/trailer located near the abandoned airstream Area Flow Range Low: 2011-2012 Winter average: 0.060 m³/s EBA chose this location as the most downstream option along Cache Creek to quantify flows let the property before the stream reaches a floodplain and its confluence with the upper branch of River. Primary purpose is to estimate % of discharge from Cache Creek that contributes to Ketza River.	te is rip.	
Area Flow Range Low: 2011-2012 Winter average: 0.060 m³/s EBA chose this location as the most downstream option along Cache Creek to quantify flows lethe property before the stream reaches a floodplain and its confluence with the upper branch of River. Primary purpose is to estimate % of discharge from Cache Creek that contributes to Ketza River.		
Low: 2011-2012 Winter average: 0.060 m³/s EBA chose this location as the most downstream option along Cache Creek to quantify flows lethe property before the stream reaches a floodplain and its confluence with the upper branch of River. Primary purpose is to estimate % of discharge from Cache Creek that contributes to Ketza River.		
Rationale EBA chose this location as the most downstream option along Cache Creek to quantify flows let the property before the stream reaches a floodplain and its confluence with the upper branch of River. Primary purpose is to estimate % of discharge from Cache Creek that contributes to Ketza River. Photos Photos		
Rationale the property before the stream reaches a floodplain and its confluence with the upper branch of River. Primary purpose is to estimate % of discharge from Cache Creek that contributes to Ketza River. Photos		
	Ketza	
Sketch BM1 TRAILER 2012 Sketch of the layout of KR10 – Cache Cr Source: EBA. 2013. Ketza River Project 2012 Hydrological Report.		
	The 2012 location is not suitable anymore due to substantial sedimentation on the right downstream	
conditions bank. Main flow is in the middle and/or in left half of the channel in the upstream vicinity. Immediately		

downstream options are limited since the channel is less constricted before the creek spills out of its old bed and braids trough the former airstrip prior to confluence with Ketza River.





https://caltopo.com/map.html#II=61.56447,-132.16224&z=17&b=imagery

EBA (2013): "A 2.5 m long, 5 cm diameter Schedule 40 galvanized steel pipe was attached to a large boulder located near the right bank of the creek by means of two heavy duty mounting brackets secured to the boulder with 3/8 inch by 6 inch long rock anchors. The pressure/temperature instrumentation located within the pipe housing is in about 0.4 metres water depth at the time of installation.

The staff gauge was mounted to a pressure treated 2" x 4" by 8' wooden stake driven into the river bed to a depth of 0.8metres. The staff gauge is further secured by attaching the back of the wooden stake to a 3 cm diameter rebar 2 meters long that was driven one meter into the river bed."

Current infrastructure

Satellite imagery

	Hydrometric Station Key Elevations
6/16/2012 9:07 AM	Date and time of the elevation survey
1094.000 metres MSL	Assumed elevation of the primary benchmark BM1 (from Google Earth)
1093.926 metres MSL	Elevation of the secondary benchmark (BM2)
1093.117 metres MSL	Elevation of the pressure / temperature sensor located within the housing
1093.099 metres MSL	Elevation of the zero reading on the staff gauge
1093.559 metres MSL	Water surface elevation near the housing at the time of the survey
-0.079 metres	Correction to staff gauge reading to obtain pressure transducer water level

Surveyed elevations in 2012 at KR-10 (EBA 2013)

2021 observations: Stilling well location now inadequate due to sediment accumulation and not proper gauging pool in surrounding area. Galvanized pipe present, partially buried in sediments. Pipe cap was seized due to corroded threads. Benchmarks rods appeared to have been subject to vertical movements.

Recommended

WRB suggests to relocate the station upstream within the same reach. The current reach still presents a long, straight reach with good channel constriction. Potential small gauging pools exist on the left

infra-	downstream bank for installing a stilling well. Alternative option is to deploy the logger mid-channel
structure	without a stilling well.
	Installation as per R.I.S.C. 2018 guidelines:
	Staff Gauge with adequate support structure
	3 elevation benchmarks (rock bolt in boulder or ground rod driven to refusal)
	Stilling well or mid-stream anchor deployment (pending site inspection)
	Pressure transducer (continuous water level logger).
	Cable way hardware (for tethered ADCP boat measurements in high flows)
	Sufficiently frequent station visits to capture:
	Pre-spring freshet (late April – early May) to ensure loggers are synchronized and in working order
	Spring freshet (late May – early June snowmelt peak)
	Late melt (late June, early July)
	Significant rain event(s)
Monitoring	Summer low flow
objectives	Pre-freeze-up (September) to winterize loggers (protect from freezing damage)
	Early winter (November)
	Late winter/winter low flow (March)
	Survey stage (water surface elevation) on each visit.
	Develop rating curve and derive continuous discharge from corrected stage time-series.
	Open water (high to moderate): Area-velocity discharge measurement with ADV or equivalent (i.e.
Measure-	wading).
ment	Low flow and winter: salt dilution gauging following R.I.S.C. 2018 best practices.
methods	Stage survey with differential leveling
	Follow R.I.S.C. 2018 guidelines.
Priority rank	1 – Essential

KR-22 Misery Creek

Station name	KR-22 Misery Creek	
Location	61.552903°, -132.218339° (WGS84), 1,221 m asl	
	Velocity –Area cross section reach located 160 m downstream of gauging pool.	
	The hydrometric station is located near the right bank of Misery Creek about 40 metres upstream of the existing water quality station and 700metres upstream of the confluence will Cache Creek. The site is accessed by traveling east from camp down the camp access. Turn north on the dirt road 2 km past K15-Peel Creek station. Then turn right (south east) at the fi intersection. Travel down this road parallel to Misery creek for about 200 m and then left to the site when you are at the same elevation as the creek.	
Watershed	KD22 Minor Cond had been been in the condition	(501
Area	KR22-Misery Creek basin has maximum extent 13.97 km². The maximum ba	·
Flow Range	Low:	Annual maximum:
	2012 October min. measured: 0.088 m³/s	2012-06-16 Freshet peak: 1.427 m³/s
Rationale	Significant tributary: in % of Cache Creek flo	w, in contaminant loading (arsenic, sulfate)
Photos		
	KR-22 Staff Gauge & Sensor Casing - looking	KR-22 Velocity-Area cross section reach (flow
Sketch	Housing S.G. BM1 BM2	GAUGING TRANSECT WIOOM D/S

Station name		KR-22 Misery Creek
	2012 Sketch of the layout of KR22 – Misery Cr	
		etza River Project 2012 Hydrological Report.
Channel	Turbulent flow with boils in the pool where the stilling well was installed. Gauging transect far	
conditions	below the sensor pool where the reach is more straight and flow is more laminar (but without a	
conditions	•	suitable gauging pool).
C 1 1111		suitable gauging pool).
Satellite imagery	Imagery date: 2005-08-09	Imagery date: 2019-06
	<u> </u>	61.55305,-132.21812&z=17&b=imagery&a=c%2Cmba
Comment infor		
Current infra-	EBA (2012): "A 2.5 m long, 5 cm diameter Schedule 40 galvanized steel pipe was attached to a	
structure	large boulder located near the right bank of the creek by means of two heavy duty mounting	
	tabs secured to the boulder with 3/8 inch by 6 inch long rock anchors. The	
	pressure/temperature instrumentation located within the pipe housing is in about 0.25 metres	
	water depth.	
	The staff gauge was vertically mounted to a pressure treated 2" x 4" by 4' pressure treated	
	wooden stake and attached to a large boulder near the right bank.	
	Two benchmarks were installed by p	placing 3/8 inch by 6 inch long rock anchors on the tops of
	two large rocks located on the right shore within 5 metres of the hydrometric station housing."	
	H	ydrometric Station Key Elevations
	June 15, 2012	Date and time of the elevation survey
	1220.000 metres MSL 1220.079 metres MSL	Assumed elevation of the primary benchmark BM1 (from Google Earth)
	1220.073 THERES WISE	Elevation of the secondary benchmark (BM2) Elevation of the pressure / temperature sensor located within the housing
	1219.518 metres MSL	Elevation of the zero reading on the staff gauge
	1219.901 metres MSL	Water surface elevation near the housing at the time of the survey
	0.014 metres	Correction to staff gauge reading to obtain pressure transducer water level
	Surveyed elevations in 2012 at KR-22 (EBA 2013)	
	2021 observations: the well cap threads are corroded and seized, does not open and the old	
	OTT logger could not be retrieved from the casing. Turbulent flow with water boils right by the	
	stilling well likely causes unreliable readings.	
Recom-	WRB suggests to keep this location and upgrade the infrastructure, especially to prevent the	
mended		gger record and staff gauge readings.
infra-	Dolls to affect to	gger record and starr gauge redulings.
	Lasta D. C.	a an may DICC 2010 modelation and
structure		n as per R.I.S.C. 2018 guidelines:
	_	e with adequate support structure
	3 elevation benchmarks (ro	ck bolt in boulder or ground rod driven to refusal)

Station name	KR-22 Misery Creek	
	Stilling well	
	Pressure transducer (continuous water level logger).	
Monitoring	Sufficiently frequent station visits to capture:	
objectives	Pre-spring freshet (late April – early May) to ensure loggers are synchronized and in working	
	order	
	Spring freshet (late May – early June snowmelt peak)	
	Late melt (late June, early July)	
	Significant rain event(s)	
	Summer low flow	
	Pre-freeze-up (September) to winterize loggers (protect from freezing damage)	
	Early winter (November)	
	Late winter/winter low flow (March)	
	Survey stage (water surface elevation) on each visit.	
	Develop rating curve and derive continuous discharge from corrected stage time-series.	
Measurement	Open water (high to moderate): velocity-area method with ADV or equivalent (i.e. wading).	
methods	Low flow and winter: salt dilution gauging following R.I.S.C. 2018 best practices.	
	Stage survey with differential leveling	
	Follow R.I.S.C. 2018 guidelines.	
Priority rank	1 – Essential	

KR-15 Peel Creek at Road

Station name	KR-15 Peel Creek at Road	
Location	61.542206°, -132.247500° (WGS84), 1314 m asl	
	Located on Peel Creek on the right bank	of the creek just upstream of where the flow enters a culvert
	which passes (under the Ketza camp access road.
Watershed	KR-15 hasin has maximum extents of	2.8 km by 1.1 km, a catchment area of 2.52 km², and the
Area		basin elevation is 2,134 m asl
	maximam	busin elevation is 2,134 in asi
Flow Range	Low:	Annual maximum:
	2011-2012 Winter base flow in the	2012-06-24 Freshet peak: 0.466 m³/s
	order of 0.010 m³/s	2012 00 211 reshet pedit. 0.100 m /5
Rationale	Significant tributary: in % of Cach	e Creek flow, in contaminant loading (arsenic, sulfate)
Photos		
	KR-15 looking at right bank	KR-15 looking upstream from culvert inlet
	ROAD CULVERT (36") ROAD 2012 Sketch of the layout of KR-15 – Peel Creek Source: EBA. 2013. Ketza River Project 2012 Hydrological Report.	
Channel	The terminus of the housing was in a gauging pool of water about 30 cm deep in 2012.	
conditions		e filled in that pool has since installation.
	I	

Station name	KR-15 Peel Creek at Road	
	03/15/2012 17:01	
Satellite imagery	The property of the 2010 OC	
	Imagery date: 2019-06 https://caltopo.com/map.html#ll=61.54284,-132.24933&z=16&b=imagery	
Current infrastructure	EBA (2013) installation notes: "A 2.5 m long, 5 cm diameter Schedule 40 galvanized steel pipe was attached to a large boulder located near the right bank of the creek by means of two heavy duty mounting tabs secured to the boulder with 3/8 inch by 6 inch long rock anchors. The pressure/temperature instrumentation located within the pipe housing is in about 0.25 metres water depth near the edge of the creek. The staff gauge was vertically mounted to a pressure treated 2" x 4" by 8' pressure treated wooden stake driven into the river bed to a depth of 0.8metres. The gauge is further secured by attaching the back of the wooden stake to a 3 cm diameter rebar 2meters long that was driven one meter into the river bed. Two benchmarks were installed consisting of rock anchor bolts installed on boulders at two locations within a 5metre radius of the hydrometric station housing."	

Station name	KR-15 Peel Creek at Road	
	Hydrometric Station Key Elevations	
	June 15, 2012 at 16:45 Date and time of the elevation survey	
	1314.000 metres MSL Assumed elevation of the primary benchmark BM1 (from Google Earth)	
	1314.356 metres MSL Elevation of the secondary benchmark (BM2)	
	Elevation of the pressure / temperature sensor located within the housing 1312.162 metres MSL Elevation of the zero reading on the staff gauge	
	1312.548 metres MSL Water surface elevation near the housing at the time of the survey	
	-0.143 metres Correction to staff gauge reading to obtain pressure transducer water level	
	Surveyed elevations in 2012 at KR-15 (EBA 2013)	
	2021 observations: staff gauge severely bent and buried in sediments. Aggradation in gauging pool	
	(filled with fine rusty sediment); sensor and bottom of casing buried. 2012 installation unusable.	
	Rock-bolted benchmarks stability not assessed.	
Recommended	WRB suggests to keep this location and upgrade the infrastructure.	
infrastructure	Clear a 50 m trail upstream of station to facilitate access to a far enough injection site for salt dilution	
	gauging.	
	94499.	
	Installation as per R.I.S.C. 2018 guidelines:	
	•	
	Staff Gauge with adequate support structure	
	3 elevation benchmarks (rock bolt in boulder or ground rod driven to refusal)	
	Stilling well	
	Pressure transducer (continuous water level logger).	
	r ressare d'ansages (contantages water level logge.).	
Monitoring	Sufficiently frequent station visits to capture:	
objectives	Pre-spring freshet (late April – early May) to ensure loggers are synchronized and in working order	
	Spring freshet (late May – early June snowmelt peak)	
	Late melt (late June, early July)	
	Significant rain event(s)	
	Summer low flow	
	Pre-freeze-up (September) to winterize loggers (protect from freezing damage)	
	Early winter (November)	
	Late winter/winter low flow (March)	
	Survey stage (water surface elevation) on each visit.	
	Develop rating curve and derive continuous discharge from corrected stage time-series.	
Measurement	High flow: velocity-area method with ADV or equivalent (i.e. wading).	
methods	Moderate – low flow: salt dilution gauging following R.I.S.C. 2018 best practices.	
Priority rank	1 – Essential	

KR-08 Cache Creek (upstream of Peel confluence)

Station name	KR-08 Cache Creek (upstream of Peel confluence)	
Location	61.542943°, -132.236814°, 1242 m asl	
Watershed Area	KR-08 basin has maximum extents of 5.3 km by 3.5 km, a catchment area of 14 km², and the maximum basin elevation is 2,075 m asl.	
Flow Range	Low: Winter base flow in the order of 0.030 m³/s	Annual maximum: 2012-06-24 Freshet peak: 3.5 m³/s (estimate)
Stage Range	N/A	N/A
Rationale	Cache Creek flow downstream of tailings pond influence (tailings and water treatment discharge and	
	tailings dam seepages).	
Photos		
	KR-08 looking upstream	KR-13 looking downstream

Station name	KR-08 Cache Creek (upstream of Peel confluence)
Sketch	ACCESS TRAIL DISCHARGE CROSS-SECTION BELOW 3.6 STAFF GAUGE 2021 Sketch of the layout of KR-08 – Cache Creek
Channel	The culvert debris from the old hydrometric infrastructure shaped the flow distribution, constricted to
conditions	left bank, which is convenient for station installation. No effective control in place, sparse boulders
	influence the water level in the reach but there is no well defined gauging pool present.

Station name	KR-08 Cache Creek (upstream of Peel confluence)	
Satellite		
imagery		
	(R-0)	
	(1) KR-15	
	We Compliance	
	KR-13 KR-14	
	KR-01	
	Imagery date: 2005-08-09	
	https://caltopo.com/map.html#ll=61.54372,-132.23447&z=15&b=imagery	
Current	Debris of old infrastructure (prior to 2005). Staff gauge remains in stream but is not reliable (tilted	
infrastructure	and wobbly). No apparent benchmarks.	
Recommended	WRB suggests to keep this location and upgrade the infrastructure.	
infrastructure	We looked at an alternate location upstream of the Mill and Camp by KR-01 but could not find a	
	suitable reach and gauging pool due to channel braiding and low banks.	
	Installation as per R.I.S.C. 2018 guidelines:	
	Staff Gauge with adequate support structure	
	3 elevation benchmarks (ground rod driven to refusal)	
	Stilling well and pressure transducer (continuous water level logger).	
Monitoring	Sufficiently frequent station visits to capture:	
Monitoring objectives	Pre-spring freshet (late April – early May) to ensure loggers are synchronized and in working order	
objectives	Spring freshet (late May – early June snowmelt peak)	
	Late melt (late June, early July)	
	Significant rain event(s)	
	Summer low flow	
	Pre-freeze-up (September) to winterize loggers (protect from freezing damage)	
	Early winter (November)	
	Late winter/winter low flow (March)	
	Survey stage (water surface elevation) on each visit.	
	Develop rating curve and derive continuous discharge from corrected stage time-series.	

Station name	KR-08 Cache Creek (upstream of Peel confluence)	
Measurement	High flow: velocity-area method with ADV or equivalent (i.e. wading).	
methods	Moderate – low flow: salt dilution gauging following R.I.S.C. 2018 best practices.	
Priority rank	1 – Essential	

KR-14 Oxo Creek

Station name	KR-14 Oxo Creek Upper	
Location	61.533064°, -132.247683°, 1316 m asl	
	Station is located on the right bank of Oxo Creek about 130 metres south (upstream)	
	of the confluence of Oxo and Cache Creek.	The station is about 820 metres east of the
	Ketza camp. To access the site, one must f	ollow a path from the tailings pond access
	road up Oxo	Creek valley.
Watershed Area	KR14-Oxo Creek basin has maximum extents of 2.4 km by 2.7 km and a catchment area of 4.29 km². The maximum basin elevation is 1,954m asl.	
Flow Range	Low:	Annual maximum:
	2011-2012 Winter base flow in the order	2012-06-24 Freshet peak: 0.937 m³/s
	of 0.010 m³/s	
Stage Range	2012 open-water min: 0.150 m	2012 open-water max: 0.508 m
Rationale	Oxo is one of the three major tributaries of	Cache Creek (along with Peel and Misery)
	with their confluence just downstream	of mine water discharge points (water
	treatment outlet and to	ailings dam seepages)
	Oxo Creek flow record is useful in order to e	estimate the mine discharge (east of tailings
	pond) occurring between KR-13 a	and KR-08 Cache Creek stations.
Photos		
	KR-14 looking upstream	KR-14 looking downstream
Sketch	Housing 3m	S.G.
	2012 Sketch of the layou	ut of KR-14 - Oxo Creek

Station name	KR-14 Oxo Creek Upper	
	Source: EBA. 2013. Ketza River Project 2012 Hydrological Report.	
Channel	To be less the Control of the Contro	
conditions	Turbulent flow in steep gradient of step-pools with cobble and boulder streambed.	
Satellite	WO Complance	
	Imagery date: 2005-08-09	
	Imagery date: 2005-08-09	
	https://caltopo.com/map.html#II=61.52989,-132.23814&z=15&b=imagery	
Current	EBA (2013): "A 2.5 m long, 5 cm diameter Schedule 40 galvanized steel pipe was	
infrastructure	attached to a large boulder located near the right bank of the creek by means of two	
	heavy duty mounting tabs secured to a boulder with 3/8 inch by 6 inch long rock	
	anchors. The pressure/temperature instrumentation located within the pipe housing	
	in about 0.4metres water depth near the center of the creek.	
	·	
	The staff gauge was vertically mounted to a pressure treated 2" x 4" by 8' pressure	
	treated wooden stake which was attached to a large boulder by means of rock ancho	
	bolts. The staff gauge is located near the left bank of the creek near the pressure	
	transducer housing.	
	Two benchmarks were installed consisting of rock anchor bolts installed on boulders	
	two locations within a 5metre radius of the hydrometric station housing."	
	Hydrometric Station Key Elevations	
	June 13, 2012 at 17:17 Date and time of the elevation survey	
	1316.000 metres MSL Assumed elevation of the primary benchmark BM1 (from Google Earth) 1316.175 metres MSL Elevation of the secondary benchmark (BM2)	
	Elevation of the pressure / temperature sensor located within the housing	
	1315.055 metres MSL Elevation of the zero reading on the staff gauge	
	1315.350 metres MSL Water surface elevation near the housing at the time of the survey 0.066 metres Correction to staff gauge reading to obtain pressure transducer water level	
	Correction to stall gauge reading to obtain pressure transducer water level	

2021 observations: staff gauge tilted, unusable since its placement is not vertical. Both sensor casing and staff gauge in a mediocre location, too close to turbulences. However, this gauging pool remains the best candidate in the reach before the gradient gets steeper and less accessible closer to confluence or upstream of current location.

Station name	KR-14 Oxo Creek Upper
Recommended	WRB suggests to keep this location and upgrade the infrastructure.
infrastructure	
	Installation as per R.I.S.C. 2018 guidelines:
	Staff Gauge with adequate support structure
	3 elevation benchmarks (rock bolt in boulder or ground rod driven to refusal)
	Stilling well and pressure transducer (continuous water level logger).
Monitoring	Sufficiently frequent station visits to capture:
objectives	Pre-spring freshet (late April – early May) to ensure loggers are synchronized and in
	working order
	Spring freshet (late May – early June snowmelt peak)
	Late melt (late June, early July)
	Significant rain event(s)
	Summer low flow
	Pre-freeze-up (September) to winterize loggers (protect from freezing damage)
	Early winter (November)
	Late winter/winter low flow (March)
	Survey stage (water surface elevation) on each visit.
	Develop rating curve and derive continuous discharge from corrected stage time-
	series.
Measurement	High flow: velocity-area method with ADV or equivalent (i.e. wading).
methods	Moderate – low flow: salt dilution gauging following R.I.S.C. 2018 best practices.
Priority rank	2 – Beneficial

KR-13 Cache Creek Upper

Station name	KR-13 Cach	e Creek Upstream of TSF
Location	61.533381°,	-132.256428°, 1331 m asl
	Located on Cache Creek in the approxim	ate vicinity of the existing camp, across the road from
	the existing tailings pond. The housing is	located on the left bank of the creek about 50 metres
	upstream of the tailings po	nd discharge location into Cache Creek.
Watershed	KR13 basin has maximum extents of 4	2 km by 2.6 km and a catchment area of 5.27 km².
Area		sin elevation is 2,075m asl.
Flow Range	Low:	Annual maximum:
	2011-2012 Winter base flow in the order of 0.011 m³/s	2012-06-24 Freshet peak: 2.491 m³/s
Stage Range	2012 open-water min: 0.119 m	2012 open-water max: 0.388 m
Rationale	Cache Creek flow upstream of mine i	nfluence (tailings and water treatment discharge).
	However, flows maybe affected by mill	and camp runoff but we expect these impacts to be
	typicall	y below 0.003 m³/s
Photos		
	KR-13 looking upstream at sensor	KR-13 looking upstream at staff gauge
Sketch		1
		12
	5.6	
	2.0	0
	← 3	HOUSENS A
	1	
	zon	(EMZ (mil)
	y/saus	No.
	TRAN	BM1/nck)
	·	rout of KR-13 – Cache Creek Upper
	Source: EBA. 2013. Ketza l	River Project 2012 Hydrological Report.

Station name	KR-1	3 Cache Creek Upstream of TSF
Channel	Turbulent flow in steep gradient	of step-pools with cobble and boulder streambed. Channel
conditions	constriction with high banks is c	onvenient to capture the whole range of water levels in the
		logger record.
Satellite	a [™] Ketza	KR-13 615325, -132 25577
imagery		EV 64-500 to COSSAN 1331 m WCSSAN 1331 m WC
	Google Omester	© Califon, MapRov, Mexik USDA Parm Service Agency, EOATT, contains modified Copernicus data (2019) N: WH 191E Keyboard shortcots Image may be subject to copyright Terms of Use.
		Imagery date: 2019-06
	https://caltopo.com/map	.html#ll=61.53294,-132.25569&z=17&b=imagery
Current infrastructure	a large boulder located on the le	diameter Schedule 40 galvanized steel pipe was attached to ft bank of the creek by means of heavy duty mounting tabs inch by 6 inch long rock anchors. The pressure/temperature
	instrumentation located within th	water depth at the time of the installation.
		•
		vas mounted to a 2" x 4" by 4' long pressure treated wood
		ed vertically to a large boulder near the right bank of the river
	25metre	es upstream of the station housing.
	The two benchmarks consist of	anchor bolts installed on the top of large boulders near the
	station. BM1 is located 3 metres	downstream of the housing near the creek left bank. BM2 is
	located about 20metres o	downstream and 3meters inland from the left bank."
		Hydrometric Station Key Elevations
	6/13/2012, 10:16 AM	Date and time of the elevation survey
	1331.000 metres MSL	Assumed elevation of the primary benchmark BM1 (from Google Earth)
	1330.584 metres MSL	Elevation of the secondary benchmark (BM2)
		Elevation of the pressure / temperature sensor located within the housing
	1330.258 metres MSL	Elevation of the zero reading on the staff gauge
	1330.601 metres MSL	Water surface elevation near the housing at the time of the survey
	-0.035 metres Surveyed ele	Correction to staff gauge reading to obtain pressure transducer water level evations in 2012 at KR-13 (EBA 2013)
Recommended	WRB suggests to ke	ep this location and upgrade the infrastructure.
infrastructure		


Station name	KR-13 Cache Creek Upstream of TSF
	We looked at an alternate location upstream of the Mill and Camp by KR-01 but could not find
	a suitable reach and gauging pool due to channel braiding and low banks.
	Installation as per R.I.S.C. 2018 guidelines:
	Staff Gauge with adequate support structure
	3 elevation benchmarks (rock bolt in boulder or ground rod driven to refusal)
	Stilling well and pressure transducer (continuous water level logger).
Monitoring	Sufficiently frequent station visits to capture:
objectives	Pre-spring freshet (late April – early May) to ensure loggers are synchronized and in working
-	order
	Spring freshet (late May – early June snowmelt peak)
	Late melt (late June, early July)
	Significant rain event(s)
	Summer low flow
	Pre-freeze-up (September) to winterize loggers (protect from freezing damage)
	Early winter (November)
	Late winter/winter low flow (March)
	Survey stage (water surface elevation) on each visit.
	Develop rating curve and derive continuous discharge from corrected stage time-series.
Measurement	High flow: velocity-area method with ADV or equivalent (i.e. wading).
methods	Moderate – low flow: salt dilution gauging following R.I.S.C. 2018 best practices.
Priority rank	1 – Essential

KR-01 Cache Creek Upstream of Mill and TSF

Station name	KR-01 Cache Creek	Upstream of Mill and TSF
Location	61.528983, -132	2.27183°, 1414 m asl
	Located on Cache Creek in the reach upst	tream of existing mill and camp, just upstream
	of waste rock / tailings piles. There is no h	ydrometric infrastructure at the current KR-01
	water quality sampling location but there	are remnants of an older pre-2005 stilling well
	50 m downs	stream of KR-01.
Watershed	KR01 basin has maximum extents of 3.3	3 km by 2.6 km and a catchment area of 4.45
Area		km².
	Maximum basin e	levation is 2,075m asl.
Flow Range	Low:	Annual maximum:
	Winter base flow in the order of 0.010	2012 Freshet peak in the order 2.4 m³/s
	m³/s	
Stage Range	N/A	N/A
Rationale		ence including the mill and its waste rock piles unoff.
Photos	KR-01 looking upstream at sampling	Downstream of KR-01 looking at old stilling
	location	well (braided channel)
Channel	1000.001	pools with cobble and boulder streambed. The
conditions		gh vegetation downstream of KR-01 sampling
	-	plicated for establishing a robust water level
		precise flow measurements.
	1 scora ana consaccing	p. 23.22 .10 W 11104041 011101101


Station name	KR-01 Cache Creek Upstream of Mill and TSF
Satellite	7 Ketza KR01 61,5290,-132,27183 80 v 645,602 62,64330 H
imagery	→ 14.1 m V/OSA 14.1 m V/OSA 16.0 m
	100 th. ©COCION SUpSite Value USOA From Service Agency ECATE contains recorded Cocamina, and (COSS) for NN 101 to Expended Advances I maps may be subsent to copyright Terms of Use.
	Imagery date: 2019-06
Comment	https://caltopo.com/map.html#ll=61.52996,-132.27089&z=18&b=imagery
Current	Old pre-2005 infrastructure is decrepit and channel conditions are not adequate there
infrastructure	for meeting continuous monitoring requirements.
Recommended	WRB suggests to limit monitoring at KR-01 to discrete discharge measurements. These
infrastructure	flow measurements must be conducted immediately after KR-13 flow measurements in
	order to potentially establish a reliable relationship between flow at KR-13 and KR-01.
	The continuous record at KR-13 could then be used to derive continuous flow at KR-01.
Monitoring	Sufficiently frequent station visits to capture:
objectives	Pre-spring freshet (late April – early May) r
	Spring freshet (late May – early June snowmelt peak)
	Late melt (late June, early July)
	Significant rain event(s)
	Summer low flow
	Pre-freeze-up (September)
	Early winter (November)
	Late winter/winter low flow (March)
	Measure flow at KR-01 immediately after KR-13.
	Estimate continuous discharge from the rating model at KR-13.
Measurement	High flow: velocity-area method with ADV or equivalent (i.e. wading).
methods	Moderate – low flow: salt dilution gauging following R.I.S.C. 2018 best practices.
Priority rank	2 – Beneficial

Appendix H – Surficial Geology of the Ketza River Mine site





Appendix I – Groundwater Contours (Hemmera, August 2021)



Appendix J – Groundwater Monitoring Exceedance Summary (Hemmera, August 2021)

Table 4.4 Groundwater Exceedance Summary

		Parameters Exceeding and Dissolved Concentration	olved Concentration	
sample Location	CCME-FAL	FIGQFCS	CSR AW	CSR DW
1510 Portal Well	Arsenic 13.8 µg/L	Sulphate 199 mg/L Arsenic 13.8 µg/L Total Cyanide 4.9 µg/L	n/a	n/a
BH-10-01A	n/a	Total Cyanide, 4.0 µg/L	n/a	n/a
BH-10-02	Fluoride 0.5 mg/L Arsenic 38.9 µg/L	Fluoride 0.5 mg/L Sulphate 103 mg/L Arsenic 38.9 µg/L	n/a	Arsenic 38.9 μg/L Total Cyanide 7.7 μg/L
BH-10-05	n/a	n/a	n/a	Manganese 69.3 µ/L
Core Shack Well	Fluoride 0.13 mg/L Arsenic 34 µg/L Selenium 1.46 µg/L	Fluoride 0.13 mg/L Arsenic 34 µg/L Selenium 1.46 µg/L	n/a	Fluoride 0.13 mg/L Arsenic 34 µg/L
GT-10-01	Fluoride 0.27 mg/L Zinc 11.8 µg/L	Fluoride 0.27 mg/L Sulphate 256 mg/L Zinc 11.8 µg/L	n/a	n/a
GT-10-06A	Fluoride 0.55 mg/L Aluminum 560 µg/L Arsenic 1710 µg/L Cadmium 0.312 µg/L Chromium, Hexavalent 11.5 µg/L Copper 69.2 µg/L Total Cyanide 7.9 µg/L	Fluoride 0.55 mg/L Sulphate 169 mg/L Aluminum 560 µg/L Arsenic 1710 µg/L Cadmium 0.312 µg/L Chromium 15.7 µg/L Copper 69.2 µg/L Total Cyanide 7.9 µg/L	Arsenic 1710 µg/L Cadmium 0.312 µg/L Chromium, Hexavalent 11.5 µg/L Copper 69.2 µg/L Nickel 369 µg/L Sodium 244 µg/L	Aluminum 560 µg/L Antimony 9.98 µg/L Arsenic 1710 µg/L
HYD-08-1A	Fluoride 0.19 mg/L Uranium 33.3 µg/L	Fluoride 0.19 mg/L Sulphate 101 mg/L Uranium 33.3 µg/L	n/a	n/a
HYD-08-01B	Arsenic 19.2 µg/L Iron 0.306 mg/L	Arsenic 19.2 µg/L Iron 0.306 mg/L	n/a	Iron 0.306 mg/L Manganese 69.4 µg/L

		Parameters Exceeding and Dissolved Concentration	lved Concentration	
Sample Location	CCME-FAL	FIGQFCS	CSR AW	CSR DW
HYD-08-02	Arsenic 12.2 µg/L Copper 5.58 µg/L Zinc 63.4 µg/L	Arsenic 12.2 µg/L Barium 647 µg/L Copper 5.58 µg/L Zinc 63.4 µg/L	n/a	Manganese 59.7 µg/L
HYD-08-04A	Fluoride 0.49 mg/L Arsenic 8.67 µg/L Zinc 14.5 µg/L	Fluoride 0.49 mg/L Sulphate 218 mg/L Arsenic 8.67 µg/L Zinc 14.5 µg/L	n/a	n/a
HYD-08-06A	Fluoride 0.13 mg/L Arsenic 11.5 µg/L Iron 0.666 mg/L	Fluoride 0.13 mg/L Sulphate 497 mg/L Arsenic 11.5 µg/L Iron 0.666 mg/L	n/a	Iron 0.666 mg/L
HYD-08-08	Fluoride 0.18 mg/L Zinc 11.7 µg/L	Fluoride 0.18 mg/L Sulphate 300 mg/L Zinc 11.7 µg/L	n/a	Manganese 262 µg/L
HYD-08-09A	Fluoride 0.21 mg/L Aluminum 2880 µg/L Cadmium 0.304 µg/L Total Cyanide 141 µg/L Zinc 129 µg/L	Fluoride 0.21 mg/L Sulphate 223 mg/L Aluminum 2880 µg/L Cadmium 0.304 µg/L Total Cyanide 141 µg/L Zinc 129 µg/L	Cobalt 21 µg/L Total Cyanide 141 µg/L	Aluminum 2880 µg/L Manganese 322 µg/L
HYD-08-10	Fluoride 0.78 mg/L Aluminum 18700 µg/L Arsenic 825 µg/L Calcium 1.25 µg/L Chromium, trivalent 13.2 µg/L Cobalt 313 µg/L Iron 62.5 mg/L Nickle 85.7 µg/L Zinc 221 µg/L	Fluoride 0.78 mg/L Sulphate 760 mg/L Aluminum 18700 µg/L Arsenic 825 µg/L Calcium 1.25 µg/L Chromium 13.2 µg/L Cobalt 313 µg/L Iron 62.5 mg/L Nickle 85.7 µg/L Zinc 221 µg/L	Arsenic 825 µg/L Calcium 1.25 µg/L Zinc 221 µg/L	Sulphate 760 mg/L Aluminum 18700 µg/L Arsenic 825 µg/L Iron 62.5 mg/L Manganese 332 µg/L

		Parameters Exceeding and Dissolved Concentration	lved Concentration	
Sample Location	CCME-FAL	FIGQFCS	CSR AW	CSRDW
HYD-08-11A	Fluoride 1.56 mg/L Aluminum 24800 µg/L Arsenic 58.6 µg/L Cadmium 6.66 µg/L Cobalt 610 µg/L Copper 529 µg/L Nickel 266 µg/L Zinc 1220 µg/L	Fluoride 1.56 mg/L Sulphate 566 mg/L Aluminum 24800 µg/L Arsenic 58.6 µg/L Cadmium 6.66 µg/L Copper 529 µg/L Manganese 1750 µg/L Nickel 266 µg/L Zinc 1220 µg/L	Arsenic 58.6 μg/L Cadmium 6.66 μg/L Cobalt 610 μg/L Copper 529 μg/L	Fluoride 1.56 mg/L Sulphate 566 mg/L Aluminum 24800 µg/L Arsenic 58.6 µg/L Cadmium 6.66 µg/L Manganese 1750 µg/L
HYD-08-17	Cyanide 9.2 μg/L Iron 2.36 mg/L Uranium 17 μg/L	Sulphate 254 mg/L Cyanide 9.2 µg/L Iron 2.36 mg/L Uranium 17 µg/L	n/a	Iron 2.36 mg/L Manganese 60.5 µg/L
KR-05-688	n/a	Sulphate 166 mg/L	n/a	n/a
New Camp Water Well	Arsenic 9.27 µg/L	Arsenic 9.27 µg/L	n/a	n/a
P90-7B	Arsenic 20.6 µg/L Total Cyanide 8.5 µg/L	Arsenic 20.6 µg/L Total Cyanide 8.5 µg/L	n/a	n/a
P90-8	Arsenic 506 µg/L Total Cyanide 10.2 µg/L Iron 1.09 mg/L	Sulphate 189 mg/L Arsenic 506 µg/L Total Cyanide 10.2 µg/L Iron 1.09 mg/L	Arsenic 506 µg/L	Arsenic 506 µg/L Iron 1.09 mg/L
P96-12A	Arsenic 9.1 µg/L Total Cyanide 15.5 µg/L	Arsenic 9.1 µg/L Total Cyanide 15.5 µg/L	n/a	Manganese 840 µg/L
P96-12B	Arsenic 427 µg/L	Sulphate 125 mg/L Arsenic 427 µg/L Manganese 1720 µg/L	Arsenic 427 µg/L	Arsenic 427 µg/L Manganese 1720 µg/L
Upper Mill Well	Fluoride 0.57 mg/L Arsenic 667 µg/L Iron 0.915 mg/L Zinc 27.2 µg/L	Fluoride 0.57 mg/L Sulphate 118 mg/L Arsenic 667 µg/L Total Cyanide 3.7 µg/L Iron 0.915 mg/L Zinc 27.2 µg/L	Arsenic 667 µg/L	Arsenic 667 µg/L Iron 0.915 mg/L